Web Development August 2026 Batch Program 2026-09-01 20:20(GMT+5:30)

java script

<script>

let username="jhon"

//let is use for create a variable,once it use with variable no need to repeat let key word.

username="teja"

console.log(username)

constant keyword

no one can do with constant

it is not possible like;

const appName="whatsapp"

appName="faceBook"

?? we get error ,variable can store only one time value.

Data Type

1.String="*****"

ex: let EmailId="teja07@gmail.com"

EmailId="Nayak@gmail.com"

In Buid Methods

Features of programming lang which we can use in specific kind of task.

check the data type:

console.log(typeof(EmailId))

Numbers

every type of number can consider as number.

if u check all int flot double all are check as NUmber only.

3.Boolean

ex: let LogInStatus=false

let NetflixSub=true

console.log(typeof(Netflixsub))

→ Boolean

undefined

ex: let score

console.log(typeof(score))

→undefined // value is not assiend here

1. null

let Score=null

console.log(typeof(score))

→object (due to bug in js)

multiple data

1.Array

multiple data store in one single place and it can also store data of different data types.

symbol-[]

//rules - Index no(Index Number is always starts with 0)

Ex:

let Students =["sathya","Thana","Teja",1232,true]

console.log(Students)

//Access the data through indexnumber

→ console.log(Students[2])

--→Teja

→console.log(Students[7])

--→Undefined

2.object - Collection of Prop(Data)

// symbol=== { }

ex:

const employee={

name:"Teja",

useId="25UBE0036",

loginStatus:false

}

console.log(employee)

→

console.log(employee.userId)

→25UBE0036

FUNCTIONS

functions ar use for do specific task .

// Function KeyWord===

function Greet(){

//Body Of the Task

console.log("hello Guys")

}

// call the function

Greet()

2. function with parameter

function Greeting(name){

console.log(name)

-→Teja

}

Greeting("Teja")

Greeting("ramu")

Greeting("kater")

Greeting("tehsja")

2.1 Return KeyWord

function Add(a,b){

return a+b

}

Add(5,6)

--→11

let result =Add(5,6)

console.log(result)

---it is to check the output

Operators

similar topic in c,java,python...

ex:

console.log(x+y//x*y//x/y//x%y)

left<right---left number

concole.log(1%6)--→1

1. comparision operator

let a=10;

let b=8;

concsole.log(a>b)

--→true

let height1=100

let height2="100"

console(height1==height2)

--→ true(it checks only values)

console(height1===height2)

--→false(it checks data type also)

2. Logical Operators