



December 8-10 | Virtual Event

**CONTRIBUTE.
COLLABORATE.
COMMERCIALIZE.**



Brought to you by

informa tech

riscvsummit.com #RISCVSUMMIT




December 8-10 | Virtual Event

kexec based bootloaders on RISC-V: Use-cases &
Advantages

Bhupesh Sharma
Senior Software Engg
Red Hat

#RISCVSUMMIT

bhsharma@redhat.com



\$ whoami

- Part of Red Hat kernel team.
- Been hacking on bootloaders and kernel since past 14 years.
- Contribute to:
 - Linux,
 - EFI/u-boot bootloader, and
 - User-space utilities like:
 - kexec-tools, and
 - makedumpfile.
- Co-maintain crash-utility tool







Outline



- About kexec – What?
- About kexec – How?
- Linux booting Linux – kexec based bootloaders
- Case for kexec based bootloaders on RISC-V
- So everything works fine, or does it ..
- Pain Points
- Suggestions



About kexec - What?

- kexec enables you to load and boot into **another kernel** from the currently running kernel.
- **Standard** system boot v/s **kexec** boot:
 - **kexec** boot - skips hardware initialization performed by BIOS / firmware.
- So, overall **kexec** reboot time reduces 
- Related [syscalls](#)
 - `kexec_load()`
 - `kexec_file_load()`



About kexec - What?

- Related kernel **CONFIG** options
 - `CONFIG_KEXEC`
 - `CONFIG_KEXEC_FILE`
- Supported **architectures**
 - x86_64,ppc64/ppc64le,s390/s390x,arm,arm64



About kexec - How?


- **2-Step** process

- **Kernel** space support


- `kexec_load()` and `kexec_file_load()` syscall(s) loads a new kernel into memory.
 - `reboot(LINUX_REBOOT_CMD_KEXEC)` syscall reboots into the new kernel.


- **User** space support

- `/usr/bin/kexec` - provided by **kexec-tools** package



Kexec design





About kexec - How?

- **2-Step** process

- **Load** a new kernel into the physical memory:

```
# kexec -l <kernel-image> --initrd=<initramfs-image> --reuse-cmdline
```

- **Boot** into the new kernel:

```
# kexec -e
```

- **Unload** the loaded kernel (*if need be*):

```
# kexec -u
```






Linux booting Linux - kexec based bootloaders



- Several **kexec** based open-source bootloaders are available:
- [LinuxBoot](#)
- [Petitboot](#)
- [kexecboot](#)
- [kboot](#), several more ...







Case for kexec based bootloader on RISC-V



- Fast reboot / Warm booting remains an important feature for RISC-V platforms as well.
- Kernel **kexec** patches were proposed for RISC-V
 - But seems further work still needed to upstream them.
- User-space **kexec-tools** patches were proposed for RISC-V
 - But seems further work still needed to upstream them.
- Requests have also come up for **crash-utility** support for RISC-V
- Look here ([riscv-for-next](#)) for more developmental features.



So everything works fine, or does it ...



On Amazon EC2 Nitro platform running RHEL 8, the Fast boot using "kexec -e" and "systemctl kexec" causes the kernel to crash.

[SOLUTION IN PROGRESS](#) - Updated June 22 2020 at 8:29 AM - [English](#)

Issue

- On Amazon EC2 Nitro platform running RHEL 8, the Fast boot using `kexec -e` and `systemctl kexec` causes the kernel to crash.
- The same kernel panic is appearing with `kexec -p` and `echo c > /proc/sysrq-trigger` as well.

```
[ 3.327901] sched: Unexpected reschedule of offline CPU#1!
[ 3.334363] WARNING: CPU: 0 PID: 1 at arch/x86/kernel/smp.c:128 native_smp_send_reschedule+0x34/0x40
[ 3.346699] Modules linked in:
[ 3.352238] CPU: 0 PID: 1 Comm: init Not tainted 4.18.0-80.1.2.el8_0.x86_64 #1
[ 3.363631] Hardware name: Amazon EC2 t3.large/, BIOS 1.0 10/16/2017
[ 3.370639] RIP: 0010:native_smp_send_reschedule+0x34/0x40
[ 3.377330] Code: 05 21 90 3b 01 73 15 48 8b 05 78 af 10 01 be fd 00 00 00 48 8b 40 30 e9 9a 94 bb 00 89 fe 48 c7 a8 68 e8
9e e8 b6 28 06 00 <0f>0f 0b c3 66 0f 1f 84 00 00 00 00 0f 1f 44 00 00 53 48 83 ec 20
[ 3.398020] RSP: 0018:ffff98e9f9403e48 EFLAGS: 00010086
[ 3.404505] RAX: 0000000000000000 RBX: ffff98e9f9523080 RCX: ffffffff9f059d28
[ 3.411891] RDX: 0000000000000001 RSI: 0000000000000096 RDI: 0000000000000046
```

Multiple Kexec in AWS Nitro instances fail

Bug #1869948 reported by [Guilherme G. Piccoli](#) on 2020-03-31

This bug affects 1 person

Affects	Status	Importance	Assigned to
linux (Ubuntu)	Fix Released	High	Guilherme G. Piccoli
Xenial	Fix Released	High	Guilherme G. Piccoli
Bionic	Fix Released	High	Guilherme G. Piccoli
Eoan	Fix Released	High	Guilherme G. Piccoli
Focal	Fix Released	High	Guilherme G. Piccoli

[Also affects project](#) [Also affects distribution/package](#) [Nominate for series](#)

Bug Description

[Impact]

* Currently, users cannot perform multiple kernel kexec loads on AWS Nitro instances (KVM-based); after the 2nd or 3rd kexec, an initrd corruption is observed, with the following signature:

Initramfs unpacking failed: junk within compressed archive

[...]

Kernel panic - not syncing: No working init found.

Try passing `init=` option to kernel. See Linux Documentation/admin-guide/init.rst for guidance.

CPU: 0 PID: 1 Comm: swapper/0 Not tainted 5.5.0-rc7-gpiccoli+ #26 Hardware name: Amazon EC2 t3.large/, BIOS 1.0 10/16/2017


Call Trace:

dump_stack+0x6d/0x9a

<https://launchpad.net/ubuntu/+source/linux/+bug/1869948>




So everything works fine, or does it ...





So everything works fine, or does it ...





So everything works fine, or does it ...

HW

SATA disk
(DMA capable)



PCIe based NIC
(DMA capable)



SCSI device
(DMA capable)



Kernel

DMA Tx

DMA capable
driver

DMA Tx
cancelled

.shutdown() ✓

DMA Tx

DMA capable
driver

DMA Tx

.shutdown() ✗


DMA Tx

DMA capable
driver

DMA Tx
cancelled

.shutdown() ✓

Possible
Corruption



kexec -e

2

SYSCALL_DEFINE4(reboot,)

kernel_kexec()


kernel_restart_prepare()

device_shutdown()

call -> **shutdown()** on each
device to shutdown.



So sometimes kexec **does not work** as intended



On Amazon EC2 Nitro platform running RHEL 8, the Fast boot using "`kexec -e`" and "`systemctl kexec`" causes the kernel to crash.

[SOLUTION IN PROGRESS](#) - Updated June 22 2020 at 8:29 AM - English ▾

Issue

- On Amazon EC2 Nitro platform running RHEL 8, the Fast boot using `kexec -e` and `systemctl kexec` causes the kernel to crash.
- The same kernel panic is appearing with `kexec -p` and `echo c > /proc/sysrq-trigger` as well.

```
[ 3.327901] sched: Unexpected reschedule of offline CPU#1!
[ 3.334363] WARNING: CPU: 0 PID: 1 at arch/x86/kernel/smp.c:128 native_smp_send_reschedule+0x34/0x40
[ 3.346699] Modules linked in:
[ 3.352238] CPU: 0 PID: 1 Comm: init Not tainted 4.18.0-80.1.2.el8_0.x86_64 #1
[ 3.363631] Hardware name: Amazon EC2 t3.large/, BIOS 1.0 10/16/2017
[ 3.370639] RIP: 0010:native_smp_send_reschedule+0x34/0x40
[ 3.377330] Code: 05 21 90 3b 01 73 15 48 8b 05 78 af 10 01 be fd 00 00 00 48 8b 40 30 e9 9a 94 bb 00 89 fe 48 c7 a8 68 e8
9e e8 b6 28 06 00 <0f> 0b c3 66 0f 1f 84 00 00 00 00 0f 1f 44 00 00 53 48 83 ec 20
[ 3.398020] RSP: 0018:ffff98e9f9403e48 EFLAGS: 00010086
[ 3.404505] RAX: 0000000000000000 RBX: ffff98e9f9523080 RCX: ffffffff9f059d28
[ 3.411891] RDX: 0000000000000001 RSI: 0000000000000096 RDI: 0000000000000046
```



Suggestions



Add shutdown()
callbacks in your driver
code

```
[PATCH] ata: ahci: Add shutdown to freeze hardware resources of ahci
spinics.net/lists/kexec/msg24305.html

device_shutdown() called from reboot/power_shutdown expect all
devices to be shutdown. Same is true for ahci pci driver.
As no shutdown function was implemented ata subsystem remains
always alive and DMA/interrupt still active.

It creates problem during kexec, here "M" bit is cleared to stop
DMA usage. Any further DMA transaction may cause instability and
the hard-disk may even not get detected for second kernel.
One of possible case is periodic file system sync.

So defining ahci pci driver shutdown to freeze hardware (mask
interrupt, stop DMA engine and free DMA resources).

Signed-off-by: Prabhakar Kushwaha <pkushwaha@xxxxxxxxxxxx>
---
drivers/ata/ahci.c | 8 ++++++
drivers/ata/libata-core.c | 21 +++++++++++++++++++++
include/linux/libata.h | 1 +
3 files changed, 30 insertions(+)

diff --git a/drivers/ata/ahci.c b/drivers/ata/ahci.c
index 4bfd1b14b390..31fc934740b6 100644
--- a/drivers/ata/ahci.c
+++ b/drivers/ata/ahci.c
@@ -81,6 +81,7 @@ enum board_ids {

static int ahci_init_one(struct pci_dev *pdev, const struct pci_device_id *ent);
static void ahci_remove_one(struct pci_dev *dev);
+static void ahci_shutdown_one(struct pci_dev *dev);
static int ahci_vt8251_hardreset(struct ata_link *link, unsigned int *class,
                                unsigned long deadline);
static int ahci_avn_hardreset(struct ata_link *link, unsigned int *class,
@@ -606,6 +607,7 @@ static struct pci_driver ahci_pci_driver = {
    .id_table      = ahci_pci_tbl,
    .probe         = ahci_init_one,
    .remove        = ahci_remove_one,
+   .shutdown      = ahci_shutdown_one,
    .driver        = {
        .pm        = &ahci_pci_pm_ops,
    },
@@ -626,6 +628,7 @@ MODULE_PARM_DESC(mobile_lpm_policy, "Default LPM policy for mobile chipsets");
static void ahci_pci_save_initial_config(struct pci_dev *pdev,
                                         struct ahci_host_priv *hpriv)
{
```


[PATCH] ata: ahci: Add shutdown to freeze hardware resources of ahci



Suggestions



Add shutdown()
callbacks in your
driver code



[PATCH] scsi: lpfc: Add shutdown method for kexec

From: Anton Blanchard <anton@xxxxxxxxxx>

We see lpfc devices regularly fail during kexec. Fix this by adding a shutdown method which mirrors the remove method.



Next Steps

- There is still work to be done for enabling **kexec** fully on RISC-V in upstream communities.
- Report **kexec reboot** failures @ kexec@lists.infradead.org
- **kexec** failures can be related to missing **shutdown()** callbacks in *DMA capable drivers*, e.g.
 - SATA, USB, NIC, PCIe driver
- Add more *debugging capabilities* to your **kexec** based bootloader.
 - console logs → pretty useful.



Questions?





December 8-10 | Virtual Event

Thank you for joining us.

Contribute to the RISC-V conversation on social!

#RISCVSUMMIT @risc_v



Brought to you by

informa tech

riscvsummit.com #RISCVSUMMIT