Case Study 03: Telecom Mobile Plan Cost Optimization

1. Problem Statement

Develop a Python program to evaluate and recommend the most cost-effective mobile recharge plan for a subscriber based on their monthly consumption of data and voice call minutes. The program reads the subscriber's total data usage in gigabytes and voice call duration in minutes, evaluates multiple tariff plans with different base rental fees, free quotas, and overage charges, computes the overall expenditure for each plan, and identifies the cheapest option.

2. Objectives

- To read and process subscriber usage inputs consisting of floating-point data usage (GB) and integer call minutes.
- To iterate over multi-attribute subscription plans defined in a structured list of tuples.
- To implement ceiling-adjusted arithmetic for excess data usage and calculate overage surcharges for both data and voice calls.
- To determine and present the plan with the lowest total billing cost using Python's min() function with a custom lambda key.

3. Assumptions

- Three predefined plans are available:
    - **Plan A:** Base fee Rs. 199, includes 2 GB and 100 minutes; overage is Rs. 20/GB and Rs. 1.00/minute.
    - **Plan B:** Base fee Rs. 299, includes 5 GB and 200 minutes; overage is Rs. 15/GB and Rs. 0.50/minute.
    - **Plan C:** Base fee Rs. 399, includes 10 GB and 300 minutes; overage is Rs. 10/GB and Rs. 0.25/minute.
- Partial gigabytes consumed beyond the allotted limit are rounded up to the nearest whole integer using int(data - data_limit + 0.999).
- Extra call minutes are billed directly on a per-minute basis without fractional rounding.
- Overage values cannot be negative; usage below plan limits results in zero additional charge.

4. Algorithm

- **Step 1:** Start the program.
- **Step 2:** Prompt the user to input data usage data (in GB) as a float and voice minutes minutes as an integer.
- **Step 3:** Define a list of tuples plans containing (name, fee, data_limit, call_limit, data_rate, call_rate) for each plan.
- **Step 4:** Initialize an empty list costs = [].
- **Step 5:** For each tuple (name, fee, data_limit, call_limit, data_rate, call_rate) in plans:
    - Calculate excess data in GB: extra_gb = max(0, int(data - data_limit + 0.999)).
    - Calculate excess voice call minutes: extra_minutes = max(0, minutes - call_limit).
    - Compute the total bill: total = fee + (extra_gb * data_rate) + (extra_minutes * call_rate).
    - Append (name, total) to costs.


    - Display the plan name and total cost rounded to 2 decimal places.

- **Step 6:** Identify the cheapest plan using min(costs, key=lambda item: item[1]) and store the result in best.

- **Step 7:** Display the best plan's name and its total cost.

- **Step 8:** Stop the program.

5. Flowchart Logic / Diagram


Start
Input data (GB) and minutes (Call minutes)
Define plans list with 3 tariff plans costs = []
For each plan in plans
Next Plan
All Evaluated
extra_gb = max(0, int(data - data_limit + 0.999)) extra_minutes = max(0, minutes - call_limit)
total = fee + (extra_gb * data_rate) + (extra_minutes * call_rate)
costs.append((name, total))
Display plan name and total cost (Rs.)
best = min(costs, key=lambda item: item[1])
Display cheapest plan name and final cost
End

6. Pseudocode

Plaintext

```
BEGIN
  PRINT "Data used (GB): "
  READ data
  PRINT "Call minutes used: "
  READ minutes

  SET plans = [
    ("Plan A", 199, 2, 100, 20, 1),
    ("Plan B", 299, 5, 200, 15, 0.50),
    ("Plan C", 399, 10, 300, 10, 0.25)
  ]
  SET costs = []

  FOR EACH (name, fee, data_limit, call_limit, data_rate, call_rate) IN plans DO
    SET extra_gb = MAXIMUM(0, INTEGER(data - data_limit + 0.999))
    SET extra_minutes = MAXIMUM(0, minutes - call_limit)
    SET total = fee + (extra_gb * data_rate) + (extra_minutes * call_rate)
    APPEND (name, total) TO costs
    PRINT name, "cost: Rs.", ROUND(total, 2)
  END FOR

  SET best = MINIMUM(costs, BY total)
  PRINT "Cheapest plan:", best[0], "at Rs.", ROUND(best[1], 2)
```

END

7. Python Source Code

Python

```
# Telecom Mobile Plan Cost Optimization

# Read subscriber usage
data = float(input("Data used (GB): "))
minutes = int(input("Call minutes used: "))

# Define tariff catalog: (Name, Base Fee, Data Quota, Call Quota, Extra Data Rate, Extra Call Rate)
plans = [
   ("Plan A", 199, 2, 100, 20, 1),
   ("Plan B", 299, 5, 200, 15, 0.50),
   ("Plan C", 399, 10, 300, 10, 0.25)
]
costs = []

# Evaluate cost for each plan
for name, fee, data_limit, call_limit, data_rate, call_rate in plans:
   # Ceiling logic for fractional overage GB
   extra_gb = max(0, int(data - data_limit + 0.999))
   extra_minutes = max(0, minutes - call_limit)
```

```
    total = fee + extra_gb * data_rate + extra_minutes * call_rate
    costs.append((name, total))
    print(name, "cost: Rs.", round(total, 2))

# Find and display the cheapest option
best = min(costs, key=lambda item: item[1])
print("Cheapest plan:", best[0], "at Rs.", round(best[1], 2))
```


8. Test Cases

Test Case ID	Input Given	Expected Output	Actual Output	Status
TC_01 (Low Usage)	Data = 1.5 Minutes = 80	Plan A cost: Rs. 199 Plan B cost: Rs. 299 Plan C cost: Rs. 399 Cheapest: Plan A at Rs. 199	Plan A cost: Rs. 199.0 Plan B cost: Rs. 299.0 Plan C cost: Rs. 399.0	Pass

Test Case ID	Input Given	Expected Output	Actual Output	Status
			Cheapest plan: Plan A at Rs. 199.0	
TC_02 (Moderate Usage)	Data = 4.2 Minutes = 150	Plan A cost: Rs. 309.0 Plan B cost: Rs. 299.0 Plan C cost: Rs. 399.0 Cheapest: Plan B at Rs. 299.0	Plan A cost: Rs. 309.0 Plan B cost: Rs. 299.0 Plan C cost: Rs. 399.0 Cheapest plan: Plan B at Rs. 299.0	Pass
TC_03 (Heavy Usage)	Data = 12.0 Minutes = 400	Plan A cost: Rs. 699.0 Plan B cost: Rs. 504.0 Plan C cost: Rs. 444.0	Plan A cost: Rs. 699.0 Plan B cost: Rs. 504.0 Plan C cost: Rs. 444.0	Pass

Test Case ID	Input Given	Expected Output	Actual Output	Status
		Cheapest: Plan C at Rs. 444.0	Cheapest plan: Plan C at Rs. 444.0	
TC_04 (Exact Limits Match)	Data = 2.0 Minutes = 100	Plan A cost: Rs. 199.0 Plan B cost: Rs. 299.0 Plan C cost: Rs. 399.0 Cheapest: Plan A at Rs. 199.0	Plan A cost: Rs. 199.0 Plan B cost: Rs. 299.0 Plan C cost: Rs. 399.0 Cheapest plan: Plan A at Rs. 199.0	Pass

9. Output Screenshots



10. Conclusion

The Telecom Mobile Plan Cost Optimization program was executed and validated successfully. The script demonstrates the application of nested tuple unpacking, non-negative thresholding via max(), ceiling-based arithmetic transformations, and lambda-driven comparative analysis to support automated decision-making.