

# solution

November 5, 2024

## 1 Decision Tree Implelentation

### 1.1 Step-1: Importing Dataset

### 1.2 Step-2: Parsing the Dataset

```
[26]: from ucimlrepo import fetch_ucirepo

# fetch dataset
lenses = fetch_ucirepo(id=58)

# data (as pandas dataframes)
X = lenses.data.features
y = lenses.data.targets

# variable information
# print(lenses.variables)

dataframe = lenses.data['original']
print(lenses.data['original'])
```

	id	age	spectacle_prescription	astigmatic	class
1	1	1	1	1	3
2	1	1	1	2	2
3	1	1	2	1	3
4	1	1	2	2	1
5	1	2	1	1	3
6	1	2	1	2	2
7	1	2	2	1	3
8	1	2	2	2	1
9	2	1	1	1	3
10	2	1	1	2	2
11	2	1	2	1	3
12	2	1	2	2	1
13	2	2	1	1	3
14	2	2	1	2	2
15	2	2	2	1	3
16	2	2	2	2	3
17	3	1	1	1	3


18	3	1	1	2	3
19	3	1	2	1	3
20	3	1	2	2	1
21	3	2	1	1	3
22	3	2	1	2	2
23	3	2	2	1	3
24	3	2	2	2	3


### 1.3 Step-3: Visual Representations

```
[27]: import pandas as pd
import seaborn as sns
import matplotlib.pyplot as plt

sns.pairplot(dataframe, hue='class', palette='viridis')
plt.show()

corr = dataframe.corr()
sns.heatmap(corr, annot=True, cmap='viridis', fmt='.2f')
plt.title('Feature Correlation Heatmap')
plt.show()
```





#### 1.4 Step-4: Train the Classifier

```
[28]: # Load libraries
from sklearn.tree import DecisionTreeClassifier # Import Decision Tree
      ↳ Classifier
from sklearn.model_selection import train_test_split # Import train_test_split
      ↳ function
from sklearn import metrics #Import scikit-learn metrics module for accuracy
      ↳ calculation

# Split dataset into training set and test set
X_train, X_test, y_train, y_test = train_test_split(X, y, test_size=0.3,
      ↳ random_state=1)

# Create a Classifier and train it
clf = DecisionTreeClassifier()
```

```

clf = clf.fit(X_train, y_train)

# Predict the response
y_pred = clf.predict(X_test)

```

## 1.5 Step-5: Write a function to descend the tree for a given instance

```

[29]: class TreeNode:
    def __init__(self, feature_index=None, threshold=None, left=None,
        right=None, value=None):
        self.feature_index = feature_index # Index of the feature to check (e.
        g., 0 for 'age')
        self.threshold = threshold # Threshold value for the feature
        self.left = left # Left child node
        self.right = right # Right child node
        self.value = value # Predicted class (for leaf nodes
        only)

def descend_tree(node, instance):
    """
    Descends the decision tree for a given instance and returns the prediction.

    Parameters:
    - node (TreeNode): The root node of the decision tree.
    - instance (list): A list of feature values for a single instance (e.g.,
        [1, 2, 1]).

    Returns:
    - The predicted class at the leaf node.
    """
    while node.left is not None and node.right is not None: # Traverse until a
        leaf
        feature_value = instance[node.feature_index] # Get feature value from
        instance

        # Check the threshold to determine the next branch
        if feature_value <= node.threshold:
            node = node.left
        else:
            node = node.right

    return node.value # Return prediction at the leaf node

# Example decision tree setup (this would normally be constructed by a training
    algorithm)

```

```

leaf1 = TreeNode(value=1) # For example, "Class 1"
leaf2 = TreeNode(value=2) # For example, "Class 2"
root = TreeNode(feature_index=0, threshold=1.5, left=leaf1, right=leaf2) #
    ↳Root node checks 'age'

# Instance to classify (e.g., age=2, spectacle_prescription=1, astigmatic=1)
instance = [2, 1, 1]

# Predict by descending the tree
prediction = descend_tree(root, instance)
print("Predicted class:", prediction)

```

Predicted class: 2

## 1.6 Step-6: Persist the tree data structure so it can be recalled without building the tree; then use it in any application.

```

[30]: import pickle

def save_tree(tree, filename):
    """
    Saves the decision tree to a file.

    Parameters:
    - tree (TreeNode): The root node of the decision tree.
    - filename (str): The name of the file to save the tree.
    """
    with open(filename, 'wb') as f:
        pickle.dump(tree, f)
    print(f"Tree saved to {filename}")

def load_tree(filename):
    """
    Loads the decision tree from a file.

    Parameters:
    - filename (str): The name of the file to load the tree from.

    Returns:
    - TreeNode: The root node of the loaded decision tree.
    """
    with open(filename, 'rb') as f:
        tree = pickle.load(f)
    print(f"Tree loaded from {filename}")
    return tree

```

```
# Save the tree to a file  
save_tree(root, 'decision_tree.pkl')  
  
# Later in your application, load the tree  
loaded_tree = load_tree('decision_tree.pkl')
```

Tree saved to decision\_tree.pkl

Tree loaded from decision\_tree.pkl