SAMPLE DATA INSERTION

ASSIGNMENT 7

DATABASE MANAGEMENT SYSTEM

ALLIANCE UNIVERSITY

Department of Computer Applications

SUMMITED BY: BHUVANA S

REGISTER NO: 2511021240036

COURSE: BCA

YEAR: 2ND YEAR

Introduction

Sample data insertion is an important step in testing a database management system. The INSERT INTO SQL command is used to add records to database tables. In this assignment, realistic sample data is inserted into the seven tables of the Food Delivery Management System using MySQL. The inserted records follow the defined constraints and relationships between tables.

1. Selecting the Database

USE Food_Delivery_DB;

This command selects the Food_Delivery_DB database for inserting sample records.

2. Inserting Data into CUSTOMER

The CUSTOMER table stores customer details.

INSERT INTO CUSTOMER

(Customer_ID, Customer_Name, Phone, Email, Address)

VALUES

(1, 'Arun Kumar', '9876543210', 'arun@gmail.com', 'Hosur'),

(2, 'Priya Sharma', '9876543211', 'priya@gmail.com', 'Bengaluru'),

(3, 'Rahul Verma', '9876543212', 'rahul@gmail.com', 'Electronic City'),

(4, 'Sneha Reddy', '9876543213', 'sneha@gmail.com', 'Whitefield'),

(5, 'Karthik Raj', '9876543214', 'karthik@gmail.com', 'Chennai');

Five customer records are inserted with unique customer IDs and email addresses.

3. Inserting Data into RESTAURANT

The RESTAURANT table stores restaurant information.

INSERT INTO RESTAURANT

(Restaurant_ID, Restaurant_Name, Phone, Rating, Address)

VALUES

(101, 'Spice Garden', '9123456780', 4.5, 'Bengaluru'),

(102, 'Green Bowl', '9123456781', 4.2, 'Electronic City'),

(103, 'Food Junction', '9123456782', 3.9, 'Hosur'),

(104, 'Urban Tandoor', '9123456783', 4.7, 'Whitefield'),

(105, 'South Kitchen', '9123456784', 4.0, 'Chennai');

Five restaurants are added with ratings between 0 and 5, satisfying the CHECK constraint.

4. Inserting Data into DELIVERY_PARTNER

The DELIVERY_PARTNER table stores delivery partner details.

INSERT INTO DELIVERY_PARTNER

(Partner_ID, Partner_Name, Phone)

VALUES

(201, 'Ravi Kumar', '9000011111'),

(202, 'Manoj Singh', '9000011112'),

(203, 'Ajay Patel', '9000011113'),

(204, 'Vijay Raj', '9000011114'),

(205, 'Suresh Babu', '9000011115');

Five delivery partners are inserted. Each partner has a unique ID.

5. Inserting Data into MENU_ITEM

The MENU_ITEM table stores the food items available at restaurants.

INSERT INTO MENU_ITEM

(Item_ID, Restaurant_ID, Item_Name, Category, Price, Availability)

VALUES

(301, 101, 'Paneer Biryani', 'Main Course', 220.00, TRUE),

(302, 101, 'Butter Naan', 'Bread', 40.00, TRUE),

(303, 102, 'Vegetable Salad', 'Healthy Food', 150.00, TRUE),

(304, 103, 'Masala Dosa', 'Breakfast', 80.00, TRUE),

(305, 104, 'Chicken Tandoori', 'Main Course', 280.00, TRUE),

(306, 105, 'Idli Sambar', 'Breakfast', 60.00, TRUE),

(307, 102, 'Fruit Bowl', 'Healthy Food', 120.00, FALSE),

(308, 104, 'Veg Fried Rice', 'Main Course', 170.00, TRUE);

Eight menu items are inserted. Each Restaurant_ID refers to an existing restaurant, satisfying the foreign key constraint.

6. Inserting Data into ORDERS

The ORDERS table stores customer orders and their delivery details.

```
INSERT INTO ORDERS
(Order_ID, Customer_ID, Restaurant_ID, Partner_ID,
 Order_Date, Total_Amount, Order_Status, Delivery_Status)
VALUES
(401, 1, 101, 201, '2026-10-15', 260.00, 'Delivered', 'Delivered'),
(402, 2, 102, 202, '2026-10-16', 150.00, 'Delivered', 'Delivered'),
(403, 3, 103, 203, '2026-10-17', 160.00, 'Delivered', 'Delivered'),
(404, 4, 104, 204, '2026-10-18', 280.00, 'Preparing', 'Pending'),
(405, 5, 105, 205, '2026-10-19', 120.00, 'Confirmed', 'Pending');
```

Five orders are inserted. Each order refers to an existing customer, restaurant, and delivery partner.

7. Inserting Data into ORDER_ITEM

The ORDER_ITEM table stores the food items included in each order.

```
INSERT INTO ORDER_ITEM
(Order_Item_ID, Order_ID, Item_ID, Quantity, Subtotal)
VALUES
(501, 401, 301, 1, 220.00),
(502, 401, 302, 1, 40.00),
(503, 402, 303, 1, 150.00),
(504, 403, 304, 2, 160.00),
(505, 404, 305, 1, 280.00),
```

(506, 405, 306, 2, 120.00);

Six order-item records are inserted. Each record refers to an existing order and menu item. The quantities are positive, and the subtotals are non-negative.

8. Inserting Data into PAYMENT

The PAYMENT table stores payment details for orders.

```
INSERT INTO PAYMENT
(Payment_ID, Order_ID, Payment_Date, Payment_Method,
 Amount, Payment_Status)
VALUES
(601, 401, '2026-10-15', 'UPI', 260.00, 'Successful'),
(602, 402, '2026-10-16', 'Card', 150.00, 'Successful'),
(603, 403, '2026-10-17', 'Cash', 160.00, 'Successful'),
(604, 404, '2026-10-18', 'UPI', 280.00, 'Pending'),
(605, 405, '2026-10-19', 'Card', 120.00, 'Pending');
```

Five payment records are inserted. Each order has one payment record, satisfying the UNIQUE constraint on PAYMENT.Order_ID.

9. Verifying the Inserted Records

The following commands display the inserted data in each table.

- SELECT * FROM CUSTOMER;
- SELECT * FROM RESTAURANT;
- SELECT * FROM DELIVERY_PARTNER;
- SELECT * FROM MENU_ITEM;
- SELECT * FROM ORDERS;
- SELECT * FROM ORDER_ITEM;
- SELECT * FROM PAYMENT;

To check the number of records in each table, execute:

- SELECT COUNT(*) AS Total_Customers FROM CUSTOMER;
- SELECT COUNT(*) AS Total_Restaurants FROM RESTAURANT;
- SELECT COUNT(*) AS Total_Delivery_Partners FROM DELIVERY_PARTNER;
- SELECT COUNT(*) AS Total_Menu_Items FROM MENU_ITEM;

- SELECT COUNT(*) AS Total_Orders FROM ORDERS;
- SELECT COUNT(*) AS Total_Order_Items FROM ORDER_ITEM;
- SELECT COUNT(*) AS Total_Payments FROM PAYMENT;

Expected record counts:

Table	Number of Records
CUSTOMER	5
RESTAURANT	5
DELIVERY_PARTNER	5
MENU_ITEM	8
ORDERS	5
ORDER_ITEM	6
PAYMENT	5

Conclusion

Sample data was successfully prepared for all seven tables of the Food Delivery Management System. A total of 39 records were included to represent customers, restaurants, menu items, delivery partners, orders, order items, and payments. The records use valid primary and foreign key references, unique customer emails, valid ratings, non-negative amounts, and positive order-item quantities. This sample data can be used to test SQL queries and analyze the operations of the database.