



Bhuvaneshvari S 250701111-2025-CSE ▾

B2

Started on Tuesday, 6 October 2026, 6:20 PM

State Finished

Completed on Tuesday, 6 October 2026, 6:21 PM

Time taken 1 min 8 secs

Marks 1.00/1.00

Grade **10.00** out of 10.00 (**100%**)

Question 1 | Correct Mark 1.00 out of 1.00

Find Duplicate in Array.

Given a read only array of n integers between 1 and n, find one number that repeats.

Input Format:

First Line - Number of elements

n Lines - n Elements

Output Format:

Element x - That is repeated

For example:

Input	Result
5 1 1 2 3 4	1

Answer: (penalty regime: 0 %)

```

1  #include<stdio.h>
2  int main(){
3  int n;
4  scanf("%d",&n);
5  int a[n];
6  for(int i=0;i<n;i++)
7  scanf("%d",&a[i]);
8  for(int i=0;i<n;i++){
9  for(int j=i+1;j<n;j++){
10 if(a[i]==a[j]){
11 printf("%d",a[i]);
12 return 0;
13 }
14 }
15 }
16 return 0;
17 }
```

	Input	Expected	Got	
✓	11 10 9 7 6 5 1 2 3 8 4 7	7	7	✓
✓	5 1 2 3 4 4	4	4	✓
✓	5 1 1 2 3 4	1	1	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

[Back to Course](#)



Started on Tuesday, 6 October 2026, 6:21 PM

State Finished

Completed on Tuesday, 6 October 2026, 6:22 PM

Time taken 42 secs

Marks 1.00/1.00

Grade **10.00** out of 10.00 (**100%**)

Question 1 | Correct Mark 1.00 out of 1.00

Find Duplicate in Array.

Given a read only array of n integers between 1 and n, find one number that repeats.

Input Format:

First Line - Number of elements

n Lines - n Elements

Output Format:

Element x - That is repeated

For example:

Input	Result
5 1 1 2 3 4	1

Answer: (penalty regime: 0 %)

```

1  #include<stdio.h>
2  int main(){
3      int n;
4      scanf("%d",&n);
5      int a[n];
6      for(int i=0;i<n;i++){
7          scanf("%d",&a[i]);
8      }
9      for(int i=0;i<n;i++){
10         for(int j=i+1;j<n;j++){
11             if(a[i]==a[j]){
12                 printf("%d",a[i]);
13             }
14         }
15     }
16     return 0;
17 }
```

	Input	Expected	Got	
✓	11 10 9 7 6 5 1 2 3 8 4 7	7	7	✓
✓	5 1 2 3 4 4	4	4	✓
✓	5 1 1 2 3 4	1	1	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

[Back to Course](#)

**Bhuvaneshvari S 250701111-2025-CSE** ▾**B2****Started on** Tuesday, 6 October 2026, 6:23 PM**State** Finished**Completed on** Tuesday, 6 October 2026, 6:26 PM**Time taken** 3 mins 10 secs**Marks** 1.00/1.00**Grade** **10.00** out of 10.00 (**100%**)

Question 1 | Correct Mark 1.00 out of 1.00

Find the intersection of two sorted arrays.

OR in other words,

Given 2 sorted arrays, find all the elements which occur in both the arrays.

Input Format

· The first line contains T, the number of test cases. Following T lines contain:

1. Line 1 contains N1, followed by N1 integers of the first array
2. Line 2 contains N2, followed by N2 integers of the second array

Output Format

The intersection of the arrays in a single line

Example

Input:

```
1
3 10 17 57
6 2 7 10 15 57 246
```

Output:

```
10 57
```

Input:

```
1
6 1 2 3 4 5 6
2 1 6
```

Output:

```
1 6
```

For example:

Input	Result
1 3 10 17 57 6 2 7 10 15 57 246	10 57

Answer: (penalty regime: 0 %)

```
1 #include<stdio.h>
2 int main(){
3     int t;
4     scanf("%d",&t);
5     while(t--){
6         int n,m;
7         scanf("%d",&n);
8         int a[n];
9         for(int i=0;i<n;i++)
10            scanf("%d",&a[i]);
11        scanf("%d",&m);
12        int b[m];
13        for(int i=0;i<m;i++)
14            scanf("%d",&b[i]);
```

```

15 | int i=0,j=0;
16 | while(i<n&& j<m){
17 |     if(a[i]==b[j]){
18 |         printf("%d ",a[i]);
19 |         i++;
20 |         j++;
21 |     }
22 |     else if(a[i]<b[j])
23 |         i++;
24 |     else
25 |         j++;
26 |     }
27 |     printf("\n");
28 | }
29 | return 0;
30 | }

```

	Input	Expected	Got	
✓	1 3 10 17 57 6 2 7 10 15 57 246	10 57	10 57	✓
✓	1 6 1 2 3 4 5 6 2 1 6	1 6	1 6	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

[Back to Course](#)

**Bhuvaneshvari S 250701111-2025-CSE** ▾**B2****Started on** Tuesday, 6 October 2026, 6:24 PM**State** Finished**Completed on** Tuesday, 6 October 2026, 6:31 PM**Time taken** 6 mins 36 secs**Marks** 1.00/1.00**Grade** 10.00 out of 10.00 (100%)

Question 1 | Correct Mark 1.00 out of 1.00

Find the intersection of two sorted arrays.

OR in other words,

Given 2 sorted arrays, find all the elements which occur in both the arrays.

Input Format

· The first line contains T, the number of test cases. Following T lines contain:

1. Line 1 contains N1, followed by N1 integers of the first array
2. Line 2 contains N2, followed by N2 integers of the second array

Output Format

The intersection of the arrays in a single line

Example

Input:

```
1
3 10 17 57
6 2 7 10 15 57 246
```

Output:

```
10 57
```

Input:

```
1
6 1 2 3 4 5 6
2 1 6
```

Output:

```
1 6
```

For example:

Input	Result
1 3 10 17 57 6 2 7 10 15 57 246	10 57

Answer: (penalty regime: 0 %)

```
1 #include<stdio.h>
2 int main(){
3     int t;
4     scanf("%d",&t);
5     while(t--){
6         int n,m;
7         scanf("%d",&n);
8         int a[n];
9         for(int i=0;i<n;i++)
10            scanf("%d",&a[i]);
11        scanf("%d",&m);
12        int b[m];
13        for(int i=0;i<m;i++)
14            scanf("%d",&b[i]);
```

```

15 | int i=0,j=0;
16 | while(i<n&& j<m){
17 |     if(a[i]==b[j]){
18 |         printf("%d ",a[i]);
19 |         i++;
20 |         j++;
21 |     }
22 |     else if(a[i]<b[j])
23 |         i++;
24 |     else
25 |         j++;
26 |     }
27 |     printf("\n");
28 | }
29 | return 0;
30 | }

```

	Input	Expected	Got	
✓	1 3 10 17 57 6 2 7 10 15 57 246	10 57	10 57	✓
✓	1 6 1 2 3 4 5 6 2 1 6	1 6	1 6	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

[Back to Course](#)

**Bhuvaneshvari S 250701111-2025-CSE** ▾**B2****Started on** Tuesday, 6 October 2026, 6:25 PM**State** Finished**Completed on** Tuesday, 6 October 2026, 6:28 PM**Time taken** 2 mins 53 secs**Marks** 1.00/1.00**Grade** 10.00 out of 10.00 (100%)

Question 1 | Correct Mark 1.00 out of 1.00

Given an array A of sorted integers and another non negative integer k, find if there exists 2 indices i and j such that $A[j] - A[i] = k$, $i \neq j$.

Input Format:

First Line n - Number of elements in an array

Next n Lines - N elements in the array

k - Non - Negative Integer

Output Format:

1 - If pair exists

0 - If no pair exists

Explanation for the given Sample Testcase:

YES as $5 - 1 = 4$

So Return 1.

For example:

Input	Result
3 1 3 5 4	1

Answer: (penalty regime: 0 %)

```

1  #include<stdio.h>
2  int main(){
3  int n,k;
4  scanf("%d",&n);
5  int a[n];
6  for(int i=0;i<n;i++)
7  scanf("%d",&a[i]);
8  scanf("%d",&k);
9  int i=0,j=1;
10 while(i<n&&j<n){
11 if(i!=j&&a[j]-a[i]==k){
12 printf("1");
13 return 0;
14 }
15 else if(a[j]-a[i]<k)
16 j++;
17 else
18 i++;
19 if(i==j)
20 j++;
21 }
22 printf("0");
23 return 0;
24 }
```

	Input	Expected	Got	
✓	3 1 3 5 4	1	1	✓
✓	10 1 4 6 8 12 14 15 20 21 25 1	1	1	✓
✓	10 1 2 3 5 11 14 16 24 28 29 0	0	0	✓
✓	10 0 2 3 7 13 14 15 20 24 25 10	1	1	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

[Back to Course](#)

**Bhuvaneshvari S 250701111-2025-CSE** ▾**B2****Started on** Tuesday, 6 October 2026, 6:26 PM**State** Finished**Completed on** Tuesday, 6 October 2026, 6:31 PM**Time taken** 4 mins 50 secs**Marks** 1.00/1.00**Grade** 10.00 out of 10.00 (100%)

Question 1 | Correct Mark 1.00 out of 1.00

Given an array A of sorted integers and another non negative integer k, find if there exists 2 indices i and j such that $A[j] - A[i] = k$, $i \neq j$.

Input Format:

First Line n - Number of elements in an array

Next n Lines - N elements in the array

k - Non - Negative Integer

Output Format:

1 - If pair exists

0 - If no pair exists

Explanation for the given Sample Testcase:

YES as $5 - 1 = 4$

So Return 1.

For example:

Input	Result
3 1 3 5 4	1

Answer: (penalty regime: 0 %)

```

1  #include<stdio.h>
2  int main(){
3  int n,k;
4  scanf("%d",&n);
5  int a[n];
6  for(int i=0;i<n;i++)
7  scanf("%d",&a[i]);
8  scanf("%d",&k);
9  int i=0,j=1;
10 while(i<n&&j<n){
11 if(i!=j&&a[j]-a[i]==k){
12 printf("1");
13 return 0;
14 }
15 if(a[j]-a[i]<k)
16 j++;
17 else
18 i++;
19 if(i==j)
20 j++;
21 }
22 printf("0");
23 return 0;
24 }
```

	Input	Expected	Got	
✓	3 1 3 5 4	1	1	✓
✓	10 1 4 6 8 12 14 15 20 21 25 1	1	1	✓
✓	10 1 2 3 5 11 14 16 24 28 29 0	0	0	✓
✓	10 0 2 3 7 13 14 15 20 24 25 10	1	1	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

[Back to Course](#)