



Department of Computer Science and Engineering (Data Science)

Subject: Artificial Intelligence (DJ19DSC502)

AY: 2023-24

Experiment 1

(Problem Solving)

Name: Bhuvi Ghosh

Sap ID: 60009210191

Batch: D22

Aim: Implement domain specific functions for given problems required for problem solving.

Theory:

There are two domain specific functions required in all problem solving methods.

1. GoalTest Function:

goalTest(State) Returns *true* if the input state is the goal state and *false* otherwise.

goalTest(State, Goal) Returns *true* if *State* matches *Goal*, and *false* otherwise.

2. MoveGen function:

```
Initialize set of successors C to empty set.  
Add M to the complement of given state N to get new state S.  
If given state has Left, then add Right to S, else add Left.  
If legal(S) then add S to set of successors C.  
For each other-entity E in N  
    make a copy S' of S,  
    add E to S',  
    If legal (S'), then add S' to C.  
Return (C).
```

Lab Assignment to do:

Create MoveGen and GoalTest Functions for the given problems



Department of Computer Science and Engineering (Data Science)

1. Water Jug Problem

There are two jugs available of different volumes such as a 3 litres and a 7 litres and you have to measure a different volume such as 6 litre.

```
a = int(input("Enter water level in A: "))
b = int(input("Enter water level in B: "))
c = int(input("Enter water level in C: "))
current_state = (a, b, c)

def move_gen(current):
    moves = []
    a, b, c = current_state
    max_a, max_b, max_c = (3, 5, 8)
    print(f"Current State: A={a}, B={b}, C={c}")
    if a > 0:
        if b < max_b:
            pour = min(a, max_b - b)
            new_state = (a - pour, b + pour, c)
            moves.append(new_state)
        if c < max_c:
            pour = min(a, max_c - c)
            new_state = (a - pour, b, c + pour)
            moves.append(new_state)
    if b > 0:
        if a < max_a:
            pour_amount = min(b, max_a - a)
            new_state = (a + pour_amount, b - pour_amount, c)
            moves.append(new_state)
        if c < max_c:
            pour_amount = min(b, max_c - c)
            new_state = (a, b - pour_amount, c + pour_amount)
            moves.append(new_state)
    if c > 0:
        if a < max_a:
            pour_amount = min(c, max_a - a)
            new_state = (a + pour_amount, b, c - pour_amount)
            moves.append(new_state)
        if b < max_b:
            pour_amount = min(c, max_b - b)
            new_state = (a, b + pour_amount, c - pour_amount)
```



Department of Computer Science and Engineering (Data Science)

```
        moves.append(new_state)
    return moves
valid_moves = move_gen(current_state)

print("\nValid Moves:")
for move in valid_moves:
    print(move)
```

```
Enter water level in A: 3
Enter water level in B: 5
Enter water level in C: 8
Current State: A=0, B=0, C=8
Valid Moves:
(3, 5, 0)
(0, 5, 3)
(3, 0, 5)
```

2. Travelling Salesman Problem

A salesman is travelling and selling his/her product to in different cities. The condition is that it has to travel each city just once.



Department of Computer Science and Engineering (Data Science)

```
import itertools

def calculate_total_distance(tour, distance_matrix):
    total_distance = 0
    for i in range(len(tour) - 1):
        total_distance += distance_matrix[tour[i]][tour[i + 1]]
    total_distance += distance_matrix[tour[-1]][tour[0]]
    return total_distance

def generate_all_tsp_states(cities, distance_matrix):
    all_states = []
    num_cities = len(cities)
    all_permutations = list(itertools.permutations(range(num_cities)))

    for permutation in all_permutations:
        total_distance = calculate_total_distance(permutation, distance_matrix)
        all_states.append((permutation, total_distance))

    return all_states

if __name__ == "__main__":
    cities = ["City A", "City B", "City C", "City D"]
    distance_matrix = [
        [0, 10, 15, 20],
        [10, 0, 35, 25],
        [15, 35, 0, 30],
        [20, 25, 30, 0]
    ]

    all_states = generate_all_tsp_states(cities, distance_matrix)

    for state in all_states:
        print(f"Tour: {state[0]}, Total Distance: {state[1]}")
```



Department of Computer Science and Engineering (Data Science)

```
Tour: (0, 1, 2, 3), Total Distance: 95
Tour: (0, 1, 3, 2), Total Distance: 80
Tour: (0, 2, 1, 3), Total Distance: 95
Tour: (0, 2, 3, 1), Total Distance: 80
Tour: (0, 3, 1, 2), Total Distance: 95
Tour: (0, 3, 2, 1), Total Distance: 95
Tour: (1, 0, 2, 3), Total Distance: 80
Tour: (1, 0, 3, 2), Total Distance: 95
Tour: (1, 2, 0, 3), Total Distance: 95
Tour: (1, 2, 3, 0), Total Distance: 95
Tour: (1, 3, 0, 2), Total Distance: 95
Tour: (1, 3, 2, 0), Total Distance: 80
Tour: (2, 0, 1, 3), Total Distance: 80
Tour: (2, 0, 3, 1), Total Distance: 95
Tour: (2, 1, 0, 3), Total Distance: 95
Tour: (2, 1, 3, 0), Total Distance: 95
Tour: (2, 3, 0, 1), Total Distance: 95
Tour: (2, 3, 1, 0), Total Distance: 80
Tour: (3, 0, 1, 2), Total Distance: 95
Tour: (3, 0, 2, 1), Total Distance: 95
Tour: (3, 1, 0, 2), Total Distance: 80
Tour: (3, 1, 2, 0), Total Distance: 95
Tour: (3, 2, 0, 1), Total Distance: 80
Tour: (3, 2, 1, 0), Total Distance: 95
```

3. 8 Puzzle Problem

An initial state is given in a 8 puzzle where one place is blank out of 9 places. You can shift this blank space and get a different state to reach to a given goal state.



Department of Computer Science and Engineering (Data Science)

```
def movegen(board):
    possible_moves = []
    for row in range(3):
        for col in range(3):
            if(board[row][col] == 0):
                empty_row = row
                empty_col = col

    moves = ["Right", "Left", "Up", "Down"]
    for move in moves:
        if move == "Right":
            new_row = empty_row
            new_col = empty_col + 1
        elif move == "Left":
            new_row = empty_row
            new_col = empty_col - 1
        elif move == "Up":
            new_row = empty_row - 1
            new_col = empty_col
        elif move == "Down":
            new_row = empty_row + 1
            new_col = empty_col
        if (0 <= new_row < 3) and (0 <= new_col < 3):
            new_board = [row[:] for row in board]
            new_board[empty_row][empty_col], new_board[new_row][new_col] = new_board[new_row][new_col], new_board[empty_row][empty_col]
            possible_moves.append((f"move - {move}", new_board))

    return possible_moves

initial_board = [[1, 2, 3], [4, 0, 5], [6, 7, 8]]

moves = movegen(initial_board)
for move in moves:
    print(move)
```

```
('move - Right', [[1, 2, 3], [4, 5, 0], [6, 7, 8]])
('move - Left', [[1, 2, 3], [0, 4, 5], [6, 7, 8]])
('move - Up', [[1, 0, 3], [4, 2, 5], [6, 7, 8]])
('move - Down', [[1, 2, 3], [4, 7, 5], [6, 0, 8]])
```