RAJALAKSHMI ENGINEERING COLLEGE

Bhuwanesh Kumar K 251801044-2025-AIDS B2

Started on	Saturday, 8 August 2026, 2:38 PM
State	Finished
Completed on	Saturday, 8 August 2026, 2:39 PM
Time taken	59 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 1.00 out of 1.00

Problem Statement:

Given a sorted array of integers say arr[] and a number x. Write a recursive program using divide and conquer strategy to check if there exist two elements in the array whose sum = x. If there exist such two elements then return the numbers, otherwise print as "No".

Note: Write a Divide and Conquer Solution

Input Format

First Line Contains Integer n – Size of array

Next n lines Contains n numbers – Elements of an array

Last Line Contains Integer x – Sum Value

Output Format

First Line Contains Integer – Element1

Second Line Contains Integer – Element2 (Element 1 and Elements 2 together sums to value "x")

Answer: (penalty regime: 0 %)

```c
#include <stdio.h>
#include <stdlib.h>

void findPairSum(int arr[], int left, int right, int x) {
    if (left >= right) {
        printf("No\n");
        return;
    }

    int current_sum = arr[left] + arr[right];

    if (current_sum == x) {
        printf("%d\n", arr[left]);
        printf("%d\n", arr[right]);
        return;
    } else if (current_sum > x) {
        findPairSum(arr, left, right - 1, x);
    } else {
        findPairSum(arr, left + 1, right, x);
    }
}

int main() {
    int n;
    if (scanf("%d", &n) != 1) return 0;

    int *arr = (int *)malloc(n * sizeof(int));
    for (int i = 0; i < n; i++) {
        if (scanf("%d", &arr[i]) != 1) {
            free(arr);
            return 0;
        }
    }

    int x;
    if (scanf("%d", &x) != 1) {
        free(arr);
        return 0;
    }

    findPairSum(arr, 0, n - 1, x);

    free(arr);
    return 0;
}

```

	Input	Expected	Got	
✔	4 2 4 8 10 14	4 10	4 10	✔
✔	5 2 4 6 8 10 100	No	No	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Back to Course