

Improving Robustness in Social Fabric-based Cultural Algorithms

Bahram Zaeri¹

Advisor: Dr. Ziad Kobti¹

Internal Reader: Dr. Mehdi Kargar¹

External Reader: Dr. Kemal Tepe²

¹University of Windsor, School of Computer Science

²University of Windsor, Dept. of Electrical and Computer Eng.

Master Thesis Defense

Outline

- 1 Introduction
- 2 Related Works
- 3 Evolutionary Computation
- 4 Cultural Algorithms
- 5 Social Fabric
- 6 PSO
- 7 Proposed Approaches
- 8 Evaluation Results
- 9 Applications

What is Evolutionary Computation(EC)?

Evolutionary Computation

Evolutionary algorithms are natural-inspired, population-based, iterative and utilize step-by-step improvement approaches. [Eiben and Smith, 2003]

- Genetic Algorithm
- Cultural Algorithms
- Particle Swarm Optimization
- Ant Colony Optimization

Robustness

Robustness in Evolutionary Algorithms

- The ability to address a vast range of problems with particular qualities with a minimum number of adjustments.
- Self-organized algorithms can learn and adapt themselves to different search landscapes.
- Such strategies improve robustness in population-based algorithms.

Social Fabric

- Social Fabric was proposed by [Ali, 2008]
- The Social Fabric is a dynamic information skin created by the agents interactions in a social context.
- Social interactions between individuals are modeled using an undirected graph $G(V; E)$ [Sterling, 2004].
- In this research work, The Social Fabric approach is used to improve the search behavior of evolutionary algorithms in multi-dimensional search spaces.

Research Motivation

Optimization Problems

- CEC-2015 expensive optimization problem set is used to evaluate the proposed approaches. [Chen et al., 2014]

$$Y = f(x_1, x_2, x_3, \dots, x_D) \quad (1)$$

For example:

$$f_1(x) = x_1^2 + 10^6 \sum_{i=2}^D x_i^2 \quad (2)$$

Research Goals

- In this research work, we improved Cultural Algorithms from three aspects:
- Applying PSO algorithm to current Social Fabric based CAs.
- Introducing a Irregular Neighborhood Restructuring operator to increase the level of diversity.
- Improving the robustness of the Belief Space by introducing a Confidence-based knowledge source inspired from Statistics.
- For the comparison purpose, we used CEC2015 benchmark optimization functions.

Related Works I

- [Ali, 2008] introduced the idea of Social Fabric as a new influence function in CA by deploying a social network between individuals.
- [Che et al., 2010] replaced the traditional idea of roulette wheel with the vector voting model to determine the controller KS in each iteration.
- [Ali et al., 2012] introduced the neighborhood restructuring in Social Fabric with a two-layered multi-population CA model.
- [Chen et al., 2006] introduced Tribe-PSO algorithm as a multi-tribe population-based algorithm to utilize the parallel nature of evolutionary algorithms.

Related Works II

- [De Oca et al., 2009] investigates different types of heterogeneity in PSO algorithm in three categories: neighborhood, update rule and parameters.
- [Ali et al., 2016] gives a detailed description of Social Fabric based MPCA with neighborhood restructuring. It, also, proves its optimality against different optimization algorithms based on an extended benchmark testbed.

Socially inspired algorithms

Swarm Intelligence

[Kennedy et al., 2001] Swarm Intelligence algorithms utilize a population of semi-rational agents that have the ability to communicate and cooperate with other agents in a **self-organized** manner.

- Cultural Algorithms(CA) [Reynolds, 1994]
- Particle Swarm Optimization(PSO) [Clerc, 2010]
- Ant Colony Optmization(ACO) [Dorigo et al., 2006]

Cultural Algorithms

CAs are composed of three components: **Population space**, **Belief space** and **Communication protocol**.




Figure: Cultural Algorithms

Cultural Algorithms

Belief Space

There are five types of **knowledge sources** in the Belief Space.
[Reynolds et al., 2010]

- Situational Knowledge
- Normative Knowledge
- Topographic Knowledge
- Domain Knowledge
- Historical Knowledge

Social Fabric

Social Fabric based CA

- In this model of CA, knowledge sources are allowed to influence the population through layers of networks.
- The interplay of these layers and networks leads us to the concept of "**Social Fabric**". [Reynolds and Ali, 2008]
- The population is divided into multiple subgroups or **tribes**. [Ali et al., 2016]

Social Fabric





Figure: Social Fabric: [Reynolds et al., 2010]

Dynamic Neighborhood Restructuring

Strategic Restructuring

- After a certain number of iterations without any progress in search behavior, the current topology is changed.



Particle Swarm Optimization

- PSO works based on the theory of social learning. Individuals (Particles) move around the search space.
- Such behaviours could be observed in natural groupings such as flocks of birds, colonies of bees, etc.





Figure: PSO

Particle Swarm Optimization

Tribe-PSO

- The whole population is divided into independent tribes. [Chen et al., 2006]
- Particles fall into two layers, and the whole process consists of three phases.
- Best particles of each tribe form the upper layer of elites.



Thesis Statement

- Based on the No Free Lunch (NFL) theorem , there is no algorithm better than others over all cost functions.
- So, robustness is one of the most desired features in search algorithms.
- Here, robustness means to develop search strategies which adapt across different landscapes.
- We improve the robustness of CAs in both population and belief components.

Proposed Approach I

Irregular Neighborhood Restructuring

- Each individual decides to increase/decrease its own neighbourhood size based on its experience.




Figure:

Proposed Approach I

Pseudo-Code

```

if  $fitness(x_i) > bestSoFar_i$  then
  if  $stagnationCounter \geq TiggerThreshold$  then
    if  $x_i == x_{best}$  then
      index = selected randomly from  $x_i$ 's neighbourhood
      remove  $x_{index}$  from  $x_i$ 's neighborhood
    else
      index = selected from  $\{S - x_i's neighborhood\}$ 
      add  $x_{index}$  to  $x_i$ 's neighbourhood
    end
     $stagnationCounter \leftarrow 0$ 
  else
     $stagnationCounter \leftarrow stagnationCounter + 1$ 
  end
else
   $stagnationCounter \leftarrow 0$ 

```

Proposed Approach II

Confidence-based Normative KS

- The standard normative KS works based on constructing a dynamic range for feasible solutions.
- A confidence interval provides a range of values which is likely to contain a certain percentage of a population.

$$(\bar{x} - q \cdot \frac{\sigma}{\sqrt{n}}, \bar{x} + q \cdot \frac{\sigma}{\sqrt{n}})$$

\bar{x} : mean , σ : standard deviation , q : confidence coefficient

Evaluation Results

Table:

		10 Dimensions				30 Dimensions			
		ISFCA	CSFCA	SFCA	TPSO	ISFCA	CSFCA	SFCA	TPSO
T1	Best	5.711750E+06	9.279149E+05	9.908642E+08	5.415067E+05	1.075684E+10	3.249525E+08	8.929425E+09	1.136511E+10
	Mean	1.576602E+08	4.091655E+09	9.246107E+09	2.479394E+08	1.497176E+10	2.168689E+10	3.786293E+10	1.718683E+10
	Std Dev	3.066335E+08	6.639431E+09	8.500530E+09	3.993037E+08	6.549615E+09	2.551255E+10	2.853221E+10	7.102879E+09
T2	Best	1.690419E+04	1.426333E+04	2.467511E+04	1.722714E+04	6.816396E+04	5.556673E+04	7.322705E+04	1.112664E+05
	Mean	1.970646E+04	2.045944E+09	3.574556E+09	2.202554E+04	7.324758E+04	1.090201E+08	2.266584E+09	1.324195E+05
	Std Dev	5.285568E+03	4.083561E+09	4.508859E+09	5.505069E+03	1.112414E+04	2.214664E+08	4.323029E+09	1.359207E+04
T3	Best	3.047026E+02	3.075572E+02	3.086619E+02	3.055813E+02	3.274619E+02	3.352212E+02	3.360418E+02	3.275333E+02
	Mean	3.055362E+02	3.095236E+02	3.108567E+02	3.064904E+02	3.307785E+02	3.400480E+02	3.410312E+02	3.305742E+02
	Std Dev	9.238688E-01	2.153735E+00	2.160320E+00	9.113892E-01	3.242337E+00	4.748334E+00	4.694844E+00	3.905358E+00
T4	Best	1.249122E+03	6.135802E+02	8.405862E+02	1.201363E+03	6.625647E+03	1.377132E+03	3.463489E+03	6.882440E+03
	Mean	1.401458E+03	1.392015E+03	1.725446E+03	1.391022E+03	6.964474E+03	4.998230E+03	6.375121E+03	7.270199E+03
	Std Dev	1.709634E+02	8.047924E+02	8.388958E+02	2.174364E+02	4.205720E+02	3.054933E+03	2.436783E+03	4.387157E+02
T5	Best	5.010726E+02	5.007002E+02	5.011836E+02	5.011289E+02	5.028153E+02	5.016618E+02	5.020560E+02	5.026209E+02
	Mean	5.013300E+02	5.017117E+02	5.023857E+02	5.013223E+02	5.030805E+02	5.031380E+02	5.036162E+02	5.029678E+02
	Std Dev	2.684750E-01	1.132619E+00	1.339239E+00	2.057213E-01	3.548877E-01	1.669277E+00	1.678840E+00	3.015601E-01
T6	Best	6.004334E+02	6.005685E+02	6.018524E+02	6.005062E+02	6.024192E+02	6.010681E+02	6.041570E+02	6.010077E+02
	Mean	6.005623E+02	6.025225E+02	6.036813E+02	6.009515E+02	6.030236E+02	6.039768E+02	6.056628E+02	6.019309E+02
	Std Dev	3.200289E-01	2.304279E+00	1.898523E+00	6.229300E-01	7.579661E-01	2.740738E+00	1.433152E+00	1.224478E+00
T7	Best	7.006188E+02	7.007965E+02	7.100632E+02	7.004902E+02	7.271223E+02	7.024000E+02	7.544377E+02	7.262179E+02
	Mean	7.019942E+02	7.260979E+02	7.418000E+02	7.038384E+02	7.389013E+02	7.605963E+02	8.116680E+02	7.498652E+02
	Std Dev	2.635216E+00	3.539268E+01	3.490056E+01	5.486938E+00	1.569694E+01	5.981939E+01	5.740507E+01	2.791729E+01

Evaluation Results

Table:

		10 Dimensions				30 Dimensions			
		ISFCA	CSFCA	SFCA	TPSO	ISFCA	CSFCA	SFCA	TPSO
T8	Best	8.060488E+02	8.475602E+02	4.118304E+03	8.057399E+02	5.240269E+04	1.095824E+03	8.508643E+04	4.126489E+05
	Mean	8.327824E+02	3.080861E+05	1.374142E+06	8.319941E+02	3.363145E+05	7.477703E+06	1.541796E+07	1.645666E+06
	Std Dev	1.428379E+02	5.970746E+05	1.940514E+06	7.254239E+01	6.891847E+05	1.270040E+07	2.340250E+07	1.667678E+06
T9	Best	9.035325E+02	9.032589E+02	9.033602E+02	9.035094E+02	9.133757E+02	9.126562E+02	9.131192E+02	9.134243E+02
	Mean	9.036469E+02	9.036343E+02	9.038043E+02	9.036178E+02	9.135258E+02	9.133575E+02	9.136351E+02	9.135977E+02
	Std Dev	1.008688E-01	3.372815E-01	4.187602E-01	1.037992E-01	1.312660E-01	5.882330E-01	4.913793E-01	1.390313E-01
T10	Best	2.148022E+04	2.365329E+03	6.578523E+03	1.417589E+04	6.072906E+06	2.225892E+06	8.682100E+06	1.311979E+07
	Mean	6.855882E+04	1.390710E+06	1.250589E+07	6.576307E+04	1.288355E+07	5.268560E+07	7.171894E+07	1.914266E+07
	Std Dev	7.234730E+04	1.778552E+06	2.276703E+07	7.783437E+04	7.703664E+06	5.803312E+07	5.952516E+07	8.464172E+06
T11	Best	1.104062E+03	1.106581E+03	1.105492E+03	1.104723E+03	1.153360E+03	1.155965E+03	1.290852E+03	1.134562E+03
	Mean	1.105085E+03	1.137076E+03	1.140188E+03	1.105442E+03	1.197912E+03	1.456495E+03	1.724513E+03	1.174516E+03
	Std Dev	1.339530E+00	5.229237E+01	4.994351E+01	9.340507E-01	4.334944E+01	4.589486E+02	5.277303E+02	6.235017E+01
T12	Best	1.247398E+03	1.342194E+03	1.419410E+03	1.259420E+03	2.100877E+03	1.748342E+03	2.153439E+03	2.280177E+03
	Mean	1.284340E+03	3.740383E+03	2.109208E+04	1.290392E+03	2.317707E+03	3.578488E+07	1.123866E+08	2.392247E+03
	Std Dev	4.080435E+01	4.569942E+03	3.705284E+04	4.016558E+01	2.430944E+02	7.154759E+07	1.253791E+08	1.588321E+02
T13	Best	1.622335E+03	1.635087E+03	1.676418E+03	1.618919E+03	1.723534E+03	1.740536E+03	2.380543E+03	1.732389E+03
	Mean	1.627982E+03	2.128914E+03	2.376883E+03	1.628781E+03	1.778258E+03	3.445463E+03	3.691270E+03	1.840829E+03
	Std Dev	7.106025E+00	6.591729E+02	7.972695E+02	1.445686E+01	9.665278E+01	2.272010E+03	1.367277E+03	1.457157E+02
T14	Best	1.601385E+03	1.591111E+03	1.597342E+03	1.604991E+03	1.646723E+03	1.660532E+03	1.693461E+03	1.658174E+03
	Mean	1.602429E+03	1.607129E+03	1.623200E+03	1.606235E+03	1.676279E+03	1.791878E+03	1.865010E+03	1.685711E+03
	Std Dev	1.577398E+00	1.953208E+01	2.617243E+01	1.478468E+00	2.842502E+01	1.553106E+02	1.760265E+02	3.566090E+01
T15	Best	1.525130E+03	1.871689E+03	1.855628E+03	1.772940E+03	2.498940E+03	2.227419E+03	3.055342E+03	2.504910E+03
	Mean	1.589476E+03	1.946018E+03	1.966892E+03	1.871080E+03	2.582142E+03	3.063021E+03	3.657078E+03	2.565208E+03
	Std Dev	8.426385E+01	8.447839E+01	1.134500E+02	7.850262E+01	9.012990E+01	1.040607E+03	1.152769E+03	8.765290E+01

Evaluation Results




Figure: ISFCA Improvement

Evaluation Results




Figure: CSFCA Improvement

Application: Community Detection in Social Networks




Figure: Community Detection

Application: Community Detection in Social Networks

Two factors to use EAs

- Model the individuals as solutions to the problem.
 - Define a fitness function
-
- We adopt the Spectral method used by [Shi et al., 2009] and [Capocci et al., 2005]
 - The spectral method weighted distance defines a dissimilarity measure between network nodes.

$$dis_{i,j} = \sqrt{\sum_{k=1}^{m-1} A_k * (v_{ki} - v_{kj})} \quad (3)$$

Application: Community Detection in Social Networks

Center existence array				Center array			
flag ₁	flag ₂	...	flag _m	center ₁	center ₂	...	center _m

Figure: Structure of Particles

Modularity-based Fitness Function

$$Q = \sum_{i=1}^n (e_{ij} - a_i^2) \quad (4)$$

$$a_i = \sum_{j=1}^n e_{ij} \quad (5)$$

Publications

- Title: Improving Robustness in Social Fabric-based Cultural Algorithms with Two New Approaches in Population and Belief Spaces
 - Conference: FLAIRS-2017
 - Status: Accepted for publication
-
- Title: Self-Organized Neighborhood Restructuring in Social Fabric
 - Conference: Canadian AI 2017
 - Status: Submitted.

References I



Ali, M. Z. (2008).

Using cultural algorithms to solve optimization problems with a social fabric approach.
ProQuest.



Ali, M. Z., Salhie, A. M., and Reynolds, R. G. (2012).

Socio-cultural evolution via neighborhood-restructuring in intricate multi-layered networks.
In *2012 IEEE Congress on Evolutionary Computation*, pages 1–8. IEEE.



Ali, M. Z., Suganthan, P. N., Reynolds, R. G., and Al-Badarneh, A. F. (2016).

Leveraged neighborhood restructuring in cultural algorithms for solving real-world numerical optimization problems.
IEEE transactions on evolutionary computation, 20(2):218–231.



Capocci, A., Servidio, V. D., Caldarelli, G., and Colaioni, F. (2005).

Detecting communities in large networks.
Physica A: Statistical Mechanics and its Applications, 352(2):669–676.



Che, X., Ali, M., and Reynolds, R. G. (2010).

Robust evolution optimization at the edge of chaos: Commercialization of culture algorithms.
In *IEEE Congress on Evolutionary Computation*, pages 1–8. IEEE.



Chen, K., Li, T., and Cao, T. (2006).

Tribe-pso: A novel global optimization algorithm and its application in molecular docking.
Chemometrics and intelligent laboratory systems, 82(1):248–259.

References II



Chen, Q., Liu, B., Zhang, Q., Liang, J., Suganthan, P., and Qu, B. (2014).

Problem definitions and evaluation criteria for cec 2015 special session on bound constrained single-objective computationally expensive numerical optimization.

Technical report, Technical Report, Computational Intelligence Laboratory, Zhengzhou University, Zhengzhou.



Clerc, M. (2010).

Particle swarm optimization, volume 93.

John Wiley & Sons.



De Oca, M. A. M., Peña, J., Stutzle, T., Pinciroli, C., and Dorigo, M. (2009).

Heterogeneous particle swarm optimizers.

In *2009 IEEE Congress on Evolutionary Computation*, pages 698–705. IEEE.



Dorigo, M., Birattari, M., and Stutzle, T. (2006).

Ant colony optimization.

IEEE computational intelligence magazine, 1(4):28–39.



Eiben, A. E. and Smith, J. E. (2003).

Introduction to evolutionary computing, volume 53.

Springer.



Kennedy, J., Kennedy, J. F., Eberhart, R. C., and Shi, Y. (2001).

Swarm intelligence.

Morgan Kaufmann.

References III



Reynolds, R. G. (1994).

An introduction to cultural algorithms.

In Proceedings of the third annual conference on evolutionary programming, volume 131139. Singapore.



Reynolds, R. G. and Ali, M. (2008).

Computing with the social fabric: The evolution of social intelligence within a cultural framework.

IEEE computational intelligence magazine, 3(1):18–30.



Reynolds, R. G., Che, X., and Ali, M. (2010).

Weaving the social fabric: The past, present and future of optimization problem solving with cultural algorithms.

International Journal of Intelligent Computing and Cybernetics, 3(4):561–592.



Shi, Z., Liu, Y., and Liang, J. (2009).

Pso-based community detection in complex networks.

In Knowledge Acquisition and Modeling, 2009. KAM'09. Second International Symposium on, volume 3, pages 114–119. IEEE.



Sterling, S. E. (2004).

Aggregation techniques to characterize social networks.

Technical report, DTIC Document.