

МИНИСТЕРСТВО ОБРАЗОВАНИЯ И НАУКИ РОССИЙСКОЙ ФЕДЕРАЦИИ
МОСКОВСКИЙ АВИАЦИОННЫЙ ИНСТИТУТ
(НАЦИОНАЛЬНЫЙ ИССЛЕДОВАТЕЛЬСКИЙ УНИВЕРСИТЕТ)

ЛАБОРАТОРНАЯ РАБОТА №5

по курсу “Объектно-ориентированное программирование”

I семестр, 2021/22 учебный год

Студент: Степанов Данила Михайлович, группа М8О-207Б-20

Преподаватель: Дорохов Евгений Павлович, каф. 806

Задание:

Необходимо спроектировать и запрограммировать на языке C++ класс-контейнер первого уровня, содержащий одну фигуру (колонка фигура 1), согласно вариантам задания. Классы должны удовлетворять следующим правилам:

- Требования к классу фигуры аналогичны требованиям из лабораторной работы №1;
- Требования к классу контейнера аналогичны требованиям из лабораторной работы No2;
- Класс-контейнер должен содержать объекты, используя `std::shared_ptr<...>`.

Нельзя использовать:

- Стандартные контейнеры `std`;
- Шаблоны (`template`);
- Объекты «по значению».

Программа должна позволять:

- Вводить произвольное количество фигур и добавлять их в контейнер.
- Распечатывать содержимое контейнера.
- Удалять фигуры из контейнера.

Вариант №24:

- Фигура: 8-угольник (Octagon)
- Контейнер: N-дерево (TNaryTree)

Описание программы:

Исходный код разделён на 9 файлов:

- `figure.h` – описание класса фигуры
- `point.h` – описание класса точки
- `point.cpp` – реализация класса точки
- `octagon.h` – описание класса 8-угольника
- `octagon.cpp` – реализация класса 8-угольника
- `TNaryTree_item.h` – описание элемента N-дерева
- `TNaryTree.h` – описание N-дерева

- TNaryTree.cpp – реализация N-дерева
- main.cpp – основная программа

Дневник отладки:

Проблем не возникло.

Тестирование программы:

The tree is empty !

0.5: [36: [12: [16.5, 16.5], 6.5], 7.5: [6, 16.5], 3.5: [21]]

44

0.5: [36: [12: [16.5, 16.5], 6.5], 7.5: [6, 16.5], 3.5: [21]]

Octagon: (1, 4) (1, 2) (5, 6) (2, 8) (3, 1) (2, 6) (9, 5) (5, 4)

The tree is not empty !

Вывод:

В лабораторной работе я познакомился с таким элементом языка C++ как умные указатели, которые позволяют избежать основных ошибок работы с памятью, так как обязанность освобождения памяти возлагается именно на них, а не на программиста. Также я обновил свой класс-контейнер N-дерева, хрянящий теперь объекты, используя `std::shared_ptr<...>`.

Исходный код:

point.h:

```
#ifndef POINT_H
#define POINT_H

#include <iostream>

class Point {
public:
    Point();
    Point(std::istream &is);
    Point(double x, double y);

    double dist(Point& other);
    double getX();
    double getY();

    friend std::istream& operator>>(std::istream& is, Point& p);
    friend std::ostream& operator<<(std::ostream& os, Point& p);

private:
    double x_;
    double y_;
```

```
};  
#endif
```

point.cpp:

```
#include "point.h"  
  
#include <cmath>  
  
Point::Point() : x_(0.0), y_(0.0) {}  
  
Point::Point(double x, double y) : x_(x), y_(y) {}  
  
Point::Point(std::istream &is) {  
    is >> x_ >> y_;  
}  
  
double Point::dist(Point& other) {  
    double dx = (other.x_ - x_);  
    double dy = (other.y_ - y_);  
    return std::sqrt(dx*dx + dy*dy);  
}  
  
double Point::getX()  
{  
    return x_;  
}  
  
double Point::getY()  
{  
    return y_;  
}  
  
std::istream& operator>>(std::istream& is, Point& p) {  
    is >> p.x_ >> p.y_;  
    return is;  
}  
  
std::ostream& operator<<(std::ostream& os, Point& p) {  
    os << "(" << p.x_ << ", " << p.y_ << ")";  
    return os;  
}
```

figure.h:

```
#ifndef FIGURE_H  
#define FIGURE_H  
  
#include "point.h"  
  
class Figure  
{  
public:  
    virtual size_t VertexesNumber() = 0;  
    virtual double Area() = 0;  
    virtual void Print(std::ostream& os) = 0;  
};  
  
#endif
```

octagon.h:

```
#ifndef OCTAGON_H
#define OCTAGON_H

#include "figure.h"

class Octagon : Figure
{
public:
    Octagon(std::istream& is);
    size_t VertexesNumber();
    double Area();
    void Print(std::ostream& os);

private:
    Point a_, b_, c_, d_;
    Point e_, f_, g_, h_;
};

#endif
```

octagon.cpp:

```
#include "octagon.h"

Octagon::Octagon(std::istream& is)
{
    std::cin >> a_ >> b_ >> c_ >> d_;
    std::cin >> e_ >> f_ >> g_ >> h_;
}

size_t Octagon::VertexesNumber()
{
    return (size_t)8;
}

double Octagon::Area()
{
    return 0.5 * abs((a_.getX() * b_.getY() + b_.getX() * c_.getY() + c_.getX() * d_.getY() + d_.getX() * e_.getY() + e_.getX() * f_.getY() + f_.getX() * g_.getY() + g_.getX() * h_.getY() + h_.getX() * a_.getY() - (b_.getX() * a_.getY() + c_.getX() * b_.getY() + d_.getX() * c_.getY() + e_.getX() * d_.getY() + f_.getX() * e_.getY() + g_.getX() * f_.getY() + h_.getX() * g_.getY() + a_.getX() * h_.getY())));
}

void Octagon::Print(std::ostream& os)
{
    std::cout << "Octagon: " << a_ << " " << b_ << " ";
    std::cout << c_ << " " << d_ << " " << e_ << " ";
    std::cout << f_ << " " << g_ << " " << h_ << "\n";
}
```

TNaryTree_item.h:

```
#ifndef TNARYTREE_ITEM
#define TNARYTREE_ITEM

#include "octagon.h"
#include <memory>
```

```

class TreeItem
{
public:
    std::shared_ptr<octagon> figure;
    int cur_size;
    std::shared_ptr<TreeItem> son;
    std::shared_ptr<TreeItem> brother;
    std::shared_ptr<TreeItem> parent;
};

#endif

```

TNaryTree.h:

```

#include "octagon.h"
#include "TNaryTree_item.h"
#include <memory>

class TNaryTree
{
public:
    TNaryTree(int n);
    TNaryTree(const TNaryTree& other);
    TNaryTree();

    void Update(const std::shared_ptr<octagon> &&polygon, const std::string &&tree_path)
    {
        Update(&root, polygon, tree_path);
    }

    void Update(const std::shared_ptr<octagon> &polygon, const std::string &tree_path)
    {
        Update(&root, polygon, tree_path);
    }

    const std::shared_ptr<octagon>& GetItem(const std::string& tree_path)
    {
        return GetItem(&root, tree_path);
    }

    void RemoveSubTree(const std::string &&tree_path);
    void RemoveSubTree(const std::string &tree_path);
    bool Empty();
    double Area(std::string&& tree_path);
    double Area(std::string& tree_path);
    friend std::ostream& operator<<(std::ostream& os, const TNaryTree& tree);
    virtual ~TNaryTree();

private:
    int size;
    std::shared_ptr<TreeItem> root;
    void Update(std::shared_ptr<TreeItem>* root, std::shared_ptr<octagon> polygon, std::string tree_path);
    const std::shared_ptr<octagon>& GetItem(std::shared_ptr<TreeItem>* root, const std::string tree_path);
};

#endif

```

TNaryTree.cpp:

```

#include "TNaryTree.h"
#include "TNaryTree_item.h"

TNaryTree::TNaryTree(int n)
{
    this->size = n;
    this->root = nullptr;
}

std::shared_ptr<TreeItem> tree_copy(std::shared_ptr<TreeItem> root)
{
    if (root != nullptr) {
        std::shared_ptr<TreeItem> new_root (new TreeItem);
        new_root->figure = root->figure;
        new_root->son = nullptr;
        new_root->brother = nullptr;
        if (root->son != nullptr) {
            new_root->son = tree_copy(root->son);
        }
        if (root->brother != nullptr) {
            new_root->brother = tree_copy(root->brother);
        }
        return new_root;
    }
    return nullptr;
}

TNaryTree::TNaryTree(const TNaryTree& other)
{
    this->root = tree_copy(other.root);
    this->root->cur_size = 0;
    this->size = other.size;
}

void TNaryTree::Update(std::shared_ptr<TreeItem>* root, std::shared_ptr<octagon> polygon, std::string tree_path)
{
    if (tree_path == "") {
        if (*root == nullptr) {
            *root = std::shared_ptr<TreeItem>(new TreeItem);
            (*root)->figure = std::shared_ptr<octagon>(new octagon);
            (*root)->figure = polygon;
            (*root)->brother = nullptr;
            (*root)->son = nullptr;
            (*root)->parent = nullptr;
        } else {
            (*root)->figure = polygon;
        }
        return;
    }
    if (tree_path == "b") {
        std::cout << "Cant add brother to root\n";
        return;
    }
    std::shared_ptr<TreeItem> cur = *root;
    if (cur == NULL) {
        throw std::invalid_argument("Vertex doesn't exist in the path\n");
        return;
    }
    for (int i = 0; i < tree_path.size() - 1; i++) {
        if (tree_path[i] == 'c') {

```

```

        cur = cur->son;
    } else {
        cur = cur->brother;
    }
    if (cur == nullptr && i < tree_path.size() - 1) {
        throw std::invalid_argument("Vertex doesn't exist in the path\n");
        return;
    }
}
if (tree_path[tree_path.size() - 1] == 'c' && cur->son == nullptr) {
    if (cur->cur_size + 1 > this->size) {
        throw std::out_of_range("Tree is overflow\n");
        return;
    }
    if (cur->son == nullptr) {
        cur->son = std::shared_ptr<TreeItem>(new TreeItem);
        cur->son->figure = std::shared_ptr<octagon>(new octagon);
        cur->son->figure = polygon;
        cur->son->son = nullptr;
        cur->son->brother = nullptr;
        cur->son->parent = cur;
        cur->son->parent->cur_size++;
    } else {
        cur->son->figure = polygon;
    }
} else if (tree_path[tree_path.size() - 1] == 'b' && cur->brother == nullptr) {
    if (cur->parent->cur_size + 1 > this->size) {
        throw std::out_of_range("Tree is overflow\n");
        return;
    }
    if (cur->brother == nullptr) {
        cur->brother = std::shared_ptr<TreeItem>(new TreeItem);
        cur->brother->figure = std::shared_ptr<octagon>(new octagon);
        cur->brother->figure = polygon;
        cur->brother->son = nullptr;
        cur->brother->brother = nullptr;
        cur->brother->parent = cur->parent;
        cur->brother->parent->cur_size++;
    } else {
        cur->brother->figure = polygon;
    }
}
}

void delete_tree(std::shared_ptr<TreeItem>* root)
{
    if ((*root)->son != nullptr) {
        delete_tree(&((*root)->son));
    }
    if ((*root)->brother != nullptr) {
        delete_tree(&((*root)->brother));
    }
    *root = nullptr;
}

void delete_undertree(std::shared_ptr<TreeItem>* root, char c)
{
    if (*root == nullptr) {
        return;
    }
}

```



```

if (c == 'b') {
    if ((*root)->brother != nullptr) {
        std::shared_ptr<TreeItem> cur = (*root)->brother;
        if ((*root)->brother->brother != nullptr) {
            (*root)->brother = (*root)->brother->brother;
            cur->brother = nullptr;
            delete_tree(&cur);
        } else {
            delete_tree(&((*root)->brother));
        }
    }
} else if (c == 'c') {
    std::shared_ptr<TreeItem> cur = (*root)->son;
    if ((*root)->son->brother != nullptr) {
        (*root)->son = (*root)->son->brother;
        if (cur->son != nullptr) {
            delete_tree(&(cur->son));
        }
        cur = nullptr;
    } else {
        delete_tree(&((*root)->son));
    }
}
}

void TNaryTree::RemoveSubTree(const std::string &&tree_path)
{
    if (tree_path == "" && this->root != nullptr) {
        std::shared_ptr<TreeItem>* iter = &(this->root);
        delete_tree(iter);
        return;
    } else if (tree_path == "" && this->root == nullptr) {
        throw std::invalid_argument("Vertex doesn't exist in the path\n");
        return;
    }
    std::shared_ptr<TreeItem> cur = this->root;
    for (int i = 0; i < tree_path.size() - 1; i++) {
        if (tree_path[i] == 'c') {
            if (cur->son == nullptr) {
                throw std::invalid_argument("Vertex doesn't exist in the path\n");
                return;
            }
            cur = cur->son;
        } else if (tree_path[i] == 'b') {
            if (cur->brother == nullptr) {
                throw std::invalid_argument("Vertex doesn't exist in the path\n");
                return;
            }
            cur = cur->brother;
        }
    }
    if (tree_path[tree_path.size() - 1] == 'c') {
        if (cur->son == nullptr) {
            throw std::invalid_argument("Vertex doesn't exist in the path\n");
            return;
        }
        delete_underTree(&cur, 'c');
    } else if (tree_path[tree_path.size() - 1] == 'b') {
        if (cur->brother == nullptr) {
            throw std::invalid_argument("Vertex doesn't exist in the path\n");

```

```

        return;
    }
    delete_undertree(&cur, 'b');
}
return;
}

void TNaryTree::RemoveSubTree(const std::string &tree_path)
{
    if (tree_path == "" && this->root != nullptr) {
        std::shared_ptr<TreeItem>* iter = &(this->root);
        delete_tree(iter);
        return;
    } else if (tree_path == "" && this->root == nullptr) {
        throw std::invalid_argument("Vertex doesn't exist in the path\n");
        return;
    }
    std::shared_ptr<TreeItem> cur = this->root;
    for (int i = 0; i < tree_path.size() - 1; i++) {
        if (tree_path[i] == 'c') {
            if (cur->son == nullptr) {
                throw std::invalid_argument("Vertex doesn't exist in the path\n");
                return;
            }
            cur = cur->son;
        } else if (tree_path[i] == 'b') {
            if (cur->brother == nullptr) {
                throw std::invalid_argument("Vertex doesn't exist in the path\n");
                return;
            }
            cur = cur->brother;
        }
    }
    if (tree_path[tree_path.size() - 1] == 'c') {
        if (cur->son == nullptr) {
            throw std::invalid_argument("Vertex doesn't exist in the path\n");
            return;
        }
        delete_undertree(&cur, 'c');
    } else if (tree_path[tree_path.size() - 1] == 'b') {
        if (cur->brother == nullptr) {
            throw std::invalid_argument("Vertex doesn't exist in the path\n");
            return;
        }
        delete_undertree(&cur, 'b');
    }
    return;
}

bool TNaryTree::Empty()
{
    if (this->root != nullptr) {
        return false;
    } else {
        return true;
    }
}

double TNaryTree::Area(std::string &&tree_path)
{

```

```

if (tree_path == "") {
    if (this->root != nullptr) {
        return this->root->figure->Area();
    } else {
        throw std::invalid_argument("Vertex doesn't exist in the path\n");
    }
}
std::shared_ptr<TreeItem> cur = this->root;
double square = 0;
for (int i = 0; i < tree_path.size(); i++) {
    if (tree_path[i] == 'c') {
        if (cur->son != nullptr) {
            cur = cur->son;
        } else {
            throw std::invalid_argument("Vertex doesn't exist in the path\n");
        }
    } else {
        if (cur->brother != nullptr) {
            cur = cur->brother;
        } else {
            throw std::invalid_argument("Vertex doesn't exist in the path\n");
        }
    }
    square += cur->figure->Area();
}
return square + this->root->figure->Area();
}

```

```

double TNaryTree::Area(std::string &tree_path)
{
    if (tree_path == "") {
        if (this->root != nullptr) {
            return this->root->figure->Area();
        } else {
            throw std::invalid_argument("Vertex doesn't exist in the path\n");
        }
    }
    std::shared_ptr<TreeItem> cur = this->root;
    double square = 0;
    for (int i = 0; i < tree_path.size(); i++) {
        if (tree_path[i] == 'c') {
            if (cur->son != nullptr) {
                cur = cur->son;
            } else {
                throw std::invalid_argument("Vertex doesn't exist in the path\n");
            }
        } else {
            if (cur->brother != nullptr) {
                cur = cur->brother;
            } else {
                throw std::invalid_argument("Vertex doesn't exist in the path\n");
            }
        }
        square += cur->figure->Area();
    }
    return square + this->root->figure->Area();
}

```

```

void Print(std::ostream& os, std::shared_ptr<TreeItem> vertex)
{

```

```

if (vertex != nullptr) {
    os << vertex->figure->Area();
    if (vertex->son != nullptr) {
        os << ": " << "[";
        Print(os, vertex->son);
        if ((vertex->son->brother == nullptr && vertex->brother != nullptr) || (vertex->son->brother == nullptr &&
vertex->brother == nullptr)) {
            os << "]";
        }
    }
    if (vertex->brother != nullptr) {
        os << ", ";
        Print(os, vertex->brother);
        if (vertex->brother->brother == nullptr) {
            os << "]";
        }
    }
} else {
    return;
}
}

```

```

std::ostream& operator<<(std::ostream& os, const TNaryTree& tree)
{
    if (tree.root != nullptr) {
        Print(os, tree.root); os << "\n";
        return os;
    } else {
        os << "Tree has no vertex\n";
        return os;
    }
}

```

```

const std::shared_ptr<octagon>& TNaryTree::GetItem(std::shared_ptr<TreeItem>* root, const std::string tree_path)
{
    if (tree_path == "" && *root == nullptr) {
        throw std::invalid_argument("Vertex doesn't exist in the path\n");
    }
    std::shared_ptr<TreeItem> cur = *root;
    for (int i = 0; i < tree_path.size(); i++) {
        if (tree_path[i] == 'c') {
            if (cur->son == nullptr) {
                throw std::invalid_argument("Vertex doesn't exist in the path\n");
            }
            cur = cur->son;
        } else if (tree_path[i] == 'b') {
            if (cur->brother == nullptr) {
                throw std::invalid_argument("Vertex doesn't exist in the path\n");
            }
            cur = cur->brother;
        }
    }
    return cur->figure;
}

```

```

TNaryTree::~TNaryTree()
{
    if (this->root != nullptr) {
        this->RemoveSubTree("");
    }
}

```

```
}
```

main.cpp:

```
#include "figure.h"
#include "TNaryTree.h"
#include "TNaryTree_item.h"
#include "octagon.h"
#include <string>

int main()
{
    TNaryTree a(4);
    if (a.Empty()) {
        std::cout << "The tree is empty !\n";
    } else {
        std::cout << "The tree is not empty !\n";
    }
    a.Update(std::shared_ptr<octagon>(new octagon(Point(1, 4), Point(1, 2), Point(5, 6), Point(2, 8),
    Point(3, 1), Point(2, 6), Point(9, 5), Point(5, 4))), ""); // 1
    a.Update(std::shared_ptr<octagon>(new octagon(Point(2, 5), Point(1, 5), Point(16, 6), Point(3, 6),
    Point(1, 8), Point(4, 2), Point(7, 3), Point(1, 15))), "c"); // 2
    a.Update(std::shared_ptr<octagon>(new octagon(Point(3, 5), Point(9, 1), Point(7, 3), Point(1, 8),
    Point(5, 6), Point(4, 8), Point(9, 5), Point(6, 4))), "cb"); // 3
    a.Update(std::shared_ptr<octagon>(new octagon(Point(4, 4), Point(1, 2), Point(5, 6), Point(2, 8),
    Point(3, 1), Point(2, 6), Point(9, 5), Point(5, 4))), "cbb"); // 4
    a.Update(std::shared_ptr<octagon>(new octagon(Point(5, 5), Point(1, 5), Point(16, 6), Point(3, 6),
    Point(1, 8), Point(4, 2), Point(7, 3), Point(1, 15))), "cbcb"); // 5
    a.Update(std::shared_ptr<octagon>(new octagon(Point(6, 5), Point(9, 1), Point(7, 3), Point(1, 8),
    Point(5, 6), Point(4, 8), Point(9, 5), Point(6, 4))), "cc"); // 6
    a.Update(std::shared_ptr<octagon>(new octagon(Point(7, 4), Point(1, 2), Point(5, 6), Point(2, 8),
    Point(3, 1), Point(2, 6), Point(9, 5), Point(5, 4))), "ccb"); // 7
    a.Update(std::shared_ptr<octagon>(new octagon(Point(8, 5), Point(1, 5), Point(16, 6), Point(3, 6),
    Point(1, 8), Point(4, 2), Point(7, 3), Point(1, 15))), "cbc"); // 8
    a.Update(std::shared_ptr<octagon>(new octagon(Point(9, 5), Point(9, 1), Point(7, 3), Point(1, 8),
    Point(5, 6), Point(4, 8), Point(9, 5), Point(6, 4))), "cbcb"); // 9
    a.Update(std::shared_ptr<octagon>(new octagon(Point(9, 5), Point(9, 1), Point(7, 3), Point(1, 8),
    Point(5, 6), Point(4, 8), Point(9, 5), Point(6, 4))), "ccc"); // 10
    a.Update(std::shared_ptr<octagon>(new octagon(Point(9, 5), Point(9, 1), Point(7, 3), Point(1, 8),
    Point(5, 6), Point(4, 8), Point(9, 5), Point(6, 4))), "cccb"); // 11
    std::cout << a;
    std::cout << a.Area("cb") << "\n";
    TNaryTree b(a);
    std::cout << b;
    std::shared_ptr<octagon> c = a.GetItem("");
    std::cout << *c;
    a.RemoveSubTree("cbc");
    if (a.Empty()) {
        std::cout << "The tree is empty !\n";
    } else {
        std::cout << "The tree is not empty !\n";
    }
    return 0;
}
```