
User Managed Access

User Managed Access

- ❖ Kantara project

“.. address the harmonization and interoperability challenges that exist between enterprise identity systems, Web 2.0 applications and services, and Web-based initiatives.”

- ❖ UMA WG

“.. to develop specs that let an individual control the authorization of data sharing and service access made between online services on the individual's behalf”

Privacy by design

- ❖ Proactive not reactive
- ❖ Benefits all actors in an online service ecosystem
- ❖ Proper testable behavior
- ❖ User centric




Use cases

- ❖ **Person-to-self**
 - ❖ Attribute release
- ❖ **Person-to-organization**
 - ❖ Health care
 - ❖ Work application
- ❖ **Person-to-person**
 - ❖ Student information
- ❖ IoT

OAuth2 is a 3-entity protocol for securing API-calls in a user context

1.2. Protocol Flow




End-user resource owner gets redirected to AS to log in and consent to access token issuance

Figure 1: Abstract Protocol Flow




AS and RS are typically in the same domain and communicate in a proprietary way

UMAs original goal: apply privacy-by-design to OAuth data sharing




The 3 Phases of UMA -and associated tokens


- ❖ Protect a resource
 - ❖ Protection API Token (PAT)
- ❖ Get Authorization
 - ❖ Authorization API Token (AAT)
- ❖ Access a resource
 - ❖ Requesting Party Token (RPT)



1. Introducing the Authorization Server



2. Translating resource API



Resource set description

- ❖ A JSON document with the following parameters
 - ❖ **name**
REQUIRED. A human-readable string describing a set of one or more resources.
 - ❖ **uri**
OPTIONAL. A URI that provides the network location for the resource set being registered
 - ❖ **type**
OPTIONAL. A string uniquely identifying the semantics of the resource set
 - ❖ **scopes**
REQUIRED. An array of strings indicating the available scopes for this resource set.
 - ❖ **icon_uri**
OPTIONAL. A URI for a graphic icon representing the resource set

Scopes description

- ❖ a JSON document with the following properties:
 - ❖ **name**
REQUIRED. A human-readable string describing some scope (extent) of access.
 - ❖ **icon_uri**
OPTIONAL. A URI for a graphic icon representing the scope.

Standardized format for describing resource sets

REST interface

GET

PUT

POST

DELETE

```
{  
  "name": <url>,  
  "scopes": [  
    "http://umu.se/uma/read",  
    "http://umu.se/uma/create",  
    "http://umu.se/uma/modify",  
    "http://umu.se/uma/delete"]  
}
```

Standardized format for describing resource sets

REST interface


GET

PUT

POST

DELETE

```
{  
  "name": <url>,  
  "scopes": [  
    "http://umu.se/uma/read",  
    "http://umu.se/uma/create",  
    "http://umu.se/uma/modify",  
    "http://umu.se/uma/delete"]  
}
```

A black arrow originates from the 'GET' text and points to the first element of the 'scopes' array, which is the URL 'http://umu.se/uma/read'.

Standardized format for describing resource sets

REST interface


GET

PUT

POST

DELETE

```
{  
  "name": <url>,  
  "scopes": [  
    "http://umu.se/uma/read",  
    "http://umu.se/uma/create",  
    "http://umu.se/uma/modify",  
    "http://umu.se/uma/delete"]  
}
```

A horizontal arrow points from the 'PUT' text on the left to the '"http://umu.se/uma/create"' entry within the 'scopes' array of the JSON object on the right.

Standardized format for describing resource sets

REST interface


GET

PUT

POST

DELETE

```
{  
  "name": <url>,  
  "scopes": [  
    "http://umu.se/uma/read",  
    "http://umu.se/uma/create",  
    "http://umu.se/uma/modify",  
    "http://umu.se/uma/delete"]  
}
```



Standardized format for describing resource sets

REST interface


GET

PUT

POST

DELETE

```
{  
  "name": <url>,  
  "scopes": [  
    "http://umu.se/uma/read",  
    "http://umu.se/uma/create",  
    "http://umu.se/uma/modify",  
    "http://umu.se/uma/delete"]  
}
```



Registration response

❖ JSON object with the following parameters:

❖ `_id`

REQUIRED The authorization server-defined identifier for the web resource corresponding to the resource set.

❖ `user_access_policy_uri`

OPTIONAL. A URI that allows the resource server to redirect an end-user resource owner to a specific user interface within the authorization server where the resource owner can immediately set or modify access policies subsequent to the resource set registration action just completed

Resource set registration API

- Create resource set description: POST {rsreguri}/resource_set
- Read resource set description: GET {rsreguri}/resource_set/{_id}
- Update resource set description: PUT {rsreguri}/resource_set/{_id}
- Delete resource set description: DELETE {rsreguri}/resource_set/{_id}
- List resource set descriptions: GET {rsreguri}/resource_set

Create resource set example

```
POST /rs/resource_set HTTP/1.1
Content-Type: application/json
Authorization: Bearer MHg30UZEQkZBMjcx
...
```


```
{
  "name" : "Tweedl Social Service",
  "icon_uri" : "http://www.example.com/icons/sharesocial.png",
  "scopes" : [
    "read-public",
    "post-updates",
    "read-private",
    "http://www.example.com/scopes/all"
  ],
  "type" : "http://www.example.com/rsets/socialstream/140-compatible"
}
```

Registration response


```
HTTP/1.1 201 Created
Content-Type: application/json
Location: /rs/resource_set/KX3A-39WE
...
```

```
{
  "_id" : "KX3A-39WE",
  "user_access_policy_uri" : "http://as.example.com/rs/222/resource/KX3A-39WE/policy"
}
```


3. Setting permissions




4a. Accessing resource




4b. Getting AAT&RPT




4c. Presenting empty RPT




4d. Assigning permission



4e. With permission







1. RS registers resource sets and scopes (ongoing)
2. C requests resource
3. RS registers permission
4. AS returns permission ticket
5. RS error with ticket
6. C requests authz data and RPT with ticket
7. AS gives RPT and authz data (after optional claim flows)
8. C requests resource with RPT
9. RS returns resource representation

SAML2 + UMA


The pieces



The configuration



UMA+SAML2



Privacy by design

- ❖ Proactive not reactive
- ❖ Benefits all actors in an online service ecosystem
- ❖ Proper testable behavior
- ❖ User centric



Status

- ❖ Version 1.0.1 of the standard published
- ❖ Have not started interop yet
- ❖ A handful of implementations, growing

Links to documents

- ❖ UMA Core V1.0.1 candidate Draft Recommendation
- ❖ OAuth RSR V1.0.1 candidate Draft Recommendation