


Peer2Peer (P2P)

Manas Ranjan Lenka
School of Computer Engineering,
KIIT University


Pure P2P architecture

- *no* always-on server
- arbitrary end systems directly communicate
- peers are intermittently connected and change IP addresses




File Distribution: Server-Client vs P2P

Question : How much time to distribute file from one server to N peers?



File distribution time: server-client

- server sequentially sends N copies:
 - NF/u_s time
- client i takes F/d_i time to download



Time to distribute F
to N clients using
client/server approach


$$= d_{cs} = \max \left\{ NF/u_s, F/\min(d_i) \right\}$$

i

increases linearly in N
(for large N)

File distribution time: P2P


- server must send one copy:
 F/u_s time
- client i takes F/d_i time to download
- NF bits must be downloaded (aggregate)
 - fastest possible upload rate: $u_s + \sum u_i$



$$d_{\text{P2P}} = \max \left\{ F/u_s, F/\min(d_i), NF/(u_s + \sum_i u_i) \right\}$$


Server-client vs. P2P: example

Client upload rate = u , $F/u = 1$ hour, $u_s = 10u$, $d_{\min} \geq u_s$



How Bit Torrent Works

- A user who wants to upload a file first creates a small torrent descriptor file that they distribute by conventional means (web, email, etc.).
- They then make the file itself available through a BitTorrent node acting as a seed.
- Those with the torrent descriptor file can give it to their own BitTorrent nodes, which—acting as peers or leechers—download it by connecting to the seed and/or other peers (see diagram on the right).



The middle computer is acting as a seed to provide a file to the other computers which act as peers.

Operations of Bit Torrent

Creating and publishing torrents

- Peers that provide a complete file are called seeders, and the peer providing the initial copy is called the initial seeder.
- The peer distributing a data file will create a torrent file with the suffix .torrent.
- Torrent files have an "announce" section, which specifies the [URL of the tracker](#), and an "info" section, containing (suggested) names for the files, their lengths, the piece length used, and a SHA-1 hash code for each piece, all of which are used by clients to verify the integrity of the data they receive.
- Torrent files are typically published on websites or elsewhere, and registered with at least one tracker.
- The tracker maintains lists of the clients currently participating in the torrent.

Operations of Bit Torrent

Downloading torrents and sharing files

- Users find a torrent of interest, by browsing the web or by other means, download it, and open it with a BitTorrent client.
- The client connects to the tracker(s) specified in the torrent file, from which it receives a list of peers currently transferring pieces of the file(s) specified in the torrent.
- The client connects to those peers to obtain the various pieces.