How much does wind cost? A paired calm/windy synthetic RGB-D benchmark that separates occlusion, sensor and wind error in 3D foliage reconstruction

Bibek Gyawali[a,*]

[a] *TODO affiliation,*

Abstract

Neural scene representations such as 3D Gaussian Splatting and neural radiance fields are increasingly used to reconstruct plants for phenotyping, but they assume a static scene, while foliage is never still outdoors or near fans and ventilation. Existing plant datasets cannot tell how much of the reconstruction error is caused by the method and occlusion, by the depth sensor, or by leaf motion, because ground truth for moving leaves is unavailable. We present SynthTree, a fully scripted generator of paired calm/windy RGB-D sequences of potted saplings that is the synthetic twin of a real RealSense capture protocol. Every tree is rendered at several canopy wind speeds with a bit-identical camera trajectory; leaves are real geometry with unique identities, and a closed-form wind model (hierarchical branch sway and rigid leaf flutter) makes the exported per-leaf rigid transforms exact by construction. Automatic checks on all 40 sequences confirm sub-pixel consistency of poses, intrinsics, depth and per-leaf motion (re-projection error ≤ 0.0036 px; per-leaf transforms predict the rendered optical flow to 0.007 px). We further propose a three-way error decomposition with an explicit interaction term and a geometry-first evaluation protocol for Gaussian reconstructions. In a benchmark of 60 training runs over four leaf types, wind at 5 m/s reduces the leaf F-score of 3D Gaussian Splatting by 0.341 and of a depth-supervised NeRF by 0.348, and raises the per-leaf centroid error by 12.0 mm, while image-space PSNR changes by only -7 %: view-synthesis metrics hide most of the geometric damage. Simulated sensor noise, in contrast, mainly trades precision for coverage. Using the exported per-leaf motion, we further show that evaluating against the rest pose over-states the wind error of static re-

*Corresponding author

Email address: TODO-institutional-email@example.org (Bibek Gyawali)

constructions by 34 %, and that a deformation-field Gaussian baseline with the temporal encoding commonly used for short clips recovers none of the lost geometry. [TODO: corrected deformable baseline; real-data validation.]

Keywords: 3D plant reconstruction, Gaussian splatting, neural radiance fields, wind, RGB-D sensor noise, synthetic data, phenotyping

---

1. Introduction

Three-dimensional reconstruction of plants underpins non-destructive phenotyping of leaf area, leaf angle distribution and canopy architecture (Paulus, 2019). Recent neural representations, neural radiance fields (Mildenhall et al., 2020; Müller et al., 2022) and 3D Gaussian Splatting (3DGS) (Kerbl et al., 2023), produce photorealistic novel views from ordinary image or RGB-D sequences and are rapidly being adopted for plants. All of them assume a static scene. Leaves, however, flutter at a few hertz in a light breeze and whole branches sway (de Langre, 2008), and capturing a full orbit around a sapling takes tens of seconds.

When a reconstruction of a real plant is poor, the cause is ambiguous: thin, self-occluding foliage is intrinsically hard for the method; consumer depth sensors add noise, holes and flying pixels at leaf boundaries (Khoshelham and Elberink, 2012; Keselman et al., 2017); and leaf motion violates the static-scene assumption. These effects cannot be separated on real data, because the true geometry of a moving canopy is unknown, and existing benchmarks either capture static scenes (Jensen et al., 2014; Knapitsch et al., 2017; Sturm et al., 2012) or provide plant point clouds without per-leaf motion (Schunck et al., 2021).

We address this with a synthetic twin of a real capture protocol in which every factor is controlled and every leaf is tracked exactly. Our contributions are:

1. **SynthTree**, an open, fully scripted pipeline (procedural saplings, exact procedural wind, sensor-matched RGB-D rendering, sensor-noise simulation with calibration from real recordings) that produces *paired* calm/windy sequences: same tree, bit-identical camera path, only the wind speed differs.
2. **Exact per-leaf ground truth under wind**: leaf identity maps, per-leaf rigid transforms, optical flow and canonical correspondences, validated to sub-pixel accuracy on all sequences.

3. **A three-way error decomposition** into occlusion/method, sensor and wind components with an explicit interaction term, and a geometry-first evaluation protocol for Gaussian reconstructions that is robust to floaters and floor splats.
4. **A benchmark** showing that wind dominates the sensor effect, that view-synthesis metrics substantially under-report the geometric degradation of foliage, and that rest-pose evaluation over-states the wind error of static reconstructions; time-resolved per-leaf ground truth corrects this and allows dynamic methods to be scored.

Code and data are released (Section 7).

2. Related work

3D plant reconstruction and phenotyping. Laser scanning, multi-view stereo and RGB-D cameras are established for measuring plant geometry (Paulus, 2019); Pheno4D (Schunck et al., 2021) provides spatio-temporal point clouds of growing plants with organ labels. These datasets are acquired in still air and, being real, cannot provide the true geometry of moving leaves.

Neural reconstruction of static and dynamic scenes. NeRF (Mildenhall et al., 2020) and its accelerated variants (Müller et al., 2022), and 3DGS (Kerbl et al., 2023) and its surface-oriented variant 2DGS (Huang et al., 2024), reconstruct static scenes; Nerfstudio (Tancik et al., 2023) provides the implementations we benchmark. Dynamic extensions model deformation over time (Pumarola et al., 2021; Luiten et al., 2024; Wu et al., 2024), and Gaussian-splatting SLAM (Matsuki et al., 2024) tracks RGB-D cameras. How these methods degrade on fluttering foliage has not been quantified with ground truth.

Synthetic data and benchmarks. Rendering pipelines such as BlenderProc (Denninger et al., 2023) and ICL-NUIM (Handa et al., 2014) provide exact ground truth for rigid indoor scenes, and procedural plant models have a long history (Prusinkiewicz and Lindenmayer, 1990; Weber and Penn, 1995; Runions et al., 2007). To our knowledge no benchmark provides paired static/dynamic foliage with per-leaf motion ground truth matched to a real sensor.

Depth-sensor noise. Depth noise of structured-light and active-stereo cameras grows approximately quadratically with distance and concentrates at depth discontinuities (Khoshelham and Elberink, 2012; Nguyen et al., 2012; Keselman et al., 2017), which is precisely where thin leaves are.




Figure 1: The 10 procedural saplings (calm, first frame): broad, small, pinnate-compound and needle leaves at sparse to dense canopy densities, including an autumn-coloured variant for vegetation-mask robustness. Leaves are real meshes, not alpha-textured cards.

3. The SynthTree generator

Figure 1 shows the 10 saplings of the released dataset and Fig. 3 the per-frame products. The pipeline is pure Python/NumPy except for rendering (Blender, headless); identical configuration and seed give bit-identical geometry, poses and ground truth, which we verified across two Blender LTS versions with different Python/NumPy versions.

3.1. Procedural saplings with leaf identities

Each tree is a skeleton of nodes (position, radius, parent) grouped into branches of increasing order, grown with stochastic wander, phototropic upturn and phyllotactic or whorled branching (Weber and Penn, 1995). Wood is meshed as parallel-transported tubes. Leaf sites are spaced along branch segments; a leaf is attached at the bark surface of a segment and inherits that segment's frame. Leaf blades are real triangulated surfaces with species-dependent outlines (ovate, elliptic, obovate, lanceolate), cupping and droop;

Table 1: Dataset composition. Height includes the pot; triangles count wood and leaves. Trees in the test split are held out for generalisation.

ID	Preset	Leaf type	Height (m)	Leaves	Leaf area (m^2)	Triangles	Split
0	broad_sparse	broad	1.00	86	0.161	2,890	train
1	broad_medium	broad	1.54	624	0.874	17,234	train
2	broad_dense	broad	1.98	2,591	2.460	65,376	train
3	small_sparse	small	0.87	535	0.064	9,190	train
4	small_dense	small	0.82	1,865	0.119	29,992	train
5	compound_medium	compound	1.44	62	0.257	6,378	train
6	compound_dense	compound	1.73	217	0.505	27,044	train
7	needle_sparse	needle	1.14	1,672	0.078	28,107	train
8	needle_dense	needle	1.11	8,192	0.146	136,748	test
9	broad_medium_autumn	broad	1.47	557	0.829	15,366	test

compound leaves consist of a rachis and leaflets, and needles are closed triangular prisms. Every leaf has an integer identity, an attachment point, a parent branch, a rest frame, an area and a centroid, stored with the canonical (rest) mesh (Table 1). Heights range from 0.82 to 1.98 m and leaf counts from 62 to 8,192.

3.2. Exact procedural wind

We deliberately do not use physics simulation or a node-based deformer: the same closed-form function both moves the rendered vertices and produces the exported ground truth, so the two are identical by construction.

Branch sway. Every skeleton node j receives a bend rotation

$$\Delta_j(t) = \mathrm{Rot}\big(\mathbf{b}, \theta_j(t)\big)\,\mathrm{Rot}\big(\mathbf{w}, \psi_j(t)\big), \tag{1}$$

where $\mathbf{w}$ is the horizontal wind direction and $\mathbf{b} = \mathbf{e}_z \times \mathbf{w}$. Rotations are accumulated from the root by forward kinematics, $A_j = A_{p(j)}\Delta_j$ and $\mathbf{p}_j = \mathbf{p}_{p(j)} + A_{p(j)}(\mathbf{p}^0_j - \mathbf{p}^0_{p(j)})$, so displacement grows with height and branching order. The bend and cross-wind angles are

$$\theta_j = c_j\, g_b(U_e)\,[\alpha_s + \alpha_o \sin(2\pi f_B t + \phi_B)], \tag{2}$$

$$\psi_j = c_j\, g_b(U_e)\,\alpha_c \sin(2\pi r f_B t + \phi'_B), \tag{3}$$

with frequency f_B and phase ϕ_B shared by all nodes of a branch B (coherent sway), and a compliance $c_j \propto (r_0/r_j)\,\ell_j$ that favours thin, long segments.

Leaf flutter. Each leaf rotates rigidly about its petiole attachment,

$$\begin{aligned} R_\ell = \mathrm{Rot}(\mathbf{m}_\ell, g_l\beta_m)\,\mathrm{Rot}\big(\mathbf{x}_\ell, g_l\beta_t \sin(2\pi r_\ell f_\ell t + \phi'_\ell)\big) \\ \mathrm{Rot}\big(\mathbf{y}_\ell, g_l\beta_p \sin(2\pi f_\ell t + \phi_\ell)\big), \end{aligned} \tag{4}$$




Figure 2: Ground-truth leaf motion per tree versus canopy wind speed (median over leaves and frames).

with a per-leaf frequency $f_\ell \in [2.5, 9]\,\mathrm{Hz}$, mean down-wind reconfiguration about $\mathbf{m}_\ell = \mathbf{n}_\ell \times \mathbf{w}$, and is carried by its node: $A_\ell = A_{n(\ell)} R_\ell$. The leaf's rigid transform from the canonical pose, $\mathbf{x}_t = A_\ell \mathbf{x}_0 + \mathbf{t}_\ell$, is exported per frame.

Amplitude laws and gusts. $g_b(U) = (U/U_r)^2$ follows the quadratic dependence of drag on speed for small elastic deflections; $g_l(U) = s \tanh\big((U/U_r)/s\big)$ lets flutter grow roughly linearly and saturate. Gusts modulate the speed, $U_e(t) = U \max\{0, 1 + \gamma\, n(t)\}$, with a smooth seeded noise $n(t)$. All angles vanish exactly at $U = 0$ and rotations are evaluated element-wise, so calm sequences are the rest pose bit-for-bit. Phases depend only on the tree seed, so different wind levels of a tree differ only in amplitude. Over 150 frames, the median leaf displacement at 5 m/s ranges from 9 to 60 mm across trees, with median leaf rotations of 23–27° (Fig. 2). These amplitudes are configurable and are calibrated against real fan recordings by matching the optical-flow leaf speed per wind level (Section 3.5). [TODO: report calibrated amplitudes.]

3.3. Sensor-matched rendering and ground-truth passes

The camera reproduces the real sensor's pinhole intrinsics exactly (focal length, principal point via lens shift, pixel aspect) and a hand-held orbit with seeded smooth jitter; the trajectory depends only on the tree seed, so it is bit-identical across wind levels. Time is explicit: frame i is rendered at $t = i\,k/\mathrm{fps}$ for both wind and camera.

RGB is rendered with EEVEE or Cycles and converted to 8-bit sRGB with the exact transfer function. Ground truth is rendered in a separate Cycles pass with one sample per pixel and a 0.01-pixel box filter, so every




Figure 3: Per-frame products for a broad-leaved sapling at $U = 5\,\mathrm{m/s}$. Clean products are exact; noisy RGB and depth follow the sensor model of Section 3.4.

value is the first hit of the ray through the pixel centre and is never blended across edges. Shader outputs store per-pixel world position, normal, leaf identity, semantic class, rest position and next-frame position. Depth is computed as $z = (\mathbf{P} - \mathbf{C}) \cdot \mathbf{o}$ from the world position, so it is z-depth by construction. Exact optical flow is obtained by projecting the interpolated next-frame position, which also covers non-rigid wood deformation. Motion blur and rolling shutter are optional and are rendered by sub-frame and row-band integration.

3.4. Sensor noise model

Clean data are always kept and a noisy copy is derived. Depth undergoes resampling to the sensor's effective depth resolution; spatially correlated noise with $\sigma(z) = a + bz^2$ or, alternatively, Gaussian disparity noise with sub-pixel quantisation; flying pixels that interpolate foreground and background depth at discontinuities; holes whose probability increases near edges, on structures thinner than a few pixels and at grazing angles; range limits; misregistration; and quantisation to millimetres. RGB receives an auto-exposure random walk, slight blur, shot and read noise and JPEG

Table 2: Automatic validation over all released sequences.

Check (all 40 sequences)	Statistic	Value
World position re-projects onto its own pixel centre	max error	0.0036 px
Cross-frame re-projection of exported depth (static geometry)	worst median	0.002 px
Back-projected floor lies on $z = 0$ (image corners)	worst median	3 μm
same test if depth were ray distance	median	147 mm
16-bit PNG depth vs. float EXR depth	max difference	0.50 mm
Leaf-ID pixels not in table / inconsistent with semantics	total	0 px
Per-leaf transforms predict rendered flow (leaf pixels)	worst median	0.007 px
Rendered flow of static geometry	worst median	0.006 px

compression. Noise draws are keyed to the tree and frame, so they are paired across wind levels.

3.5. Calibration against the real sensor

The noise parameters are fitted from real recordings of a flat textured wall at six distances (plane-fit residuals give a, b and the spatial correlation; invalid pixels give the random hole rate) and of real leaves against a distant background (vegetation silhouettes give flying-pixel, edge-hole and thin-structure-hole rates by fixed-point matching of simulated statistics). On synthetic recordings with known parameters, the procedure recovers a, b and the correlation length within 3 % and the flying-pixel and hole rates within 2 %. Wind amplitudes are calibrated analogously by matching the median metric leaf speed (optical flow scaled by depth) of real static-camera fan clips, iterating until all wind levels agree within 3 %; a self-test with a known amplitude factor of 1.6 recovers 1.57. [TODO: insert real-sensor calibration results and plots.]

3.6. Validation

Every sequence is validated automatically on the exported products (Table 2); all 40 of 40 sequences pass. The decisive check for depth convention is geometric: back-projecting the depth of the floor yields points within 3 μm of the plane $z = 0$ even in the image corners, whereas interpreting the same values as ray distance would displace them by 147 mm.

4. Benchmark protocol

Data and splits. Each tree is rendered calm and at 0, 1.5, 3, 5 m/s along a single orbit of 150 frames at the real sensor's resolution. Every eighth frame is held out for view-synthesis evaluation, and two trees are held out entirely for generalisation studies.

Methods. We evaluate splatfacto (3DGS) and depth-nerfacto (NeRF with depth supervision) from Nerfstudio (Tancik et al., 2023), trained with the ground-truth poses in metric world coordinates (no re-centring or re-scaling) and initialised from back-projected sensor depth of the same variant (clean or noisy). To test whether modelling motion helps, we additionally implement, on the same gsplat rasteriser, a static 3DGS and a deformable 3DGS that share initialisation, losses ($0.8\,\mathrm{L1} + 0.2\,\mathrm{D\text{-}SSIM}$), densification, background and iteration budget (10,000); the deformable variant adds a time-conditioned MLP (8 layers, 256 units) that predicts per-Gaussian offsets of position, rotation and scale from positionally encoded canonical position and time (Yang et al., 2024), enabled after 2,000 static warm-up iterations. [TODO: add a simple mitigation.]

Geometry-first evaluation. Reconstructions are compared with the canonical leaf surface. Each reconstructed point is attributed to its nearest ground-truth surface (leaf, wood, pot/soil or floor); points farther than 3 cm from every surface are floaters and are reported separately. For Gaussians, precision-side quantities (accuracy, precision, floaters, per-leaf centroids, leaf angles) use Gaussian centres, so each splat counts once, whereas coverage-side quantities (completeness, recall, recovered leaf area, leaf coverage) use samples spread over each Gaussian's footprint, because centres alone under-cover thin surfaces. We report the F-score at $\tau = 5\,\mathrm{mm}$, a capped chamfer distance, the relative leaf-area error, the 1-D Wasserstein distance between leaf inclination distributions (Ross, 1981), and the median per-leaf centroid error. Needles are thinner than a pixel, so for conifers per-leaf quantities are computed per shoot (all needles of a twig). View-synthesis PSNR is reported on held-out views.

Rest-pose and posed evaluation. The canonical (rest) surface is the natural target when the goal is the plant's architecture, but under wind the true surface at any instant is displaced from it. Because SynthTree exports the rigid transform of every leaf at every frame, we also evaluate *posed*: the leaf surface is posed with the transforms of a held-out frame and compared with the reconstruction at that frame's time (the same reconstruction for static methods, the deformed one for dynamic methods), averaged over four held-out frames.

Table 3: Benchmark results, mean over trees (and seeds). CD: capped chamfer distance; Area err: relative leaf-area error; Angle W1: leaf inclination distribution distance.

Method	Condition	F@5mm↑	CD [mm]↓	Centroid [mm]↓	Area err↓	Angle W1 [deg]↓	Floaters↓	PSNR [dB]↑
depth-nerfacto	calm / clean	0.558	6.4	5.6	0.53	10.1	0.01	35.5
	calm / noisy	0.525	6.7	6.5	0.55	10.9	0.01	26.2
	low / noisy	0.424	7.6	8.4	0.65	12.1	0.01	26.9
	medium / noisy	0.151	19.8	14.1	0.82	15.6	0.10	25.6
	high / noisy	0.178	17.0	18.1	0.85	12.5	0.04	26.2
	high / clean	0.193	14.6	14.5	0.85	12.3	0.04	29.2
splatfacto	calm / clean	0.379	19.3	6.7	0.58	12.6	0.19	36.1
	calm / noisy	0.439	17.8	8.6	0.40	12.0	0.32	29.1
	low / noisy	0.306	19.3	10.8	0.48	15.4	0.34	28.7
	medium / noisy	0.168	22.2	13.8	0.69	16.7	0.35	27.9
	high / noisy	0.099	25.9	20.6	0.81	17.7	0.43	27.1
	high / clean	0.098	26.0	19.4	0.86	16.7	0.19	29.5

Three-way decomposition. For a metric E oriented so that larger is worse,

$$E_{\text{method}} = E(\text{calm}, \text{clean}), \tag{5}$$

$$E_{\text{sensor}} = E(\text{calm}, \text{noisy}) - E(\text{calm}, \text{clean}), \tag{6}$$

$$E_{\text{wind}}(U) = E(U, \text{noisy}) - E(\text{calm}, \text{noisy}), \tag{7}$$

$$E_{\text{int}}(U) = \big[E(U, \text{noisy}) - E(U, \text{clean})\big] - E_{\text{sensor}}. \tag{8}$$

The interaction term measures how far sensor and wind errors are from additive. Values are averaged over seeds per configuration, and mean and standard deviation over trees are reported.

5. Results

The benchmark comprises 60 training runs: splatfacto on 4 trees (one per leaf type: broad, small, compound, needle) under six conditions with 2 seeds each, and depth-nerfacto on a broad-leaved and a needle tree with one seed. The mean standard deviation of the leaf F-score between seeds is 0.014, an order of magnitude below the wind effects reported below. [TODO: extend depth-nerfacto to more trees and seeds; add a dynamic method.]

Calm and clean (occlusion/method error). Even with exact poses and noise-free depth, splatfacto reaches only F@5mm = 0.379 and a chamfer distance of 19.3 mm on leaves (Table 4), and inclines leaves more steeply than they are; this is the intrinsic difficulty of thin, self-occluding foliage. Depth-supervised depth-nerfacto recovers markedly better calm geometry (F@5mm = 0.558, chamfer distance 6.4 mm) with almost no floaters.




Figure 4: Wind error versus canopy wind speed (mean ± std over trees); dotted lines mark the sensor error.

Wind. Wind is the dominant degradation. For splatfacto at 5 m/s the leaf F-score drops by 0.341, the chamfer distance increases by 8.1 mm and the per-leaf (per-shoot for the conifer) centroid error by 12.0 mm (Fig. 4); the F-score decreases monotonically with wind speed on all four trees. Depth-nerfacto loses a comparable amount (F-score −0.348, chamfer distance +10.3 mm), so its better calm geometry does not protect it against leaf motion; for the conifer its single-seed curve is not monotonic, which more seeds must resolve. Broad-, small- and compound-leaved trees degrade most; the needle tree, whose shoots move less (Fig. 2), degrades least.

Sensor. For splatfacto the sensor term is negative in F-score (-0.060) and chamfer distance (-1.5 mm), i.e. noisy input appears to *help*. The components explain why: with noisy RGB-D input, splatfacto converges to 2.0× fewer Gaussians near the tree (14,873 vs. 30,249), which are larger, so recall rises from 0.42 to 0.60 while precision is unchanged (0.38 vs. 0.39) and the floater fraction grows from 0.19 to 0.32. Sensor noise thus trades geometric precision for coverage, and aggregate scores such as the F-score or a capped chamfer distance can mistake this for an improvement; we therefore recommend reporting precision and recall separately. For depth-nerfacto, which is supervised by the depth itself, the sensor term is positive (0.033 in F-score) as expected. [TODO: re-evaluate with the noise profile calibrated on the real sensor.]

Interaction. The interaction at 5 m/s is 1.4 mm in chamfer distance for splatfacto, small relative to the wind term, so the decomposition is approximately additive in this regime.

Table 4: Three-way error decomposition (mean ± std over trees). †Absolute baseline values; other rows are increases in error (decrease for F-score).

Method	Component	ΔF@5mm	ΔCD [mm]	ΔCentroid [mm]
depth-nerfacto	Occlusion/method†	0.558 ± 0.078	6.4 ± 0.6	5.6 ± 1.5
	Sensor	+0.033 ± 0.090	+0.2 ± 1.1	+1.0 ± 0.3
	Wind, $U = 1.5$ m/s	+0.101 ± 0.045	+1.0 ± 0.4	+1.8 ± 0.2
	Wind, $U = 3$ m/s	+0.374 ± 0.009	+13.1 ± 7.1	+7.6 ± 3.1
	Wind, $U = 5$ m/s	+0.348 ± 0.063	+10.3 ± 0.7	+11.6 ± 3.9
	Interaction, $U = 5$	-0.018 ± 0.089	+2.2 ± 3.1	+2.6 ± 4.5
splatfacto	Occlusion/method†	0.379 ± 0.117	19.3 ± 4.1	6.7 ± 5.7
	Sensor	-0.060 ± 0.055	-1.5 ± 1.5	+1.9 ± 3.1
	Wind, $U = 1.5$ m/s	+0.134 ± 0.073	+1.5 ± 0.4	+2.2 ± 1.8
	Wind, $U = 3$ m/s	+0.272 ± 0.112	+4.3 ± 1.8	+5.2 ± 6.7
	Wind, $U = 5$ m/s	+0.341 ± 0.131	+8.1 ± 4.7	+12.0 ± 8.5
	Interaction, $U = 5$	+0.059 ± 0.054	+1.4 ± 1.5	-0.8 ± 2.1




Figure 5: Geometry (left) versus view-synthesis quality (right) under increasing wind, splatfacto, noisy sensor.

View synthesis hides geometric damage. From calm to 5 m/s, PSNR on held-out views changes by -7 % while the leaf F-score changes by -75 % (Fig. 5). Methods that average moving leaves into blurred but plausible appearance are rewarded by image metrics; per-leaf geometric ground truth is needed to expose the error.

Rest pose versus posed ground truth. For static 3DGS (4 trees, noisy sensor), the calm-to-5 m/s drop in F-score is 0.355 against the rest pose but only 0.265 against the posed leaves (Table 5 and Fig. 6): at 5 m/s the reconstruction matches the moving canopy (F@5mm = 0.191) better than the rest pose (0.108). A static reconstruction of a windy plant converges towards

Table 5: Static versus deformable 3DGS (same implementation; noisy sensor; mean over 4 trees). F and CD against the rest pose and against the leaves posed at held-out frame times; PSNR on held-out views. *Deformation field with a 6-band temporal encoding.

Wind	Method	F (rest)	F (posed)	CD rest [mm]	CD posed [mm]	Centroid posed [mm]	PSNR [dB]
calm	static 3DGS	0.463	0.456	7.1	7.1	5.1	31.3
	deformable 3DGS*	0.405	0.431	7.5	7.2	5.8	31.3
low	static 3DGS	0.301	0.308	9.7	9.8	7.9	30.5
	deformable 3DGS*	0.269	0.293	10.4	10.2	7.8	30.5
medium	static 3DGS	0.166	0.217	14.0	12.8	12.0	29.6
	deformable 3DGS*	0.146	0.212	14.7	13.0	12.1	29.7
high	static 3DGS	0.108	0.191	18.8	15.1	15.7	28.7
	deformable 3DGS*	0.100	0.186	19.1	15.1	14.5	28.8




Figure 6: Leaf F-score versus wind speed against the rest pose (left) and against the posed leaves (right); mean ± std over trees.

its mean, down-wind-deflected shape, so rest-pose evaluation over-states the wind error by 34 % here; the time-resolved per-leaf ground truth is needed to separate deflection from blur.

Deformable baseline. With the temporal encoding of Yang et al. (2024) (six frequency bands of normalised time), the deformable model is no better than its static counterpart on any metric: posed F@5mm 0.186 vs. 0.191 at 5 m/s, identical PSNR, and its training loss does not fall below the static one on windy sequences, i.e. it does not fit the motion. Over a 20 s orbit, six bands limit temporal variation to about 0.8 Hz, below the branch-sway (0.6–2 Hz) and flutter (2.5–9 Hz) frequencies; moreover, frames are 0.13 s apart, so flutter above 3.75 Hz is aliased for any method, and each instant is observed from a single viewpoint. Short-clip deformation fields therefore do not transfer to orbit captures of fluttering foliage without adaptation. [TODO: re-run with a 10-band temporal encoding (implemented; pending GPU quota) to separate the encoding limit from the intrinsic monocular ambiguity.]

Real data. [TODO: reconstruction of the real saplings at the same wind levels; real-vs-synthetic agreement of the error-versus-U trend.]

6. Discussion and limitations

The generator trades biomechanical fidelity for exactness: branch bending is piecewise rigid along skeleton segments, compound leaves move as single rigid units, leaves may interpenetrate, gusts are spatially uniform, and wind amplitudes and noise parameters must be calibrated to the target setup (Section 3.5). Motion blur and rolling shutter affect RGB only; ground truth refers to the frame-centre time, as for a global-shutter depth sensor. Rendered pixels are deterministic per machine but not across GPUs, whereas geometry, poses and ground truth are bit-identical. Our deformable baseline is a single, deliberately simple design; dedicated dynamic methods (Wu et al., 2024; Luiten et al., 2024) and capture protocols with higher frame rates or synchronised multi-view rigs (which SynthTree supports through its static camera ring) are natural next steps, and the exported per-leaf transforms and optical flow allow their motion to be evaluated directly.

7. Conclusion

SynthTree provides paired calm/windy RGB-D sequences of plants with exact per-leaf ground truth and a protocol that separates occlusion, sensor and wind error. Across four leaf types and two reconstruction families, wind, not sensor noise, is the dominant source of geometric error for neural foliage reconstruction; image-space metrics conceal most of it, rest-pose evaluation over-states it for static methods, and a standard short-clip deformation field does not recover it.

Data and code availability

Code: `https://github.com/bibekgyawali2/synthtree`. Dataset: [TODO: public Kaggle/Zenodo DOI] (CC BY 4.0).

CRediT authorship contribution statement

[TODO:]

Declaration of competing interest

The authors declare no competing interests.

References

Denninger, M., Winkelbauer, D., Sundermeyer, M., Boerdijk, W., Knauer, M., Strobl, K.H., Humt, M., Triebel, R., 2023. BlenderProc2: A procedural pipeline for photorealistic rendering. Journal of Open Source Software 8.

Handa, A., Whelan, T., McDonald, J., Davison, A.J., 2014. A benchmark for RGB-D visual odometry, 3D reconstruction and SLAM, in: IEEE International Conference on Robotics and Automation (ICRA).

Huang, B., Yu, Z., Chen, A., Geiger, A., Gao, S., 2024. 2D gaussian splatting for geometrically accurate radiance fields, in: ACM SIGGRAPH 2024 Conference Papers.

Jensen, R., Dahl, A., Vogiatzis, G., Tola, E., Aanæs, H., 2014. Large scale multi-view stereopsis evaluation, in: IEEE Conference on Computer Vision and Pattern Recognition (CVPR).

Kerbl, B., Kopanas, G., Leimkühler, T., Drettakis, G., 2023. 3D gaussian splatting for real-time radiance field rendering. ACM Transactions on Graphics 42.

Keselman, L., Woodfill, J.I., Grunnet-Jepsen, A., Bhowmik, A., 2017. Intel RealSense stereoscopic depth cameras, in: IEEE Conference on Computer Vision and Pattern Recognition Workshops (CVPRW).

Khoshelham, K., Elberink, S.O., 2012. Accuracy and resolution of Kinect depth data for indoor mapping applications. Sensors 12.

Knapitsch, A., Park, J., Zhou, Q.Y., Koltun, V., 2017. Tanks and temples: Benchmarking large-scale scene reconstruction. ACM Transactions on Graphics 36.

de Langre, E., 2008. Effects of wind on plants. Annual Review of Fluid Mechanics 40.

Luiten, J., Kopanas, G., Leibe, B., Ramanan, D., 2024. Dynamic 3D gaussians: Tracking by persistent dynamic view synthesis, in: International Conference on 3D Vision (3DV).

Matsuki, H., Murai, R., Kelly, P.H.J., Davison, A.J., 2024. Gaussian splatting SLAM, in: IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR).

Mildenhall, B., Srinivasan, P.P., Tancik, M., Barron, J.T., Ramamoorthi, R., Ng, R., 2020. NeRF: Representing scenes as neural radiance fields for view synthesis, in: European Conference on Computer Vision (ECCV).

Müller, T., Evans, A., Schied, C., Keller, A., 2022. Instant neural graphics primitives with a multiresolution hash encoding. ACM Transactions on Graphics 41.

Nguyen, C.V., Izadi, S., Lovell, D., 2012. Modeling Kinect sensor noise for improved 3D reconstruction and tracking, in: Second International Conference on 3D Imaging, Modeling, Processing, Visualization and Transmission (3DIMPVT).

Paulus, S., 2019. Measuring crops in 3D: Using geometry for plant phenotyping. Plant Methods 15.

Prusinkiewicz, P., Lindenmayer, A., 1990. The Algorithmic Beauty of Plants. Springer.

Pumarola, A., Corona, E., Pons-Moll, G., Moreno-Noguer, F., 2021. D-NeRF: Neural radiance fields for dynamic scenes, in: IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR).

Ross, J., 1981. The Radiation Regime and Architecture of Plant Stands. Dr W. Junk Publishers.

Runions, A., Lane, B., Prusinkiewicz, P., 2007. Modeling trees with a space colonization algorithm, in: Eurographics Workshop on Natural Phenomena.

Schunck, D., Magistri, F., Rosu, R.A., Cornelißen, A., Chebrolu, N., Paulus, S., Léon, J., Behnke, S., Stachniss, C., Kuhlmann, H., Klingbeil, L., 2021. Pheno4D: A spatio-temporal dataset of maize and tomato plant point clouds for phenotyping and advanced plant analysis. PLOS ONE 16.

Sturm, J., Engelhard, N., Endres, F., Burgard, W., Cremers, D., 2012. A benchmark for the evaluation of RGB-D SLAM systems, in: IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS).

Tancik, M., Weber, E., Ng, E., Li, R., Yi, B., Kerr, J., Wang, T., Kristoffersen, A., Austin, J., Salahi, K., Ahuja, A., McAllister, D., Kanazawa, A., 2023. Nerfstudio: A modular framework for neural radiance field development, in: ACM SIGGRAPH 2023 Conference Proceedings.

Weber, J., Penn, J., 1995. Creation and rendering of realistic trees, in: Proceedings of SIGGRAPH '95.

Wu, G., Yi, T., Fang, J., Xie, L., Zhang, X., Wei, W., Liu, W., Tian, Q., Wang, X., 2024. 4D gaussian splatting for real-time dynamic scene rendering, in: IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR).

Yang, Z., Gao, X., Zhou, W., Jiao, S., Zhang, Y., Jin, X., 2024. Deformable 3D gaussians for high-fidelity monocular dynamic scene reconstruction, in: IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR).