

```
Uptime: up 1 hour, 23 minutes

---- GPU Information ----
GPU: 00:02.0 VGA compatible controller: Intel Corporation Raptor Lake-P [Iris Xe Graphics]
(rev 04)

---- Disk Information ----
NAME          MODEL          SIZE TYPE MOUNTPOINT
loop0          48.1M loop /snap/snapd/25935
loop1          91.7M loop /snap/gtk-common-themes/1535
loop2          74M loop /snap/core22/2292
loop3          4K loop /snap/bare/5
loop4          20.5M loop /snap/tectonic/43
loop5          74M loop /snap/core22/2339
loop6          531.4M loop /snap/gnome-42-2204/247
loop7          227M loop /snap/thunderbird/1001
loop8          227M loop /snap/thunderbird/995
nvme0n1        BC901 NVMe SK hynix 256GB 238.5G disk
\234\200nvme0n1p1          512M part /boot/efi
\200nvme0n1p2          238G part /
total          256G 113G 131G 47% -

---- RAM Information ----
Total Memory:30Gi
Memory Used:4.8Gi
Free Memory:23Gi
Swap Total2.0Gi
Swap Used:0B
Swap Free:2.0Gi

---- CPU Information ----
Model: 13th Gen Intel(R) Core(TM) i7-1365U 13th Gen Intel(R) Core(TM) i7-1365U CPU @ 4.8GHz
Vendor: GenuineIntel Intel(R) Corporation
Architecture: x86_64
CPU Family: 198 6
Cores per Socket: 10
Threads per Core: 2
Total Threads: 12
Max MHz: 5200.0000

---- Network Interface: ----
Interface Summary:
lo          UNKNOWN          127.0.0.1/8 ::1/128
wlp0s20f3   UP          10.125.232.23/24 fe80::8edf:6023:745:f8b8/64
Interface: lo
State: unknown
MAC Address: 00:00:00:00:00:00
MTU: 65536
Interface: wlp0s20f3
State: up
MAC Address: 04:e8:b9:86:bf:2d
MTU: 1500
Default Gateway: default via 10.125.232.172 dev wlp0s20f3 proto dhcp src 10.125.232.23 metr
ic 600
DNS Servers: nameserver 127.0.0.53
Active Connections: Total Connections: 8

---- PCI devices: ----
--+-00.0 Intel Corporation Raptor Lake-P/U 2p+8e cores Host Bridge/DRAM Controller
+-02.0 Intel Corporation Raptor Lake-P [Iris Xe Graphics]
+-04.0 Intel Corporation Raptor Lake Dynamic Platform and Thermal Framework Processor Part
icipant
+-05.0 Intel Corporation Device a75d
+-06.0-----00.0 SK hynix BC901 NVMe Solid State Drive (DRAM-less)
+-07.0-[02-39]--
+-07.1-[3a-71]--
+-08.0 Intel Corporation GNA Scoring Accelerator module
+-0a.0 Intel Corporation Raptor Lake Crashlog and Telemetry
```

+0d.0 Intel Corporation Raptor Lake-P Thunderbolt 4 USB Controller
+0d.2 Intel Corporation Raptor Lake-P Thunderbolt 4 NHI #0
+12.0 Intel Corporation Alder Lake-P Integrated Sensor Hub
+14.0 Intel Corporation Alder Lake PCH USB 3.2 xHCI Host Controller
+14.2 Intel Corporation Alder Lake PCH Shared SRAM
+14.3 Intel Corporation Raptor Lake PCH CNVi WiFi
+15.0 Intel Corporation Alder Lake PCH Serial IO I2C Controller #0
+15.1 Intel Corporation Alder Lake PCH Serial IO I2C Controller #1
+16.0 Intel Corporation Alder Lake PCH HECI Controller
+16.3 Intel Corporation Alder Lake AMT SOL Redirection
+1e.0 Intel Corporation Alder Lake PCH UART #0
+1e.3 Intel Corporation Alder Lake SPI Controller
+1f.0 Intel Corporation Raptor Lake LPC/eSPI Controller
+1f.3 Intel Corporation Raptor Lake-P/U/H cAVS
+1f.4 Intel Corporation Alder Lake PCH-P SMBus Host Controller
+1f.5 Intel Corporation Alder Lake-P PCH SPI Controller

---- BIOS information: ----

Vendor: Dell Inc.
Version: 1.26.1
Release Date: 09/04/2025
ROM Size: 32 MB
Characteristics:
BIOS Revision: 1.26
Firmware Revision: 1.22
Language Description Format: Abbreviated
Installable Languages: 1
Currently Installed Language: enUS