

Mar 13, 2026 14:17	stdin	Page 1/2
=====		
Uptime: up 6 minutes		
=====		
---- GPU Information ----		
GPU: 00:02.0 VGA compatible controller: Intel Corporation Raptor Lake-P [Iris Xe Graphics] (rev 04)		
=====		
---- Disk Information ----		
nvme0n1 BC901 NVMe SK hynix 256GB 238.5G disk		
nvme0n1p1 512M part /boot/efi		
nvme0n1p2 238G part /		
total 256G 114G 130G 47% -		
=====		
---- RAM Information ----		
Total Memory:30Gi		
Memory Used:3.3Gi		
Free Memory:25Gi		
Swap Total2.0Gi		
Swap Used:0B		
Swap Free:2.0Gi		
=====		
---- CPU Information ----		
Model: 13th Gen Intel(R) Core(TM) i7-1365U		
Vendor: GenuineIntel		
Architecture: x86_64		
CPU Family: 6		
Cores per Socket: 10		
Threads per Core: 2		
Total Threads: 12		
Max MHz: 5200.0000		
=====		
---- Network Interface: ----		
Interface Summary:		
lo UNKNOWN 127.0.0.1/8 ::1/128		
wlp0s20f3 UP 192.168.1.15/24 fe80::2e87:d97:730f:990d/64		
Interface: lo		
State: unknown		
MAC Address: 00:00:00:00:00:00		
MTU: 65536		
Interface: wlp0s20f3		
State: up		
MAC Address: 04:e8:b9:86:bf:2d		
MTU: 1500		
Default Gateway: default via 192.168.1.1 dev wlp0s20f3 proto dhcp src 192.168.1.15 metric 600		
DNS Servers: nameserver 127.0.0.53		
Active Connections: Total Connections: 10		
=====		
---- PCI devices: ----		
--+-00.0 Intel Corporation Raptor Lake-P/U 2p+8e cores Host Bridge/DRAM Controller		
+-02.0 Intel Corporation Raptor Lake-P [Iris Xe Graphics]		
+-04.0 Intel Corporation Raptor Lake Dynamic Platform and Thermal Framework Processor Participant		
+-05.0 Intel Corporation Device a75d		
+-06.0-----00.0 SK hynix BC901 NVMe Solid State Drive (DRAM-less)		
+-07.0-[02-39]--		
+-07.1-[3a-71]--		
+-08.0 Intel Corporation GNA Scoring Accelerator module		
+-0a.0 Intel Corporation Raptor Lake Crashlog and Telemetry		
+-0d.0 Intel Corporation Raptor Lake-P Thunderbolt 4 USB Controller		
+-0d.2 Intel Corporation Raptor Lake-P Thunderbolt 4 NHI #0		

Mar 13, 2026 14:17	stdin	Page 2/2
+-12.0 Intel Corporation Alder Lake-P Integrated Sensor Hub		
+-14.0 Intel Corporation Alder Lake PCH USB 3.2 xHCI Host Controller		
+-14.2 Intel Corporation Alder Lake PCH Shared SRAM		
+-14.3 Intel Corporation Raptor Lake PCH CNVi WiFi		
+-15.0 Intel Corporation Alder Lake PCH Serial IO I2C Controller #0		
+-15.1 Intel Corporation Alder Lake PCH Serial IO I2C Controller #1		
+-16.0 Intel Corporation Alder Lake PCH HECI Controller		
+-16.3 Intel Corporation Alder Lake AMT SOL Redirection		
+-1e.0 Intel Corporation Alder Lake PCH UART #0		
+-1e.3 Intel Corporation Alder Lake SPI Controller		
+-1f.0 Intel Corporation Raptor Lake LPC/eSPI Controller		
+-1f.3 Intel Corporation Raptor Lake-P/U/H cAVS		
\-1f.4 Intel Corporation Alder Lake PCH-P SMBus Host Controller		
\-1f.5 Intel Corporation Alder Lake-P PCH SPI Controller		
=====		
---- BIOS information: ----		
=====		