
Instructor: Prof. Dr. Katharina Jahn

Introduction to Focus Areas Data Science WS22/23 Project 1

Group 7 Maike, Jule, Carlos, Abhinav

Goals


- 1. Exploratory data analysis
- 2. Classification
- 3. Performance metrics




Exploratory Data Analysis


- 1. Barplot
- 2. Pairplot
- 3. Boxplot
- 4. Heatmap

Results






Effect of Categorical Variables




Yes

Boxplots for Numeric Variables



Heat Map
Pearson correlation




Classifiers

- 1. Logistic regression
- 2. Boosted Logistic regression
- 3. Random forest
- 4. K-nearest neighbour

Logistic regression

- A logistic regression model is used
- Model improvement by error minimization





Boosted Logistic regression

- First classification based on each feature separately (decision stumps)
- Combining of the classifications by applying different weights and a logistic regression

Classifier 1


Classifier 2







Random Forest

- Multiple Decision Trees are randomly created
- A data point is classified by each of them
- The class with the most 'votes' is the final classification










kNN

- A new datapoint is classified by looking at the k nearest neighbors
- Best tuned model $\rightarrow k = 13$









Performance Metrics

- 1. Accuracy dotplot
- 2. Comparison graph
- 3. PR curve
- 4. PRG curve
- 5. ROC curve
- 6. Calibration curve





The amount of agreement correct by the agreement expected by chance is Cohen's Kappa

Performance Chart




Logistic Optimal Informedness = 0.68370126146789
Random Forest Optimal Informedness = 0.673165137614679
Boosted Logistic Optimal Informedness = 0.598767201834862
kNN Optimal Informedness = 0.654816513761468






$$precG = \frac{prec - \pi}{(1 - \pi)prec} = 1 - \frac{\pi}{1 - \pi} \frac{FP}{TP}$$

$$recG = \frac{rec - \pi}{(1 - \pi)rec} = 1 - \frac{\pi}{1 - \pi} \frac{FN}{TP}$$







References

- 1. Pisula T. "An Ensemble Classifier-Based Scoring Model for Predicting Bankruptcy of Polish Companies in the Podkarpackie Voivodeship." Journal of Risk and Financial Management. 2020; 13(2):37. https://doi.org/10.3390/jrfm13020037.
- 2. Detrano, R et al. "International application of a new probability algorithm for the diagnosis of coronary artery disease." The American journal of cardiology vol. 64,5 (1989): 304-10. https://doi.org/10.1016/0002-9149(89)90524-9.
- 3. J. H. Gennari, P. Langley, and D. Fisher. 1989. "Models of incremental concept formation." Artif. Intell. 40, 1–3 (Sep. 1989), 11–61. https://doi.org/10.1016/0004-3702(89)90046-5
- 4. Kibler, Dennis, David W. Aha, and Marc K. Albert. "Instance-based prediction of real-valued attributes." Computational Intelligence 5.2 (1989): 51-57.
- 5. R Core Team (2022). "R: A language and environment for statistical computing." R Foundation for Statistical Computing, Vienna, Austria. https://www.R-project.org/.
- 6. Illustrations
 https://www.researchgate.net/figure/Data-classification-by-logistic-regression-aClassification-of-1D-data-showing-the-fitted-fig1-353913155
- 7. Random Forest sketch https://www.researchgate.net/figure/Example-of-a-Random-Forest-workflow-fig2-3420288
 55


Dataset description can be found here, and data file here.

Thanks for listening! Questions?





Top features: chest pain type (cp), number of major vessels (ca), maximum heart rate achieved (thalach), thallium scintigraphy (thal)



Boosting Iterations

25

$Accuracy \Rightarrow Downward trend$

Possible reason: Tuning parameters

- mtry (by default) \rightarrow bagging
- Fast
- Good variance-bias tradeoff

- nIter (by default) \rightarrow decision stump
- Speedy
- Weak