ACCIDENT PREVENTION PROGRAM

for

BICKNELL BUILDS LLC



Bicknell Builds Accident Prevention Plan Table of Contents

Subject	Page
General Instructions	1
Responsibilities	2
Safety Disciplinary Policy	3
Procedure for Injury or Illness on the Job	4
Basic Rules for Accident Investigation	5
How to Hold an Effective Safety Meeting	6
Construction Safety Meeting Topic Suggestions	7
First Aid Kits and Posters	8
Situations Involving Blood	8
Confined Space	9
Fall Protection Safety Rules	10
General Safety Rules for Construction	14
Hearing Conservation Program	15
Heat Stress - How do you prevent heat illness?	16
Ladder Safety Rules	19
General Materials Handling Safety	20
Motorized Vehicles and Equipment	22
Respirator Program	22
Scaffold Safety Rules	23
Trenching and Excavating	24
Welding and Cutting Safety Rules	25
Wildfire Smoke Response Plan	29
What to Do	31
Site Specific Safety Plan	33
Project Safety Orientation	34
Weekly Jobsite Inspection	35
Safety Meeting Minutes	36
Safety Writeup Form	37
Incident Report Form	38
Supervisor Incident Investigation Form	39

Bicknell Builds Accident Prevention Plan

SAFETY AND HEALTH POLICY FOR BICKNELL BUILDS

At Bicknell Builds, safety is a core part of everything we do. Our goal is to maintain a safe, healthy, and respectful work environment where no employee is expected to work under hazardous or unsanitary conditions.

We believe that employees should take pride in and enjoy their work. Protecting the health and well being of our team is essential to that goal, which is why preventing workplace injuries and illnesses remains a top priority in all of our operations.

Bicknell Builds is committed to providing ongoing safety training and maintaining a strong accident prevention program. Safety is a shared responsibility that starts with leadership and extends to every member of our team. Each employee is responsible for looking out for their own safety as well as the safety of their coworkers.

By working together and making safe practices part of our daily routine, we can create a safer workplace and contribute to the well being of everyone on our team.

General Information

1. General Instructions

1. Overview

   Across the construction industry, safety is of paramount importance to everyone. From keeping workers safe and as comfortable as possible to ensuring our company runs efficiently and earns a positive reputation, it is in everyone's best interest to understand and follow the policies of this plan in order to establish and maintain an injury-free workplace environment.
2. Procedures
   This document contains guidance for safety procedures to be followed and forms to be used. Supervisors are expected to integrate these procedures into the appropriate work activity and employees are expected to apply them on the job. The included forms are to be used if they apply to the job concerned.
3. Dissemination
   A copy of this statement will be issued to all management personnel

4. Regulations
   A copy of the following documents will be maintained on each job site in the jobsite binder:

   1. Chapter 155, Construction Safety Standards from the Division of Industrial Safety and Health, Washington State Department of Labor and Industries.

   2. A copy of this Accident Prevention Plan.

   3. The WISHA Poster, form F416-081-909, which tells employees and employers their rights under the Washington Industrial Safety and Health Act.
      1. Your Rights as a Worker, form F700-074-000, which tells employees about minimum wage, mealtimes and other rights they are entitled to.
      2. Notice to Employees – If an Injury Occurs, F242-191-909.
      3. A copy of the completed [Site Specific Safety Plan.](link to SSSP)

2. Responsibilities

Responsibilities for safety and health include the establishment and maintenance of an effective communication system among workers, supervisors and management officials. To this end, all personnel are responsible to speak up when further clarity is required. Specific safety and health responsibilities for company personnel are as follows:

1. Management Officials

   Active participation in and support of safety and health programs is essential. Management officials will display their interest in safety and health matters at every opportunity. At least one manager (as designated) will participate in the safety and health committee meetings, incident investigations and inspections. Each manager will establish realistic goals for implementing instructions for meeting the goals. Goals and implementing instructions shall be within the framework established by this document.
2. Supervisors

   The safety and health of the employees they supervise is a primary responsibility of the supervisors. To accomplish this obligation, supervisors will:

1.	Assure that all safety and health rules, regulations, policies and procedures are understood and observed.
2.	Require the proper care and use of all required personal protective equipment (PPE).
3.	Identify and eliminate job hazards quickly through job safety analysis procedures. (See the sample Job Safety Analysis form attached to this document.)
4.	Inform and train employees on the hazardous chemicals and/or procedures they MAY encounter under normal working conditions or during an emergency. (See the sample hazard communication program.)
5.	Receive and take initial action on employee suggestions, awards or disciplinary measures.
6.	Conduct daily crew/leader "huddles" the first five minutes of each work shift to discuss safety and health matters and work plans for the workday.
7.	Conduct walk-around safety inspections at the beginning of each job, and at least weekly thereafter.
8.	Train employees (new and experienced) in the safe and efficient methods of accomplishing each job or task as necessary.
9.	Review injury trends and establish prevention measures.
10.	Conduct weekly safety meetings and actively participate in the proceedings.
11.	Participate in incident investigations and inspections.
12.	Promote employee participation in the safety and health program.
13.	Actively follow the progress of injured workers and display an interest in their rapid recovery and return to work.

3. Employees

Observe the items of responsibility established in this document as well as job safety rules which may apply to specific task assignments.

3. Disciplinary Policy

Bicknell Builds believes that a safety and health Accident Prevention Program is unenforceable without some type of disciplinary policy. Our company believes that in order to maintain a safe and healthful workplace, the employees must be cognizant and aware of all company, State, and Federal safety and health regulations as they apply to the specific job duties required. The following disciplinary policy is in effect and will be applied to all safety and health violations.

The following steps will be followed unless the seriousness of the violation would dictate going directly to Step 2 or Step 3.

1. A first-time violation will be discussed orally between company supervision and the offending party. This will be done as soon as possible.
2. A second-time offense will be followed up with a safety write-up and a copy of this written documentation will be distributed to management as appropriate.
3. A third time violation will result in time off or possible removal from site, depending on the seriousness of the violation.

4. Injury or Illness on the Job

Procedure for Injury or Illness on the Job

A. Owner or lead person immediately takes charge

1. Supervise and administer first aid as you wish(Good Samaritan Law applies).
2. Arrange for transportation (ambulance, helicopter, company vehicle, etc.), depending on the seriousness of the injury. Protect the injured person from further injury.
3. Notify Chris or Project Manager, if not already present.
4. Do not move anything unless necessary, pending investigation of the incident.
5. Accompany or take injured person(s) to doctor, hospital, home etc. (depending on the extent of injuries).
6. Take injured person to family doctor, if available.
7. Remain with the injured person until relieved by other authorized persons (manager, EMT, doctor, etc.).
8. When the injured person's immediate family is known, the owner or supervisor should properly notify family members, preferably in person, or have an appropriate person do so.

B. Documentation

1. Minor injuries – requiring doctor or outpatient care: After the emergency actions following an injury, an investigation of the incident will be conducted by the immediate supervisor and any witness to determine the causes.

The findings must be documented on our investigation form.

2. Major injuries – fatality, hospitalization, non-hospitalized amputation or loss of an eye(s): Top management must see that L&I is notified as soon as possible, but at least within 8 hours of the incident that caused the fatality or in-patient hospitalization. Also, any non-hospitalized amputation or loss of an eye(s) must be reported to L&I within 24 hours of the incident.

Call L&I at 1-800-423-7233 or visit the nearest L&I office or call OSHA at 1-800-321-6742. Top management will then assist the Department in the investigation. The findings must be documented on our investigation form. and recorded on the OSHA 300 log, if applicable (this will be required when we have more than 10 employees.)

C. Near Misses

1. All near-miss incidents must be investigated. Worker must complete Incident Report Form and submit to Site Supervisor.
2. Document the incident using Supervisor Incident Investigation
3. Review the findings at the monthly safety meetings or sooner if the situation warrants.

5. Accident Investigation

Basic Rules for Accident Investigation

- The purpose of an investigation is to find the cause of an incident and prevent future occurrences, not to fix blame. An unbiased approach is necessary to obtain objective findings.
- Visit the incident scene as soon as possible – while facts are fresh and before witnesses forget important details.
- If possible, interview the injured worker at the scene of the incident and “walk” him or her through a re-enactment. Be careful not to actually repeat the act that caused the injury.
- All interviews should be conducted as privately as possible. Interview witnesses one at a time. Talk with anyone who has knowledge of the incident, even if they did not actually witness the mishap.
- Consider taking signed statements in cases where facts are unclear or there is an element of controversy.
- Graphically document details of the incident: area, tools, and equipment. Use sketches, diagrams, and photos as needed, and take measurements when appropriate.

- Focus on causes and hazards. Develop an analysis of what happened, how it happened, and how it could have been prevented. Determine what caused the incident itself (unsafe equipment/condition, unsafe act, etc), not just the injury.
- How will you prevent such incidents in the future? Every investigation should include an action plan.
- If a third party or defective product contributed to the incident, save any evidence. It could be critical to the recovery of the claim costs.

Use Supervisor Incident Investigation Report Form to write up accident investigation report.

Safety Meetings

1. How to Hold an Effective Safety Meeting

1. Be certain everyone knows the time and place of the next meeting.
2. Insist that everyone attend. Before the next meeting, remind those who were late or failed to attend that attendance is not optional.
3. Pick an appropriate topic. If you can't think of an appropriate topic, use one from this list.
4. Start the meeting on time.
5. Don't waste time – give the meeting your undivided attention.
6. Discuss the topic you have chosen and prepared. Don't wait until the meeting to choose your topic.
7. Use handouts or posters to illustrate your topic.
8. Discuss current job site safety events, injuries and close calls.
9. Encourage employees to discuss safety problems as they arise. Do not save safety concerns for the meeting. Allow some time for employee questions or input at the end of the meeting.
10. Invite managers or owners to speak. Ask fellow employees to speak on a safety topic.
11. If you prevented one injury, it is time well spent. Your topic may be one that some employees have heard many times, but there may be one person who is new or has never been told of the safety requirement for that topic. Repeating topics several times during the course of a project is beneficial as long as it applies to the work being done.
12. Follow up on employee concerns or questions and get back to them with the answer before the next meeting.
13. Be certain to document the attendance and the topics discussed.

Toolbox Talk Topics

Construction Safety Meeting Suggestions

(The crew leader’s guide)

Suggested good topics for construction safety meetings (as they apply to your jobsite):

1. Fall protection/fall prevention
2. Personal protective equipment
    1. Hard hats
    2. Eye protection
    3. Hearing protection
    4. Footwear
    5. Safety harness/belts
    6. Respiratory protection
3. Housekeeping
4. Tool inspection
5. Emergency procedures
6. Electrical safety
7. Ladder safety
8. Scaffold safety
9. Fire prevention/fire extinguishers
10. Reporting injuries and unsafe conditions
11. Confined spaces
12. Lock-out procedures
13. Heat Stress
14. Excavation and trenching
15. Mental Health and substance abuse
16. Repetitive motion/fatigue related injuries
17. Bloodborne Pathogens

Training programs, educational materials, films, videos and posters are available from the Department of Labor and Industries’ Safety & Health webpage (eyeonsafety.info).

Training Info

1. First Aid Kits and Posters

FIRST AID TRAINING, KITS AND POSTER

A. Purpose: To afford the employees immediate and effective attention should an injury result, Bicknell Builds will ensure that certified first aid responder(s) will be available.

1. To meet the above objectives, the following procedures, in accordance with WAC 296-155, Safety Standards for Construction will be followed:

a. All supervisors or persons in charge of crews will be trained in first aid unless their duties require them to be away from the jobsite. If so, other persons who are certified in first aid will be designated as the recognized first aid responder.

b. Other persons will be trained in order to augment or surpass the standard requirements.

c. Valid first aid cards are recognized as ones that include both first aid and cardiopulmonary resuscitation (CPR) and have not reached the expiration date.

2. First aid kits and procedures will be in accordance with the requirements of WAC 296-800, Safety & Health Core Rules

a. First aid kit locations include:

1. In every company vehicle
2. Company shop
3. In every on site job box

b. Site supervisors is designated to ensure that the first aid kits are properly maintained and stocked.

2. Situations Involving Blood

If personnel who are trained in first aid are involved in a situation involving blood, they should:

1. Avoid skin contact with blood/other potentially infectious materials by letting the victim help as much as possible, and by using gloves provided in the first aid kit.
2. Remove clothing, etc. with blood on it after rendering help.
3. Wash thoroughly with soap and water to remove blood. A 10% chlorine bleach solution is good for disinfecting areas contaminated with blood (spills, etc.).
4. Report such first aid incidents within the shift to supervisors (time, date, blood presence, exposure, names of others helping).

Hepatitis B vaccinations will be provided as soon as possible but not later than 24 hours after the first aid incident.

If an exposure incident occurs, we will immediately make available appropriate:

1. Post exposure evaluation
2. Follow-up treatment
3. Follow-up as listed in WAC 296-823, Occupational Exposure to Bloodborne Pathogens.

Training covering the above information should be conducted at job site safety meetings.

Site Specific Hazards

1. Confined Spaces

Fatalities and injuries too often occur among construction workers who, during the course of their jobs, are required to enter confined spaces. In some circumstances, these workers are exposed to multiple hazards, any of which may cause bodily injury, illness, or death. Workers are injured and killed from a variety of atmospheric hazards (such as toxic gases or insufficient oxygen) and physical hazards (such as moving machinery or excessive heat).

The construction standard (WAC 296-155) requires that companies follow WAC 296-809, when working in confined spaces. There is an exception for work on sewer systems under construction.

Employers must consult with employees and their authorized representatives on the development and implementation of all aspects of the permit required confined space entry program required by the Confined Space Standard, (WAC 296-809).

All information required by the Confined Space Standard must be available to employees covered by the standard (or their authorized representatives).

You must first determine if you have any confined spaces at your job site. A confined space has three characteristics; it must have all three characteristics to be considered a confined space:

1. Large enough to get your body entirely inside to do your work
2. Not designed or intended for continuous occupation
3. Restricted entry or exit

If you do have any confined spaces, you must not enter them until you have carefully evaluated the hazards inside to determine what type of entry procedure may be used for each confined space you have.

Note to the employer: L&I's confined space rule includes requirements not listed here. Please consult WAC 296-809 Confined Spaces for more information. For additional help (including a sample written program), visit https://lni.wa.gov/safety-health/safety-training-materials/workshops-events/beheatsmart

2. Fall Protection

Falls from elevation are a major cause of injuries and deaths in the construction industry. We at Bicknell Builds are committed to eliminating injuries caused by fall hazards by instituting a program of 100% fall protection for all hazards based on type and stated trigger heights starting at zero height.

Zero Feet WAC 296-880-10010 Regardless of height:

1. All open sided floors, walkways, platforms, or runways above or adjacent to dangerous equipment must be guarded by a standard guardrail system.
2. We must guard all holes into which anyone can trip, step into, or step through by a cover of standard strength and construction or a standard guardrail system.
3. We must protect everyone from falling into or onto impalement hazards, such as: Reinforcing steel (rebar), exposed steel, or wood. We will train all employees exposed to fall hazards according to WA State Training requirements as spelled out in WAC 296-880-10015(1–5).

Four Feet or More WAC 296-880-20005 (This section does not include everything in WAC 296-880-20005.)

Applies to:

1. Every open sided walking/working surface with unprotected sides and edges.
2. Ramps, runways, and inclined walkways.
3. Form and rebar work — while placing or tying reinforcing steel or working on the face of formwork or reinforcing steel.
4. Steep-pitched roofs.
5. Low-pitched roofs. All construction work activities EXCEPT roofing and actively constructing a leading edge. Those activities fall under the 6-foot rule.
6. Hazardous slopes for employees are exposed to falls of 4 feet or more to a lower surface.
7. Wall opening is an opening at least 30-inches high and 18-inches wide in any wall/partition that must be guarded when the bottom of the opening is less than 39 inches above the working surface.
8. When employees are using stilts, the height of the top rail or equivalent member of the standard guardrail system must be increased (or additional railings may be added) an amount equal to the height of the stilts while maintaining the strength specifications of the guardrail system.
9. Working on platforms or ladders above the protection of the guardrail system, the employer must either increase the height of the guardrail system or select another form of fall protection.
10. When guardrails are removed to perform a specific task, the area must be constantly attended by an employee whose duty is to warn persons approaching the hazard until the guardrail is replaced.
11. Holes through which a person can fall into or through. This includes skylight holes as well as skylights that have been installed.
12. Wall openings.

Six Feet or More WAC 296-880-30005(1)

a. Roofing work on a low-pitched roof;

b. Constructing a leading edge work (see definition).

Note: Employees not directly involved with constructing the leading edge, or are not performing roofing work must comply with WAC 296-880-20005, Fall Protection Required at 4 Feet.

Ten Feet or More WAC 296-880-30005(2)

a. Employees engaged in erection/ placement of structural members. Exception: When the erection or placement of structural members is performed on or from a floor, deck, roof, or similar surface you must comply with WAC 296-880-200, Fall protection required at four feet or more.

b. Engaged in excavation and trenching operations.

i. Exceptions. Fall protection is not required at excavations when employees are:

A. Directly involved with the excavation process and on the ground at the top edge of the excavation; or

B. Working at an excavation site where appropriate sloping of side walls has been implemented as the excavation protective system.

ii. Fall protection is required for employees standing in or working in the affected area of a trench or excavation exposed to a fall hazard of 10 feet or more; and:

A. The employees are not directly involved with the excavation process; or

B. The employees are on the protective system or any other structure in the excavation.
Note: Persons considered directly involved in the excavation process include:

1. Foreman of the crew.
2. Signal person.
3. Employee hooking on pipe or other materials.
4. Grade person.
5. State, county, or city inspectors inspecting the excavation or trench.
6. An engineer or other professional conducting a quality-assurance inspection.

Fall Protection Work Plan WAC 296-880-10020

1. Employer must develop and implement a written fall protection work plan that addresses each area of the work place where the employees are assigned and where fall hazards of 10 feet or more exist.
2. The FPWP must:

a. Identify all fall hazards in the work area;

b. Describe the method of fall arrest or fall restraint to be provided;

c. Describe the proper procedures for the assembly, maintenance, inspection, and disassembly of the fall protection system to be used;

d. Describe the proper procedures for the handling, storage, and securing of tools and materials;

e. Describe the method of providing overhead protection for workers who may be in, or pass through the area below the work area;

f. Describe the method for prompt, safe removal of injured workers; and

g. Be available on the job site for inspection by the department.

3.Prior to permitting employees into areas where fall hazards exist, the employer must ensure employees are trained and instructed in the items described in WAC 296-880-10020(2)(a–f) above.

Systems Criteria See WAC 296-880-400.

Special Notes

1. A Safety Watch System: PROHIBITED for all construction work.
2. Warning lines can be used for activities other than roofing work and constructing a leading edge. Ref: 20005(1)(f) and 40040(1)(c). Another system would be required anytime a warning line system is used and a worker is outside the warning line system.
3. Skylights whether holes or installed must be addressed on the FPWP if the fall is 10 feet or more.

L&I Fall Protection Work Plan Template: https://www.lni.wa.gov/forms-publications/F417-272-000.pdf

3. General Construction Safety

L&I Construction Safety Checklist: https://www.lni.wa.gov/forms-publications/F418-055-000.pdf

1. Always store materials in a safe manner. Tie down or support piles if necessary to prevent falling, rolling, or shifting.
2. Shavings, dust, scraps, oil or grease should not be allowed to accumulate. Good housekeeping is a part of the job.
3. Trash piles must be removed as soon as possible. Trash is a safety and fire hazard.
4. Remove or bend over the nails in lumber that has been used or removed from a structure.
5. Immediately remove all loose materials from stairs, walkways, ramps, platforms, etc.
6. Do not block aisles, traffic lanes, fire exits, gangways, or stairs.
7. Avoid shortcuts – use ramps, stairs, walkways, ladders, etc.
8. Standard guardrails must be erected around all floor openings and excavations must be barricaded. Contact your supervisor for the correct specifications.
9. Do not remove, deface or destroy any warning, danger sign, or barricade, or interfere with any form of protective device or practice provided for your use or that is being used by other workers.
10. Get help with heavy or bulky materials to avoid injury to yourself or damage to material.
11. Keep all tools away from the edges of scaffolding, platforms, shaft openings, etc.
12. Do not use tools with split, broken, or loose handles, or burred or mushroomed heads. Keep cutting tools sharp and carry all tools in a container.
13. Know the correct use of hand and power tools. Use the right tool for the job.
14. Know the location and use of fire extinguishing equipment and the procedure for sounding a fire alarm.
15. Flammable liquids shall be used only in small amounts at the job location and in approved safety cans.
16. Proper guards or shields must be installed on all power tools before use. Do not use any tools without the guards in their proper working condition. No “homemade” handles or extensions (cheaters) will be used!
17. All electrical power tools (unless double insulated), extension cords, and equipment must be properly grounded.

18. All electrical power tools and extension cords must be properly insulated. Damaged cords must be replaced.
19. Do not operate any power tool or equipment unless you are trained in its operation and authorized by your firm to do so.
20. All electrical power equipment and tools must be grounded or double insulated.

4. Hearing Conservation

Purpose:

The purpose of the Hearing Conservation Program is to ensure that all employees are protected from exposure to noise hazards. When workers are exposed to high noise levels, the employer must have an effective, written hearing protection program.

Procedure:

An effective hearing conservation program should first assess companywide noise exposures in order to identify any employee or group of employees exposed to noise. Noise is measured with a sound level meter or noise dosimeters, which measure average noise levels over time. Employees who are exposed to noise at or above an eight-hour time-weighted average of 85 dBA (decibels, A-weighted) must be covered under a written hearing conservation program. For these employees, the employer must develop, implement, and maintain (at no cost to the employees) a program consisting of:

1. Mandatory audiometric testing
2. Making hearing protectors available and ensuring their use.
3. Comprehensive training explaining hearing loss, hearing protective devices, and the employer’s hearing conservation program.
4. Warning signs for high noise areas (115 dBA or higher).
5. Keeping accurate records.
6. Ensuring employee access to their records.

Additionally, the employer must post a copy of the hearing conservation standard or post a notice to affected employees or their representatives that a copy of the standard is available at the workplace for their review.

Note to the employer: L&I’s hearing conservation rule includes requirements not listed here. Please consult WAC 296-842 Hearing Loss Prevention for more information. For

additional help (including a sample written program), visit https://www.lni.wa.gov/safety-health/safety-topics/topics/noise#overview

The Department of Labor and Industries Division of Occupational Safety and Health has a team of no-cost consultants who can visit your worksite and take the necessary noise measurements. To learn more, please contact DOSH Consultation by submitting a consultation request at https://www.lni.wa.gov/safety-health/preventing-injuries-illnesses/request-consultation/onsite-consultation

5. Heat Stress

1. • Supply adequate water and encourage workers who work in hot weather to drink regularly, even when not thirsty. A small amount of water every 15 minutes is recommended rather that a large amount after hours of sweating.
2. • Learn the signs and symptoms of heat-related illness.
3. • Inform workers they should avoid alcohol or drinks with caffeine before or during work in hot weather.
4. • Try to do the heaviest work during the cooler parts of the day.
5. • Adjusting to work in heat takes time. Allow workers to acclimatize. Start slower and work up to your normal pace.
6. • Wear lightweight, loose-fitting, light-colored, breathable (e.g. cotton) clothing and a hat.
7. • Allow workers to take regular breaks from the sun. Loosen or remove clothing that restricts cooling.
8. • Watch workers for symptoms of heat-related illness. This is especially important for non-acclimatized workers, those returning from vacations and for all workers during heat-wave events.
9. • If exertion causes someone’s heart to pound or makes them gasp for breath, become lightheaded, confused, weak or faint, they should STOP all activity and get into a cool area or at least into the shade, and rest.

The two major heat-related illnesses are heat exhaustion and heat stroke. Heat exhaustion, if untreated, may progress to deadly heat stroke. Heat stroke is very dangerous and frequently fatal. If workers show symptoms, always take this seriously and have them take a break and cool down before returning to work. Stay with them. If symptoms worsen or the worker does not recover within about 15 minutes, call 911 and have them transported and medically evaluated. Do not delay transport.

Heat Exhaustion or Heat Stroke?

How do you tell the difference?

The telling difference is mental confusion or disorientation in ALL heat stroke victims

You can ask these 3 questions: What is your name? What day is this? Where are we?

If a worker can’t answer these questions, assume it is heat stroke.

What are the symptoms of heat exhaustion and heat stroke?

Heat Exhaustion	Heat Stroke
1. • Heavy sweating 2. • Exhaustion, weakness 3. • Fainting / Lightheadedness 4. • Paleness 5. • Headache 6. • Clumsiness, dizziness 7. • Nausea or vomiting 8. • Irritability	1. • Sweating may or may not be present 2. • Red or flushed, hot dry skin 3. • Any symptom of heat exhaustion but more severe 4. • Confusion / Bizarre behavior 5. • Convulsions before or during cooling 6. • Collapse 7. • Panting/rapid breathing 8. • Rapid, weak pulse 9. • Note: May resemble a heart attack

What do you do if someone is suffering from heat exhaustion or heat stroke?

Heat Exhaustion	Heat Stroke
Move the worker to a cool, shaded area to rest; do not leave them alone. Loosen and remove heavy clothing that restricts evaporative cooling.	Heat stroke is a medical emergency Get medical help immediately, call 911 and transport as soon as possible. Move the worker to a cool, shaded area and remove clothing that restricts cooling. Seconds count.

Give cool water to drink, about a cup every 15 minutes. Fan the worker, spray with cool water, or apply a wet cloth to their skin to increase evaporative cooling. Recovery should be rapid. Call 911 if they do not feel better in a few minutes. Do not further expose the worker to heat that day. Have them rest and continue to drink cool water or electrolyte drinks.	Cool the worker rapidly using whatever methods you can. For example, immerse the worker in a tub of cool water; place the worker in a cool shower; spray the worker with cool water from a garden hose; sponge the worker with cool water; or, if the humidity is low, wrap the worker in a cool, wet sheet and fan them vigorously. Continue cooling until medical help arrives. If emergency medical personnel are delayed, call the hospital emergency room for further instruction. Do not give the worker water to drink until instructed by medical personnel.

Heat Stress Check List

- Does the worksite have temperatures that may cause heat stress?
  - Please note: An employee's risk of heat stress is directly affected by what clothing and gear are worn. Employers must take specific actions to protect employees wearing nonbreathable clothing or gear beginning at 52° F. Employers must take specific actions to protect employees wearing other types of clothing/gear beginning at 80° F.
- Do employees have access to an adequate supply of cool drinking water at all times?
- Are employees allowed cool-down rest breaks during prolonged heavy labor?
- Do workers have access to adequate shade during breaks?
- Have employees been trained on the symptoms of heat-related illness?
- Are employees trained on first aid measures for heat-related illness?

Outdoor Heat Safety Program

Sample template for optional use. Customize the content so it reflects the working conditions and safety precautions at your job sites:

Outdoor Heat APP addendum (Updated July 17, 2023)

Outdoor Heat APP addendum, (Spanish version)

Note to the employer: For additional help with requirements, Training and Resources and Q&A, visit L&I's Be Heat Smart page https://lni.wa.gov/safety-health/safety-training-materials/workshops-events/beheatsmart

6. Ladder Safety

General:

- Inspect before use for physical defects. If defects are found remove from service.
- Ladders will not be painted except for numbering purposes.
- Do not use ladders for skids, braces, workbenches, or any purpose other than climbing.
- When you are ascending or descending a ladder, do not carry objects that will prevent you from grasping the ladder with both hands.
- Always face the ladder when ascending and descending.
- If you must place a ladder over a doorway, barricade the door to prevent its use and post a warning sign.
- Only one person is allowed on a ladder at a time.
- Do not jump from a ladder when descending.
- All joints between steps, rungs, and side rails must be tight.
- Safety feet must be in good working order and in place.
- Rungs must be free of grease and/or oil.

Stepladders

- Do not place tools or materials on the steps or platform of a stepladder
- Do not use the top two steps of a stepladder as a step or stand.
- Always level all four feet and lock spreaders in place.
- Do not use a stepladder as a straight ladder.

Straight type or extension ladders

- All straight or extension ladders must extend at least three feet beyond the supporting object when used as an access to an elevated work area.
- After raising the extension portion of a two or more stage ladder to the desired height, check to ensure that the safety dogs or latches are engaged.
- All extension or straight ladders must be secured or tied off at the top.
- All ladders must be equipped with safety (non-skid) feet.

- Portable ladders must be used at such a pitch that the horizontal distance from the top support to the foot of the ladder is about one-quarter of the working length of the ladder.

7. Material Handling Safety

General material storage safety:

- Make sure that all materials stored in tiers are stacked, racked, blocked, interlocked, or otherwise secured to prevent sliding, falling, or collapse.
- Clearly post the maximum safe load limits of floors within buildings and structures, in pounds per square foot, in all storage areas, except for floor or slab on grade. Do not exceed the maximum safe loads.
- Keep aisles and passageways clear to provide for the free and safe movement of material handling equipment or employees. Keep these areas in good repair.
- Do not store materials on scaffolds or runways in excess of supplies needed for immediate operations.
- Use ramps, blocking, or grading when a difference in road or working levels exists to ensure the safe movement of vehicles between the two levels.
- Do not place materials stored inside buildings under construction within 6 feet of any hoistway or inside floor openings, or within 10 feet of an exterior wall which does not extend above the top of the material stored.
- Segregate non-compatible materials in storage.
- Do not stack lumber more than 20 feet high; if handling lumber manually, do not stack more than 16 feet high.

1. Remove all nails from used lumber before stacking.
2. Stack lumber on level and solidly supported sills, and such that the stack is stable and self-supporting.
3. Stack stored lumber on timber sills to keep it off the ground. Sills must be placed level on solid supports.
4. Place cross strips in the stacks when they are stacked more than 4 feet high.

- If not racked, stack and block structural steel, poles, pipe, bar stock, and other cylindrical materials as to prevent spreading or tilting.

1. Wear heavy gloves when handling reinforcing steel.

2. When bending reinforcing steel on the job, use a strong bench set up on even dry ground or a floor to work on.
3. Carefully pile structural steel to prevent danger of members rolling off or the pile toppling over.
4. Keep structural steel in low piles, giving consideration to the sequence of use of its members.
5. Stack corrugated and flat iron in flat piles, with the piles not more than 4 feet high; place spacing strips between each bundle.

- Frequently inspect stock piles of sand, gravel, and crushed stone to prevent their becoming unsafe by continued adding to or withdrawing from the stock.

General Rigging Equipment Safety:

- Inspect rigging equipment for material handling prior to use on each shift and as necessary during its use to ensure that it is safe. Remove defective rigging equipment from service.
- Never load rigging equipment in excess of its recommended safe working load.
- Remove rigging equipment when not in use from the immediate work area so as not to present a hazard to employees.
- Mark special rigging accessories (i.e., spreader bars, grabs, hooks, clamps, etc.) or other lifting accessories with the rated capacity. Proof test all components to 125% of the rated load prior to the first use. Maintain permanent records on the job site for all special rigging accessories.

Disposal of waste materials:

- Whenever materials are dropped more than 20 feet to any point lying outside the exterior walls of the building, use an enclosed chute of wood or equivalent material.
- When debris is dropped without the use of chutes, make sure that the area onto which the material is dropped is completely enclosed with barricades at least 42 inches high and 20 feet back from the projected edge of the opening above. Post at each level warning signs of the hazard of falling materials. Do not remove debris in this lower area until debris handling ceases above.
- Remove all scrap lumber, waste material, and rubbish from the immediate work area as the work progresses.
- Make sure to comply with local fire regulations if disposing of waste material or debris by burning.

- Keep all solvent waste, oily rags, and flammable liquids in fire-resistant covered containers until removed from the work site.

Forklift safety

Click on the link below to access basic forklift training. Employees must be trained on specific equipment that they will be operating in addition to this basic information.

https://www.lni.wa.gov/safety-health/safety-training-materials/online-safety-training#Forklifts

8. Motorized Vehicles and Equipment

1. Do not ride on motorized vehicles or equipment unless a proper seat is provided for each rider.
2. Always be seated when riding authorized vehicles (unless they are designed for standing).
3. Do not operate any motorized vehicle or equipment unless you are specifically authorized to do so by your supervisor.
4. Always use your seat belts in the correct manner.
5. Obey all speed limits and other traffic regulations.
6. Always be aware of pedestrians and give them the right-of-way.
7. Always inspect your vehicle or equipment before and after daily use.
8. Never mount or dismount any vehicles or equipment while they are still in motion.
9. Do not dismount any vehicle without first shutting down the engine, setting the parking brake and securing the load.
10. Do not allow other persons to ride the hook or block, dump box, forks, bucket or shovel of any equipment.
11. Each operator must be knowledgeable of all hand signals and obey them.
12. Each operator is responsible for the stability and security of his/her load.

For other rules and regulations regarding motor vehicles, mechanized equipment and marine operations, please refer to Part M of the construction Safety Standard, WAC 296-155.

9. Respirators

Purpose:

The purpose of the Respirator Program is to ensure that all employees are protected from exposure to respiratory hazards. Engineering controls such as ventilation and substitution of less toxic materials are the first line of defense. However, engineering controls are not feasible for some operations or do not completely control the identified hazards. In these situations, respirators and other protective equipment must be used. Respirators are also utilized for protection during emergencies.

Procedure:

This program applies to all employees who are required to wear respirators during normal work operations and during certain non-routine or emergency operations. Employees participating in the respiratory protection program do so at no cost to them. The expense associated with medical evaluations, training, and respiratory protection equipment will be borne by the company.

Employees who voluntarily choose to use a cartridge style respirator when the respirator is not required are subject to the medical evaluation, cleaning, maintenance, and storage elements only of this program. These individuals will also receive training covering proper procedures for cleaning, maintenance and storage of their respirators.

Note to the employer: L&I's Respirator rule includes respiratory protection requirements not listed here. Please consult WAC 296-842 Respirators for more information. For additional help (including a sample written program), visit https://lni.wa.gov/safety-health/safety-topics/topics/respirators

10. Scaffolds

1. General

Before starting work on a scaffold, inspect it for the following:

1. Are guardrails, toeboards, and planking in place and secure?
2. Are locking pins at each joint in place?
3. Are all wheels on moveable scaffolds locked?
4. Do not attempt to gain access to a scaffold by climbing on it (unless it is specifically designed for climbing) – always use a ladder.
5. Scaffolds and their components must be capable of supporting four times the maximum intended load.

6. Any scaffold, including accessories such as braces, brackets, trusses, screw legs, ladders, etc., damaged or weakened in any way, must be immediately repaired or replaced.
7. Scaffold planks must extend over their end supports not less than 6 inches nor more than 12 inches, unless otherwise specifically required.
8. Scaffold platforms must be at least 18 inches wide unless otherwise specifically required or exempted.
9. Where persons are required to work or pass under the scaffold, scaffolds shall be provided with a screen between the toeboard and guardrail, extending along the entire opening.
10. All scaffolds must be erected level and plumb, and on a solid footing.
11. Do not change or remove scaffold members unless authorized.
12. Do not allow workers to ride on a rolling scaffold when it is being moved. Remove or secure all materials and tools on deck before moving.
13. Do not alter any scaffold member by welding, burning, cutting, drilling, or bending.

For other rules and regulations regarding scaffolding, please refer Scaffolds, Chapter 296-874 WAC.

11. Trenching and Excavating

Trenching and Excavating

1. The determination of the angle of slope and design of the supporting system shall be based on careful evaluation of pertinent factors, such as:

    a. Depth and/or cut/soils classification

    b. Possible variation in water content of the material while excavation is open

    c. Anticipated changes in materials from exposure to air, sun, water, or freezing

    d. Loading imposed by structures, equipment, or overlaying or stored material

    e. Vibration from equipment, blasting, traffic, or other sources

Approximate Angle of Slope for sloping of sides of excavations

The presence of ground water requires special treatment	Solid rock and compact shale (90°)		Type A Cohesive and cemented soils. Unconfined compressive strength of 1.5 tsf* or greater. ¾ :1 (63°26’)	Type B Non-cohesive Granular soils. Unconfined compressive strength >0.5 tsf but <1.5 tsf*. 1:1 (45°)	Type C Compacted sharp sand. Unconfined compressive strength of 0.5 tsf* or less. 1 ½:1 (33°41’)	Well rounded loose sand 2:1 (26°34’)	

*tsf = ton per square foot

2. Walkways or bridges with standard railings must be provided when employees or equipment are required to cross over excavations.
3. The walls and faces of all excavations in which employees are exposed to danger from moving ground must be guarded by a shoring system, sloping of the ground, or some other equivalent means.
4. No person is permitted under loads handled by power shovels, derricks, or hoists.
5. All employees must be protected with personal protective equipment for the protection of the head, eyes, respiratory system, hands, feet, and other parts of the body.

See Construction Safety standard WAC 296-155-650 – Excavation & Trenching

12. Welding and Cutting Safety

1. Always follow the manufacturer’s recommendations for setting up and operating equipment, selection of tip size, and gas cylinder operating pressures.
2. Always use a regulator to reduce gas cylinder pressure to the operating pressures recommended by the equipment manufacturer. All piping and equipment must meet the standards of the Compressed Gas Association.

3. Always ensure that all connections are leak tight. Each time connections are loosened and retightened each connection should be checked with a soap and water solution (oil free soap). Do not check with flame.
4. Before “lighting up” clear out each line by letting a small amount of gas flow (separately) to remove any mixed gases that might be in the lines.
5. Never use defective, worn or leaky equipment. Repair it or take it out of service.
6. Never use acetylene in excess of 15 psi pressure. Higher pressures with acetylene are dangerous. If the cylinder is not fitted with a hand wheel valve control, any special wrench required must be placed on the cylinder while the cylinder is in service. On manifolds, one wrench for each manifold will suffice.
7. Always have an appropriate fire extinguisher in good operating condition readily available when operating welding or cutting equipment.
8. Never perform welding, cutting, brazing, or heating operations in a poorly ventilated area. Avoid breathing fumes from these operations at all times, particularly when zinc, cadmium, or lead coated metals are involved.
9. Never perform welding or cutting operations near combustible materials (gasoline cans, paints, paper, rags, etc.).
10. Always protect yourself, others present, welding hoses, gas cylinders, and flammable materials in the area from hot slag and sparks from the welding and cutting operations.
11. The welder and spectators must always wear goggles to protect the eyes from injurious light rays, sparks and hot molten metal during welding, cutting, and heating operations. Eye protection must comply with the established ANSI Standards.
12. Always wear clean, oil free clothing during welding and cutting operations. Protect the hands with leather welding gloves to avoid burns from radiation and hot molten slag. Low cut shoes and trousers with cuffs or open pockets should not be worn.
13. Never use a match or cigarette lighter to light a cutting or welding torch. Always use a spark igniter. Fingers are easily burned by the igniting gas when a match or cigarette lighter is used.
14. Ensure that the material being welded or cut is secure and will not move or fall on anyone.
15. Never use a welding, cutting, or heating torch on a container that has held a flammable liquid. Explosive vapors can accumulate and linger in closed containers for extended periods of time.
16. Never use a regulator for gasses other than those for which it was designed for by the manufacturer since the diaphragm and seat materials may not be compatible with other gasses.
17. Never attempt to adapt and use a fuel gas or inert gas regulator on an oxygen cylinder. A special protective device is incorporated on the oxygen regulator to

harmlessly dissipate the heat caused by the recompression when the cylinder valve is quickly opened. Such a protective device is not furnished on fuel gas and inert gas regulators.

18. Never tamper with the safety devices on cylinders, fuse plugs, safety discs, etc. and do not permit torch flames or sparks to strike the cylinder.
19. Always refer to the various gasses by their proper names. (Do not refer to oxygen as “air” or acetylene as “gas”.)
20. All cylinders, particularly acetylene, should be restrained securely in an upright position to prevent accidents. A non-vertical position for an acetylene cylinder in use would allow the discharge of acetone through the regulator and into the cutting torch, clogging the mixer passages and creating a fire hazard. It would reduce the efficiency of the flame and contaminate the weld area. It also can cause voids in the porous material inside the cylinder, which can lead to acetylene explosions.
21. Store all gas cylinders not in use away from excessive heat sources, such as stoves, furnaces, radiators, the direct rays of the sun, and the presence of open flames. Cylinders in storage should always be secured in an upright position.
22. Keep all burning or flammable substances away from the oxygen or fuel gas storage area (at least 20 feet) and post “No Smoking” signs.
23. Upon completion of a welding, heating, or cutting operation immediately inspect the surrounding areas for smoldering embers. Allow at least one half hour to elapse before leaving the area and conduct another thorough inspection just before leaving. Also alert other personnel of fire possibilities.
24. Always have the properly fitted wrench to fasten a regulator to a cylinder. Never tighten the regulator by hand.
25. Always leave the fuel gas cylinder valve wrench in place when the cylinder valve is open so that it can be closed quickly in an emergency. Do not open acetylene valves more than one-quarter (1/4) turn.
26. Before connecting a regulator to a gas cylinder, open the cylinder valve for a moment. Called cracking the cylinder valve, this will blow out any foreign material that may have lodged in the valve during transit. Do not stand in front of the valve when “cracking”.
27. After attaching a regulator to a gas cylinder, be sure the regulator adjusting screw is fully released (backed off in a counter clockwise direction so that it swivels freely) before the cylinder valve is opened. Never stand in front of a regulator when you are opening a cylinder valve.
28. Always open the cylinder valve slowly so that gas pressure will build up slowly in the regulator (particularly in the oxygen cylinder). Quick opening of the cylinder valve causes a build up of heat due to recompression of the gas. When combined with combustible materials, ignition and explosion may result.

29. If a leak develops in a fuel gas cylinder that cannot be stopped by closing the valve, immediately place the cylinder outside of the building away from possible fire or ignition sources in a location that is free from wind currents that might carry the gas to an ignition source.
30. Never attempt to mix gasses in a cylinder or fill an empty one from another (particularly oxygen cylinders). Mixture of incompatible gasses and/or heat caused by recompression of the gas or gasses may result in ignition and fire. Only the owner of a cylinder may mix gasses in it.
31. When a gas cylinder is ready for return to the supplier, be certain the cylinder valve is closed to prevent internal contamination and the shipping cap is in place to protect the cylinder valve. Identify empty cylinders.
32. Never use oxygen or other gasses as a substitute for compressed air in operation of air-operated tools, blowing off parts, or for ventilation purposes. The only exception to this rule is where oxygen is used to blow out port passages and talcum powder or dust from welding hoses when setting up new or old “dusty” equipment.
33. Do not attempt to do your own repair on welding equipment. Equipment that is improperly repaired can cause leaks and other hazardous conditions. Repairs must be performed by qualified repair personnel.
34. Never repair welding hose with tape. Use of tape and many hose splicers can reduce the pressure to the torch and can cause hazardous conditions. Welding hose must meet the specifications of the Compressed Gas Association.
35. Use the shortest length of hose possible. Longer hoses require higher gas pressures and can be hard to handle.
36. Never use oil or grease on any part of welding or cutting equipment and never let it come into contact with oil or grease. This includes gas cylinders, work bench, regulators, torches, tips, threads on bottles, and clothes that are worn, such as jackets, gloves, and aprons. Oxygen and oil or grease can cause explosions and fire.
37. Never use a hammer on the valve cover caps to loosen them. Use a piece of wood to soften the impact and prevent sparks and damage to the cap.
38. When moving gas cylinders always roll them on their bottom edges or in a cart designed for their movement. Sliding or dragging them or rolling causes excessive wear and may weaken their walls by metal erosion. Slings and electromagnets are not authorized when transporting cylinders.
39. Never use cylinders as rollers to move material. Do not let them bump into each other or let them fall.
40. Fuel gas and liquefied fuels must be stored and shipped valve end up.
41. Do not hammer on any cylinder. Do not tamper with the relief valves. If you have trouble, contact the supplier for assistance.
42. Suitable eye protection must be worn for all welding and cutting operations.

43. Cylinders must be secured. Valves must be closed when unattended and caps must be on the cylinders when the regulators are not on the cylinders.
44. Cylinders must be upright when they are transported in powered vehicles.
45. All cylinders with a water weight of over 30 lbs. must have caps or other protection.
46. All fuel gases must be used through a regulator on cylinder or manifold.
47. Compressed gas cylinders must be upright except for short periods for transportation.
48. Repair work on gauges and regulators must be done by qualified personnel.
49. When parallel sections of oxygen and fuel gas hose are taped together, you must not cover more than 4 inches out of 12 inches by tape. Defective hoses must be removed from service
50. Oxygen must not be used for ventilation.
51. Oxygen regulators must be marked “Use No Oil”. Regulators and fittings must meet the specifications of the Compressed Gas Association.
52. Union nuts on regulators must be checked for damage.
53. Before removing a regulator, shut off cylinder valve and release gas from regulator. Equipment must be used only as approved by the manufacturer.
54. Caps must be on cylinders unless they are transported on a special carrier.
55. Hot warnings on materials are required.
56. Fire is the biggest hazard in welding. The area should be cleared for a radius of 35 feet. Fire shields should be used. The area should be monitored for 30 minutes or more after end of work to ensure there is no delayed ignition.
57. Proper personal protective equipment must be worn by all welders and assisting personnel.
58. All welding personnel should be advised of the hazards from heating zinc, lead, cadmium, and any other substances that could cause health problems from the welding activity.

13. Wildfire Smoke

WA wildfire smoke rules apply to employers that have employees working in outdoor environments. Employers in industry sectors including agriculture, construction, forestry, utilities, transportation, and others may be impacted by the rules.

Wildfire smoke contains a mixture of harmful chemicals and particles. This smoke can make anyone sick, even healthy individuals.

Exposure to the small particles in wildfire smoke can cause mild to serious symptoms, including:

Respiratory: Cough, difficulty breathing, wheezing, shortness of breath; asthma attack, runny nose, sore throat, sinus pain or pressure; phlegm.

Cardiovascular: Chest pain or discomfort, fast or irregular heartbeat, feeling weak, light-headed, faint, or dizzy; or pain or discomfort in the jaw, neck or back.

Symptoms concerning for a stroke: Sudden numbness or weakness in the face, arm or leg – especially on one side of the body; sudden confusion; trouble speaking or difficulty understanding speech; sudden trouble seeing in one or both eyes; sudden trouble walking, dizziness, loss of balance, or lack of coordination; sudden severe headache with no known cause.

Headache, scratchy or irritated eyes, fatigue or tiredness.

Employers covered under the Wildfire Smoke Rules must provide workers with training on wildfire smoke before exposing them to a PM2.5 concentration of 20.5 µg/m3 (AQI 69) or more. Training needs to be done before smoke exposure and repeated every year.

The information and training section of the wildfire smoke rules (WAC 296-820-825) provides more information about employee wildfire smoke training requirements.

Sample Smoke Response Plan

Ensure you are meeting employee and supervisor training requirements by reviewing the requirements in the wildfire smoke rules (General Industry - Chapter 296-820 WAC; Agriculture - WAC 296-307-09805 through 296-307-09860).

Wildfire Smoke Response Plan Template - adapt this plan to your workplace.

Modelo del programa por escrito de humo de incendios forestales (Spanish version)

Note to the employer: For additional help with requirements, Training and Resources and Q&A, visit L&I's Wildfire Smoke page https://www.lni.wa.gov/safety-health/safety-topics/topics/wildfire-smoke#training-and-resources

What To Do

1. New Job Startup

1. Complete SSSP and ensure that Safety Packages are in the safety binder and in the digital safety folder.
2. Complete Walk-around Safety Inspection
3. Perform Jobsite Orientation and distribute Safety Cards

2. Beginning of Every Week

1. Complete Weekly Jobsite Inspection
2. Plan safety meeting
3. Plan Jobsite Orientation for anyone new on site and distribute Safety Cards

3. In Case of a Safety Incident

1. Follow this process as necessary, including the Supervisor Incident Investigation linked within
2. Worker to fill out incident report form, if relevant
3. Review whether disciplinary action is merited

#Images

Bicknell Builds

Site Specific Safety Plan

Project: **Supervisor:** **Date:**

Work Hazard Analysis

Scope of Work	Potential Hazards	Steps to Mitigate Hazard

Reviewed by:	Signature	Date

Bicknell Builds

Project Safety Orientation Form

Project: **Supervisor:** **Date:**

Safety Topics Discussed:

1.) Competent Person Onsite
2.) Safety Rules & Regulations
3.) PPE Requirements (Glasses, Gloves, Footwear, etc)
4.) Reporting Unsafe Conditions, Injuries & Accidents
5.) Location of First Aid Kits
6.) Fire Protection
7.) Hazardous Materials on Site
8.) Active Hazards on Site
9.) Emergency Procedures
10.) Housekeeping
11.) Other Items

Attendee Endorsement

Attendee Name	Company	Signature	Date

Supervisor Signature/Date:

Bicknell Builds

Weekly Jobsite Inspection Form

Project: **Supervisor:** **Date:**

Inspection Item	Details Verified	Condition Acceptable
Power lines	Minimum 10’ clearance required from working area.	◯ Yes ◯ No ◯ N/A
Trench/excavation	Any trench four feet or must be sloped, shored or braced.	◯ Yes ◯ No ◯ N/A
Guardrails	All openings four feet or more above ground level must be guarded	◯ Yes ◯ No ◯ N/A
Standard guardrail	Top rail = 39” to 45” above working surface. Midrail = halfway between top rail and floor. Toeboard = 4”.	◯ Yes ◯ No ◯ N/A
Scaffold	Fully planked with fall protection for fall hazards over 10 feet.	◯ Yes ◯ No ◯ N/A
Stairs	Four or more risers must have handrails.	◯ Yes ◯ No ◯ N/A
Fall Protection	All fall hazards greater than 4' secured.	◯ Yes ◯ No ◯ N/A
Miter/Chop Saws	Cutting head returns to starting position, guard in working order.	◯ Yes ◯ No ◯ N/A
Table Saws	Anti-kickback, push stick, guard in working order.	◯ Yes ◯ No ◯ N/A
Circular Saws	Blade guard instantly returns to covering position.	◯ Yes ◯ No ◯ N/A
Angle Grinders	180-degree guard in working order.	◯ Yes ◯ No ◯ N/A
Ladders	Extended 36" above landing and secured.	◯ Yes ◯ No ◯ N/A
Floor Holes & Openings	Covered and secured; be sure no tripping hazards in the area.	◯ Yes ◯ No ◯ N/A
Extension Cords & Power Tools	All cords undamaged.	◯ Yes ◯ No ◯ N/A

Hard Hats	Readily accessible at all times; worn when overhead hazard exists.	◯ **Yes**	◯ **No**	◯ **N/A**
PPE	Head, eye, ear, respiratory, and leg protection – high visibility vests when required.	◯ **Yes**	◯ **No**	◯ **N/A**
Housekeeping	Worksite in orderly condition.	◯ **Yes**	◯ **No**	◯ **N/A**
First Aid Kit & Fire Extinguishers	Readily accessible and in good working order.	◯ **Yes**	◯ **No**	◯ **N/A**
First Aid Trained Personnel	Minimum of one person on-site at all times with First Aid/CPR training.	◯ **Yes**	◯ **No**	◯ **N/A**
Site Specific Safety Plan	Complete & accessible by all workers on site.	◯ **Yes**	◯ **No**	◯ **N/A**
Weekly Safety Meetings	Orientation & weekly meeting minutes present and up to date.	◯ **Yes**	◯ **No**	◯ **N/A**

Corrections Needed:

Supervisor Signature/Date:	

Bicknell Builds

Safety Meeting Minutes

Project: **Supervisor:** **Date:**

Attendees:

Safety Topics Discussed:

Concerns Raised by Attendees:

Minutes Created By:

Bicknell Builds

Record of Safety Violation

Date:
Name:
Project:
Supervisor:
Violation Description:
Action Required:
Next Course of Action:
Issued By:
Signature/Initials of Recipient:

Bicknell Builds

Record of Safety Violation

Date:
Name:
Project:
Supervisor:
Violation Description:
Action Required:
Next Course of Action:
Issued By:
Signature/Initials of Recipient:

Bicknell Builds

Record of Safety Violation

Date:
Name:
Project:
Supervisor:
Violation Description:
Action Required:
Next Course of Action:
Issued By:
Signature/Initials of Recipient:

Bicknell Builds

Record of Safety Violation

Date:
Name:
Project:
Supervisor:
Violation Description:
Action Required:
Next Course of Action:
Issued By:
Signature/Initials of Recipient:

Incident Report Form

Instructions: Workers may use this form to report all work related injuries, illnesses, or "near miss" events (which could have caused an injury or illness) – *no matter how minor*. This helps identify and correct hazards before they cause serious injuries. This form should be completed by workers as soon as possible and given to a supervisor for further action.

I am reporting a work related:	◯ Injury	◯ Illness	◯ Near Miss

Your Name:	
Job title:	
Supervisor:	

Have you told your supervisor about this injury/near miss?	◯ Yes	◯ No

Date & Time of injury/near miss:	
Names of witnesses (if any):	
Where, exactly, did it happen?	
What were you doing at the time?	
Describe step by step what led up to the injury/near miss. (continue on the back if necessary):	
What could have been done to prevent this injury/near miss?	
What parts of your body were injured?	
If a near miss, how could you have been hurt?	

Did you see a doctor about this injury/illness?	◯ Yes	◯ No

If yes, whom did you see?	Doctor's phone number:
Date:	Time:

Has this part of your body been injured before?	◯ Yes	◯ No

If yes, when?	Supervisor:
Your signature:	Date:

Supervisor Incident Investigation Report Form

This is a report of a:	◯ Death	◯ Injury	◯ First Aid	◯ Near Miss	Date:

Step 1: Injured employee (complete this part for each injured employee)

Name:	Job Title:
Describe the injury and the body part(s) affected:	

Step 2: Describe the incident

Location:	Exact time:
What PPE was being used (if any)?	
Describe events that led up to the injury (items, people, and other important details).	

Step 3: Why did this incident happen?

Was this safety issue reported prior to the incident?	◯ Yes	◯ No

Step 4: How can we prevent future incidents?

◯ Stop this activity	◯ Guard the hazard	◯ Added training	◯ PPE
◯ Create new policy	◯ Enforce existing policy	◯ Routinely inspect	◯ Other:

Steps to be taken to prevent this in the future:

Step 5: This form was completed by:

Name:	Title:	Date:
Reviewed by:	Title:	Date: