

SEQ NO	REV	NOTE NO.	ITEM NAME	ITEM CODE	SIZE RANGE / SMALL END SIZES		DESCRIPTION	REFERENCE / LARGE END SIZES		NOTES	
10		FAX								812	NIPPLE TO BE CUT FROM SS SCH XXS PIPE.
20										816	COMPACT FLANGES CAN BE USED FOR TIE-IN PURPOSE ONLY TO EXISTING PIPING AND EQUIPMENT.
20							*****VALVES*****				
30											
30							***** MODULAR VALVES *****			817	USE ONLY FOR TIE IN
40										B1	ALL BOLTS ARE METRIC DIA.
40		VAW, 817	MODULAR DBB	K10CL16	2	3	MODULAR VALVE DB&B BALL TYPE 10000 CF INCONEL 625 BODY AND TRIM METAL GO FULL SIZE TYPE 2BV	0	0	BA3	TO BE USED WITH API 6A FLANGES ONLY.
50		817	MODULAR DBB	K10CL16-A60	2	3	MODULAR VALVE DB&B BALL TYPE 10000 CF INCONEL 625 BODY AND TRIM METAL GO FULL SIZE TYPE 2BV	0	0	BA4	TO BE USED WITH COMPACT FLANGES REQUIRING STANDARD NUTS ONLY.
60	U04	VAW, 817	MODULAR DBB	M10CL14-A60	2	2	MODULAR VALVE DB&B BALL TYPE 10000 CF INCONEL 625 BODY AND TRIM METAL LO - CONTROLLED BORE TYPE 2BVR	0	0	BA5	TO BE USED WITH COMPACT FLANGES REQUIRING COMPACT NUTS ONLY. FOR FGP ONLY.
70	U04	VAX, 817		M10TL14-A60	2	2	MODULAR VALVE DB&B BALL TYPE 10000 CF X RTJ (BX TYPE) INCONEL 625 BODY AND TRIM METAL LO - CONTROLLED BORE TYPE 2BVR	0	0	FAX	API 6BX FLANGE TO NB PIPE DESIGNATION SEE PIM-SU-5112-TCO
80	U04	VAX, 817	MODULAR DBB	M10TL14L-A60	2	2	MODULAR VALVE DB&B BALL TYPE 10000 CF X RTJ (BX TYPE) INCONEL 625 BODY AND TRIM METAL LO - CONTROLLED BORE TYPE 2BVR	0	0	VAV	USAGE IS LIMITED TO INSTRUMENT ISOLATION PURPOSE.
90		VAW, 817	MODULAR DBB	K10PL16	2	2	MODULAR VALVE DB&B BALL TYPE 10000 CF INCONEL 625 BODY AND TRIM METAL GO FULL SIZE TYPE 2BV REDUCING FLANGES	3	3	VAV	VALVE ONLY TO BE USED IN ACCORDANCE WITH DOCUMENT L-ST-2055 - VENT DRAIN AND INSTRUMENT CONNECTION DETAILS.
100							***** BALL VALVES *****			VAX	VALVE ONLY TO BE USED IN ACCORDANCE WITH DOCUMENT L-ST-2055 - VENT DRAIN AND INSTRUMENT CONNECTION DETAILS.
100											
110											
110		VAW, 817	BALL	B10CL16-A60	0.75	8	BALL 10000 CF INCONEL 625 BODY AND TRIM TRUNNION METAL FB GO	0	0		
120			BALL	B10LL16	0.75	6	BALL 10000 API 6A RJ INCONEL 625 BODY AND TRIM TRUNNION METAL FB GO	0	0		
130										VC7	10000PSI RATED CHECK VALVES SHALL BE SP ITEMS. REFER TO SP LIST FOR DETAILS
130		VQ2					***** THROUGH CONDUIT GATE VALVES *****			VQ2	QUARTER TURN VALVES ARE TO BE SELECTED FOR PROCESS APPLICATIONS.
140		817	GATE	W10CL72-A60	2	2	GATE 10000 CF INCONEL 625 BODY AND TRIM THROUGH CONDUIT SOLID SLAB HW	0	0		
150		817	GATE	W10CL73	3	6	GATE 10000 CF INCONEL 625 BODY AND TRIM THROUGH CONDUIT SOLID SLAB GO	0	0		
160							***** GLOBE VALVES *****				
160											
170		817	GLOBE	L10CL43-A60	2	2	GLOBE 10000# CF INC 625 B564 INC 625 TRIM OS&Y HW	0	0		
170											
180		VC7					***** CHECK VALVES *****				
180											
190							*****PIPE*****				
190											
200											
200			PIPE	5362279	0.75	1.5	PIPE SCH 160 SMLS ALLOY 625 B444 UNS N06625 PE	0	0		
210			PIPE	5362289	2	3	PIPE SCH 160 SMLS ALLOY 625 B444 UNS N06625 BE	0	0		
220			PIPE	5362281	4	4	PIPE WT 14MM SMLS ALLOY 625 B444 UNS N06625 BE	0	0		
230			PIPE	5362282	6	6	PIPE WT 20MM SMLS ALLOY 625 B444 UNS N06625 BE	0	0		
240			PIPE	5362283	8	8	PIPE WT 26MM SMLS ALLOY 625 B444 UNS N06625 BE	0	0		
250		812	PIPE	5362285	0.75	0.75	PIPE SCH XXS SMLS ALLOY 625 B444 UNS N06625 BE	0	0		
260	U04		PIPE	5362290	16	16	PIPE WT 47MM SMLS ALLOY 625 B444 UNS N06625 BE	0	0		
270							***** FITTINGS *****				
270											
280											
280	U04		ELBOW	5426512	0.5	3	ELL BW 90 DEG LR SCH 160 ALLOY 625 B366-WPS UNS N06625	0	0		
290			ELBOW	5426513	4	4	ELL BW 90 DEG LR WT 14.0MM ALLOY 625 B366-WPS UNS N06625	0	0		
300			ELBOW	5426514	6	6	ELL BW 90 DEG LR WT 20.0MM ALLOY 625 B366-WPS UNS N06625	0	0		
310	U04		ELBOW	5426515	8	8	ELL BW 90 DEG LR WT 26.0MM ALLOY 625 B366-WPS UNS N06625	0	0		
320	U04		ELBOW	5426584	16	16	ELL BW 90 DEG LR WT 47.0MM ALLOY 625 B366-WPS UNS N06625	0	0		
330	U04		ELBOW	5426517	0.5	3	ELL BW 45 DEG LR SCH 160 ALLOY 625 B366-WPS UNS N06625	0	0		
340			ELBOW	5426517	0.75	3	ELL BW 45 DEG LR SCH 160 ALLOY 625 B366-WPS UNS N06625	0	0		
350			ELBOW	5426523	4	4	ELL BW 45 DEG LR WT 14.0MM ALLOY 625 B366-WPS UNS N06625	0	0		
360	U04		ELBOW	5426523	4	4	ELL BW 45 DEG LR WT 14.0MM ALLOY 625 B366-WPS UNS N06625	0	0		
370			ELBOW	5426524	6	6	ELL BW 45 DEG LR WT 20.0MM ALLOY 625 B366-WPS UNS N06625	0	0		
380	U04		ELBOW	5426582	16	16	ELL BW 45 DEG LR WT 47.0MM ALLOY 625 B366-WPS UNS N06625	0	0		
390											
390			TEE	5426564	0.75	3	TEE BW SCH 160 ALLOY 625 B366-WPS UNS N06625	0	0		
400			TEE	5426565	4	4	TEE BW WT 14.0MM ALLOY 625 B366-WPS UNS N06625	0	0		
410			TEE	5426566	6	6	TEE BW WT 20.0MM ALLOY 625 B366-WPS UNS N06625	0	0		
420	U04		TEE RED	5426551	0.75	2	TEE RED SCH 160 ALLOY 625 B366-WPS UNS N06625	1	3		
430	U04		TEE RED	5426553	1.5	3	TEE RED WT 14.0MM/ SCH 160 ALLOY 625 B366-WPS UNS N06625	4	4		
440	U04		TEE RED	5426554	3	3	TEE RED WT 20.0MM/ SCH 160 ALLOY 625 B366-WPS UNS N06625	6	6		
450	U04		TEE RED	5426555	4	4	TEE RED WT 20.0MM/ 14MM ALLOY 625 B366-WPS UNS N06625	6	6		
460											
460			CAP	5426526	0.75	3	CAP SCH 160 ALLOY 625 B366 UNS N06625	0	0		
470	U04		CAP	5426526	0.75	3	CAP SCH 160 ALLOY 625 B366 UNS N06625	0	0		
480			CAP	5426527	4	4	CAP WT 14.0MM ALLOY 625 B366 UNS N06625	0	0		
490	U04		CAP	5426527	4	4	CAP WT 14.0MM ALLOY 625 B366 UNS N06625	0	0		

	TENGIZCHEVROIL TCO TENGIZ, KAZAKHSTAN	CONSTRUCTION	CORR.ALLOW.	SERVICE	MATERIAL	DATE	BY	REV	SHEET	PIPING LINE CLASS
		ALL SIZES - BUTT WELD SEAL WELDING - NONE PIPE BENDS - NONE THREAD SEALANT - NONE	CORR. ALLOW. 1 MM	SOUR SERVICE NACE STD. MR0175 / ISO 15156 DESIGN CODE ASME B31.3 CHAPTER IX / API 6A DESIGN PRESSURE - 600 BARG FLUID CODES - PIM-SU-5112-TCO	MATERIAL: INCONEL 625 FLANGE RATING: 10000 RJ/CF TEMPERATURE RANGE: -120 / 130 °C	12/16/2024	BY OZAC	U04	Page 1 of 3	10000A60

SEQ NO	REV	NOTE NO.	ITEM NAME	ITEM CODE	SIZE RANGE / SMALL END SIZES		DESCRIPTION	REFERENCE / LARGE END SIZES		NOTES
500			CAP	5426528	6	6	CAP WT 20.0MM ALLOY 625 B366 UNS N06625	0	0	
510										
510	U04		RED CONC	5426570	0.5	2	REDUCER CONC SCH 160 ALLOY 625 B366-WPS N06625	0.75	3	
520			RED CONC	5426571	1.5	3	REDUCER CONC WT 14.0MM/ SCH 160 ALLOY 625 B366-WPS N06625	4	4	
530			RED CONC	5426572	3	3	REDUCER CONC WT 20.0MM/ SCH 160 ALLOY 625 B366-WPS N06625	6	6	
540			RED CONC	5426573	4	4	REDUCER CONC WT 20.0MM/ 14.0MM ALLOY 625 B366-WPS N06625	6	6	
550	U04		RED CONC	5426574	4	4	REDUCER CONC WT 26.0MM/ 14.0MM ALLOY 625 B366-WPS N06625	8	8	
560	U04		RED CONC	5426599	8	8	REDUCER CONC WT 47.0MM/ 26.0MM ALLOY 625 B366-WPS N06625	16	16	
570	U04		RED ECC	5426580	4	4	REDUCER ECC WT 26.0MM/ 14.0MM ALLOY 625 B366-WPS N06625	8	8	
580	U04		RED ECC	5426576	0.5	2	REDUCER ECC SCH 160 ALLOY 625 B366-WPS N06625	0.75	3	
590			RED ECC	5426577	1.5	3	REDUCER ECC WT 14.0MM/SCH 160 ALLOY 625 B366-WPS N06625	4	4	
600			RED ECC	5426578	3	3	REDUCER ECC WT 20.0MM/SCH 160 ALLOY 625 B366-WPS N06625	6	6	
610			RED ECC	5426579	4	4	REDUCER ECC WT 20.0MM/14.0MM ALLOY 625 B366-WPS N06625	6	6	
620							***** OLETS *****			
630										
630	U04		OLETS	5506928	2	2	REINFORCED BRANCH INSERT CONNECTION 20.0MM X SCH 160, BW OUTLET API ALLOY 625 B564 UNS N06625	6	6	
640	U04		OLETS	5506929	2	2	REINFORCED BRANCH INSERT CONNECTION 26.0MM X SCH 160, BW OUTLET API ALLOY 625 B564 UNS N06625	8	8	
650										
650		816					***** FLANGES *****			
660										
660		817	COUPLING	5851251	2	2	FLANGE COMPACT 10000# RJ WITH 9/16" FEMALE AUTOCLAVE CONNECTION ALLOY 625 B564 UNS N06625	0	0	
670	U04	817	FLANGE	5851251	2	2	FLANGE COMPACT 10000# RJ WITH 9/16" FEMALE AUTOCLAVE CONNECTION ALLOY 625 B564 UNS N06625	0	0	
680										
680		817	FLANGE	5619910	0.75	0.75	FLG COMPACT 10000# RJ BORE 15.6MM ALLOY 625 B564 UNS N06625	0	0	
690		817	FLANGE	5619909	1	1	FLG COMPACT 10000# RJ BORE 20.7MM ALLOY 625 B564 UNS N06625	0	0	
700		817	FLANGE	5619912	1.5	1.5	FLG COMPACT 10000# RJ BORE 34.0MM ALLOY 625 B564 UNS N06625	0	0	
710	U04	817	FLANGE	5619900	0.5	0.5	FLG COMPACT 10000# RJ BORE 11.8MM ALLOY 625 B564 UNS N06625 LINE CLASS 10000A60	0	0	
720	U04	817	FLANGE	5619998	12	12	FLG COMPACT 10000# RJ BORE 248.9MM ALLOY 625 B564 UNS N06625 LINE CLASS 10000A60	0	0	
730	U04	817	FLANGE	5619992	16	16	FLG COMPACT 10000# RJ BORE 312.4MM ALLOY 625 B564 UNS N06625 LINE CLASS 10000A60	0	0	
740	U04	817	FLANGE	5619997	24	24	FLG COMPACT 10000# RJ BORE 470.6MM ALLOY 625 B564 UNS N06625 LINE CLASS 10000A60	0	0	
750		817	FLANGE	5619913	2	2	FLG COMPACT 10000# RJ BORE 42.8MM ALLOY 625 B564 UNS N06625	0	0	
760		817	FLANGE	5619914	3	3	FLG COMPACT 10000# RJ BORE 66.6MM ALLOY 625 B564 UNS N06625	0	0	
770		817	FLANGE	5619915	4	4	FLG COMPACT 10000# RJ BORE 86.3MM ALLOY 625 B564 UNS N06625	0	0	
780		817	FLANGE	5619916	6	6	FLG COMPACT 10000# RJ BORE 128.3MM ALLOY 625 B564 UNS N06625	0	0	
790		817	FLANGE	5619917	8	8	FLG COMPACT 10000# RJ BORE 167.1MM ALLOY 625 B564 UNS N06625	0	0	
800			FLANGE	5563432	2	2	FLG WN 10000 API 6A TYPE 6BX 1 13/16" NS (2" NB) RTJ BORE 42.8MM ALLOY 625 B564 UNS N06625	0	0	
810			FLANGE	5563433	3	3	FLG WN 10000 API 6A TYPE 6BX 3 1/16" NS (3" NB) RTJ BORE 66.6MM ALLOY 625 B564 UNS N06625	0	0	
820			FLANGE	5563434	4	4	FLG WN 10000 API 6A TYPE 6BX 4 1/16" NS (4" NB) RTJ BORE 86.3MM ALLOY 625 B564 UNS N06625	0	0	
830			FLANGE	5563435	6	6	FLG WN 10000 API 6A TYPE 6BX 5 1/8" NS (6" NB) RTJ BORE 128.3MM ALLOY 625 B564 UNS N06625	0	0	
840			BLIND	5407440	2	2	FLG BLIND 10000 API 6A TYPE 6BX 1 13/16" NS RTJ ALLOY 625 B564 UNS N06625	0	0	
850			BLIND	5407441	3	3	FLG BLIND 10000 API 6A TYPE 6BX 3 1/16" NS RTJ ALLOY 625 B564 UNS N06625	0	0	
860			BLIND	5407442	4	4	FLG BLIND 10000 API 6A TYPE 6BX 4 1/6" NS RTJ ALLOY 625 B564 UNS N06625	0	0	
870			BLIND	5407443	6	6	FLG BLIND 10000 API 6A TYPE 6BX 5 1/8" NS RTJ ALLOY 625 B564 UNS N06625	0	0	
880		817	BLIND	5619751	0.5	8	FLG COMPACT BLIND 10000# RJ ALLOY 625 B564 UNS N06625 PIPE CLASS 10000A60	0	0	
890										
890		FAX					***** ORIFICE FLANGES *****			
900										
900			ORIFICE FLG	5407523	2	2	WN ORIF SET 10000 API 6A TYPE 6BX 1 13/16" NS (2" NB) RTJ BORE 42.8MM ALLOY 625 B564 UNS N06625	0	0	
910			ORIFICE FLG	5407524	3	3	WN ORIF SET 10000 API 6A TYPE 6BX 3 1/16" NS (3" NB) RTJ BORE 66.6MM ALLOY 625 B564 UNS N06625	0	0	
920			ORIFICE FLG	5407525	4	4	WN ORIF SET 10000 API 6A TYPE 6BX 4 1/16" NS (4" NB) RTJ BORE 86.3MM ALLOY 625 B564 UNS N06625	0	0	
930			ORIFICE FLG	5407526	6	6	WN ORIF SET 10000 API 6A TYPE 6BX 5 1/8" NS (6" NB) RTJ BORE 128.3MM ALLOY 625 B564 UNS N06625	0	0	
940										
940							*****PIPE NIPPLES*****			
950										
950		812		0			NIPPLE PBE CUT FROM PIPE			
960										
960		FAX					***** GASKETS *****			
970										
970			GASKET	5674476	2	2	GASKET 10000 API 6A BX 151 1 13/16" NS ALLOY 625 RING	0	0	
980	U04		GASKET	5674496	3	3	GASKET 10000 API 6A BX 154 3 1/16" NS ALLOY 625 RING	0	0	
990	U04		GASKET	5674499	4	4	GASKET 10000 API 6A BX 155 4 1/16" NS ALLOY 625 RING	0	0	
1000			GASKET	5674469	6	6	GASKET 10000 API 6A BX 169 5 1/8" NS ALLOY 625 RING	0	0	
1010	U04	817	GASKET	5673540	0.5	24	GASKET 10000# RJ INC 718 ENERGIZED SEALRING COMPACT FLANGE LINE CLASS 10000A60	0	0	
1020										
1020		B1					***** BOLTING *****			
1030										

	TENGIZCHEVROIL TCO TENGIZ, KAZAKHSTAN	CONSTRUCTION	CORR.ALLOW.	SERVICE	MATERIAL	DATE	BY	REV	SHEET	PIPING LINE CLASS
		ALL SIZES - BUTT WELD SEAL WELDING - NONE PIPE BENDS - NONE THREAD SEALANT - NONE	CORR. ALLOW. 1 MM	SOUR SERVICE NACE STD. MR0175 / ISO 15156 DESIGN CODE ASME B31.3 CHAPTER IX / API 6A DESIGN PRESSURE - 600 BARG FLUID CODES - PIM-SU-5112-TCO	MATERIAL: INCONEL 625 FLANGE RATING: 10000 RJ/CF TEMPERATURE RANGE: -120 / 130 °C	12/16/2024	BY OZAC	U04	Page 2 of 3	10000A60

SEQ NO	REV	NOTE NO.	ITEM NAME	ITEM CODE	SIZE RANGE / SMALL END SIZES		DESCRIPTION	REFERENCE / LARGE END SIZES		NOTES
1030	U04	BA4	BOLTING	5675776	0.5	6	STUD-BOLT WITH 2 NUTS API-6A718	0	0	
1040		BA5	BOLTING	5675778	6	99	STUD-BOLT C/W 2 COMPACT NUTS API-6A718	0	0	
1050		BA3	BOLTING	5675770	2	6	STUD-BOLT A320 GR L7M/A194 GR 7M (S3) WITH 2 NUTS	0	0	
1060		FAX								
1070						***** BLINDS & SPACERS *****				
1070		817	SPEC BLIND	5749572	2	4	SPECTACLE BLIND COMPACT 10000# RJ FEMALE ALLOY 625 B443 UNS N06625 PIPE CLASS 10000A60	0	0	
1080			SPEC BLIND	5407625	2	2	SPECTACLE BLIND 10000 API 6A 1 13/16" NS FOR 2" PIPE RTJ FEMALE ALLOY 625 B443 UNS 06625	0	0	
1090			SPEC BLIND	5407626	3	3	SPECTACLE BLIND 10000 API 6A 3 1/16" NS FOR 3" PIPE RTJ FEMALE ALLOY 625 B443 UNS 06625	0	0	
1100			SPEC BLIND	5407627	4	4	SPECTACLE BLIND 10000 API 6A 4 1/16" NS FOR 4" PIPE RTJ FEMALE ALLOY 625 B443 UNS 06625	0	0	
1110										
1110	U04	817	PADDLE	5750279	2	4	PADDLE BLANK COMPACT 10000# RJ ALLOY 625 B443 UNS N06625 LINE CLASS 10000A60	0	0	
1120	U04	817	PADDLE	5750281	2	4	PADDLE SPACER COMPACT 10000# RJ ALLOY 625 B443 UNS N06625 LINE CLASS 10000A60	0	0	
1130										
1140										

	TENGIZCHEVROIL TCO TENGIZ, KAZAKHSTAN	CONSTRUCTION	CORR.ALLOW.	SERVICE	MATERIAL	DATE	BY	REV	SHEET	PIPING LINE CLASS
		ALL SIZES - BUTT WELD SEAL WELDING - NONE PIPE BENDS - NONE THREAD SEALANT - NONE	CORR. ALLOW. 1 MM	SOUR SERVICE NACE STD. MR0175 / ISO 15156 DESIGN CODE ASME B31.3 CHAPTER IX / API 6A DESIGN PRESSURE - 600 BARG FLUID CODES - PIM-SU-5112-TCO	MATERIAL: INCONEL 625 FLANGE RATING: 10000 RJ/CF TEMPERATURE RANGE: -120 / 130 °C	12/16/2024	BY OZAC	U04	Page 3 of 3	10000A60