

SEQ NO	REV	NOTE NO.	ITEM NAME	ITEM CODE	SIZE RANGE / SMALL END SIZES		DESCRIPTION	REFERENCE / LARGE END SIZES		NOTES	
10							*****VALVES*****			817	USE ONLY FOR TIE IN
20										819	TO BE USED FOR THERMOWELLS
20							***** MODULAR VALVES *****			B1	ALL BOLTS ARE METRIC DIA.
30										BA4	TO BE USED WITH COMPACT FLANGES
30	U04	817	MODULAR DBB	K10CL16	2	2	MODULAR VALVE DB&B BALL TYPE 10000 CF INCONEL 625 BODY AND TRIM METAL GO FULL SIZE TYPE 2BV	0	0	FA1	REQUIRING STANDARD NUTS ONLY.
40	U04	817	MODULAR DBB	K10CL16-H5A	2	2	MODULAR VALVE DB&B BALL TYPE 10000 CF INCONEL 625 BODY AND TRIM METAL GO FULL SIZE TYPE 2BV	0	0		API 6BX FLANGE TO NB PIPE DESIGNATION SEE PIM-SU-5112-TCO
50	U04	817	MODULAR DBB	K10CL16-H5A	3	3	MODULAR VALVE DB&B BALL TYPE 10000 CF INCONEL 625 BODY AND TRIM METAL GO FULL SIZE TYPE 2BV	0	0	VAX	VALVE ONLY TO BE USED IN ACCORDANCE WITH DOCUMENT L-ST-2055 - VENT DRAIN AND INSTRUMENT CONNECTION DETAILS.
60	U04	817	MODULAR DBB	K10CL16L-H5A	2	2	MODULAR VALVE DB&B BALL TYPE 10000 CF INCONEL 625 BODY AND TRIM METAL GO FULL SIZE TYPE 2BV	0	0		RTJ(BX TYPE) END IS SIDE MATING WITH INSTRUMENTATION
70	U04	817	MODULAR DBB	K10CL16L-H5A	3	3	MODULAR VALVE DB&B BALL TYPE 10000 CF INCONEL 625 BODY AND TRIM METAL GO FULL SIZE TYPE 2BV	0	0	VU1	USE THIS VALVE FOR PRESSURE INSTRUMENT CONNECTIONS, VENTS AND DRAINS.
80	U04	VAX, 817	MODULAR DBB	M10CL14-H5A	2	2	MODULAR VALVE DB&B BALL TYPE 10000 CF INCONEL 625 BODY AND TRIM METAL LO - CONTROLLED BORE TYPE 2BVR	0	0		
90	U04	VAX, 817	MODULAR DBB	M10TL14-H5A	2	2	MODULAR VALVE DB&B BALL TYPE 10000 CF X RTJ (BX TYPE) INCONEL 625 BODY AND TRIM METAL LO - CONTROLLED BORE TYPE 2BVR	0	0		
100	U04	VAX, 817	MODULAR DBB	M10TL14L-H5A	2	2	MODULAR VALVE DB&B BALL TYPE 10000 CF X RTJ (BX TYPE) INCONEL 625 BODY AND TRIM METAL LO - CONTROLLED BORE TYPE 2BVR	0	0		
110	U04	VAX, 817	MODULAR DBB	M10UL14-H5A	2	2	MODULAR VALVE DB&B BALL TYPE 10000 CF X RTJ (BX TYPE) INCONEL 625 BODY AND TRIM METAL LO-CONTROLLED BORE TYPE R2BVR	3	3		
120	U04	VAX, 817	MODULAR DBB	M10UL14L-H5A	2	2	MODULAR VALVE DB&B BALL TYPE 10000 CF X RTJ (BX TYPE) INCONEL 625 BODY AND TRIM METAL LO-CONTROLLED BORE TYPE R2BVR	3	3		
130							***** BALL VALVES *****				
130											
140											
140		VU1, 817	BALL	B10CL16-H5A	2	2	BALL 10000 CF INCONEL 625 BODY AND TRIM TRUNNION METAL FB GO	0	0		
150							***** THROUGH CONDUIT GATE VALVES *****				
150											
160	U04		GATE	W10LH75	3	3	GATE 10000 API 6A 6BX F22 TRIM INC 625 THROUGH CONDUIT SOLID SLAB GO	0	0		
170	U04	817	GATE	W10CH73	4	4	GATE 10000 CF F22 TRIM INC 625 THROUGH CONDUIT SOLID SLAB GO	0	0		
180	U04	817	GATE	W10CL72	2	2	GATE 10000 CF INCONEL 625 BODY AND TRIM THROUGH CONDUIT SOLID SLAB HW	0	0		
190							***** GLOBE VALVES *****				
190											
200	U04		CHECK	C10LH51	3	3	CHECK PISTON 10000# API INC 625 TRIM 625	0	0		
210	U04	817	GLOBE	L10CL43-H5A	2	2	GLOBE 10000# CF INC 625 B564 INC 625 TRIM OS&Y HW	0	0		
220							*****PIPE ABOVE GROUND*****				
220											
230											
230	U04		PIPE	9005451	2	2	LINEPIPE SMLS WT= 11.07 MM API-5L X60 BE	0	0		
240			PIPE	9005453	3	3	LINEPIPE SMLS WT= 17.48 MM API-5L X60 BE	0	0		
250			PIPE	9005452	4	4	LINEPIPE SMLS WT= 19.51 MM API-5L X60 BE	0	0		
260							*****FITTINGS ABOVE GROUND*****				
260											
270											
270			ELBOW	9006586	2	2	ELL BW 90 DEG LR WT 11.07MM A860 WPHY 60	0	0		
280			ELBOW	9006584	2	2	ELL BW 45 DEG LR WT 11.07MM A860 WPHY 60	0	0		
290	U04		ELBOW	9006582	3	3	ELL BW 45 DEG LR WT 17.48MM A860 WPHY 60	0	0		
300	U04		ELBOW	9006597	3	3	ELL BW 90 DEG LR WT 17.48 MM A860 WPHY 60	0	0		
310			ELBOW	9006587	4	4	ELL BW 90 DEG LR WT 19.51MM A860 WPHY 60	0	0		
320			ELBOW	9006585	4	4	ELL BW 45 DEG LR WT 19.51MM A860 WPHY 60	0	0		
330											
330			TEE	9006653	2	2	TEE BW WT 11.07 MM LTCS A860 WPHY 60	0	0		
340			TEE	9006654	4	4	TEE BW WT 19.51 MM LTCS A860 WPHY 60	0	0		
350			FLANGE	9006655	2	2	TEE RED BW WT 19.51/11.07 MM LTCS A860 WPHY 60	4	4		
360	U04		TEE	9004201	3	3	TEE BW WT 17.48MM A860 WPHY 60	0	0		
370	U04		TEE RED	9006679	2	2	TEE RED BW WT 17.48MM/11.07MM A860 WPHY 60	3	3		
380	U04		TEE RED	9006680	3	3	TEE RED BW WT 19.51MM/17.38 MM A860 WPHY 60	4	4		
390											
390			RED ECC	9006913	2	2	REDUCER ECC WT 19.51 MM / 11.07 MM LTCS A860 WPHY-60	4	4		
400			RED CONC	9006914	2	2	REDUCER CONC WT 19.51 MM / 11.07 MM LTCS A860 WPHY-60	4	4		
410		FA1					***** FLANGES ABOVE GROUND*****				
410											
420											
420	U04	817	FLANGE	9006725	2	2	FLANGE COMPACT 10000# RJ LINE CLASS 10000H5A WITH 9/16" FEMALE AUTOCLAVE CONNECTION LTCS A694 F60	0	0		
430											

	TENGIZCHEVROIL TCO TENGIZ, KAZAKHSTAN	CONSTRUCTION	CORR.ALLOW.	SERVICE	MATERIAL	DATE	BY	REV	SHEET	PIPING LINE CLASS
		ALL SIZES - BUTT WELD PWHT - 4" ONLY	CORR. ALLOW. 1.5 MM	NON SOUR SERVICE DESIGN CODE ASME B31.8 / API 6A DESIGN PRESSURE - 600 BARG FLUID CODES - PIM-SU-5112-TCO	MATERIAL: API-5L X60 FLANGE RATING: 10000 RJ/CF TEMPERATURE RANGE: -40 / 110 °C	12/16/2024	BY OZAC	U04	Page 1 of 2	10000H5A

SEQ NO	REV	NOTE NO.	ITEM NAME	ITEM CODE	SIZE RANGE / SMALL END SIZES		DESCRIPTION	REFERENCE / LARGE END SIZES		NOTES
430	U04	817	FLANGE	9006721	2	2	FLG COMPACT 10000# RJ A694 F60 WT 11.07 MM	0	0	
440	U04	817	FLANGE	9006722	4	4	FLG COMPACT 10000# RJ A694 F60 WT 19.51 MM	0	0	
450	U04	817	BLIND	9619758	2	2	FLG COMPACT BLIND 10000# RJ LTCS A694 F60 LINE CLASS 10000H5A - 2 INCH ONLY	0	0	
460	U04	817	BLIND	9619759	4	4	FLG COMPACT BLIND 10000# RJ LTCS A694 F60 LINE CLASS 10000H5A - 4 INCH ONLY	0	0	
470			FLANGE	SP-9521	2	2	FLG WN 10000 API 6A TYPE 6BX 2 1/16" NS (2" NB) RTJ 38.16MM BORE ASTM A694 F60	0	0	
480	U04	819	FLANGE	9006759	2	2	FLG WN 10000 API 6A TYPE 6BX 1 13/16" NS (2" NB) RTJ 38.16MM BORE ASTM A694 F60	0	0	
490	U04		FLANGE	9616193	3	3	FLG WN 10000 API 6A TYPE 6BX 2 9/16" NS (3" NB) RTJ 38.16MM BORE ASTM A694 F60	0	0	
500										
500							***** GASKETS *****			
510										
510	U04	819	GASKET	5674471	2	2	GASKET 10000 API 6A BX 151 1 13/16" NS 316 SS RING	0	0	
520	U04		GASKET	5674475	3	3	GASKET 10000 API 6A BX 153 2 9/16" NS 316SS RING	0	0	
530	U04	817	GASKET	5673562	2	2	GASKET 10000# RJ INC 718 ENERGIZED SEALRING COMPACT FLANGE LINE CLASS 10000H5A FOR NPS 3 INCH & BELOW	0	0	
540	U04	817	GASKET	5673560	4	4	GASKET 10000# RJ INC 718 ENERGIZED SEALRING COMPACT FLANGE LINE CLASS 10000H5A NPS 4 INCH & ABOVE	0	0	
550			GASKET	5674472	2	2	GASKET 10000 API 6A BX 152 2 1/16" NS 316 SS RING	0	0	
560										
560		B1					***** BOLTING *****			
570										
570		BA4	BOLTING	5675770	2	4	STUD-BOLT A320 GR L7M/A194 GR 7M (S3) WITH 2 NUTS	0	0	
580										
590										

	TENGIZCHEVROIL TCO TENGIZ, KAZAKHSTAN	CONSTRUCTION	CORR.ALLOW.	SERVICE	MATERIAL	DATE	BY	REV	SHEET	PIPING LINE CLASS
		ALL SIZES - BUTT WELD PWHT - 4" ONLY	CORR. ALLOW. 1.5 MM	NON SOUR SERVICE DESIGN CODE ASME B31.8 / API 6A DESIGN PRESSURE - 600 BARG FLUID CODES - PIM-SU-5112-TCO	MATERIAL: API-5L X60 FLANGE RATING: 10000 RJ/CF TEMPERATURE RANGE: -40 / 110 °C	12/16/2024	BY OZAC	U04	Page 2 of 2	10000H5A