

SEQ NO	REV	NOTE NO.	ITEM NAME	ITEM CODE	SIZE RANGE / SMALL END SIZES		DESCRIPTION	REFERENCE / LARGE END SIZES		NOTES
10	U04						***** VALVES *****			B1 ALL BOLTS ARE METRIC DIA.
20										
20	U04		BALL	B01AP39	0.75	3	BALL 150# RF LTCS PTFE LINED FLOATING SOFT FB LO	0	0	
30	U04		BALL	B01AP40	16	18	BALL 150# RF LTCS PTFE LINED TRUNNION SOFT FB GO	0	0	
40	U04		BALL	B01AM10	1	1	BALL 150# RF INC 825 INC TRIM 625 FLOATING METAL FB LO	0	0	
50	U04		BALL	B01AM09	2	2	BALL 150# RF INC 825 INC TRIM 625 FLOATING SOFT FB LO	0	0	
60										
60	U04		GATE	W01AM73	16	16	GATE 150# RF INC 825 INC TRIM 625 THROUGH COND SOLID SLAB GO	0	0	
70										
70	U04		MODULAR DBB	K01AM10	0.75	0.75	MODULAR VALVE DB&B BALL TYPE 150# RF INC 825 INC TRIM 625 METAL LO - FULL SIZE TYPE 2BV	0	0	
80										
80	U04						***** PIPE*****			
90										
90	U04		PIPE	5717204	16	18	PIPE SCH 20 SMLS LTCS A333 GR.6 PTFE LINED 150# FLANGED ENDS	0	0	
100	U04		PIPE	5717211	16	18	PIPE SCH 20 SMLS LTCS A333 GR.6 PTFE LINED 150# 3M FLANGED ENDS	0	0	
110	U04		PIPE	5717212	16	18	PIPE SCH 20 SMLS LTCS A333 GR.6 PTFE LINED 150# 2M FLANGED ENDS	0	0	
120	U04		PIPE	5717213	16	18	PIPE SCH 20 SMLS LTCS A333 GR.6 PTFE LINED 150# 1M FLANGED ENDS	0	0	
130	U04		PIPE	5717214	16	18	PIPE SCH 20 SMLS LTCS A333 GR.6 PTFE LINED 150# 0.5M FLANGED ENDS	0	0	
140	U04		PIPE	5358511	1	1	PIPE SCH XXS SMLS LTCS A333 GR.6 PE	0	0	
150										
150	U04		PIPE	9001495	16	16	LINEPIPE SMLS WT= 12.70 MM API-5L X60 BE	0	0	
160	U04		PIPE	9001495CTD	16	16	LINEPIPE SMLS WT= 12.70 MM API-5L X60 BE COATED	0	0	
170										
170	U04						**** FITTINGS ****			
180										
180	U04		ELBOW	5717630	16	18	ELL 90 DEG 150# FLANGED SCH 20 LTCS PTFE LINED	0	0	
190	U04		ELBOW	5392870	1	1	ELL 90 DEG LR XXS LTCS A420 WPL6	0	0	
200	U04		ELBOW	5717631	16	18	ELL 45 DEG 150# FLANGED SCH 20 LTCS PTFE LINED	0	0	
210										
210	U04		TEE	9006633	16	16	TEE BW WT 12.7 MM A860 WPHY 60	0	0	
220	U04		TEE	5717632	16	18	TEE EQUAL 150# FLANGED SCH 20 LTCS PTFE LINED	0	0	
230										
230	U04		INDUC BEND	9005333	16	16	INDUCTION BEND 22.5 DEG X 5D RADIUS WT 12.70 MM API 5L X60 C/W 1.5D TANGENT ENDS BW	0	0	
240	U04		INDUC BEND	9005333CTD	16	16	INDUCTION BEND 22.5 DEG X 5D RADIUS WT 12.70 MM API 5L X60 C/W 1.5D TANGENT ENDS BW COATED	0	0	
250	U04		INDUC BEND	9007137CTD	16	16	INDUCTION BEND 81 DEG X 5D RADIUS WT 12.70 MM API 5L X60 C/W 1.5D TANGENT ENDS BW COATED	0	0	
260										
260	U04		OLETS	9006822	0.75	1	NIPOFLANGE 150# RF 12.7 MM/XS WT LTCS A694 F60	16	16	
270	U04		OLETS	9006824	0.75	1	NIPOFLANGE 150# RF 12.7 MM/XXS WT LTCS A694 F60	16	16	
280										
280	U04		OLETS	9002467	1	1	WELDOLET WT 12.70 MM/ SCH XS WT LTCS A694 F60	16	16	
290	U04		OLETS	9006825	1	1	WELDOLET WT 12.70 MM/ SCH XXS WT LTCS A694 F60	16	16	
300										
300							**** FLANGES ****			
310										
310	U04		FLANGE	5556221	1	1	FLG WN 150# RF LTCS A350 LF2 CL.1 SCH XXS	0	0	
320	U04		FLANGE	9001476	16	16	FLG WN 150# RF LTCS A694 F60 WT 12.7MM	0	0	
330	U04		BLIND	5615566	2	2	FLG BLIND 150# RF LTCS A350 LF2 CL.1	0	0	
340	U04		BLIND	5715115	0.75	18	FLG BLIND 150# PTFE LINED LTCS A350 LF2 CL.1	0	0	
350										
350	U04						***** GASKETS *****			
360										
360	U04		GASKET	5673043	0.75	16	GASKET 150# 316SS SPIRAL WOUND GRAPHITE IR	0	0	
370	U04		GASKET	5664201	0.75	18	GASKET 150# RF FLAT RING PTFE	0	0	
380										
380	U04						***** BOLTING *****			
390										
390	U04	B1	BOLTING	5675769	0.75	18	STUD-BOLT A320 GR L7M/A194 GR 7M NUTS + LTCS WASHERS	0	0	
400										
410										
410	U04			0			USE TEES AND REDUCERS AS REQUIRED			

	TENGIZCHEVROIL TCO TENGIZ, KAZAKHSTAN	CONSTRUCTION	CORR.ALLOW.	SERVICE	MATERIAL	DATE	BY	REV	SHEET	PIPING LINE CLASS
		ALL SIZES - FLANGED SEAL WELDING - FOR THREADED CONNECTIONS ONLY PIPE BENDS - LONG RADIUS THREAD SEALANT - NONE	CORR. ALLOW. 6 MM	SOUR SERVICE - NACE MR0175 / ISO 15156 DESIGN: 10 BAR G CODE: ASME B31.8 FLUID CODES - PIM-SU-5112-TCO	MATERIAL: PTFE LINED LTCS FLANGE RATING: 150 RF TEMPERATURE RANGE: -40 / 75 °C	12/16/2024	BY OZAC	U04	Page 1 of 1	150K5E