

SEQ NO	REV	NOTE NO.	ITEM NAME	ITEM CODE	SIZE RANGE / SMALL END SIZES		DESCRIPTION	REFERENCE / LARGE END SIZES		NOTES	
10	U04						***** MODULAR VALVES *****			810	NIPPLE TO BE CUT FROM SCH 160 PIPE.
30	U04						***** GATE VALVES *****			B1	ALL BOLTS ARE METRIC DIA.
40										FA3	FLAT FACE FLANGES & FULL FACE GASKETS SHALL ONLY BE USED WHEN MATING WITH FLAT FACE EQUIPMENT.
40	U04		GATE	GA1M1	0.75	1.5	GATE 150# RF 6 MO A182 F44/F44 HF TRIM	0	0		
50	U04		GATE	GA1M2	2	10	GATE 150# RF 6 MO A351 CK3MUN/F44 HF TRIM	0	0	FA8	USE THREADED FLANGES FOR INSTRUMENT CONNECTIONS ONLY.
60										FS1	USE FLANGES, GASKETS & VALVES AS REQUIRED TO MATCH EQUIPMENT OR VESSEL NOZZLES.
60	U04						*****PLUG VALVES*****				
70	U04		PLUG	PA1M1	0.75	10	PLUG 150# RF A744 GR CN-3MN OR CK-3CUN BODY & PLUG PTFE SLEEVE 2 WAY STANDARD PORT BOLTED BONNET WRENCH OP.	0	0	UJ2	USE 1 1/2IN WITH THERMOWELL CONNECTIONS ONLY & 3/4IN (IF SHOWN) FOR DBB PRESSURE CONNECTIONS WITH CHEMICAL SEALS.
80										VC1	SPRING PISTON CHECK VALVES ARE PREFERED IN THE HORIZONTAL POSITION, BUT MAY BE USED IN THE VERTICAL POSITION WITH ENGINEERING APPROVAL.
80	U04						***** GLOBE VALVES *****				
90											
90	U04		GLOBE	LA1M1	0.75	1.5	GLOBE 150# RF 6MO A182 F44/F44 HF TRIM	0	0		
100	U04		GLOBE	LA1M2	2	6	GLOBE 150# RF 6MO A351 CK3MCUN/F44 HF TRIM	0	0		
110											
110	U04						***** CHECK VALVES *****				
120	U04	VC1	CHECK	CA1M1	0.75	1.5	CHECK 150# RF 6MO A182 F44 / F44 HF TRIM SPRING PISTON	0	0		
130	U04		CHECK	CA1M5	2	10	CHECK 150# RF 6MO A351 CK3MCUN / F44 TRIM WAFER LUG TYPE THRU BOLTED	0	0		
140											
140	U04						***** PIPE *****				
150											
150	U04		PIPE	5366358	0.75	1.5	PIPE SCH 80S SMLS 6 MO A312 UNS S31254, PE	0	0		
160	U04		PIPE	5721004	2	6	PIPE SCH 40S SMLS 6 MO A312 UNS S31254 BE	0	0		
170	U04		PIPE	5721005	8	10	PIPE SCH 30 SMLS 6 MO A312 UNS S31254 BE	0	0		
180	U04	810	PIPE	5366359	0.5	0.5	PIPE SCH 160 SMLS 6 MO A312 UNS S31254, PE	0	0		
190											
190	U04						***** FITTINGS *****				
200											
200	U04		ELBOW	5721124	0.75	1.5	ELL 90 DEG LR SCH 80S 6MO A403 UNS S31254	0	0		
210	U04		ELBOW	5721104	2	6	ELL BW 90 DEG LR SCH 40S 6MO A403 UNS S31254	0	0		
220	U04		ELBOW	5721105	8	10	ELL BW 90 DEG LR SCH 30 6MO A403 UNS S31254	0	0		
230	U04		ELBOW	5721934	0.75	1.5	ELL 45 DEG SCH 80S SS 6MO A403 UNS S31254	0	0		
240	U04		ELBOW	5721902	2	6	ELL BW 45 DEG LR SCH 40S 6MO A403 UNS S31254	0	0		
250	U04		ELBOW	5721922	8	10	ELL BW 45 DEG LR SCH 30S 6 MO A403 UNS S31254	0	0		
260											
260	U04		TEE	5721210	0.75	1.5	TEE SCH 80S 6MO A403 UNS S31254	0	0		
270	U04		TEE	5721204	2	6	TEE BW SCH 40S 6MO A403 UNS S31254	0	0		
280	U04		TEE	5721205	8	10	TEE BW SCH 30 6MO A403 UNS S31254	0	0		
290	U04		TEE RED	5721211	0.75	1	TEE RED SCH 80S 6MO A403 UNS S31254	1	1.5		
300	U04		TEE RED	5721212	1.5	1.5	TEE RED SCH 40S/80S 6MO A403 UNS S31254	2	3		
310	U04		TEE RED	5721201	2	4	TEE RED SCH 40S 6MO A403 UNS S31254	3	6		
320	U04		TEE RED	5721206	4	6	TEE RED BW SCH 30/SCH 40S 6MO A403 UNS S31254	8	10		
330	U04		TEE RED	5721209	8	8	TEE RED BW SCH 30 6MO A403 UNS S31254	10	10		
340											
340	U04		CAP	5721936	0.75	1.5	CAP SCH 80S 6MO A403 UNS S31254	0	0		
350	U04		CAP	5721905	2	6	CAP BW SCH 40S 6MO A403 UNS S31254	0	0		
360	U04		CAP	5721923	8	10	CAP BW SCH 30 6MO A403 UNS S31254	0	0		
370											
370	U04		RED CONC	5721935	0.75	1	REDUCER CONC SCH 80S 6MO A403 UNS S31254	1	1.5		
380	U04		RED CONC	5721938	0.75	1.5	REDUCER CONC SCH 40S/80S 6MO A403 UNS S31254	2	4		
390	U04		RED CONC	5721924	2	4	REDUCER CONC SCH 40S 6 MO A403 UNS S31254	3	6		
400	U04		RED CONC	5721925	4	6	REDUCER CONC SCH 30/SCH 40S 6MO A403 UNS S31254	8	10		
410	U04		RED CONC	5721926	8	8	REDUCER CONC SCH 30 6MO A403 UNS S31254	10	10		
420	U04		RED ECC	5721945	0.75	1	REDUCER ECC SCH 80S 6MO A403 UNS S31254	1	1.5		
430	U04		RED ECC	5721948	0.75	1.5	REDUCER ECC SCH 40S/80S 6MO A403 UNS S31254	2	4		
440	U04		RED ECC	5721927	2	4	REDUCER ECC SCH 40S 6 MO A403 UNS S31254	3	6		
450	U04		RED ECC	5721928	4	6	REDUCER ECC SCH 30/SCH 40S 6MO A403 UNS S31254	8	10		
460	U04		RED ECC	5721929	8	8	REDUCER ECC SCH 30 6MO A403 UNS S31254	10	10		
470											
470	U04		OLETS	5721616	0.75	1.5	NIPOFLANGE 150# RF SCH 40S/80S 6MO A182 F44	2	6		
480	U04		OLETS	5721617	0.75	1.5	NIPOFLANGE 150# RF SCH 30/80S 6MO A182 F44	8	10		
490	U04		OLETS	5721606	2	2	NIPOFLANGE 150# RF SCH 40S 6MO A182 F44	3	6		
500	U04		OLETS	5721607	2	2	NIPOFLANGE 150# RF SCH 30/ SCH 40S 6MO A182 F44	8	10		
510	U04	UJ2	OLETS	5721610	1.5	1.5	NIPOFLANGE 300# RF SCH 40S/160 6MO A182 F44	4	6		
520	U04	UJ2	OLETS	5721611	1.5	1.5	NIPOFLANGE 300# RF SCH 30/160 6MO A182 F44	8	10		
530											
530	U04	UJ2	ELBOFLG	5721612	1.5	1.5	ELBOFLANGE 300# RF SCH 40S/160 6MO A182 F44	4	6		
540	U04	UJ2	ELBOFLG	5721613	1.5	1.5	ELBOFLANGE 300# RF SCH 30/160 6MO A182 F44	8	10		
550											
550	U04		OLETS	5721654	0.75	1.5	WELDOLET SCH 40S/80S 6MO A182 F44	2	6		
560	U04		OLETS	5721655	0.75	1.5	WELDOLET SCH 30/80S 6MO A182 F44	8	10		

	TENGIZCHEVROI TCO TENGIZ, KAZAKHSTAN	CONSTRUCTION	CORR.ALLOW.	SERVICE	MATERIAL	DATE	BY	REV	SHEET	PIPING LINE CLASS
		ALL SIZES - BUTT WELD SEAL WELDING - NONE PIPE BENDS - NONE THREAD SEALANT - PTFE TAPE	CORR. ALLOW. 1 MM	SOUR SERVICE - NACE MR0175 / ISO 15156 DESIGN: ASME B16.5 MG 2.8 CODE: ASME B31.3 FLUID CODES - PIM-SU-5112-TCO	MATERIAL: 6% MO FLANGE RATING: 150 RF TEMPERATURE RANGE: -40 / 200 °C	12/16/2024	BY OZAC	U04	Page 1 of 2	150MO6

SEQ NO	REV	NOTE NO.	ITEM NAME	ITEM CODE	SIZE RANGE / SMALL END SIZES		DESCRIPTION	REFERENCE / LARGE END SIZES		NOTES
570	U04		OLETS	5721608	2	2	WELDOLET SCH 40S/40S 6MO A182 F44	2	6	
580	U04		OLETS	5721609	2	3	WELDOLET SCH 30/40S 6MO A182 F44	8	10	
590										
590	U04	FS1					***** FLANGES *****			
600										
600	U04	FA8	FLANGE	5721712	0.5	0.5	FLG SCRD (FNPT) REDUCING 150# RF 6MO A182 F44	1.5	1.5	
610	U04		FLANGE	5721744	0.75	1.5	FLG WN 150# RF 6MO A182 F44 SCH 80S BORE	0	0	
620	U04		FLANGE	5721714	2	6	FLG WN 150# RF 6MO A182 F44 SCH 40S	0	0	
630	U04		FLANGE	5721715	8	10	FLG WN 150# RF 6MO A182 F44 SCH 30	0	0	
640	U04	FA3	FLANGE	5721764	0.75	1.5	FLG WN 150# FF 6MO A182 F44 SCH 80S BORE	0	0	
650	U04	FA3	FLANGE	5721722	2	6	FLG WN 150# FF 6MO A182 F44 SCH 40S	0	0	
660	U04		BLIND	5721717	0.75	10	FLG BLIND 150# RF 6MO A182 F44	0	0	
670	U04		FLANGE	5721814	0.5	1.5	FLG WN 300# RF 6MO A182 F44 SCH 80S BORE	0	0	
680	U04		FLANGE	5721709	2	6	FLG WN 300# RF 6MO A182 F44 SCH 40S	0	0	
690	U04		FLANGE	5721716	8	10	FLG WN 300# RF 6MO A182 F44 SCH 30	0	0	
700	U04		BLIND	5721711	0.75	10	FLG BLIND 300# RF 6MO A182 F44	0	0	
710										
710	U04						**** ORIFICE FLANGES ****			
720										
720	U04		ORIFICE FLG	5721718	2	6	WN ORIF SET 300# RF 6MO A182 F44 SCH 40S	0	0	
730	U04		ORIFICE FLG	5721719	8	10	WN ORIF SET 300# RF 6MO A182 F44 SCH 30	0	0	
740										
740	U04						*****PIPE NIPPLES*****			
750										
750	U04	810					NIPPLE PBE CUT FROM PIPE			
760										
760	U04	FS1					***** GASKETS *****			
770										
770	U04		GASKET	5673059	0.5	10	GASKET 150# S31254 SPIRAL WOUND GRAPHITE FILLED IR	0	0	
780	U04		GASKET	5664562	0.75	6	GASKET 150# FF RING EPDM 3MM THK	0	0	
790	U04		GASKET	5673056	0.5	10	GASKET 300# S31254 SPIRAL WOUND GRAPHITE FILLED IR	0	0	
800										
800	U04						***** BOLTING *****			
810										
810	U04	B1	BOLTING	5675770	0.5	99	STUD-BOLT A320 GR L7M/A194 GR 7M (S3) WITH 2 NUTS	0	0	
820										
820	U04						***** SPECTACLE BLINDS *****			
830										
830	U04		SPEC BLIND	5721720	1.5	10	SPECTACLE BLIND 150# RF 6MO A240 UNS S31254	0	0	
840										

	TENGIZCHEVROIL TCO TENGIZ, KAZAKHSTAN	CONSTRUCTION	CORR.ALLOW.	SERVICE	MATERIAL	DATE	BY	REV	SHEET	PIPING LINE CLASS
		ALL SIZES - BUTT WELD SEAL WELDING - NONE PIPE BENDS - NONE THREAD SEALANT - PTFE TAPE	CORR. ALLOW. 1 MM	SOUR SERVICE - NACE MR0175 / ISO 15156 DESIGN: ASME B16.5 MG 2.8 CODE: ASME B31.3 FLUID CODES - PIM-SU-5112-TCO	MATERIAL: 6% MO FLANGE RATING: 150 RF TEMPERATURE RANGE: -40 / 200 °C	12/16/2024	BY OZAC	U04	Page 2 of 2	150M06