

SEQ NO	REV	NOTE NO.	ITEM NAME	ITEM CODE	SIZE RANGE / SMALL END SIZES		DESCRIPTION	REFERENCE / LARGE END SIZES		NOTES	
10	U04						***** VALVES*****			811 B1 VC1	NIPPLE TO BE CUT FROM SCH 80S PIPE ALL BOLTS ARE METRIC DIA. SPRING PISTON CHECK VALVES ARE PREFERED IN THE HORIZONTAL POSITION, BUT MAY BE USED IN THE VERTICAL POSITION WITH ENGINEERING APPROVAL.
20	U04						***** MODULAR VALVES *****				
30	U04		MODULAR DBB	M01AS02	0.75	2	MODULAR VALVE DB&B BALL TYPE 150# RF SS A182 F316 316 SS TRIM METAL LO - CONTROLLED BORE TYPE 2BVR	0	0		
40	U04						***** BALL VALVES *****				
50	U04		BALL	BE5S3OX	0.5	0.75	BALL COMPRESSIBLE TUBE ENDS 1500# 316 SS BODY & TRIM STANDARD PORT TFE SEAT & SEALS.	0	0	811 B1 VC1	NIPPLE TO BE CUT FROM SCH 80S PIPE ALL BOLTS ARE METRIC DIA. SPRING PISTON CHECK VALVES ARE PREFERED IN THE HORIZONTAL POSITION, BUT MAY BE USED IN THE VERTICAL POSITION WITH ENGINEERING APPROVAL.
60	U04		BALL	B01AS01	0.75	2	BALL 150# RF SS A182 F316 316SS TRIM FLOATING SOFT FB LO	0	0		
70	U04						***** GLOBE VALVES *****				
80	U04		GLOBE	L01AS48	0.75	1.5	GLOBE 150# RF SS A182 F316 TRIM 16 OS&Y HW	0	0		
90	U04		GLOBE	L01AS41	2	2	GLOBE 150# RF SS A351 CF8M TRIM 16 OS&Y HW	0	0	811 B1 VC1	NIPPLE TO BE CUT FROM SCH 80S PIPE ALL BOLTS ARE METRIC DIA. SPRING PISTON CHECK VALVES ARE PREFERED IN THE HORIZONTAL POSITION, BUT MAY BE USED IN THE VERTICAL POSITION WITH ENGINEERING APPROVAL.
100	U04						***** CHECK VALVES *****				
110	U04	VC1	CHECK	C01AS50	0.75	1.5	CHECK PISTON 150# RF SS A182 F316 TRIM 16	0	0		
120	U04		CHECK	C01AS45	2	2	CHECK DUAL WAFER LUG 150# RF SS A351 CF8M TRIM 16 THROU BOLTED	0	0		
130	U04						***** TUBES *****			811 B1 VC1	NIPPLE TO BE CUT FROM SCH 80S PIPE ALL BOLTS ARE METRIC DIA. SPRING PISTON CHECK VALVES ARE PREFERED IN THE HORIZONTAL POSITION, BUT MAY BE USED IN THE VERTICAL POSITION WITH ENGINEERING APPROVAL.
140	U04		TUBE	5851000	0.5	0.5	TUBE SMLS WT 0.065" SS A269 TP 316	0	0		
150	U04		TUBE	5851001	0.75	0.75	TUBE SMLS WT 0.083" SS A269 TP 316	0	0		
160	U04						***** FITTINGS *****				
170	U04						***** FITTINGS *****			811 B1 VC1	NIPPLE TO BE CUT FROM SCH 80S PIPE ALL BOLTS ARE METRIC DIA. SPRING PISTON CHECK VALVES ARE PREFERED IN THE HORIZONTAL POSITION, BUT MAY BE USED IN THE VERTICAL POSITION WITH ENGINEERING APPROVAL.
180	U04		ELBOW	5851100	0.5	0.75	ELBOW 90 DEG TWIN FERRULE TYPE COMPRESSION TUBE UNION ENDS 316 STAINLESS STEEL.	0	0		
190	U04		TEE	5851101	0.5	0.75	TEE TWIN FERRULE TYPE COMPRESSION TUBE UNION ENDS 316 STAINLESS STEEL.	0	0		
200	U04		UNION	5851102	0.5	0.75	UNION TWIN FERRULE TYPE COMPRESSION TUBE UNION ENDS 316 STAINLESS STEEL	0	0		
210	U04		CAP	5851103	0.5	0.75	CAP TWIN FERRULE TYPE COMPRESSION TUBE UNION END 316 STAINLESS STEEL	0	0	811 B1 VC1	NIPPLE TO BE CUT FROM SCH 80S PIPE ALL BOLTS ARE METRIC DIA. SPRING PISTON CHECK VALVES ARE PREFERED IN THE HORIZONTAL POSITION, BUT MAY BE USED IN THE VERTICAL POSITION WITH ENGINEERING APPROVAL.
220	U04		UNION	5851104	0.5	0.5	REDUCING UNION TWIN FERRULE TYPE COMPRESSION TUBE UNION ENDS 316 STAINLESS STEEL	0.75	0.75		
230	U04						***** FLANGES *****				
240	U04		FITTING SCRD	5851105	0.5	0.5	ADAPTOR TWIN FERRULE TYPE COMPRESSION TUBE UNION TO FEMALE NPT PIPE CONNECTION 316 STAINLESS STEEL	0.5	0.5		
250	U04						***** PIPE, PIPE FITTINGS *****			811 B1 VC1	NIPPLE TO BE CUT FROM SCH 80S PIPE ALL BOLTS ARE METRIC DIA. SPRING PISTON CHECK VALVES ARE PREFERED IN THE HORIZONTAL POSITION, BUT MAY BE USED IN THE VERTICAL POSITION WITH ENGINEERING APPROVAL.
260	U04						***** PIPE *****				
270	U04	811	PIPE	5365140	0.75	2	PIPE SCH 80S SMLS SS A312 TP316/316L PE	0	0		
280	U04		PIPE	5365207	0.5	0.5	PIPE SCH 160 SMLS SS A312 TP316/316L PE	0	0		
290	U04		ELBOW	5449033	0.75	2	ELL 90 DEG LR SCH 80S SS A403 WP316/316L-S	0	0	811 B1 VC1	NIPPLE TO BE CUT FROM SCH 80S PIPE ALL BOLTS ARE METRIC DIA. SPRING PISTON CHECK VALVES ARE PREFERED IN THE HORIZONTAL POSITION, BUT MAY BE USED IN THE VERTICAL POSITION WITH ENGINEERING APPROVAL.
300	U04		ELBOW	5449146	0.75	2	ELL 45 DEG LR SCH 80S SS A403 WP316/316L-S	0	0		
310	U04		TEE	5449156	0.75	2	TEE SCH 80S SS A403 WP316/316L-S	0	0		
320	U04		CAP	5449049	0.75	2	CAP SCH 80S SS A403 WP316/316L-S	0	0		
330	U04		RED CONC	5449158	0.75	1.5	REDUCER CONC SCH 80S SS A403 WP316/316L-S	1	2	811 B1 VC1	NIPPLE TO BE CUT FROM SCH 80S PIPE ALL BOLTS ARE METRIC DIA. SPRING PISTON CHECK VALVES ARE PREFERED IN THE HORIZONTAL POSITION, BUT MAY BE USED IN THE VERTICAL POSITION WITH ENGINEERING APPROVAL.
340	U04		RED ECC	5449159	0.75	1.5	REDUCER ECC SCH 80S SS A403 WP316/316L-S	1	2		
350	U04		OLETS	5509637	0.75	0.75	WELDOLET SCH 80S SS A182 F316/316L	2	2		
360	U04						***** FLANGES *****				
370	U04		FLANGE	5582724	0.75	2	FLG WN 150# RF SS A182 F316/316L SCH 80S BORE	0	0	811 B1 VC1	NIPPLE TO BE CUT FROM SCH 80S PIPE ALL BOLTS ARE METRIC DIA. SPRING PISTON CHECK VALVES ARE PREFERED IN THE HORIZONTAL POSITION, BUT MAY BE USED IN THE VERTICAL POSITION WITH ENGINEERING APPROVAL.
380	U04		BLIND	5852201	0.75	2	FLG BLIND 150# RF SS A182 F316/316L	0	0		
390	U04						***** NIPPLES*****				
400	U04	811					NIPPLE PBE - CUT FROM PIPE				
410	U04						***** GASKETS*****				

	TENGIZCHEVROIL TCO TENGIZ, KAZAKHSTAN	CONSTRUCTION	CORR.ALLOW.	SERVICE	MATERIAL	DATE	BY	REV	SHEET	PIPING LINE CLASS
		TUBE - 3/4" & SMALLER - TUBE COMPRESSION FITTINGS PIPE - 3/4" & LARGER - BUTT WELD SEAL WELDING - NONE PIPE BENDS - NONE THREAD SEALANT - PTFE PASTE	CORR. ALLOW. 0 MM	SOUR SERVICE - NACE MR0175/ ISO 15156 DESIGN: 10 BARG CODE - ASME B31.3 FLUID CODES - PIM-SU-5112-TCO	MATERIAL: 316/316L SS DUAL GRADE FLANGE RATING: 150 RF TEMPERATURE RANGE: -40 / 145 °C	12/16/2024	BY OZAC	U04	Page 1 of 2	150P23

SEQ NO	REV	NOTE NO.	ITEM NAME	ITEM CODE	SIZE RANGE / SMALL END SIZES		DESCRIPTION	REFERENCE / LARGE END SIZES		NOTES
420										
420	U04		GASKET	5673043	0.75	2	GASKET 150# 316SS SPIRAL WOUND GRAPHITE IR	0	0	
430										
430	U04						***** BOLTING *****			
440										
440	U04	B1	BOLTING	5675770	0.5	99	STUD-BOLT A320 GR L7M/A194 GR 7M (S3) WITH 2 NUTS	0	0	

	TENGIZCHEVROIL TCO TENGIZ, KAZAKHSTAN	CONSTRUCTION	CORR.ALLOW.	SERVICE	MATERIAL	DATE	BY	REV	SHEET	PIPING LINE CLASS
		TUBE - 3/4" & SMALLER - TUBE COMPRESSION FITTINGS PIPE - 3/4" & LARGER - BUTT WELD SEAL WELDING - NONE PIPE BENDS - NONE THREAD SEALANT - PTFE PASTE	CORR. ALLOW. 0 MM	SOUR SERVICE - NACE MR0175/ ISO 15156 DESIGN: 10 BARG CODE - ASME B31.3 FLUID CODES - PIM-SU-5112-TCO	MATERIAL: 316/316L SS DUAL GRADE FLANGE RATING: 150 RF TEMPERATURE RANGE: -40 / 145 °C	12/16/2024	BY OZAC	U04	Page 2 of 2	150P23