

SEQ NO	REV	NOTE NO.	ITEM NAME	ITEM CODE	SIZE RANGE / SMALL END SIZES		DESCRIPTION	REFERENCE / LARGE END SIZES		NOTES	
10	U04						***** BUTTERFLY VALVES *****			B1 GA3	ALL BOLTS ARE METRIC DIA. SPIRAL WOUND GASKETS SHALL ONLY BE USED BETWEEN CARBON STEEL FLANGES AND CARBON STEEL VALVES.
20											
20	U04		BUTTERFLY	T01AC61	24	24	BUTTERFLY 150# RF LTCS A352 LCC 316SS TRIM TOV METAL DBL FLG SHORT PAT GO	0	0		
30											
30	U04						***** PIPE *****				
40											
40	U04		PIPE	5713120	6	6	PIPE SDR 9 HD POLYETHYLENE PE 100 WATER HOSTALEN 4731B PE-RT ISO 4427	0	0		
50	U04		PIPE	5713120	10	10	PIPE SDR 9 HD POLYETHYLENE PE 100 WATER HOSTALEN 4731B PE-RT ISO 4427	0	0		
60	U04		PIPE	5713120	24	24	PIPE SDR 9 HD POLYETHYLENE PE 100 WATER HOSTALEN 4731B PE-RT ISO 4427	0	0		
70											
70	U04						***** FITTINGS *****				
80											
80	U04		ELBOW	5713122	24	24	BEND 90 DEG FABRICATED TYPE SDR 9 HD POLYETHYLENE PE 100 WATER HOSTALEN 4731B PE-RT ISO 4427	0	0		
90	U04		ELBOW	5713124	10	10	BEND 45 DEG FABRICATED TYPE SDR 9 HD POLYETHYLENE PE 100 WATER HOSTALEN 4731B PE-RT ISO 4427	0	0		
100	U04		ELBOW	5713124	24	24	BEND 45 DEG FABRICATED TYPE SDR 9 HD POLYETHYLENE PE 100 WATER HOSTALEN 4731B PE-RT ISO 4427	0	0		
110											
110	U04		TEE	5713125	24	24	TEE EQUAL FABRICATED TYPE SDR 9 HD POLYETHYLENE PE 100 WATER HOSTALEN 4731B PE-RT ISO 4427	0	0		
120											
120	U04		CAP	5713127	24	24	CAP ELONGATED TYPE SDR 9 HD POLYETHYLENE PE 100 WATER HOSTALEN 4731B PE-RT ISO 4427	0	0		
130											
130	U04		Coupling	5713130	2	24	COUPLING ELECTRO FUSION SDR 9 HD POLYETHYLENE PE 100 WATER HOSTALEN 4731B PE-RT ISO 4427	0	0		
140											
140	U04						***** FLANGES *****				
150											
150	U04		FLANGE	5713131	6	6	HP FLANGE CONNECTION FOR FULL PRESSURE LOAD SDR 9 HD POLYETHYLENE C/W BACKING RING PE 100 WATER HOSTALEN PE-RT ISO 4427	0	0		
160	U04		FLANGE	5713131	24	24	HP FLANGE CONNECTION FOR FULL PRESSURE LOAD SDR 9 HD POLYETHYLENE C/W BACKING RING PE 100 WATER HOSTALEN PE-RT ISO 4427	0	0		
170											
170	U04						***** PUDDLE FLANGE SPOOL ADAPTORS *****				
180											
180	U04		FLG ADAPTER	5713142	24	24	SPOOL - PUDDLE (ANCHOR) FLANGE WITH STUB FLANGE C/W BACKING RING AND 24" PIPE SDR 9 HD PE 100 HOSTALEN PE-RT ISO 4427	0	0		
190											
190	U04						***** PUDDLE FLANGE SPOOLS *****				
200											
200	U04		PUDDLE FLG	5713480	10	10	SPOOL - PUDDLE (ANCHOR) FLANGE WITH STUB FLANGE C/W BACKING RING AND 10" PIPE SDR 9 HD PE 100 HOSTALEN PE-RT ISO 4427	0	0		
210											
210	U04		PUDDLE FLG	5713143	24	24	PUDDLE (ANCHOR) FLANGE WITH PIPE SDR 9 HD PE 100 HOSTALEN 4731B PE-RT ISO 4427 LENGTH 750MM	0	0		
220											
220	U04						***** GASKETS *****				
230											
230	U04		GASKET	5664201	24	24	GASKET 150# RF FLAT RING PTFE	0	0		
240	U04	GA3	GASKET	5673043	24	24	GASKET 150# 316SS SPIRAL WOUND GRAPHITE IR	0	0		
250											
250	U04	B1					***** BOLTING *****				
260											
260	U04		BOLTING	5675768	0.5	99	STUD-BOLT A320 GR L7M/A194 GR 7M (S3) W/ 2 NUTS + LTCS WASHERS	0	0		
270											

	TENGIZCHEVROIL TCO TENGIZ, KAZAKHSTAN	CONSTRUCTION	CORR.ALLOW.	SERVICE	MATERIAL	DATE	BY	REV	SHEET	PIPING LINE CLASS
		ALL SIZES - BUTT FUSION SEAL WELDING - NONE PIPE BENDS - NONE THREAD SEALANT - NONE ELECTRIC SOCKET WELDING OR BUTT WELDING AS APPLICABLE	CORR. ALLOW. 0 MM	DESIGN: DESIGN PRESSURE RANGE AS PER PIM-SU-5112-TCO CODE - SHALL BE ADVISED BY TCO SME FLUID CODES - PIM-SU-5112-TCO	MATERIAL: HDPE PERT TYPE 2 SDR 9 ID COLOR: RED FLANGE RATING: 150 RF TEMPERATURE RANGE: -40 / 75 °C	12/16/2024	BY OZAC	U04	Page 1 of 1	150PE15