

SEQ NO	REV	NOTE NO.	ITEM NAME	ITEM CODE	SIZE RANGE / SMALL END SIZES		DESCRIPTION	REFERENCE / LARGE END SIZES		NOTES	
10	U04						***** VALVES *****			B1	ALL BOLTS ARE METRIC DIA.
20	U04	VB2					***** BALL VALVES *****			B2	7/8" X 145MM BOLTS ONLY TO BE USED FOR 1 INCH 1500# PERAR BALL VALVES ITEM CODE B15AM10
30											
30	U04		BALL	A01AC01	1	4	BALL 150# RF LTCS A350 LF2 CL.1 316SS TRIM FLOATING SOFT RB LO	0	0		
40	U04		BALL	A01AC03	6	6	BALL 150# RF LTCS A350 LF2 CL.1 316SS TRIM FLOATING SOFT RB GO	0	0	FS1	USE FLANGES, GASKETS & VALVES AS REQUIRED TO MATCH EQUIPMENT OR VESSEL NOZZLES.
50	U04		BALL	A01AC07	8	8	BALL 150# RF LTCS A350 LF2 CL.1 316SS TRIM TRUNNION SOFT RB GO	0	0		
60		VU2	BALL	BA6B2	0.5	2	BALL 150# SCRD FNPT BS1400 LG2 BODY AND TRIM FB LO	0	0		
70	U04	VA5	BALL	B01AC01	0.75	3	BALL 150# RF LTCS A350 LF2 CL.1 316SS TRIM FLOATING SOFT FB LO	0	0	FV5	WHERE THERE IS A SIZE CHANGE FROM 18" - 24" CARBON STEEL TO VICTAULIC SYSTEM, USE REDUCER AND STANDARD RF WNK FLANGE TO CONNECT TO FLANGE ADAPTER NIPPLE ON VICTAULIC END.
80	U04	VA5	BALL	B01AC03	4	4	BALL 150# RF LTCS A350 LF2 CL.1 316SS TRIM FLOATING SOFT FB GO	0	0		
90	U04	VA5	BALL	B01AC07	6	8	BALL 150# RF LTCS A350 LF2 CL.1 316SS TRIM TRUNNION SOFT FB GO	0	0		
100	U04	VA5	BALL	B03AC01	0.75	1.5	BALL 300# RF LTCS A350 LF2 CL.1 316SS TRIM FLOATING SOFT FB LO	0	0		
110											
110	U04						***** BUTTERFLY VALVES *****			GA6	SPECIAL GASKET ONLY FOR USE AS SPECIFIED IN ENG-200-117
120											
120	U04		BUTTERFLY	T01AC61	10	24	BUTTERFLY 150# RF LTCS A352 LCC 316SS TRIM TOV METAL DBL FLG SHORT PAT GO	0	0	ND9	USE ONLY WITH CONSENT OF MATERIALS ENGINEER.
130											
130	U04						***** GATE VALVES *****			NR1	SIZES SHOWN IN SIZE COLUMNS ARE THE SMALL END OF REDUCERS AND THE BRANCH SIZE OF OLETS AND TEES.
140											
140	U04		GATE	GA6B1	0.5	1	GATE 150# SCRD FNPT BS1400 LG2 BODY AND TRIM HW	0	0	PA6	PIPE IS SUPPLIED WITH STANDARD PLAIN END/ BW END AND GROOVE TO BE CUT DURING FABRICATION.
150	U04		GATE	G01AC48	1.5	1.5	GATE 150# RF LTCS A350 LF2 CL.1 TRIM 16 WEDGE HW	0	0		
160	U04		GATE	G01AC41	2	14	GATE 150# RF LTCS A352 LCC TRIM 16 WEDGE HW	0	0		
170	U04	VA5	GATE	G01AC42	18	20	GATE 150# RF LTCS A352 LCC TRIM 16 WEDGE GO	0	0		
180	U04	VA5	GATE	G01JC42	36	36	GATE 150# RF LTCS A352 LCC TRIM 16 WEDGE GO B16.47 SERIES A	0	0	PS1	PIPE ONLY TO BE USED AS TRUNNION SUPPORTS
190	U04		GATE	G03AC41	3	3	GATE 300# RF LTCS A352 LCC TRIM 16 WEDGE HW	0	0		
200	U04		GATE	G01AC96	2	16	GATE 150# RF LTCS A352 LCC TRIM 16 WEDGE HW 2800MM EXT	0	0	UD4	USE WHERE THREADED OUTLET IS REQUIRED FOR TRUCK SUCTION HOSE CONNECTIONS.
210	U04		GATE	G01AC99	2	16	GATE 150# RF LTCS A352 LCC TRIM 16 WEDGE HW 3300MM EXT	0	0	UDF	USE THREDOLET AND SCREWED PLUG FOR HYDROSTATIC TEST VENTS AND DRAINS.
220											
220	U04						***** GLOBE VALVES *****			UG3	PTFE GASKET ONLY TO BE USED FOR INTERFACE WITH POLYETHYLENE (HDPE) UNDERGROUND PIPING
230											
230	U04		GLOBE	LA6B1	0.75	1	GLOBE 150# SCRD FNPT BS1400 LG2 BODY AND TRIM HW	0	0		
240	U04		GLOBE	L01AC48	1.5	1.5	GLOBE 150# RF LTCS A350 LF2 CL.1 TRIM 16 OS&Y HW	0	0		
250	U04		GLOBE	L01AC41	2	6	GLOBE 150# RF LTCS A352 LCC TRIM 16 OS&Y HW	0	0	UG4	BOLTS ONLY TO BE USED FOR INTERFACE WITH POLYETHYLENE (HDPE) UNDERGROUND PIPING
260	U04		GLOBE	L01AC42	8	10	GLOBE 150# RF LTCS A352 LCC TRIM 16 OS&Y GO	0	0		
270											
270	U04						***** CHECK VALVES *****			VA5	USE THESE VALVES ONLY WHERE SPECIFIED ON PIPING AND INSTRUMENT DIAGRAMS
280											
280	U04	VC1	CHECK	CA6B1	0.75	1	CHECK 150# SCRD FNPT BS1400 LG2 BODY AND TRIM SPRING PISTON	0	0	VB2	SOFT SEATED BALL VALVES ARE LIMITED TO MAXIMUM TEMPERATURE OF 200°C.
290	U04	VC1	CHECK	C01AC50	1.5	1.5	CHECK PISTON 150# RF LTCS A350 LF2 CL.1 TRIM 16	0	0		
300	U04		CHECK	C01AC45	2	6	CHECK DUAL WAFER LUG 150# RF LTCS A352 LCC TRIM 16 THROU BOLTED	0	0	VC1	SPRING PISTON CHECK VALVES ARE PREFERRED IN THE HORIZONTAL POSITION, BUT MAY BE USED IN THE VERTICAL POSITION WITH ENGINEERING APPROVAL.
310	U04		CHECK	C01AC52	8	24	CHECK DUAL DBL FLG 150# RF LTCS A352 LCC TRIM 16	0	0		
320											
320	U04						***** PIPE *****			VU2	USE THIS VALVE FOR ORIFICE TAP BLOCK VALVE ONLY.
330											
330	U04		PIPE	5358601	0.5	1	PIPE SCH 160 SMLS LTCS A333 GR.6 GALV A153 T&C	0	0		
340	U04	PA6	PIPE	5358167_VC	1.5	3	PIPE SCH 80 SMLS LTCS A333 GR. 6 PE GALV (GROOVING NOT BY SUPPLIER - TO BE DONE DURING FABRICATION)	0	0		
350	U04	PA6	PIPE	5358164_VC	4	10	PIPE SCH STD SMLS LTCS A333 GR. 6 PE GALV (GROOVING NOT BY SUPPLIER - TO BE DONE DURING FABRICATION)	0	0		
360	U04	PA6	PIPE	5358162_VC	12	12	PIPE SCH 30 SMLS LTCS A333 GR. 6 PE GALV (GROOVING NOT BY SUPPLIER - TO BE DONE DURING FABRICATION)	0	0		
370	U04	PA6	PIPE	5358161_VC	14	16	PIPE SCH 20 SMLS LTCS A333 GR. 6 PE GALV (GROOVING NOT BY SUPPLIER - TO BE DONE DURING FABRICATION)	0	0		
380	U04		PIPE	5358597	18	24	PIPE SCH 20 EFW LTCS A671 CC60 CL.22 BE	0	0		
390	U04		PIPE	5358576	36	36	PIPE SCH STD EFW LTCS A671 CC60 CL.22 BE	0	0		
400											
400	U04	NR1, FV5					***** FITTINGS *****				
410											
410	U04		ELBOW	5491290	0.5	1	ELL 90 DEG 3000# SCRD FNPT LTCS A350 LF2 CL.1 GALV A153	0	0		
420	U04		ELBOW	5491300	0.5	1	ELL 45 DEG 3000# SCRD FNPT LTCS A350 LF2 CL.1 GALV A153	0	0		
430	U04		ELBOW	5392280	18	24	ELL BW 90 DEG LR SCH 20 LTCS A420 WPL6-W	0	0		
440	U04		ELBOW	5392281	18	24	ELL BW 45 DEG LR SCH 20 LTCS A420 WPL6-W	0	0		
450	U04		ELBOW	5392496	36	36	ELL 90 DEG LR SCH STD LTCS A420 WPL6-W	0	0		
460											
460	U04		TEE	5491310	0.5	1	TEE 3000# SCRD FNPT LTCS A350 LF2 CL.1 GALV A153	0	0		
470	U04		TEE	5392295	18	24	TEE BW SCH 20 LTCS A420 WPL6-W	0	0		
480	U04		TEE	5392405	36	36	TEE SCH STD LTCS A420 WPL6-W	0	0		
490	U04		TEE RED	5491311	0.75	0.75	TEE RED 3000# SCRD FNPT LTCS A350 LF2 CL.1 GALV A153	1	1		
500	U04		TEE RED	5392296	8	10	TEE RED BW SCH 20/STD LTCS A420 WPL6-W	18	24		
510	U04		TEE RED	5392244	12	12	TEE RED BW SCH 20/SCH 30 LTCS A420 WPL6-W	18	24		
520	U04		TEE RED	5392292	14	20	TEE RED BW SCH 20 LTCS A420 WPL6-W	18	24		
530	U04		TEE RED	5556912	16	18	TEE RED BW SCH STD/ SCH 20 LTCS A420 WPL6-W	36	36		
540											

	TENGIZCHEVROI TCO TENGIZ, KAZAKHSTAN	CONSTRUCTION	CORR.ALLOW.	SERVICE	MATERIAL	DATE	BY	REV	SHEET	PIPING LINE CLASS
		3/4" - 1" - SCREWED 1 1/2" - 16" - VICTAULIC GROOVE & COUPLING 18" & ABOVE - GALV'D AFTER FABRICATION SEAL WELDING - NONE PIPE BENDS - NONE THREAD SEALANT - PTFE PASTE	CORR. ALLOW. 3 MM	DESIGN: 15.8 BARG CODE - ASME B31.3 FLUID CODES - PIM-SU-5112-TCO	MATERIAL: GALVANISED LTCS VICTAULIC COUPLINGS FLANGE RATING: 150 RF TEMPERATURE RANGE: -40 / 110 °C	12/16/2024	BY OZAC	U04	Page 1 of 3	150VG01

SEQ NO	REV	NOTE NO.	ITEM NAME	ITEM CODE	SIZE RANGE / SMALL END SIZES		DESCRIPTION	REFERENCE / LARGE END SIZES		NOTES
540	U04	UD4	CAP	5491330	0.75	1	CAP 3000# SCRD FNPT LTCS A350 LF2 CL.1 GALV A153	0	0	
550	U04		CAP	5491330	2.5	2.5	CAP 3000# SCRD FNPT LTCS A350 LF2 CL.1 GALV A153	0	0	
560	U04		CAP	5392286	18	24	CAP BW SCH 20 LTCS A420 WPL6	0	0	
570	U04		CAP	5392448	36	36	CAP BW SCH STD LTCS A420 WPL6	0	0	
580										
580	U04		RED CONC	5392297	10	10	REDUCER CONC SCH 20/STD LTCS A420 WPL6-W	18	18	
590	U04		RED CONC	5392243	12	12	REDUCER CONC SCH 20/SCH 30 LTCS A420 WPL6-W	18	20	
600	U04		RED CONC	5392287	14	20	REDUCER CONC SCH 20 LTCS A420 WPL6-W	18	24	
610	U04		RED ECC	5392298	10	10	REDUCER ECC SCH 20/STD LTCS A420 WPL6-W	18	18	
620	U04		RED ECC	5392242	12	12	REDUCER ECC SCH 20/SCH 30 LTCS A420 WPL6-W	18	20	
630	U04		RED ECC	5392288	14	20	REDUCER ECC SCH 20 LTCS A420 WPL6-W	18	24	
640										
640	U04						***** FITTINGS - VICTAULIC *****			
650										
650	U04		ELBOW	5484860	1.5	3	ELL 90 DEG GRV SCH 80 LTCS A352 GR LCC GALV	0	0	
660	U04		ELBOW	5484861	4	10	ELL 90 DEG GRV SCH STD LTCS A352 GR LCC GALV	0	0	
670	U04		ELBOW	5484865	1.5	3	ELL 45 DEG GRV SCH 80 LTCS A352 GR LCC GALV	0	0	
680	U04		ELBOW	5484866	4	10	ELL 45 DEG GRV SCH STD LTCS A352 GR LCC GALV	0	0	
690	U04		ELBOW	5407038	6	6	ELL 22.5 DEG GRV SCH STD LTCS A352 GR LCC GALV	0	0	
700										
700	U04		TEE	5485120	1.5	3	TEE GRV SCH 80 LTCS A352 GR LCC GALV	0	0	
710	U04		TEE	5485121	4	10	TEE GRV SCH STD LTCS A352 GR LCC GALV	0	0	
720	U04		TEE RED	5484799	0.5	1	TEE RED GRV X THREAD SCH 80/SCH 160 LTCS A352 GR LCC GALV	1.5	1.5	
730			TEE RED	5484884	1.5	3	TEE RED GRV SCH STD/SCH 80 LTCS A352 GR LCC GALV	4	10	
740			TEE RED	5484881	4	8	TEE RED GRV SCH STD LTCS A352 GR LCC GALV	6	10	
750										
750	U04		CAP	5485130	1.5	3	CAP GRV SCH 80 LTCS A352 GR LCC GALV	0	0	
760	U04		CAP	5485131	4	10	CAP GRV SCH STD LTCS A352 GR LCC GALV	0	0	
770										
770			RED CONC	5543791	0.75	1.5	REDUCER CONC GRV X FNPT LTCS A352 LCC GALV	1.5	2	
780	U04		RED CONC	5484890	1.5	2	REDUCER CONC GRV SCH 80 LTCS A352 GR LCC GALV	2	3	
790	U04		RED CONC	5484891	1.5	3	REDUCER CONC GRV SCH STD/SCH 80 LTCS A352 GR LCC GALV	4	6	
800	U04		RED CONC	5484892	4	8	REDUCER CONC GRV SCH STD LTCS A352 GR LCC GALV	6	10	
810	U04		RED ECC	5484898	0.75	1	REDUCER ECC GRV X FNPT LTCS A352 LCC GALV	2	2	
820	U04		RED ECC	5484830	1.5	2	REDUCER ECC GRV SCH 80 LTCS A352 GR LCC GALV	2	3	
830	U04		RED ECC	5484831	1.5	3	REDUCER ECC GRV SCH STD/SCH 80 LTCS A352 GR LCC GALV	4	6	
840	U04		RED ECC	5484832	4	8	REDUCER ECC GRV SCH STD LTCS A352 GR LCC GALV	6	10	
850										
850	U04						***** COUPLINGS, UNIONS & PLUGS *****			
860										
860	U04		Coupling	5491250	0.5	1	COUPLING 3000# SCRD FNPT LTCS A350 LF2 CL.1 GALV A153	0	0	
870	U04		COUPLING	5491260	0.5	0.5	COUPLING RED 3000# SCRD FNPT LTCS A350 LF2 CL.1 GALV A153	0.75	0.75	
880										
880	U04		UNION	5491270	0.75	1	UNION 3000# SCRD FNPT LTCS A350 LF2 CL.1 GALV A153	0	0	
890										
890	U04	UDF	FITTING SCRD	5491280	0.5	2	PLUG ROUND HEAD SCRD MNPT LTCS A350 LF2 CL.1 GALV A153	0	0	
900										
900	U04		FITTING SCRD	5491325	0.5	1.5	BUSHING 3000# SCRD (MNPT/FNPT) HEX HEAD LTCS A350 LF2 CL.1 GALV A153	0.75	2	
910										
910	U04	UDF	OLETS	5514772	0.75	2	THREDOLET 3000# LTCS A350 LF2 CL.1	18	36	
920										
920	U04		OLETS	5505571	4	6	WELDOLET SCH 20/STD LTCS A350 LF2 CL.1	24	24	
930	U04		OLETS	5505164	6	6	WELDOLET SCH STD LTCS A350 LF2 CL.1	36	36	
940										
940	U04						***** COUPLINGS - VICTAULIC *****			
950										
950	U04		Coupling	5484764	1.5	16	COUPLING RIGID GRV ASTM A352 GRADE LCC EPDM GASKET GALV	0	0	
960										
960			SADDLE	5485125	0.5	2	VICTAULIC BOLTED BRANCH OUTLET FNPT LTCS A352 GR LCC GALV	2	16	
970										
970	U04						***** FLANGES *****			
980										
980	U04		FLANGE	5599691	0.5	0.75	FLG SCRD (FNPT) REDUCING 150# RF LTCS A350 LF2 CL.1 GALV A153	0.75	2	
990	U04		FLANGE	5599689	0.5	1	FLG SCRD (FNPT) 150# RF LTCS A350 LF2 CL.1 GALV A153	0	0	
1000	U04		FLANGE	5599701	0.75	1.5	FLG SCRD (FNPT) 300# RF LTCS A350 LF2 CL.1 GALV A153	0	0	
1010										
1010	U04		FLG ADAPTER	5851200	0.5	1	FLANGE ADAPTER 150# RF 316 SS X 12 MM TUBE	0	0	
1020										
1020	U04	ND9	FLANGE	5556261	4	10	FLG WN 150# RF LTCS A350 LF2 CL.1 SCH STD	0	0	
1030	U04	ND9	FLANGE	5556274	12	12	FLG WN 150# RF LTCS A350 LF2 CL.1 SCH 30	0	0	
1040	U04		FLANGE	5556265	14	24	FLG WN 150# RF LTCS A350 LF2 CL.1 SCH 20	0	0	
1050	U04	ND9	FLANGE	5556262	36	36	FLG WN 150# RF LTCS A350 LF2 CL.1 SCH STD B16.47 SERIES A	0	0	
1060	U04	ND9	FLANGE	5556457	16	16	FLG WN 300# FF LTCS A350 LF2 CL.1 SCH 20	0	0	

	TENGIZCHEVROI TCO TENGIZ, KAZAKHSTAN	CONSTRUCTION	CORR.ALLOW.	SERVICE	MATERIAL	DATE	BY	REV	SHEET	PIPING LINE CLASS
		3/4" - 1" - SCREWED 1 1/2" -16" - VICTAULIC GROOVE & COUPLING 18" & ABOVE - GALV'D AFTER FABRICATION SEAL WELDING - NONE PIPE BENDS - NONE THREAD SEALANT - PTFE PASTE	CORR. ALLOW. 3 MM	DESIGN: 15.8 BARG CODE - ASME B31.3 FLUID CODES - PIM-SU-5112-TCO	MATERIAL: GALVANISED LTCS VICTAULIC COUPLINGS FLANGE RATING: 150 RF TEMPERATURE RANGE:- 40 / 110 °C	12/16/2024	BY OZAC	U04	Page 2 of 3	150VG01

SEQ NO	REV	NOTE NO.	ITEM NAME	ITEM CODE	SIZE RANGE / SMALL END SIZES		DESCRIPTION	REFERENCE / LARGE END SIZES		NOTES
1070	U04	ND9	BLIND	5615567	0.5	24	FLG BLIND 150# RF LTCS A350 LF2 CL.1 GALV A153	0	0	
1080	U04		BLIND	5615577	0.5	2	FLG BLIND 300# RF LTCS A350 LF2 CL.1 GALV A153	0	0	
1090	U04	ND9		5615575	36	36	FLG BLIND 150# RF LTCS A350 LF2 CL.1 GALV A153 B16.47 SERIES A	0	0	
1100										
1100	U04						***** FLANGES - VICTAULIC *****			
1110										
1110	U04		FLANGE	5754404	1.5	16	FLANGE ADAPTER NIPPLE 150# RF / GRV A352 GR LCC GALV	0	0	
1120	U04	FS1	FLANGE	5754407	1.5	14	FLANGE ADAPTER NIPPLE 150# FF / GRV A352 GR LCC GALV	0	0	
1130	U04	FS1	FLANGE	5754405	1.5	16	FLANGE ADAPTER NIPPLE 300# RF / GRV A352 GR LCC GALV	0	0	
1140	U04	FS1	FLANGE	5754408	2	16	FLANGE ADAPTER NIPPLE 300# FF / GRV A352 GR LCC GALV	0	0	
1150										
1150	U04						***** ORIFICE FLANGE *****			
1160										
1160	U04		ORIFICE FLG	5623959	18	24	WN ORIF SET 300# RF LTCS A350 LF2 CL.1 SCH 20 (FNPT TAP)	0	0	
1170										
1170	U04						***** PIPE NIPPLES *****			
1180										
1180	U04		NIPPLE	5541200	0.5	1.5	NIPPLE SCH 160 LTCS A333 GR.6 TBE 3" LG (MNPT) GALV A153	0	0	
1190	U04		NIPPLE	5541201	0.5	1	NIPPLE SCH 160 LTCS A333 GR.6 TBE 7" LG (MNPT) GALV A153	0	0	
1200	U04		NIPPLE	5541214	2	2	NIPPLE SCH XS LTCS A333 GR.6 TBE 3" LG (MNPT) GALV A153	0	0	
1210	U04		NIPPLE	5541202	1.5	2.5	NIPPLE SCH 160 LTCS A333-6 GRV/TOE (MNPT) 4" LG GALV A153	0	0	
1220										
1220	U04						***** SWAGE NIPPLES *****			
1230										
1230	U04		RED CONC	5544150	0.5	1	SWAGE CONC SCH 160 LTCS A420 WPL6 TBE (MNPT) GALV A153	1	1.5	
1240	U04		RED ECC	5549150	0.75	1	SWAGE ECC SCH 160 LTCS A420 WPL6 TBE (MNPT) GALV A153	1	1.5	
1250										
1250	U04						***** GASKETS *****			
1260										
1260	U04		GASKET	5673043	0.5	24	GASKET 150# 316SS SPIRAL WOUND GRAPHITE IIR	0	0	
1270	U04		GASKET	5674011	36	36	GASKET 150# 316SS KAMMPROFILE GRAPHITE ASME B16.47 SERIES A	0	0	
1280	U04	FS1	GASKET	5664562	1.5	14	GASKET 150# FF RING EPDM 3MM THK	0	0	
1290		FS1	GASKET	5664563	2	12	GASKET 300# FF RING EPDM 3MM THICK	0	0	
1300	U04	GA6	GASKET	5673017	2	3	GASKET 300# 316SS KAMMPROFILE GRAPHITE ASME B16.5	0	0	
1310		FS1	GASKET	5673033	0.5	24	GASKET 300# 316SS SPIRAL WOUND GRAPHITE IIR	0	0	
1320	U04	UG3	GASKET	5664201	2	24	GASKET 150# RF FLAT RING PTFE	0	0	
1330										
1330	U04						***** GASKETS - VICTAULIC *****			
1340	U04	B1					***** BOLTING *****			
1350										
1350	U04		BOLTING	5675770	0.5	99	STUD-BOLT A320 GR L7M/A194 GR 7M (S3) WITH 2 NUTS	0	0	
1360	U04	UG4	BOLTING	5675768	0.5	99	STUD-BOLT A320 GR L7M/A194 GR 7M (S3) W/ 2 NUTS + LTCS WASHERS	0	0	
1370										
1370	U04						***** BLINDS & SPACERS *****			
1380										
1380	U04		SPEC BLIND	5749582	0.75	14	SPECTACLE BLIND 150# RF LTCS A 516 GR.70 GALV A153	0	0	
1390	U04		SPEC BLIND	5749583	0.75	10	SPECTACLE BLIND 300# RF LTCS A516 GR.70 GALV A153	0	0	
1400										
1400		FS1	PADDLE	5749942	16	24	PADDLE BLANK 150# RF LTCS A516 GR.70 GALV A153	0	0	
1410		FS1	PADDLE	5750195	16	24	PADDLE SPACER 150# RF LTCS A516 GR.70 GALV A153	0	0	
1420	U04		PADDLE	5750025	36	36	PADDLE BLANK 150# RF LTCS A516 GR70 B16.47 SERIES A GALV A153	0	0	
1430	U04		PADDLE	5750194	36	36	PADDLE SPACER 150# RF LTCS A516 GR.70 B16.47 SERIES A GALV A153	0	0	
1440	U04		PADDLE	5749853	12	24	PADDLE BLANK 300# RF LTCS A516 GR.70 GALV A153	0	0	
1450	U04		PADDLE	5750201	12	24	PADDLE SPACER 300# RF LTCS A516-GR70 GALV A153	0	0	
1460										
1460	U04						*****TRUNNION SUPPORTS FOR PIPE SIZES 18" & ABOVE*****			
1470										
1470	U04	PS1	PIPE	5358505	10	10	PIPE SCH STD SMLS LTCS A333 GR.6 BE	0	0	
1480	U04	PS1	PIPE	5358502	12	12	PIPE SCH 30 SMLS LTCS A333 GR 6 BE	0	0	
1490	U04	PS1	PIPE	5358501	16	16	PIPE SCH 20 SMLS LTCS A333 GR.6 BE	0	0	
1500										
1500	U04						***** MISCELLANEOUS*****			
1510										
1510	U04		GASKET	5707599			LUBRICANT FOR GASKET PUSH-ON CI & DI			
1520										

	TENGIZCHEVROI TCO TENGIZ, KAZAKHSTAN	CONSTRUCTION	CORR.ALLOW.	SERVICE	MATERIAL	DATE	BY	REV	SHEET	PIPING LINE CLASS
		3/4" - 1" - SCREWED 1 1/2" - 16" - VICTAULIC GROOVE & COUPLING 18" & ABOVE - GALV'D AFTER FABRICATION SEAL WELDING - NONE PIPE BENDS - NONE THREAD SEALANT - PTFE PASTE	CORR. ALLOW. 3 MM	DESIGN: 15.8 BARG CODE - ASME B31.3 FLUID CODES - PIM-SU-5112-TCO	MATERIAL: GALVANISED LTCS VICTAULIC COUPLINGS FLANGE RATING: 150 RF TEMPERATURE RANGE: -40 / 110 °C	12/16/2024	BY OZAC	U04	Page 3 of 3	150VG01