

[illegible]

	TENGIZCHEVROIL TCO TENGIZ, KAZAKHSTAN	CONSTRUCTION	CORR.ALLOW.	SERVICE	MATERIAL	DATE	BY	REV	SHEET	PIPING LINE CLASS
		ALL SIZES - BUTT WELDED SEAL WELDING - FOR THREADED CONNECTIONS ONLY PIPE BENDS - NONE THREAD SEALANT - PTFE PASTE	CORR. ALLOW. 1 MM	SOUR SERVICE - NACE MR0175/ ISO 15156 DESIGN: ASME B16.5 MG 2.2 CODE: ASME B31.3 FLUID CODES - PIM-SU-5112-TCO	MATERIAL: 316/316L SS DUAL GRADE FLANGE RATING: 2500 RF/CF TEMPERATURE RANGE: -40 / 120°C	12/16/2024	BY OZAC	U04	Page 1 of 3	2500P1

SEQ NO	REV	NOTE NO.	ITEM NAME	ITEM CODE	SIZE RANGE / SMALL END SIZES		DESCRIPTION	REFERENCE / LARGE END SIZES		NOTES
490			TEE RED	5449063	0.75	1.5	TEE RED WT 12.7MM X SCH XXS SS A403 WP316/316L-S	2	2	
500			TEE RED	5449064	1.5	1.5	TEE RED WT 19.05MM X SCH XXS SS A403 WP316/316L-S	3	3	
510			TEE RED	5449065	2	2	TEE RED WT 19.05MM/WT 12.7 MM SS A403 WP316/316L-S	3	3	
520			TEE RED	5449098	3	3	TEE RED WT 22.0MM/WT 19.05 MM SS A403 WP316/316L-S	4	4	
530										
530			CAP	5449056	0.75	1.5	CAP SCH XXS SS A403 WP316/316L-S	0	0	
540			CAP	5449066	2	2	CAP WT 12.7MM SS A403 WP316/316L-S	0	0	
550			CAP	5449067	3	3	CAP WT 19.05MM SS A403 WP316/316L-S	0	0	
560			CAP	5449099	4	4	CAP WT 22.00MM SS A403 WP316/316L-S	0	0	
570										
570			RED CONC	5449181	0.75	1	REDUCER CONC SCH XXS SS A403 WP316/316L-S	1	1.5	
580			RED CONC	5449068	0.75	1.5	REDUCER CONC WT 12.7MM/SCH XXS SS A403 WP316/316L-S	2	2	
590			RED CONC	5449069	1.5	1.5	REDUCER CONC WT 19.05MM/SCH XXS SS A403 WP316/316L-S	3	3	
600			RED CONC	5392365	1.5	1.5	REDUCER CONC WT 22.0MM/ SCH XXS SS A403 WP316/316L-S	4	4	
610			RED CONC	5449070	2	2	REDUCER CONC WT 19.05MM/WT 12.7MM SS A403 WP316/316L-S	3	3	
620			RED CONC	5392349	2	2	REDUCER CONC WT 22.0MM/ 12.7MM SS A403 WP316/316L-S	4	4	
630			RED CONC	5449074	3	3	REDUCER CONC WT 22.0MM/19.05MM SS A403 WP316/316L-S	4	4	
640			RED ECC	5449186	0.75	1	REDUCER ECC SCH XXS SS A403 WP316/316L-S	1	1.5	
650			RED ECC	5449071	0.75	1.5	REDUCER ECC WT 12.7MM/SCH XXS SS A403 WP316/316L-S	2	2	
660			RED ECC	5449072	1.5	1.5	REDUCER ECC WT 19.05MM / SCH XXS SS A403 WP316/316L-S	3	3	
670			RED ECC	5449182	1.5	1.5	REDUCER ECC WT 22.0MM / SCH XXS SS A403 WP316/316L-S	4	4	
680	U04		RED ECC	5449073	2	2	REDUCER ECC WT 19.05MM / WT 12.7MM SS A403 WP316/316L-S	3	3	
690			RED ECC	5449188	2	2	REDUCER ECC WT 22.0MM / 12.7MM SS A403 WP316/316L-S	4	4	
700			RED ECC	5449075	3	3	REDUCER ECC WT 22.0MM / 19.05MM SS A403 WP316/316L-S	4	4	
710										
710							***** OLETS *****			
720										
720		UJ2	OLETS	5504575	0.75	1.5	NIPOFLANGE 2500# RTJ WT 12.7MM/ SCH XXS SS A182 F316/316L	2	2	
730		UJ2	OLETS	5504446	0.75	1.5	NIPOFLANGE 2500# RTJ WT 19.05 MM / SCH XXS SS A182 F316/316L	3	3	
740		UJ2	OLETS	5504447	0.75	1.5	NIPOFLANGE 2500# RTJ WT 22.00MM / SCH XXS SS A182 F316/316L	4	4	
750	U04		OLETS	5404478	0.75	1.5	NIPOFLANGE 2500# RTJ WT 19.05 MM / SCH XXS SS A182 F316/316L	3	3	
760	U04		OLETS	5404481	0.75	1.5	NIPOFLANGE 2500# RTJ WT 22.00MM / SCH XXS SS A182 F316/316L	4	4	
770										
770			OLETS	5509662	0.75	1	WELDOLET19.05MM WT/SCH XXS SS A182 F316/316L	3	3	
780										
780			OLETS	5509663	0.75	1.5	WELDOLET 22.00MM WT/SCH XXS SS A182 F316/316L	4	4	
790										
790		UJ2	ELBOFLG	5516452	1.5	1.5	ELBOFLANGE 2500# RTJ WT 12.7MM/ SCH XXS SS A182 F316/316L	2	2	
800		UJ2	ELBOFLG	5516446	1.5	1.5	ELBOFLANGE 2500# RTJ WT 19.05MM / SCH XXS SS A182 F316/316L	3	3	
810		UJ2	ELBOFLG	5516447	1.5	1.5	ELBOFLANGE 2500# RTJ WT 22.00MM / SCH XXS SS A182 F316/316L	4	4	
820										
820		816					***** FLANGES *****			
830										
830			FLANGE	5584166	0.75	1.5	FLG WN 2500# RTJ SS A182 F316/316L SCH XXS	0	0	
840			FLANGE	5584170	2	2	FLG WN 2500# RTJ SS A182 F316/316L WT 12.7MM	0	0	
850			FLANGE	5584171	3	3	FLG WN 2500# RTJ SS A182 F316/316L WT 19.05MM	0	0	
860	U04	817	FLANGE	5619863	3	3	FLG COMPACT 2500# RJ SS A182 F316/316L WT 19.05MM	0	0	
870	U04	817	FLANGE	5619864	4	4	FLG COMPACT 2500# RJ SS A182 F316/316L WT 22.0MM	0	0	
880			FLANGE	5584174	3	3	FLG WN 2500# RF SS A182 F316/316L WT 19.05MM	0	0	
890			FLANGE	5584175	4	4	FLG WN 2500# RF SS A182 F316/316L WT 22.0MM	0	0	
900		FA8	TEE RED	5599830	0.5	0.5	FLG SCRDR (FNPT) REDUCING 2500# RTJ SS A182 F316/316L	0.75	0.75	
910										
910			FLANGE	5851202	0.75	0.75	FLANGE ADAPTER 2500# RTJ 316 SS X 12 MM TUBE	0	0	
920			FLANGE	5851202	2	2	FLANGE ADAPTER 2500# RTJ 316 SS X 12 MM TUBE	0	0	
930										
930			BLIND	5616574	0.5	4	FLG BLIND 2500# RF SS A182 316/316L	0	0	
940			BLIND	5616570	0.75	2	FLG BLIND 2500# RTJ SS A182 316/316L	0	0	
950	U04	817	BLIND	5619797	3	4	FLG COMPACT BLIND 2500# RJ SS A182 316/316L PIPE CLASS 2500P1	0	0	
960										
960							***** GASKETS *****			
970										
970			GASKET	5672272	0.5	4	GASKET 2500# 316SS SPIRAL WOUND GRAPHITE IR MANUFACTURERS STANDARD	0	0	
980	U04		GASKET	5674480	3	3	GASKET 2500# RTJ SS OCTAGONAL RING	0	0	
990			GASKET	5674480	0.5	2	GASKET 2500# RTJ SS OCTAGONAL RING	0	0	
1000	U04	817	GASKET	5673530	3	4	GASKET 2500# RJ INC 718 ENERGIZED SEALRING COMPACT FLANGE PIPE CLASS 2500P1	0	0	
1010										
1010		B1					***** BOLTING *****			
1020										
1020	U04		BOLTING	5675770	0.5	4	STUD-BOLT A320 GR L7M/A194 GR 7M (S3) WITH 2 NUTS	0	0	
1030										
1030							***** BLINDS & SPACERS *****			
1040										
1040			SPEC BLIND	5749514	3	4	SPECTACLE BLIND 2500# RF SS A240 GR 316	0	0	

	TENGIZCHEVROIL TCO TENGIZ, KAZAKHSTAN	CONSTRUCTION	CORR.ALLOW.	SERVICE	MATERIAL	DATE	BY	REV	SHEET	PIPING LINE CLASS
		ALL SIZES - BUTT WELDED SEAL WELDING - FOR THREADED CONNECTIONS ONLY PIPE BENDS - NONE THREAD SEALANT - PTFE PASTE	CORR. ALLOW. 1 MM	SOUR SERVICE - NACE MR0175/ ISO 15156 DESIGN: ASME B16.5 MG 2.2 CODE: ASME B31.3 FLUID CODES - PIM-SU-5112-TCO	MATERIAL: 316/316L SS DUAL GRADE FLANGE RATING: 2500 RF/CF TEMPERATURE RANGE: -40 / 120°C	12/16/2024	BY OZAC	U04	Page 2 of 3	2500P1

SEQ NO	REV	NOTE NO.	ITEM NAME	ITEM CODE	SIZE RANGE / SMALL END SIZES		DESCRIPTION	REFERENCE / LARGE END SIZES		NOTES
1050			SPEC BLIND	5749592	1	2	SPECTACLE BLIND 2500# RTJ SS A240 GR 316	0	0	
1060			SPEC BLIND	5749592	3	3	SPECTACLE BLIND 2500# RTJ SS A240 GR 316	0	0	
1070	U04	817	SPEC BLIND	5749573	3	3	SPECTACLE BLIND COMPACT 2500# RJ SS A240 GR 316	0	0	
1080										
1080	U04	817	PADDLE	5407808	3	3	PADDLE BLANK COMPACT 2500# RJ SS A240 GR 316	0	0	
1090	U04	817	PADDLE	5407807	3	3	PADDLE SPACER COMPACT 2500# RJ SS A240 GR 316	0	0	
1100										

	TENGIZCHEVROI TCO TENGIZ, KAZAKHSTAN	CONSTRUCTION	CORR.ALLOW.	SERVICE	MATERIAL	DATE	BY	REV	SHEET	PIPING LINE CLASS
		ALL SIZES - BUTT WELDED SEAL WELDING - FOR THREADED CONNECTIONS ONLY PIPE BENDS - NONE THREAD SEALANT - PTFE PASTE	CORR. ALLOW. 1 MM	SOUR SERVICE - NACE MR0175/ ISO 15156 DESIGN: ASME B16.5 MG 2.2 CODE: ASME B31.3 FLUID CODES - PIM-SU-5112-TCO	MATERIAL: 316/316L SS DUAL GRADE FLANGE RATING: 2500 RF/CF TEMPERATURE RANGE: -40 / 120°C	12/16/2024	BY OZAC	U04	Page 3 of 3	2500P1