

SEQ NO	REV	NOTE NO.	ITEM NAME	ITEM CODE	SIZE RANGE / SMALL END SIZES		DESCRIPTION	REFERENCE / LARGE END SIZES		NOTES
10							***** VALVES*****			812 NIPPLE TO BE CUT FROM SS SCH XXS PIPE.
20										B1 ALL BOLTS ARE METRIC DIA.
20							***** MODULAR VALVES *****			B2 7/8" X 145MM BOLTS ONLY TO BE USED FOR 1
30										INCH 1500# PERAR BALL VALVES ITEM CODE
30	U04	ND9	MODULAR DBB	M03AC02	1	1	MODULAR VALVE DB&B BALL TYPE 300# RF LTCS A350 LF2 CL.1 316 SS TRIM METAL LO - CONTROLLED BORE TYPE 2BVR	0	0	B15AM10
40										B6 7/8" X 145MM BOLTS ONLY TO BE USED FOR 1
40		VB2					***** BALL VALVES *****			INCH 1500# PERAR BALL VALVES ITEM CODE
50										B15AS22
50	U04		BALL	A03AC01	3	4	BALL 300# RF LTCS A350 LF2 CL.1 316SS TRIM FLOATING SOFT RB LO	0	0	FA8 USE THREADED FLANGES FOR INSTRUMENT
60	U04		BALL	A03AC02	3	4	BALL 300# RF LTCS A350 LF2 CL.1 316SS TRIM FLOATING METAL RB LO	0	0	CONNECTIONS ONLY.
70	U04		BALL	A03AC07	6	8	BALL 300# RF LTCS A350 LF2 CL.1 316SS TRIM TRUNNION SOFT RB GO	0	0	FF5 FLAT BOTTOM NIPOFLANGES FOR USE ON
80	U04		BALL	A03AC08	6	8	BALL 300# RF LTCS A350 LF2 CL.1 316SS TRIM TRUNNION METAL RB GO	0	0	WELD CAPS AND BLIND FLANGES
90	U04		BALL	B03AC01	0.5	2	BALL 300# RF LTCS A350 LF2 CL.1 316SS TRIM FLOATING SOFT FB LO	0	0	GA6 SPECIAL GASKET ONLY FOR USE AS SPECIFIED
100	U04	VA5	BALL	B03AC01	3	3	BALL 300# RF LTCS A350 LF2 CL.1 316SS TRIM FLOATING SOFT FB LO	0	0	IN ENG-200-117
110	U04		BALL	B03AC02	0.5	2	BALL 300# RF LTCS A350 LF2 CL.1 316SS TRIM FLOATING METAL FB LO	0	0	ND9 USE ONLY WITH CONSENT OF MATERIALS
120	U04	VA5	BALL	B03AC02	3	3	BALL 300# RF LTCS A350 LF2 CL.1 316SS TRIM FLOATING METAL FB LO	0	0	ENGINEER.
130	U04	VA5	BALL	B03AC03	4	4	BALL 300# RF LTCS A350 LF2 CL.1 316SS TRIM FLOATING SOFT FB LO	0	0	SB6 USE JACKSCREWS FOR PADDLE
140	U04	VA5	BALL	B03AC04	4	4	BALL 300# RF LTCS A350 LF2 CL.1 316SS TRIM FLOATING METAL FB LO	0	0	BLANKS/SPACERS AND FLANGE SPREADERS
150	U04	VA5	BALL	B03AC07	6	24	BALL 300# RF LTCS A350 LF2 CL.1 316SS TRIM TRUNNION SOFT FB GO	0	0	FOR SPECTACLE BLINDS.
160	U04	VA5	BALL	B03AC08	6	24	BALL 300# RF LTCS A350 LF2 CL.1 316SS TRIM TRUNNION METAL FB GO	0	0	UD6 USE FOR UNVALVED CAPPED HYDROSTATIC
170										TEST VENTS AND DRAINS. SEAL WELD AFTER
170							***** BUTTERFLY VALVES *****			HYDROSTATIC TEST.
180			BUTTERFLY	T03AC61	10	24	BUTTERFLY 300# RF LTCS A352 LCC 316SS TRIM TOV METAL DBL FLG SHORT PAT GO	0	0	UD7 USE THREDOLET AND SCREWED PLUG FOR
180										HYDROSTATIC TEST VENTS AND DRAINS. SEAL
190							***** GATE VALES*****			WELD AFTER HYDROSTATIC TEST
190										USE 1 1/2IN WITH THERMOWELL
200	U04		GATE	G03AC48	0.5	1.5	GATE 300# RF LTCS A350 LF2 CL.1 TRIM 16 WEDGE HW	0	0	UJ2 CONNECTIONS ONLY & 3/4IN (IF SHOWN) FOR
210			GATE	G03AC41	2	8	GATE 300# RF LTCS A352 LCC TRIM 16 WEDGE HW	0	0	DBB PRESSURE CONNECTIONS WITH
220							***** GLOBE VALVES *****			CHEMICAL SEALS.
220										DO NOT USE FOR ORIFICE FLANGE TAP
230										ASSEMBLIES.
230	U04		GLOBE	L03AC48	0.75	1.5	GLOBE 300# RF LTCS A350 LF2 CL.1 TRIM 16 OS&Y HW	0	0	VA5 USE THESE VALVES ONLY WHERE SPECIFIED
240			GLOBE	L03AC41	2	6	GLOBE 300# RF LTCS A352 LCC TRIM 16 OS&Y HW	0	0	ON PIPING AND INSTRUMENT DIAGRAMS
250			GLOBE	L03AC42	8	10	GLOBE 300# RF LTCS A352 LCC TRIM 16 OS&Y GO	0	0	VB2 SOFT SEATED BALL VALVES ARE LIMITED TO
260										MAXIMUM TEMPERATURE OF 200°C.
260							***** CHECK VALVES *****			VC1 SPRING PISTON CHECK VALVES ARE PREFERED
270	U04	VC1	CHECK	C03AC50	0.5	1.5	CHECK PISTON 300# RF LTCS A350 LF2 CL.1 TRIM 16	0	0	IN THE HORIZONTAL POSITION, BUT MAY BE
280			CHECK	C03AC45	2	10	CHECK DUAL WAFER LUG 300# RF LTCS A352 LCC TRIM 16 THROU BOLTED	0	0	USED IN THE VERTICAL POSITION WITH
290			CHECK	C03AC52	12	24	CHECK DUAL DBL FLG 300# RF LTCS A352 LCC TRIM 16	0	0	ENGINEERING APPROVAL.
300							***** PIPES*****			
300										
310			PIPE	5358512	0.75	0.75	PIPE SCH 160 SMLS LTCS A333 GR.6 PE	0	0	
320			PIPE	5358508	1	1.5	PIPE SCH XS SMLS LTCS A333 GR.6 PE	0	0	
330			PIPE	5358514	2	2	PIPE SCH XS SMLS LTCS A333 GR.6 BE	0	0	
340			PIPE	5358514	10	14	PIPE SCH XS SMLS LTCS A333 GR.6 BE	0	0	
350			PIPE	5358505	3	8	PIPE SCH STD SMLS LTCS A333 GR.6 BE	0	0	
360			PIPE	5358504	16	16	PIPE SCH 40 SMLS LTCS A333GR.6 BE	0	0	
370			PIPE	5358598	18	24	PIPE SCH 40 EFW LTCS A671 C060 CL.22 BE	0	0	
380	U04	UK9	PIPE	5358511	0.5	0.75	PIPE SCH XXS SMLS LTCS A333 GR.6 PE	0	0	
390							***** FITTINGS*****			
390										
400	U04		ELBOW	5392816	0.5	0.75	ELL BW 90 DEG LR SCH 160 LTCS A420 WPL6	0	0	
410	U04	UK9	ELBOW	5392815	0.5	0.75	ELL BW 90 DEG LR SCH XXS LTCS A420 WPL6	0	0	
420			ELBOW	5392600	1	2	ELL BW 90 DEG LR SCH XS LTCS A420 WPL6	0	0	
430			ELBOW	5392600	10	14	ELL BW 90 DEG LR SCH XS LTCS A420 WPL6	0	0	
440			ELBOW	5392438	3	8	ELL BW 90 DEG LR SCH STD LTCS A420 WPL6	0	0	
450			ELBOW	5392384	16	16	ELL 90 DEG LR SCH 40 LTCS A420 WPL6	0	0	
460			ELBOW	5392386	18	24	ELL 90 DEG LR SCH 40 LTCS A420 WPL6-W	0	0	
470			ELBOW	5392822	0.75	0.75	ELL BW 45 DEG LR SCH 160 LTCS A420 WPL6	0	0	
480	U04	UK9	ELBOW	5392831	0.5	0.75	ELL BW 45 DEG LR SCH XXS LTCS A420 WPL6	0	0	
490			ELBOW	5392606	1	2	ELL BW 45 DEG LR SCH XS LTCS A420 WPL6	0	0	
500			ELBOW	5392606	10	14	ELL BW 45 DEG LR SCH XS LTCS A420 WPL6	0	0	
510			ELBOW	5392444	3	8	ELL BW 45 DEG LR SCH STD LTCS A420 WPL6	0	0	
520			ELBOW	5392390	16	16	ELL 45 SCH 40 LTCS A420 WPL6	0	0	
530			ELBOW	5392389	18	24	ELL 45 DEG SCH 40 LTCS A420 WPL6 -W	0	0	
540	U04		ELBOW	5478803	0.75	1.5	ELL 90 DEG 6000# SW LTCS A350 LF2 CL.1	0	0	
550	U04		ELBOW	5478804	0.75	1.5	ELL 45 DEG 6000# SW LTCS A350 LF2 CL.1	0	0	
560										

	TENGIZCHEVROI TCO TENGIZ, KAZAKHSTAN	CONSTRUCTION	CORR.ALLOW.	SERVICE	MATERIAL	DATE	BY	REV	SHEET	PIPING LINE CLASS
		ALL SIZES - BUTT WELD PWHT FOR WT > 19 MM SEAL WELDING - FOR THREADED CONNECTIONS ONLY PIPE BENDS - NONE THREAD SEALANT - PTFE PASTE	CORR. ALLOW. 3 MM	SOUR SERVICE - NACE MR0175/ ISO 15156 DESIGN: ASME B16.5 MG 1.1 CODE: ASME B31.3 FLUID CODES - PIM-SU-5112-TCO	MATERIAL: LTCS FLANGE RATING: 300 RF TEMPERATURE RANGE: -40 / 343 °C	12/16/2024	BY OZAC	U04	Page 1 of 4	300H25

SEQ NO	REV	NOTE NO.	ITEM NAME	ITEM CODE	SIZE RANGE / SMALL END SIZES		DESCRIPTION	REFERENCE / LARGE END SIZES		NOTES
560	U04		TEE	5478805	0.75	1.5	TEE 6000# SW LTCS A350 LF2 CL.1	0	0	
570	U04		TEE RED	5478811	0.75	1	TEE RED 6000# SW LTCS A350 LF2 CL.1	1	1.5	
580										
580	U04	UD6	CAP	5491312	0.75	1	CAP 3000# SCRD LTCS A350 LF2 CL.1	0	0	
590	U04		CAP	5478806	0.75	1.5	CAP 6000# SW LTCS A350 LF2 CL.1	0	0	
600										
600							***** OLETS *****			
610										
610	U04		OLETS	5533071	0.75	1.5	SOCKOLET 6000# LTCS A350 LF2 CL.1	2	24	
620	U04		OLETS	5533233	0.75	1.5	SOCKOLET FLAT BOTTOM 6000# LTCS A350 LF2 CL.1	0	0	
630										
630	U04	UD7	OLETS	5514772	0.75	1	THREDOLET 3000# LTCS A350 LF2 CL.1	2	24	
640										
640							***** COUPLINGS, UNIONS & PLUGS *****			
650										
650	U04		COUPLING	5478807	0.75	1.5	COUPLING 6000# SW LTCS A350 LF2 CL.1	0	0	
660	U04		TEE RED	5478812	0.75	1	COUPLING RED 6000# SW LTCS A350 LF2 CL.1	1	1.5	
670										
670	U04		UNION	5478809	0.75	1.5	UNION 6000# SW LTCS STL A350 LF2 CL.1	0	0	
680										
680	U04	UD7	FITTING SCRD	5491303	0.75	1	PLUG ROUND HEAD SCRD LTCS A350 LF2 CL.1	0	0	
690										
690			TEE	5392825	0.5	0.75	TEE BW SCH 160 LTCS A420 WPL6	0	0	
700			TEE	5392609	1	2	TEE BW SCH XS LTCS A420 WPL6	0	0	
710			TEE	5392609	10	14	TEE BW SCH XS LTCS A420 WPL6	0	0	
720	U04	UK9	TEE	5392879	0.5	0.75	TEE SCH XXS LTCS A420 WPL6	0	0	
730			TEE	5392447	3	8	TEE BW SCH STD LTCS A420 WPL6	0	0	
740			TEE	5392393	16	16	TEE SCH 40 LTCS A420 WPL6	0	0	
750			TEE	5392400	18	24	TEE SCH 40 LTCS A420 WPL6-W	0	0	
760			TEE RED	5392469	0.75	0.75	TEE RED BW SCH XS/160 LTCS A420 WPL6	1	1.5	
770			TEE RED	5392661	1	1.5	TEE RED BW SCH XS LTCS A420 WPL6	1.5	2	
780			TEE RED	5392661	10	12	TEE RED BW SCH XS LTCS A420 WPL6	12	14	
790			TEE RED	5392454	1.5	2	TEE RED BW SCH STD/XS LTCS A420 WPL6	3	4	
800			TEE RED	5392445	3	6	TEE RED BW SCH STD LTCS A420 WPL6	4	8	
810			TEE RED	5392460	4	8	TEE RED BW SCH XS/STD LTCS A420 WPL6	10	14	
820			TEE RED	5392293	6	8	TEE RED SCH 40/STD LTCS A420 WPL6	16	16	
830			TEE RED	5392299	8	8	TEE RED SCH 40/STD LTCS A420 WPL6-W	18	20	
840			TEE RED	5392294	10	14	TEE RED SCH 40/XS LTCS A420 WPL6	16	16	
850			TEE RED	5392304	10	14	TEE RED BW SCH 40/XS LTCS A420 WPL6-W	18	24	
860			TEE RED	5392474	16	20	TEE RED SCH 40 LTCS A420 WPL6-W	18	24	
870										
870			CAP	5392826	0.75	0.75	CAP BW SCH 160 LTCS A420 WPL6	0	0	
880			CAP	5392610	1	2	CAP BW SCH XS LTCS A420 WPL6	0	0	
890			CAP	5392610	10	14	CAP BW SCH XS LTCS A420 WPL6	0	0	
900			CAP	5392448	3	8	CAP BW SCH STD LTCS A420 WPL6	0	0	
910			CAP	5392394	16	24	CAP SCH 40 LTCS STL A420 WPL6	0	0	
920										
920			RED CONC	5392462	0.75	0.75	REDUCER CONC SCH XS/160 LTCS A420 WPL6	1	2	
930			RED CONC	5392458	1	1.5	REDUCER CONC SCH XS LTCS A420 WPL6	1.5	2	
940			RED CONC	5392458	10	12	REDUCER CONC SCH XS LTCS A420 WPL6	12	14	
950			RED CONC	5392452	1.5	2	REDUCER CONC SCH STD/XS LTCS A420 WPL6	3	4	
960			RED CONC	5392449	3	6	REDUCER CONC SCH STD LTCS A420 WPL6	4	8	
970			RED CONC	5392457	4	8	REDUCER CONC SCH XS/STD LTCS A420 WPL6	10	14	
980			RED CONC	5392300	8	8	REDUCER CONC SCH 40/STD LTCS A420 WPL6	16	16	
990			RED CONC	5392305	10	14	REDUCER CONC SCH 40/XS LTCS A420 WPL6	16	16	
1000			RED CONC	5392306	10	14	REDUCER CONC SCH 40/XS LTCS A420 WPL6-W	18	20	
1010			RED CONC	5392395	16	20	REDUCER CONC SCH 40 LTCS A420 WPL6-W	18	24	
1020			RED ECC	5392465	0.75	0.75	REDUCER ECC SCH XS/160 LTCS A420 WPL6	1	2	
1030			RED ECC	5392461	1	1.5	REDUCER ECC SCH XS LTCS A420 WPL6	1.5	2	
1040			RED ECC	5392461	10	12	REDUCER ECC SCH XS LTCS A420 WPL6	12	14	
1050			RED ECC	5392453	1.5	2	REDUCER ECC SCH STD/XS LTCS A420 WPL6	3	4	
1060			RED ECC	5392450	3	6	REDUCER ECC SCH STD LTCS A420 WPL6	4	8	
1070			RED ECC	5392459	4	8	REDUCER ECC SCH XS/STD LTCS A420 WPL6	10	14	
1080			RED ECC	5392302	8	8	REDUCER ECC SCH 40/STD LTCS A420 WPL6	16	16	
1090			RED ECC	5392307	10	14	REDUCER ECC SCH 40/XS LTCS A420 WPL6	16	16	
1100			RED ECC	5392264	10	14	REDUCER ECC SCH 40/XS LTCS A420 WPL6-W	18	20	
1110			RED ECC	5392396	16	20	REDUCER ECC SCH 40 LTCS A420 WPL6-W	18	24	
1120										
1120	U04		OLETS	5504450	0.75	0.75	NIPOFLANGE 300# RF SCH XS/160 LTCS A350 LF2 CL.1	2	2	
1130	U04		OLETS	5504450	0.75	0.75	NIPOFLANGE 300# RF SCH XS/160 LTCS A350 LF2 CL.1	10	14	
1140	U04		OLETS	5504020	1	1.5	NIPOFLANGE 300# RF SCH XS LTCS A350 LF2 CL.1	2	2	
1150	U04		OLETS	5504020	1	2	NIPOFLANGE 300# RF SCH XS LTCS A350 LF2 CL.1	10	14	
1160	U04		OLETS	5504451	0.75	0.75	NIPOFLANGE 300# RF SCH STD/SCH 160 LTCS A350 LF2 CL.1	3	8	

	TENGIZCHEVROI TCO TENGIZ, KAZAKHSTAN	CONSTRUCTION	CORR.ALLOW.	SERVICE	MATERIAL	DATE	BY	REV	SHEET	PIPING LINE CLASS
		ALL SIZES - BUTT WELD PWHT FOR WT > 19 MM SEAL WELDING - FOR THREADED CONNECTIONS ONLY PIPE BENDS - NONE THREAD SEALANT - PTFE PASTE	CORR. ALLOW. 3 MM	SOUR SERVICE - NACE MR0175/ ISO 15156 DESIGN: ASME B16.5 MG 1.1 CODE: ASME B31.3 FLUID CODES - PIM-SU-5112-TCO	MATERIAL: LTCS FLANGE RATING: 300 RF TEMPERATURE RANGE: -40 / 343 °C	12/16/2024	BY OZAC	U04	Page 2 of 4	300H25

SEQ NO	REV	NOTE NO.	ITEM NAME	ITEM CODE	SIZE RANGE / SMALL END SIZES		DESCRIPTION	REFERENCE / LARGE END SIZES		NOTES
1170	U04		OLETS	5504021	1	2	NIPOFLANGE 300# RF SCH STD/XS LTCS A350 LF2 CL.1	3	8	
1180	U04		OLETS	5504452	0.75	0.75	NIPOFLANGE 300# RF SCH 40/160 LTCS A350 LF2 CL.1	16	24	
1190	U04		OLETS	5504022	1	2	NIPOFLANGE 300# RF SCH 40/XS LTCS A350 LF2 CL.1	16	24	
1200	U04	UJ2	OLETS	5504025	1.5	1.5	NIPOFLANGE 300# RF SCH STD/160 LTCS A350 LF2 CL.1	4	8	
1210	U04	UJ2	OLETS	5504023	1.5	1.5	NIPOFLANGE 300# RF SCH XS/160 LTCS A350 LF2 CL.1	10	14	
1220	U04	UJ2	OLETS	5504018	1.5	1.5	NIPOFLANGE 300# RF SCH 40/160 LTCS A350 LF2 CL.1	16	24	
1230	U04	FF5	OLETS	5504515	0.75	0.75	NIPOFLANGE FLAT BOTTOM 300# RF SCH 160 LTCS A350 LF2 CL.1	0	0	
1240										
1240	U04		OLETS	5505393	0.75	0.75	WELDOLET SCH XS/160 LTCS A350 LF2 CL.1	2	2	
1250	U04		OLETS	5505393	0.75	0.75	WELDOLET SCH XS/160 LTCS A350 LF2 CL.1	10	14	
1260	U04		OLETS	5505192	0.75	0.75	WELDOLET STD/160 LTCS A350 LF2 CL.1	3	8	
1270	U04		OLETS	5505333	1	1	WELDOLET SCH XS LTCS A350 LF2 CL.1	2	2	
1280	U04		OLETS	5505591	0.75	0.75	WELDOLET SCH 40/ SCH 160 LTCS A350 LF2 CL.1	16	24	
1290	U04		OLETS	5505179	1	2	WELDOLET SCH STD/XS LTCS A350 LF2 CL.1	3	8	
1300	U04		OLETS	5505335	1	2	WELDOLET SCH XS LTCS A350 LF2 CL.1	10	14	
1310	U04		OLETS	5505574	1	2	WELDOLET SCH 40/XS LTCS A350 LF2 CL.1	16	24	
1320	U04		OLETS	5505164	3	3	WELDOLET SCH STD LTCS A350 LF2 CL.1	8	8	
1330	U04		OLETS	5505334	3	4	WELDOLET SCH XS/STD LTCS A350 LF2 CL.1	10	14	
1340	U04		OLETS	5505554	3	8	WELDOLET SCH 40/STD LTCS A350 LF2 CL.1	16	24	
1350	U04		OLETS	5504374	1	1	WELDOLET FLAT BOTTOM SCH XS LTCS A350 LF2 CL.1	0	0	
1360										
1360	U04	UJ2	ELBOFLG	5516625	1.5	1.5	ELBOFLANGE 300# RF SCH STD/160 LTCS A350 LF2 CL.1	4	8	
1370	U04	UJ2	ELBOFLG	5516623	1.5	1.5	ELBOFLANGE 300# RF SCH XS/160 LTCS A350 LF2 CL.1	10	14	
1380	U04	UJ2	ELBOFLG	5516618	1.5	1.5	ELBOFLANGE 300# RF SCH 40/160 LTCS A350 LF2 CL.1	16	24	
1390										
1390							***** FLANGES *****			
1400										
1400	U04	FA8	FLANGE	5599703	0.5	0.5	FLG SCRDR (FNPT) REDUCING 300# RF LTCS A350 LF2 CL.1	0.75	2	
1410	U04		FLANGE	5556480	0.5	0.75	FLG WN 300# RF LTCS A350 LF2 CL.1 SCH 160	0	0	
1420	U04		FLANGE	5556476	1	2	FLG WN 300# RF LTCS A350 LF2 CL.1 SCH XS	0	0	
1430	U04		FLANGE	5556476	10	14	FLG WN 300# RF LTCS A350 LF2 CL.1 SCH XS	0	0	
1440	U04		FLANGE	5556473	3	8	FLG WN 300# RF LTCS A350 LF2 CL.1 SCH STD	0	0	
1450	U04		FLANGE	5556472	16	24	FLG WN 300# RF LTCS A350 LF2 CL.1 SCH 40 BORE	0	0	
1460	U04		FLANGE	5557141	10	10	FLG WN 900# RF LTCS A350 LF2 CL.1 SCH XS	0	0	
1470	U04		FLANGE	5557397	0.75	0.75	FLG WN 1500# RF LTCS A350 LF2 CL.1 SCH 160 BORE	0	0	
1480	U04		FLANGE	5557393	2	2	FLG WN 1500# RF LTCS A350 LF2 CL.1 SCH XS	0	0	
1490	U04		FLANGE	5557036	6	6	FLG WN 600# RF LTCS A350 LF2 CL.1 SCH XS	0	0	
1500	U04		FLANGE	5555935	3	3	FLG WN 900# RF LTCS A350 LF2 CL.1 SCH STD	0	0	
1510	U04		BLIND	5615576	0.5	24	FLG BLIND 300# RF LTCS A350 LF2 CL.1	0	0	
1520										
1520			FLANGE	5851203	0.5	3	FLANGE ADAPTER 300# RF 316 SS X 12 MM TUBE	0	0	
1530										
1530							***** ORIFICE FLANGES *****			
1540										
1540	U04		ORIFICE FLG	5623947	2	2	WN ORIF SET 300# RF LTCS A350 LF2 CL.1 SCH XS	0	0	
1550	U04		ORIFICE FLG	5623947	10	14	WN ORIF SET 300# RF LTCS A350 LF2 CL.1 SCH XS	0	0	
1560	U04		ORIFICE FLG	5623944	3	8	WN ORIF SET 300# RF LTCS A350 LF2 CL.1 SCH STD	0	0	
1570	U04		ORIFICE FLG	5623943	16	24	WN ORIF SET 300# RF LTCS A350 LF2 CL.1 SCH 40	0	0	
1580										
1580							***** PIPE NIPPLES *****			
1590										
1590		812		0			NIPPLE PBETO BE CUT FROM PIPE			
1600	U04	812					NIPPLE PBETO BE CUT FROM PIPE			
1610										
1610							***** GASKETS *****			
1620										
1620			GASKET	5673033	0.5	24	GASKET 300# 316SS SP WOUND GRAPHITE IR	0	0	
1630	U04		GASKET	5673117	3	3	GASKET 900# 316SS SPIRAL WOUND GRAPHITE IR	0	0	
1640			GASKET	5673117	10	10	GASKET 900# 316SS SPIRAL WOUND GRAPHITE IR	0	0	
1650	U04		GASKET	5672251	0.75	0.75	GASKET 1500# 316SS SPIRAL WOUND GRAPHITE IR	0	0	
1660	U04		GASKET	5672251	2	2	GASKET 1500# 316SS SPIRAL WOUND GRAPHITE IR	0	0	
1670	U04	GA6	GASKET	5673017	2	3	GASKET 300# 316SS KAMMPROFILE GRAPHITE ASME B16.5	0	0	
1680	U04		GASKET	5673103	6	6	GASKET 600# 316SS SPIRAL WOUND GRAPHITE IR	0	0	
1690										
1690		B1					***** BOLTING *****			
1700										
1700	U04		BOLTING	5675770	0.5	99	STUD-BOLT A320 GR L7M/A194 GR 7M (S3) WITH 2 NUTS	0	0	
1710										
1710		SB6	BOLTING	5675675	12	24	JACK SCREW HEX HEAD A320 GR L7M	0	0	
1720										
1720							***** BLINDS & SPACERS *****			
1730										
1730			SPEC BLIND	5749581	0.75	10	SPECTACLE BLIND 300# RF LTCS A516 GR.70	0	0	

	TENGIZCHEVROIL TCO TENGIZ, KAZAKHSTAN	CONSTRUCTION	CORR.ALLOW.	SERVICE	MATERIAL	DATE	BY	REV	SHEET	PIPING LINE CLASS
		ALL SIZES - BUTT WELD PWHT FOR WT > 19 MM SEAL WELDING - FOR THREADED CONNECTIONS ONLY PIPE BENDS - NONE THREAD SEALANT - PTFE PASTE	CORR. ALLOW. 3 MM	SOUR SERVICE - NACE MR0175/ ISO 15156 DESIGN: ASME B16.5 MG 1.1 CODE: ASME B31.3 FLUID CODES - PIM-SU-5112-TCO	MATERIAL: LTCS FLANGE RATING: 300 RF TEMPERATURE RANGE: -40 / 343 °C	12/16/2024	BY OZAC	U04	Page 3 of 4	300H25

SEQ NO	REV	NOTE NO.	ITEM NAME	ITEM CODE	SIZE RANGE / SMALL END SIZES		DESCRIPTION	REFERENCE / LARGE END SIZES		NOTES
1740										
1740			PADDLE	5750100	12	24	PADDLE BLANK 300# RF LTCS A516 GR.70	0	0	
1750			PADDLE	5750200	12	24	PADDLE SPACER 300# RF LTCS A516 GR.70	0	0	
1760										
1770										
1770							*****MISCELLANEOUS*****			
1780										
1780	U04		FLG GUARD	5558882	0.75	10	SAFETY SHIELD PTFE SUITABLE FOR 300# FLANGE	0	0	

	TENGIZCHEVROIL TCO TENGIZ, KAZAKHSTAN	CONSTRUCTION	CORR.ALLOW.	SERVICE	MATERIAL	DATE	BY	REV	SHEET	PIPING LINE CLASS
		ALL SIZES - BUTT WELD PWHT FOR WT > 19 MM SEAL WELDING - FOR THREADED CONNECTIONS ONLY PIPE BENDS - NONE THREAD SEALANT - PTFE PASTE	CORR. ALLOW. 3 MM	SOUR SERVICE - NACE MR0175/ ISO 15156 DESIGN: ASME B16.5 MG 1.1 CODE: ASME B31.3 FLUID CODES - PIM-SU-5112-TCO	MATERIAL: LTCS FLANGE RATING: 300 RF TEMPERATURE RANGE: -40 / 343 °C	12/16/2024	BY OZAC	U04	Page 4 of 4	300H25