

SEQ NO	REV	NOTE NO.	ITEM NAME	ITEM CODE	SIZE RANGE / SMALL END SIZES		DESCRIPTION	REFERENCE / LARGE END SIZES		NOTES	
10							*****VALVES*****			B1 FA8	ALL BOLTS ARE METRIC DIA. USE THREADED FLANGES FOR INSTRUMENT CONNECTIONS ONLY.
20							***** MODULAR VALVES *****				
20											
30			MODULAR DBB	M03AM10	0.75	2	MODULAR VALVE DB&B BALL TYPE 300# RF INC 825 INC TRIM 625 METAL LO - CONTROLLED BORE TYPE 2BVR	0	0		
40											
40							***** BALL VALVES *****				
50											
50			BALL	B03AM10	0.75	1.5	BALL 300# RF INC 825 INC 625 TRIM FLOATING METAL FB LO	0	0		
60			BALL	A03AM10	2	2	BALL 300# RF INC 825 INC TRIM 625 FLOATING METAL RB LO	0	0		
70			BALL	A03AR16	6	8	BALL 300# RF LTCS + CLAD INC 825 INC 625 TRIM TRUNNIION METAL RB GO	0	0		
80											
80							***** THROUGH CONDUIT GATE VALVES *****				
90											
90			GATE	W03AM71	16	16	GATE 300# RF INCONEL 825 N08825 THROUGH COND SOLID SLAB GO	0	0		
100	B1		GATE	W03AM71	8	10	GATE 300# RF INCONEL 825 N08825 THROUGH COND SOLID SLAB GO	0	0		
110											
110							***** GATE VALVES *****				
120											
120			GATE	G03AM49	0.75	2	GATE 300# RF INC 825 INC 625 TRIM WEDGE HW	0	0		
130											
130							***** CHECK VALVES *****				
140											
140			CHECK	C03AR46	8	8	CHECK DUAL WAFER LUG 300# RF LTCS + CLAD INC 825 TRIM INC 625 THROU BOLTED	0	0		
150											
150							***** PIPE *****				
160											
160			PIPE	5361607	0.75	3	PIPE SCH 80S SMLS ALLOY 825 B423 UNS N08825 BE	0	0		
170			PIPE	9002671	6	8	PIPE STD WT SMLS API 5L X60 WITH 3 MM INCONEL 825 INTERNAL CLADDING	0	0		
180			PIPE	9002671	16	16	PIPE STD WT SMLS API 5L X60 WITH 3 MM INCONEL 825 INTERNAL CLADDING	0	0		
190											
190							***** FITTINGS *****				
200											
200			ELBOW	5425111	0.75	3	ELL 90 DEG LR SCH 80S ALLOY 825 B366-WPS UNS N08825	0	0		
210			ELBOW	9002672	6	8	ELL BW 90 DEG LR STD WT A860 WPHY 60 WITH 3 MM INCONEL 825 INTERNAL CLADDING	0	0		
220			ELBOW	9002672	16	16	ELL BW 90 DEG LR STD WT A860 WPHY 60 WITH 3 MM INCONEL 825 INTERNAL CLADDING	0	0		
230			ELBOW	5425113	0.75	2	ELL 45 DEG SCH 80S ALLOY 825 B366-WPS UNS N08825	0	0		
240			ELBOW	9002673	8	8	ELL BW 45 DEG LR STD WT A860 WPHY 60 WITH 3 MM INCONEL 825 INTERNAL CLADDING	0	0		
250											
250			TEE	9002674	8	8	TEE BW STD WT A860 WPHY 60 WITH 3 MM INCONEL 825 INTERNAL CLADDING	0	0		
260			TEE	9002674	16	16	TEE BW STD WT A860 WPHY 60 WITH 3 MM INCONEL 825 INTERNAL CLADDING	0	0		
270			TEE RED	9002698	6	6	TEE RED BW SCH STD WT A860 WPHY 60 WITH 3 MM INCONEL 825 INTERNAL CLADDING	8	8		
280			TEE RED	9002698	6	8	TEE RED BW SCH STD WT A860 WPHY 60 WITH 3 MM INCONEL 825 INTERNAL CLADDING	16	16		
290											
290			CAP	9002675	8	8	CAP BW STD WT A860 WPHY60 WITH 3 MM INCONEL 825 INTERNAL CLADDING	0	0		
300											
300							***** OLETS *****				
310											
310			FLANGE	9002690	0.75	2	NIPOFLANGE 300# RF SCH STD/80S INCONEL 825 N08825	8	8		
320			FLANGE	9002690	0.75	2	NIPOFLANGE 300# RF SCH STD/80S INCONEL 825 N08825	16	16		
330											
330			OLETS	9002677	0.75	3	WELDOLET STD WT/80S INCONEL 825 N08825	8	8		
340			OLETS	9002677	0.75	2	WELDOLET STD WT/80S INCONEL 825 N08825	16	16		
350											
350							**** FLANGES ****				
360											
360	FA8		TEE RED	5600656	0.5	0.5	FLG SCRD (FNPT) REDUCING 300# RF SS A182 F316/316L	0.75	1.5		
370			FLANGE	9002691	0.5	3	FLG WN 300# RF SCH 80S INCONEL 825 UNS N08825	0	0		
380			FLANGE	9002692	6	8	FLG WN 300# RF STD WT A694 F60 WITH 3 MM INCONEL 825 CLAD FACE & BORE	0	0		
390			FLANGE	9002692	16	16	FLG WN 300# RF STD WT A694 F60 WITH 3 MM INCONEL 825 CLAD FACE & BORE	0	0		
400			BLIND	9002693	0.5	16	FLG BLIND 300# RF A694 F60 WITH 3 MM INCONEL 825 CLAD FACE	0	0		
410											
410							***** PIPE NIPPLES *****				
420											
420				0			NIPPLE PBE - CUT FROM PIPE				
430											
430							***** GASKETS *****				
440											
440			GASKET	5673657	0.5	16	GASKET 300# ALLOY 825 SPIRAL WOUND GRAPHITE IR	0	0		
450											
450							***** BOLTING *****				
460											

	TENGIZCHEVROIL TCO TENGIZ, KAZAKHSTAN	CONSTRUCTION	CORR.ALLOW.	SERVICE	MATERIAL	DATE	BY	REV	SHEET	PIPING LINE CLASS
		ALL SIZES - BUTT WELD PWHT - SOUR SERVICE ALL WELDS ABOVE GROUND SEAL WELDING - FOR THREADED CONNECTIONS ONLY PIPE BENDS - INDUCTION BENDS THREAD SEALANT - PTFE PASTE	CORR. ALLOW. 0 MM	SOUR SERVICE - NACE MR0175/ ISO 15156 DESIGN: ASME B16.5 MG 1.1 CODE: ASME B31.8 FLUID CODES - PIM-SU-5112-TCO	MATERIAL: LTCS + CRA FLANGE RATING: 300 RF TEMPERATURE RANGE: -40 / 95 °C	12/16/2024	BY OZAC	U04	Page 1 of 2	300K5G

SEQ NO	REV	NOTE NO.	ITEM NAME	ITEM CODE	SIZE RANGE / SMALL END SIZES		DESCRIPTION	REFERENCE / LARGE END SIZES		NOTES
460	U04	B1	BOLTING	5675770	0.5	99	STUD-BOLT A320 GR L7M/A194 GR 7M (S3) WITH 2 NUTS	0	0	
470							***** BLINDS AND SPACERS *****			
480										
480			SPEC BLIND	5749683	0.75	3	SPECTACLE BLIND 300# RF ALLOY 825 B424 UNS N08825	0	0	
490			SPEC BLIND	5749581_C80	4	10	SPECTACLE BLIND 300# RF LTCS A516 GR.70 WITH 3MM INC 825 CLAD FACE & BORE	0	0	
500										
500			PADDLE	5750100_C80	16	16	PADDLE BLANK 300# RF LTCS A516 GR.70 WITH 3MM INC 825 CLAD FACE	0	0	
510			PADDLE	5750200_C80	16	16	PADDLE SPACER 300# RF LTCS A516 GR.70 WITH 3MM INC 825 CLAD FACE & BORE	0	0	
520										

	TENGIZCHEVROIL TCO TENGIZ, KAZAKHSTAN	CONSTRUCTION	CORR.ALLOW.	SERVICE	MATERIAL	DATE	BY	REV	SHEET	PIPING LINE CLASS
		ALL SIZES - BUTT WELD PWHT - SOUR SERVICE ALL WELDS ABOVE GROUND SEAL WELDING - FOR THREADED CONNECTIONS ONLY PIPE BENDS - INDUCTION BENDS THREAD SEALANT - PTFE PASTE	CORR. ALLOW. 0 MM	SOUR SERVICE - NACE MR0175/ ISO 15156 DESIGN: ASME B16.5 MG 1.1 CODE: ASME B31.8 FLUID CODES - PIM-SU-5112-TCO	MATERIAL: LTCS + CRA FLANGE RATING: 300 RF TEMPERATURE RANGE: -40 / 95 °C	12/16/2024	BY OZAC	U04	Page 2 of 2	300K5G