

SEQ NO	REV	NOTE NO.	ITEM NAME	ITEM CODE	SIZE RANGE / SMALL END SIZES		DESCRIPTION	REFERENCE / LARGE END SIZES		NOTES	
10							***** VALVES *****			810	NIPPLE TO BE CUT FROM SCH 160 PIPE.
20							***** MODULAR VALVES *****			817	USE ONLY FOR TIE IN
30										B1	ALL BOLTS ARE METRIC DIA.
30			MODULAR DBB	K06AM10	0.5	1.5	MODULAR VALVE DB&B BALL TYPE 600# RF INC 825 INC 625 TRIM METAL LO - FULL SIZE TYPE 2BV	0	0	B6	7/8" X 145MM BOLTS ONLY TO BE USED FOR 1
40			MODULAR DBB	K06AM14	2	2	MODULAR VALVE DB&B BALL TYPE 600# RF INC 825 INC 625 TRIM METAL LO - FULL SIZE TYPE 2BV	0	0		INCH 1500# PERAR BALL VALVES ITEM CODE
50		VAV	MODULAR DBB	K06AM14	3	3	MODULAR VALVE DB&B BALL TYPE 600# RF INC 825 INC 625 TRIM METAL LO - FULL SIZE TYPE 2BV	0	0		B15AS22
60			MODULAR DBB	M06AM10	0.5	1.5	MODULAR VALVE DB&B BALL TYPE 600# RF INC 825 INC 625 TRIM METAL LO - CONTROLLED BORE TYPE 2BVR	0	0	BA1	TO BE USED WITH RAISED FACE FLANGES ONLY.
70			MODULAR DBB	M06AM14	2	2	MODULAR VALVE DB&B BALL TYPE 600# RF INC 825 INC 625 TRIM METAL LO - CONTROLLED BORE TYPE 2BVR	0	0	BA5	TO BE USED WITH COMPACT FLANGES REQUIRING COMPACT NUTS ONLY. FOR FGP ONLY.
80		VAW	MODULAR DBB	M06EM10	0.75	1	MODULAR VALVE DB&B BALL TYPE 600# RF INC 825 INC TRIM 625 METAL LO REDUCING - CONTROLLED BORE TYPE 2BVR	2	2	BA7	718 BOLTING TO BE USED FOR BOLT DIAMETER GREATER THAN M63.
90		VAW	MODULAR DBB	M06EM10	1	1	MODULAR VALVE DB&B BALL TYPE 600# RF INC 825 INC TRIM 625 METAL LO REDUCING - CONTROLLED BORE TYPE 2BVR	3	3	DP4	THE MAXIMUM FLANGE RATING FOR 36" IS LIMITED TO 93 BAR @ 230 DEG C.
100							***** BALL VALVES *****			FF5	FLAT BOTTOM NIPOFLANGES FOR USE ON WELD CAPS AND BLIND FLANGES
100										ND9	USE ONLY WITH CONSENT OF MATERIALS ENGINEER.
110										SB6	USE JACKSCREWS FOR PADDLE
110			BALL	A06AM14	2	4	BALL 600# RF 825 INCONEL 625 TRIM TRUNNION METAL RB LO	0	0		BLANKS/SPACERS AND FLANGE SPREADERS
120			BALL	A06AM16	6	24	BALL 600# RF INC 825 INC 625 TRIM TRUNNION METAL RB GO	0	0		FOR SPECTACLE BLINDS.
130			BALL	B06AM10	0.75	1.5	BALL 600# RF 825 INCONEL 625 TRIM FLOATING METAL FB LO	0	0	UJ2	USE 1 1/2IN WITH THERMOWELL
140	U04	VA5	BALL	B06AM14	2	3	BALL 600# RF 825 INCONEL 625 TRIM TRUNNION METAL FB LO	0	0		CONNECTIONS ONLY & 3/4IN (IF SHOWN) FOR DBB PRESSURE CONNECTIONS WITH CHEMICAL SEALS.
150	U04	VA5	BALL	B06AM16	4	24	BALL 600# RF INC 825 INC 625 TRIM TRUNNION METAL FB GO	0	0	UJ3	USE 3IN WITH THERMOWELL CONNECTIONS ONLY
160							***** GLOBE VALVES *****			VA5	USE THESE VALVES ONLY WHERE SPECIFIED ON PIPING AND INSTRUMENT DIAGRAMS
170										VAV	USAGE IS LIMITED TO INSTRUMENT ISOLATION PURPOSE.
170			GLOBE	L06AM43	0.75	4	GLOBE 600# RF INC 825 INC TRIM 625 OS&Y HW	0	0	VAW	VALVE ONLY TO BE USED IN ACCORDANCE WITH DOCUMENT L-ST-2055 - VENT DRAIN AND INSTRUMENT CONNECTION DETAILS.
180			GLOBE	L06AM44	6	10	GLOBE 600# RF INC 825 INC 625 TRIM TRIM OS&Y GO	0	0	VC1	SPRING PISTON CHECK VALVES ARE PREFERED IN THE HORIZONTAL POSITION, BUT MAY BE USED IN THE VERTICAL POSITION WITH ENGINEERING APPROVAL.
190							***** CHECK VALVES *****				
190											
200		VC1	CHECK	C06AM51	0.75	1.5	CHECK PISTON 600# RF INC 825 TRIM 625	0	0		
200			CHECK	C06AM46	2	8	CHECK DUAL WAFER LUG 600# RF INCONEL 825 N08825 THROU BOLTED	0	0		
210	U04		CHECK	C06AM53	10	24	CHECK DUAL DBL FLG 600# RF INC 825 INC 625 TRIM	0	0		
220	U04		CHECK	C06AM53	10	24	CHECK DUAL DBL FLG 600# RF INC 825 INC 625 TRIM	0	0		
230							***** BUTTERFLY VALVES *****				
230											
240			BUTTERFLY	T06AM63	10	24	BUTTERFLY 600# RF INC 825 TRIM 625 TOV METAL DBL FLG SHORT PAT GO	0	0		
250			BUTTERFLY	T06CM63	30	30	BUTTERFLY 600# CF INC 825 TRIM 625 TOV METAL DBL FLG SHORT PAT GO	0	0		
260							***** PIPE *****				
260											
270											
270			PIPE	5732001	0.75	1	PIPE SCH 80S SMLS ALLOY 825 B423 UNS N08825 PE	0	0		
280			PIPE	5732002	1.5	1.5	PIPE SCH 40S SMLS ALLOY 825 B423 UNS N08825 PE	0	0		
290			PIPE	5361603	2	4	PIPE SCH 40S SMLS ALLOY 825 B423 UNS N08825 BE	0	0		
300			PIPE	5361607	6	8	PIPE SCH 80S SMLS ALLOY 825 B423 UNS N08825 BE	0	0		
310			PIPE	5361635	10	10	PIPE SCH 80S WLD ALLOY 825 B705 CL.2 N08825 BE	0	0		
320			PIPE	5361637	12	24	PIPE SCH 60 WLD ALLOY 825 B705 CL.2 N08825 BE	0	0		
330			PIPE	5361640	30	30	PIPE NOM. WT 29.0MM WLD ALLOY 825 B705 CL.2 N08825 BE	0	0		
340		810	PIPE	5361608	0.5	0.5	PIPE SCH 160 SMLS ALLOY 825 B423 UNS N08825 BE	0	0		
350		810	PIPE	5361608	0.75	0.75	PIPE SCH 160 SMLS ALLOY 825 B423 UNS N08825 BE	0	0		
360	U04		PIPE	5361642	36	36	PIPE NOM. WT 31.0MM WLD ALLOY 825 B705 CL.2 N08825 BE	0	0		
370	U04	ND9	PIPE	5365200	30	30	PIPE WT 38.0MM EFW SS A358 316/316L BE	0	0		
380							***** FITTINGS *****				
380											
390											
390			ELBOW	5425111	0.75	1	ELL 90 DEG LR SCH 80S ALLOY 825 B366-WPS UNS N08825	0	0		
400			ELBOW	5425111	6	8	ELL 90 DEG LR SCH 80S ALLOY 825 B366-WPS UNS N08825	0	0		
410			ELBOW	5424722	1.5	4	ELL 90 DEG LR SCH 40S ALLOY 825 B366-WPS UNS N08825	0	0		
420			ELBOW	5425109	10	10	ELL 90 DEG LR SCH 80S ALLOY 825 B366-WPW UNS N08825	0	0		
430			ELBOW	5425130	12	24	ELL 90 DEG LR SCH 60 ALLOY 825 B366-WPW UNS N08825	0	0		
440			ELBOW	5425144	30	30	ELL 90 DEG LR WT 29.0 MM ALLOY 825 B366-WPW UNS N08825	0	0		
450			ELBOW	5425163	36	36	ELL 90 DEG LR WT 31.0 MM ALLOY 825 B366-WPW UNS N08825	0	0		
460	U04		ELBOW	5425113	0.75	1	ELL 45 DEG SCH 80S ALLOY 825 B366-WPS UNS N08825	0	0		
470			ELBOW	5425113	6	8	ELL 45 DEG SCH 80S ALLOY 825 B366-WPS UNS N08825	0	0		
480			ELBOW	5424727	1.5	4	ELL 45 DEG SCH 40S ALLOY 825 B366-WPS UNS N08825	0	0		
490			ELBOW	5425115	10	10	ELL 45 DEG SCH 80S ALLOY 825 B366-WPW UNS N08825	0	0		
500			ELBOW	5425131	12	24	ELL 45 DEG SCH 60 ALLOY 825 B366-WPW UNS N08825	0	0		
510			ELBOW	5425114	30	30	ELL 45 DEG WT 29.0MM ALLOY 825 B366-WPW UNS N08825	0	0		
520											
520			TEE	5425119	0.75	1	TEE SCH 80S ALLOY 825 B366-WPS UNS N08825	0	0		
530			TEE	5425119	6	8	TEE SCH 80S ALLOY 825 B366-WPS UNS N08825	0	0		
540			TEE	5424725	1.5	4	TEE SCH 40S ALLOY 825 B366-WPS UNS N08825	0	0		
550			TEE	5425118	10	10	TEE SCH 80S ALLOY 825 B366-WPW UNS N08825	0	0		

	TENGIZCHEVROIL TCO TENGIZ, KAZAKHSTAN	CONSTRUCTION	CORR.ALLOW.	SERVICE	MATERIAL	DATE	BY	REV	SHEET	PIPING LINE CLASS
		ALL SIZES - BUTT WELD SEAL WELDING - FOR THREADED CONNECTIONS ONLY PIPE BENDS - NONE THREAD SEALANT - NONE	CORR. ALLOW. 1 MM	SOUR SERVICE - NACE MR0175/ ISO 15156 DESIGN: ASME B16.5 MG 3.8 CODE: ASME B31.3 FLUID CODES - PIM-SU-5112-TCO	MATERIAL: ALLOY 825 FLANGE RATING: 600 RF TEMPERATURE RANGE: -40 / 230 °C	12/16/2024	BY OZAC	U04	Page 1 of 3	600A80

SEQ NO	REV	NOTE NO.	ITEM NAME	ITEM CODE	SIZE RANGE / SMALL END SIZES		DESCRIPTION	REFERENCE / LARGE END SIZES		NOTES	
560			TEE	5425132	12	24	TEE SCH 60 ALLOY 825 B366-WPW UNS N08825	0	0		
570			TEE	5425151	30	30	TEE WT 29.0MM ALLOY 825 B366-WPW UNS N08825	0	0		
580			TEE RED	5425126	0.75	0.75	TEE RED SCH 80S ALLOY 825 B366-WPS UNS N08825	1	1		
590			TEE RED	5425126	6	6	TEE RED SCH 80S ALLOY 825 B366-WPS UNS N08825	8	8		
600			TEE RED	5425124	0.75	1	TEE RED SCH 40S/80S ALLOY 825 B366-WPS UNS N08825	1.5	2		
610			TEE RED	5424724	1.5	3	TEE RED SCH 40S ALLOY 825 B366-WPS UNS N08825	2	4		
620			TEE RED	5425125	3	4	TEE RED SCH 80S/40S ALLOY 825 B366-WPS UNS N08825	6	8		
630			TEE RED	5425134	3	4	TEE RED SCH 80S/40S ALLOY 825 B366-WPW UNS N08825	10	10		
640			TEE RED	5425117	6	8	TEE RED SCH 80S ALLOY 825 B366-WPW UNS N08825	10	10		
650			TEE RED	5425135	6	10	TEE RED SCH 60/80S ALLOY 825 B366-WPW UNS N08825	12	24		
660			TEE RED	5425133	12	20	TEE RED SCH 60 ALLOY 825 B366-WPW UNS N08825	14	24		
670			TEE RED	5425153	10	10	TEE RED WT 29.0MM/SCH 80S ALLOY 825 B366-WPW UNS N08825	30	30		
680			TEE RED	5425154	12	24	TEE RED WT 29.0MM/SCH 60 ALLOY 825 B366-WPW UNS N08825	30	30		
690											
690			CAP	5424270	0.75	1	CAP SCH 80S ALLOY 825 B366 UNS N08825	0	0		
700			CAP	5424270	6	10	CAP SCH 80S ALLOY 825 B366 UNS N08825	0	0		
710			CAP	5424219	1.5	4	CAP SCH 40S ALLOY 825 B366 UNS N08825	0	0		
720			CAP	5425136	12	24	CAP SCH 60 ALLOY 825 B366 UNS N08825	0	0		
730			CAP	5425150	30	30	CAP WT 29.0MM ALLOY 825 B366 UNS N08825	0	0		
740											
740			RED CONC	5425122	0.75	0.75	REDUCER CONC SCH 80S ALLOY 825 B366-WPS N08825	1	1		
750			RED CONC	5425122	6	6	REDUCER CONC SCH 80S ALLOY 825 B366-WPS N08825	8	8		
760			RED CONC	5425143	0.75	1	REDUCER CONC SCH 40S/80S ALLOY 825 B366-WPS N08825	1.5	2		
770			RED CONC	5424733	1.5	3	REDUCER CONC SCH 40S ALLOY 825 B366-WPS N08825	2	4		
780			RED CONC	5425142	3	4	REDUCER CONC SCH 80S/40S ALLOY 825 B366-WPS N08825	6	8		
790			RED CONC	5425100	4	4	REDUCER CONC SCH 80S/40S ALLOY 825 B366-WPW N08825	10	10		
800			RED CONC	5425120	6	8	REDUCER CONC SCH 80S ALLOY 825 B366-WPW N08825	10	10		
810			RED CONC	5425141	6	10	REDUCER CONC SCH 60/80S ALLOY 825 B366-WPW N08825	12	18		
820			RED CONC	5425137	12	20	REDUCER CONC SCH 60 ALLOY 825 B366-WPW N08825	14	24		
830			RED CONC	5425155	20	24	REDUCER CONC WT 29MM/SCH 60 ALLOY 825 B366-WPW N08825	30	30		
840			RED CONC	5425157	30	30	REDUCER CONC WT 31MM/29 MM ALLOY 825 B366-WPW N08825	36	36		
850			RED ECC	5425123	0.75	0.75	REDUCER ECC SCH 80S ALLOY 825 B366-WPS N08825	1	1		
860			RED ECC	5425145	0.75	1	REDUCER ECC SCH 40S/80S ALLOY 825 B366-WPS N08825	1.5	2		
870			RED ECC	5424734	1.5	3	REDUCER ECC SCH 40S ALLOY 825 B366-WPS N08825	2	4		
880			RED ECC	5425101	3	4	REDUCER ECC SCH 80S/40S ALLOY 825 B366-WPS N08825	6	8		
890			RED ECC	5425121	6	6	REDUCER ECC SCH 80S ALLOY 825 B366-WPS N08825	8	8		
900			RED ECC	5425139	4	4	REDUCER ECC SCH 80S/40S ALLOY 825 B366-WPW N08825	10	10		
910			RED ECC	5424732	6	8	REDUCER ECC SCH 80S ALLOY 825 B366-WPW N08825	10	10		
920			RED ECC	5425140	6	10	REDUCER ECC SCH 60/80S ALLOY 825 B366-WPW N08825	12	18		
930			RED ECC	5425138	12	20	REDUCER ECC SCH 60 ALLOY 825 B366-WPW N08825	14	24		
940			RED ECC	5425156	20	24	REDUCER ECC WT 29MM/SCH 60 ALLOY 825 B366-WPW N08825	30	30		
950											
950							***** OLETS *****				
960											
960			OLETS	5513485	0.75	1	NIPOFLANGE 600# RF SCH 40S/80S ALLOY 825 B564 UNS N08825	2	4		
970			OLETS	5513481	1.5	2	NIPOFLANGE 600# RF SCH 40S ALLOY 825 B564 UNS N08825	2	4		
980			OLETS	5513486	0.75	1	NIPOFLANGE 600# RF SCH 80S ALLOY 825 B564 UNS N08825	6	10		
990			OLETS	5513482	1.5	2	NIPOFLANGE 600# RF SCH 80S/40S ALLOY 825 B564 UNS N08825	6	10		
1000			OLETS	5513487	0.75	1	NIPOFLANGE 600# RF SCH 60/80S ALLOY 825 B564 UNS N08825	12	24		
1010			OLETS	5513483	1.5	2	NIPOFLANGE 600# RF SCH 60/40S ALLOY 825 B564 UNS N08825	12	24		
1020			OLETS	5513488	0.75	1	NIPOFLANGE 600# RF WT 29.0MM/SCH 80S ALLOY 825 B564 UNS N08825	30	30		
1030			OLETS	5513484	1.5	2	NIPOFLANGE 600# RF WT 29.0MM/SCH 40S ALLOY 825 B564 UNS N08825	30	30		
1040		UJ2	OLETS	5516485	1.5	1.5	NIPOFLANGE 600# RF SCH 40S/160 ALLOY 825 B564 UNS N08825	4	4		
1050		UJ2	OLETS	5516486	1.5	1.5	NIPOFLANGE 600# RF SCH 80S/160 ALLOY 825 B564 UNS N08825	6	10		
1060		UJ2	OLETS	5516487	1.5	1.5	NIPOFLANGE 600# RF SCH 60/160 ALLOY 825 B564 UNS N08825	12	24		
1070		UJ2	OLETS	5516488	1.5	1.5	NIPOFLANGE 600# RF WT 29.0MM/SCH 160 ALLOY 825 B564 UNS N08825	30	30		
1080	U04	UJ3	OLETS	5516489	3	3	NIPOFLANGE 600# RF SCH 60/160 ALLOY 825 B564 UNS N08825	18	18		
1090	U04	UJ3	OLETS	5516484	3	3	NIPOFLANGE 600# RF WT 29.0MM/SCH 160 ALLOY 825 B564 UNS N08825	30	30		
1100		FF5	OLETS	5516491	0.75	1	NIPOFLANGE FLAT BOTTOM 600# RF SCH 80S ALLOY 825 B564 UNS N08825	0	0		
1110		FF5	OLETS	5516490	1.5	1.5	NIPOFLANGE FLAT BOTTOM 600# RF SCH 40S ALLOY 825 B564 UNS N08825	0	0		
1120											
1120			OLETS	5513437	0.75	1	WELDOLET SCH 40S/80S ALLOY 825 B564 UNS N08825	2	4		
1130			OLETS	5513411	1.5	1.5	WELDOLET SCH 40S ALLOY 825 B564 UNS N08825	3	4		
1140			OLETS	5513438	0.75	1	WELDOLET SCH 80S ALLOY 825 B564 UNS N08825	6	10		
1150			OLETS	5513412	1.5	4	WELDOLET SCH 80S/40S ALLOY 825 B564 UNS N08825	6	10		
1160			OLETS	5513433	0.75	1	WELDOLET SCH 60/80S ALLOY 825 B564 UNS N08825	12	24		
1170			OLETS	5513433	6	8	WELDOLET SCH 60/80S ALLOY 825 B564 UNS N08825	12	24		
1180			OLETS	5513432	1.5	4	WELDOLET SCH 60/40S ALLOY 825 B564 UNS N08825	12	24		
1190			OLETS	5513434	0.75	1	WELDOLET WT 29.0MM/SCH 80S ALLOY 825 B564 UNS N08825	30	30		
1200			OLETS	5513434	6	8	WELDOLET WT 29.0MM/SCH 80S ALLOY 825 B564 UNS N08825	30	30		
1210			OLETS	5513435	1.5	4	WELDOLET WT 29.0MM/SCH 40S ALLOY 825 B564 UNS N08825	30	30		
1220											
1220		UJ2	ELBOFLG	5516662	1.5	1.5	ELBOFLANGE 600# RF SCH 40S/ SCH 160 ALLOY 825 B564 UNS N08825	4	4		

	TENGIZCHEVROI TCO TENGIZ, KAZAKHSTAN	CONSTRUCTION		CORR.ALLOW.		SERVICE		MATERIAL		DATE	BY	REV	SHEET	PIPING LINE CLASS
		ALL SIZES - BUTT WELD SEAL WELDING - FOR THREADED CONNECTIONS ONLY PIPE BENDS - NONE THREAD SEALANT - NONE		CORR. ALLOW. 1 MM		SOUR SERVICE - NACE MR0175/ ISO 15156 DESIGN: ASME B16.5 MG 3.8 CODE: ASME B31.3 FLUID CODES - PIM-SU-5112-TCO		MATERIAL: ALLOY 825 FLANGE RATING: 600 RF TEMPERATURE RANGE: -40 / 230 °C		12/16/2024	BY OZAC	U04	Page 2 of 3	600A80

SEQ NO	REV	NOTE NO.	ITEM NAME	ITEM CODE	SIZE RANGE / SMALL END SIZES		DESCRIPTION	REFERENCE / LARGE END SIZES		NOTES
1230		UJ2	ELBOFLG	5516663	1.5	1.5	ELBOFLANGE 600# RF SCH 80S/ SCH 160 ALLOY 825 B564 UNS N08825	6	10	
1240		UJ2	ELBOFLG	5516671	1.5	1.5	ELBOFLANGE 600# RF SCH 60/ SCH 160 ALLOY 825 B564 UNS N08825	12	24	
1250		UJ2	ELBOFLG	5516672	1.5	1.5	ELBOFLANGE 600# RF WT 29.0MM/ SCH 160 ALLOY 825 B564 UNS N08825	30	30	
1260							***** FLANGES *****			
1260										
1270										
1270			TEE RED	5614300	0.5	0.5	FLG SCRD (FNPT) REDUCING 600# RF ALLOY 825 B564 UNS N08825	0.75	0.75	
1280										
1280			FLANGE	5851204	0.5	2	FLANGE ADAPTER 600# RF 316 SS X 12 MM TUBE	0	0	
1290	U04	ND9	FLG ADAPTER	5851214	0.5	2	FLANGE ADAPTER 600# RF ALLOY 825 B564 UNS N08825 X 12 MM TUBE	0	0	
1300										
1300			FLANGE	5569391	0.5	1	FLG WN 600# RF ALLOY 825 SCH 80S B564 UNS N08825	0	0	
1310			FLANGE	5569391	6	10	FLG WN 600# RF ALLOY 825 SCH 80S B564 UNS N08825	0	0	
1320			FLANGE	5569392	1.5	4	FLG WN 600# RF ALLOY 825 SCH 40S B564 UNS N08825	0	0	
1330			FLANGE	5569393	12	24	FLG WN 600# RF ALLOY 825 SCH 60 B564 UNS N08825	0	0	
1340			FLANGE	5569394	30	30	FLG WN 600# RF ALLOY 825 WT 29.0MM B564 UNS N08825	0	0	
1350	U04		FLANGE	5569395	36	36	FLG WN 600# RF ALLOY 825 WT 31.0MM B564 UNS N08825 B16.47 SERIES A	0	0	
1360	U04	817	FLANGE	5619812	30	30	FLG COMPACT 600# RJ ALLOY 825 WT 29.0MM B564 UNS N08825	0	0	
1370	U04	DP4 ,817	FLANGE	5619969	36	36	FLG COMPACT 600# RJ ALLOY 825 WT 31.0MM B564 UNS N08825	0	0	
1380			BLIND	5617167	0.5	24	FLG BLIND 600# RF ALLOY 825 B564 UNS N08825	0	0	
1390			BLIND	5617168	30	30	FLG BLIND 600# RF ALLOY 825 B564 UNS N08825 B16.47 SERIES A	0	0	
1400	U04	817	BLIND	5619745	30	36	FLG COMPACT BLIND 600# RJ ALLOY 825 B564 UNS N08825 PIPE CLASS 600A80	0	0	
1410							***** ORIFICE FLANGES *****			
1410										
1420										
1420			ORIFICE FLG	5650840	2	4	WN ORIF SET 600# RF ALLOY 825 B564 UNS N08825 SCH 40S	0	0	
1430			ORIFICE FLG	5650841	6	10	WN ORIF SET 600# RF ALLOY 825 B564 UNS N08825 SCH 80S	0	0	
1440			ORIFICE FLG	5650842	12	24	WN ORIF SET 600# RF ALLOY 825 B564 UNS N08825 SCH 60	0	0	
1450							***** NIPPLES *****			
1450										
1460				0			NIPPLE CUT FROM PIPE			
1460										
1470							***** GASKETS *****			
1470										
1480			GASKET	5673661	0.5	24	GASKET 600# ALLOY 825 SPIRAL WOUND GRAPHITE IR	0	0	
1490	U04		GASKET	5674014	30	36	GASKET 600# ALLOY 825 KAMMPROFILE GRAPHITE ASME B16.47 SERIES A	0	0	
1500	U04	817	GASKET	5673400	30	36	GASKET 600# RJ INC 718 ENERGIZED SEALRING COMPACT FLANGE PIPE CLASS 600A80	0	0	
1510							***** BOLTING *****			
1510		B1								
1520										
1520		BA1	BOLTING	5675770	0.5	28	STUD-BOLT A320 GR L7M/A194 GR 7M (S3) WITH 2 NUTS	0	0	
1530		BA1	BOLTING	5675770	30	36	STUD-BOLT A320 GR L7M/A194 GR 7M (S3) WITH 2 NUTS	0	0	
1540	U04	BA1	BOLTING	5675770	30	30	STUD-BOLT A320 GR L7M/A194 GR 7M (S3) WITH 2 NUTS	0	0	
1550	U04	BA5, BA7	BOLTING	5675778	30	99	STUD-BOLT C/W 2 COMPACT NUTS API-6A718	0	0	
1560	U04	BA1	BOLTING	5675776	36	36	STUD-BOLT WITH 2 NUTS API-6A718	0	0	
1570										
1570		SB6	BOLTING	5675675	10	30	JACK SCREW HEX HEAD A320 GR L7M	0	0	
1580							***** BLINDS & SPACERS *****			
1580										
1590										
1590			SPEC BLIND	5750230	0.75	8	SPECTACLE BLIND 600# RF ALLOY 825 B424 UNS N08825	0	0	
1600										
1600			PADDLE	5750231	10	24	PADDLE BLANK 600# RF ALLOY 825 B424 UNS N08825	0	0	
1610			PADDLE	5750232	10	24	PADDLE SPACER 600# RF ALLOY 825 B424 UNS N08825	0	0	
1620	U04		PADDLE	5750229	36	36	PADDLE BLANK 600# RF ALLOY 825 B424 UNS N08825 B16.47 SERIES A	0	0	
1630			PADDLE	5750229	30	30	PADDLE BLANK 600# RF ALLOY 825 B424 UNS N08825 B16.47 SERIES A	0	0	
1640	U04		PADDLE	5750241	36	36	PADDLE SPACER 600# RF ALLOY 825 B424 UNS N08825 B16.47 SERIES A	0	0	
1650			PADDLE	5750241	30	30	PADDLE SPACER 600# RF ALLOY 825 B424 UNS N08825 B16.47 SERIES A	0	0	
1660										

	TENGIZCHEVROIL TCO TENGIZ, KAZAKHSTAN	CONSTRUCTION	CORR.ALLOW.	SERVICE	MATERIAL	DATE	BY	REV	SHEET	PIPING LINE CLASS
		ALL SIZES - BUTT WELD SEAL WELDING - FOR THREADED CONNECTIONS ONLY PIPE BENDS - NONE THREAD SEALANT - NONE	CORR. ALLOW. 1 MM	SOUR SERVICE - NACE MR0175/ ISO 15156 DESIGN: ASME B16.5 MG 3.8 CODE: ASME B31.3 FLUID CODES - PIM-SU-5112-TCO	MATERIAL: ALLOY 825 FLANGE RATING: 600 RF TEMPERATURE RANGE: -40 / 230 °C	12/16/2024	BY OZAC	U04	Page 3 of 3	600A80