

SEQ NO	REV	NOTE NO.	ITEM NAME	ITEM CODE	SIZE RANGE / SMALL END SIZES		DESCRIPTION	REFERENCE / LARGE END SIZES		NOTES																				
10							***** BALL VALVES *****			810	NIPPLE TO BE CUT FROM SCH 160 PIPE. B1 ALL BOLTS ARE METRIC DIA. VA5 USE THESE VALVES ONLY WHERE SPECIFIED ON PIPING AND INSTRUMENT DIAGRAMS VC1 SPRING PISTON CHECK VALVES ARE PREFERED IN THE HORIZONTAL POSITION, BUT MAY BE USED IN THE VERTICAL POSITION WITH ENGINEERING APPROVAL.																			
20	U04		BALL	A06AC05	2	3	BALL 600# RF LTCS A350 LF2 CL.1 316SS TRIM TRUNNION SOFT RB LO	0	0	B1																				
30	U04		BALL	B06AC01	0.75	1.5	BALL 600# RF LTCS A350 LF2 CL.1 316SS TRIM FLOATING SOFT FB LO	0	0	VA5																				
40	U04	VA5	BALL	B06AC05	2	3	BALL 600# RF LTCS A350 LF2 CL.1 316SS TRIM TRUNNION SOFT FB LO	0	0	VC1																				
50							***** GATE VALVES *****																							
60	U04		GATE	G06AC48	0.75	1.5	GATE 600# RF LTCS A350 LF2 CL.1 TRIM 16 WEDGE HW	0	0																					
70			GATE	G06AC41	2	3	GATE 600# RF LTCS A352 LCC TRIM 16 WEDGE HW	0	0																					
80							***** GLOBE VALVES *****																							
90	U04		GLOBE	L06AC48	0.75	1.5	GLOBE 600# RF LTCS A350 LF2 CL.1 TRIM 16 OS&Y HW	0	0																					
100			GLOBE	L06AC41	2	3	GLOBE 600# RF LTCS A352 LCC TRIM 16 OS&Y HW	0	0																					
110							***** CHECK VALVES *****																							
120	U04	VC1	CHECK	C06AC50	0.75	1.5	CHECK PISTON 600# RF LTCS A350 LF2 CL.1 TRIM 16	0	0																					
130			CHECK	C06AC45	2	3	CHECK DUAL WAFER LUG 600# RF LTCS A352 LCC TRIM 16 THROU BOLTED	0	0																					
140							***** PIPE *****																							
150			PIPE	5358601	0.75	2	PIPE SCH 160 SMLS LTCS A333 GR.6 GALV A153 T&C	0	0																					
160			PIPE	5358515	3	3	PIPE SCH 160 SMLS LTCS A333 GR.6 BE	0	0																					
170							***** FITTINGS *****																							
180	U04		ELBOW	5491290	0.75	2	ELL 90 DEG 3000# SCRD FNPT LTCS A350 LF2 CL.1 GALV A153	0	0																					
190			ELBOW	5392816	3	3	ELL BW 90 DEG LR SCH 160 LTCS A420 WPL6	0	0																					
200	U04		ELBOW	5491300	0.75	2	ELL 45 DEG 3000# SCRD FNPT LTCS A350 LF2 CL.1 GALV A153	0	0																					
210			ELBOW	5392822	3	3	ELL BW 45 DEG LR SCH 160 LTCS A420 WPL6	0	0																					
220	U04		TEE	5491310	0.75	2	TEE 3000# SCRD FNPT LTCS A350 LF2 CL.1 GALV A153	0	0																					
230			TEE	5392825	3	3	TEE BW SCH 160 LTCS A420 WPL6	0	0																					
240	U04		TEE RED	5491311	0.75	1.5	TEE RED 3000# SCRD FNPT LTCS A350 LF2 CL.1 GALV A153	1	2																					
250			TEE RED	5392821	1.5	2	TEE RED BW SCH 160 LTCS A420 WPL6	3	3																					
260	U04		CAP	5491330	0.75	2	CAP 3000# SCRD FNPT LTCS A350 LF2 CL.1 GALV A153	0	0																					
270			CAP	5392826	3	3	CAP BW SCH 160 LTCS A420 WPL6	0	0																					
280							***** COUPLINGS, UNIONS, PLUGS & BUSHINGS *****																							
290	U04		COUPLING	5491250	0.75	2	COUPLING 3000# SCRD FNPT LTCS A350 LF2 CL.1 GALV A153	0	0																					
300	U04		TEE RED	5491260	0.75	1.5	COUPLING RED 3000# SCRD FNPT LTCS A350 LF2 CL.1 GALV A153	1	2																					
310	U04		UNION	5491270	0.75	2	UNION 3000# SCRD FNPT LTCS A350 LF2 CL.1 GALV A153	0	0																					
320	U04		FITTING SCRD	5491280	0.75	2	PLUG ROUND HEAD SCRD MNPT LTCS A350 LF2 CL.1 GALV A153	0	0																					
330	U04		FITTING SCRD	5491325	0.5	1.5	BUSHING 3000# SCRD (MNPT/FNPT) HEX HEAD LTCS A350 LF2 CL.1 GALV A153	0.75	2																					
340							***** FLANGES *****																							
350	U04		TEE RED	5599707	0.5	0.5	FLG SCRD (FNPT) REDUCING 600# RF A350 LF2 CL.1 GALV A153	0.75	0.75																					
360			FLANGE	5599710	0.75	2	FLG SCRD (FNPT) 600# RF LTCS LF2 CL.1 GALV A153	0	0																					
370	U04		FLANGE	5557038	3	3	FLG WN 600# RF LTCS A350 LF2 CL.1 SCH 160	0	0																					
380	U04		BLIND	5615599	0.75	3	FLG BLIND 600# RF LTCS A350 LF2 CL.1 GALV A153	0	0																					
390							***** ORIFICE FLANGES *****																							
400	U04		ORIFICE FLG	5623949	2	2	ORIF SET 600# RF SCRD (FNPT) LTCS A350 LF2 CL.1 GALV A153	0	0																					
410	U04		ORIFICE FLG	5624351	3	3	WN ORIF SET 600# RF LTCS A350 LF2 CL.1 SCH 160	0	0																					
420		810					***** PIPE NIPPLES *****																							
430			NIPPLE	5541200	0.5	2	NIPPLE SCH 160 LTCS A333 GR.6 TBE 3" LG (MNPT) GALV A153	0	0																					
440			NIPPLE	5541201	0.5	2	NIPPLE SCH 160 LTCS A333 GR.6 TBE 7" LG (MNPT) GALV A153	0	0																					
450							***** SWAGE NIPPLES *****																							
460			RED CONC	5544150	0.75	2	SWAGE CONC SCH 160 LTCS A420 WPL6 TBE (MNPT) GALV A153	1	2																					
 TENGIZCHEVROIL TCO TENGIZ, KAZAKHSTAN <table><thead><tr><th colspan="2">CONSTRUCTION</th><th>CORR.ALLOW.</th><th>SERVICE</th><th>MATERIAL</th><th>DATE</th><th>BY</th><th>REV</th><th>SHEET</th><th>PIPING LINE CLASS</th></tr></thead><tbody><tr><td colspan="2">2" AND SMALLER-GALVANIZED THREADED AND COUPLED 3" - BUTT WELD,GALVANIZED AFTER FABRICATION SEAL WELDING - NONE PIPE BENDS - NONE THREAD SEALANT - PTFE PASTE</td><td>CORR. ALLOW. 1.5 MM</td><td>SOUR SERVICE - NACE MR0175/ ISO 15156 DESIGN: ASME B16.5 MG 1.1 CODE: ASME B31.3 FLUID CODES - PIM-SU-5112-TCO</td><td>MATERIAL: GALVANISED LTCS FLANGE RATING: 600 RF TEMPERATURE RANGE: -40 / 38 °C</td><td>12/16/2024</td><td>BY OZAC</td><td>U04</td><td>Page 1 of 2</td><td>600H2G</td></tr></tbody></table>											CONSTRUCTION		CORR.ALLOW.	SERVICE	MATERIAL	DATE	BY	REV	SHEET	PIPING LINE CLASS	2" AND SMALLER-GALVANIZED THREADED AND COUPLED 3" - BUTT WELD,GALVANIZED AFTER FABRICATION SEAL WELDING - NONE PIPE BENDS - NONE THREAD SEALANT - PTFE PASTE		CORR. ALLOW. 1.5 MM	SOUR SERVICE - NACE MR0175/ ISO 15156 DESIGN: ASME B16.5 MG 1.1 CODE: ASME B31.3 FLUID CODES - PIM-SU-5112-TCO	MATERIAL: GALVANISED LTCS FLANGE RATING: 600 RF TEMPERATURE RANGE: -40 / 38 °C	12/16/2024	BY OZAC	U04	Page 1 of 2	600H2G
CONSTRUCTION		CORR.ALLOW.	SERVICE	MATERIAL	DATE	BY	REV	SHEET	PIPING LINE CLASS																					
2" AND SMALLER-GALVANIZED THREADED AND COUPLED 3" - BUTT WELD,GALVANIZED AFTER FABRICATION SEAL WELDING - NONE PIPE BENDS - NONE THREAD SEALANT - PTFE PASTE		CORR. ALLOW. 1.5 MM	SOUR SERVICE - NACE MR0175/ ISO 15156 DESIGN: ASME B16.5 MG 1.1 CODE: ASME B31.3 FLUID CODES - PIM-SU-5112-TCO	MATERIAL: GALVANISED LTCS FLANGE RATING: 600 RF TEMPERATURE RANGE: -40 / 38 °C	12/16/2024	BY OZAC	U04	Page 1 of 2	600H2G																					

SEQ NO	REV	NOTE NO.	ITEM NAME	ITEM CODE	SIZE RANGE / SMALL END SIZES		DESCRIPTION	REFERENCE / LARGE END SIZES		NOTES
470			RED CONC	5544137	1.5	2	SWAGE CONC SCH 160 LTCS A420 WPL6 PLE/TSE	3	3	
480			RED ECC	5549150	0.75	2	SWAGE ECC SCH 160 LTCS A420 WPL6 TBE (MNPT) GALV A153	1	2	
490			RED ECC	5549197	1.5	2	SWAGE ECC SCH 160 LTCS A420 WPL6 PLE/TSE	3	3	
500							***** GASKETS *****			
510										
510			GASKET	5673102	0.75	3	GASKET 600# 316SS SPIRAL WOUND GRAPHITE IR	0	0	
520							***** BOLTING *****			
520										
530										
530	U04	B1	BOLTING	5675770	0.5	99	STUD-BOLT A320 GR L7M/A194 GR 7M (S3) WITH 2 NUTS	0	0	
540							**** BLINDS & SPACERS ****			
540										
550										
550			SPEC BLIND	5749588	0.75	3	SPECTACLE BLIND 600# RF LTCS A516 GR.70 GALV A153	0	0	
560										

	TENGIZCHEVROIL TCO TENGIZ, KAZAKHSTAN	CONSTRUCTION	CORR.ALLOW.	SERVICE	MATERIAL	DATE	BY	REV	SHEET	PIPING LINE CLASS
		2" AND SMALLER-GALVANIZED THREADED AND COUPLED 3" - BUTT WELD,GALVANIZED AFTER FABRICATION SEAL WELDING - NONE PIPE BENDS - NONE THREAD SEALANT - PTFE PASTE	CORR. ALLOW. 1.5 MM	SOUR SERVICE - NACE MR0175/ ISO 15156 DESIGN: ASME B16.5 MG 1.1 CODE: ASME B31.3 FLUID CODES - PIM-SU-5112-TCO	MATERIAL: GALVANISED LTCS FLANGE RATING: 600 RF TEMPERATURE RANGE: -40 / 38 °C	12/16/2024	BY OZAC	U04	Page 2 of 2	600H2G