

SEQ NO	REV	NOTE NO.	ITEM NAME	ITEM CODE	SIZE RANGE / SMALL END SIZES		DESCRIPTION	REFERENCE / LARGE END SIZES		NOTES	
10							***** MODULAR VALVES *****			814	NIPPLE TO BE CUT FROM SS SCH 160 PE PIPE.
20										815	TO BE USED WITH COMPACT FLANGES ONLY.
20			MODULAR DBB	K06AS22	0.5	1.5	MODULAR VALVE DB&B BALL TYPE 600# RF SS A182 F316 316 SS TRIM METAL LO 718 BOLT - FULL SIZE TYPE 2BV	0	0	816	COMPACT FLANGES CAN BE USED FOR TIE-IN PURPOSE ONLY TO EXISTING PIPING AND EQUIPMENT.
30		VAV	MODULAR DBB	K06AS26	2	3	MODULAR VALVE DB&B BALL TYPE 600# RF SS A182 F316 316 SS TRIM METAL LO 718 BOLT - FULL SIZE TYPE 2BV	0	0	817	USE ONLY FOR TIE IN
40			MODULAR DBB	M06AS22	0.5	1.5	MODULAR VALVE DB&B BALL TYPE 600# RF SS A182 F316 316 SS TRIM METAL LO 718 BOLT - CONTROLLED BORE TYPE 2BVR	0	0	B1	ALL BOLTS ARE METRIC DIA.
50			MODULAR DBB	M06AS26	2	2	MODULAR VALVE DB&B BALL TYPE 600# RF SS A182 F316 316 SS TRIM METAL LO 718 BOLT - CONTROLLED BORE TYPE 2BVR	0	0	B2	7/8" X 145MM BOLTS ONLY TO BE USED FOR 1 INCH 1500# PEARL BALL VALVES ITEM CODE B15AM10
60		VAW	MODULAR DBB	M06ES22	0.75	1	MODULAR VALVE DB&B BALL TYPE 600# RF SS A182 F316SS TRIM METAL LO 718 BOLT REDUCING - CONTROLLED BORE TYPE 2BVR	2	3	B22	L7M BOLTS SHALL ONLY BE USED IN SOUR SERVICE LINES WITH DESIGN TEMPS GREATER THAN OR EQUAL TO -46 DEG C AND AT LOCATIONS WHERE FLANGE JOINTS ARE INSULATED
70							***** BALL VALVES *****				
70		VB2									
80											
80		VA5	BALL	A06AS27	2	10	BALL 600# RF SS A182 F316 316SS TRIM TRUNNION SOFT RB GO 718 BOLT	0	0	BA1	TO BE USED WITH RAISED FACE FLANGES ONLY.
90		VA5	BALL	A06AS28	2	8	BALL 600# RF SS A182 F316 316SS TRIM TRUNNION METAL RB GO 718 BOLT	0	0		
100			BALL	B06AS21	0.75	1.5	BALL 600# RF SS A182 F316 316SS TRIM FLOATING SOFT FB LO 718 BOLT	0	0	BA5	TO BE USED WITH COMPACT FLANGES REQUIRING COMPACT NUTS ONLY. FOR FGP ONLY.
110			BALL	B06AS22	0.75	1.5	BALL 600# RF SS A182 F316 316SS TRIM FLOATING METAL FB LO 718 BOLT	0	0		
120		VA5	BALL	B06AS27	2	24	BALL 600# RF SS A182 F316 316SS TRIM TRUNNION SOFT FB GO 718 BOLT	0	0		
130		VA5	BALL	B06AS28	2	24	BALL 600# RF SS A182 F316 316SS TRIM TRUNNION METAL FB GO 718 BOLT	0	0	FA8	USE THREADED FLANGES FOR INSTRUMENT CONNECTIONS ONLY.
140	U04	817	BALL	B06CS27	26	48	BALL 600# CF SS A182 F316 316SS TRIM TRUNNION SOFT FB GO 718 BOLT	0	0		
150	U04	817	BALL	B06CS28	26	48	BALL 600# CF SS A182 F316 316SS TRIM TRUNNION METAL FB GO 718 BOLT	0	0	FF5	FLAT BOTTOM NIPOLFLANGES FOR USE ON WELD CAPS AND BLIND FLANGES
160							***** BUTTERFLY VALVES *****			FS1	USE FLANGES, GASKETS & VALVES AS REQUIRED TO MATCH EQUIPMENT OR VESSEL NOZZLES.
160											
170											
170			BUTTERFLY	T06AS65	10	24	BUTTERFLY 600# RF SS A351 CF8M 316SS TRIM TOV METAL DBL FLG SHORT PAT GO 718 BOLT	0	0		
180	U04	817	BUTTERFLY	T06CS65	26	48	BUTTERFLY 600# CF SS A351 CF8M 316SS TRIM TOV METAL DBL FLG SHORT PAT GO 718 BOLT	0	0	UD7	USE THREDOLET AND SCREWED PLUG FOR HYDROSTATIC TEST VENTS AND DRAINS. SEAL WELD AFTER HYDROSTATIC TEST
190							***** GLOBE VALVE*****				
190											
200										UJ2	USE 1 1/2IN WITH THERMOWELL CONNECTIONS ONLY & 3/4IN (IF SHOWN) FOR DBB PRESSURE CONNECTIONS WITH CHEMICAL SEALS.
200			GLOBE	L06AS55	0.75	1.5	GLOBE 600# RF SS A182 F316 TRIM 16 OS&Y HW 718 BOLT	0	0		
210			GLOBE	L06AS56	2	4	GLOBE 600# RF SS A351 CF8M TRIM 16 OS&Y HW 718 BOLT	0	0		
220			GLOBE	L06AS57	6	10	GLOBE 600# RF SS A351 CF8M TRIM 16 OS&Y GO 718 BOLT	0	0	VA5	USE THESE VALVES ONLY WHERE SPECIFIED ON PIPING AND INSTRUMENT DIAGRAMS
230							***** CHECK VALVES *****			VAV	USAGE IS LIMITED TO INSTRUMENT ISOLATION PURPOSE.
230											
240											
240		VC1	CHECK	C06AS54	0.75	1.5	CHECK PISTON 600# RF SS A182 F316 TRIM 16 718 BOLT	0	0		
250			CHECK	C06AS45	2	8	CHECK DUAL WAFER LUG 600# RF SS A351 CF8M TRIM 16 THROU BOLTED	0	0	VAW	VALVE ONLY TO BE USED IN ACCORDANCE WITH DOCUMENT L-ST-2055 - VENT DRAIN AND INSTRUMENT CONNECTION DETAILS.
260			CHECK	C06AS52	10	24	CHECK DUAL DBL FLG 600# RF SS A351 CF8M TRIM 16	0	0		
270	U04	817	CHECK	C06CS52	26	48	CHECK DUAL DBL FLG 600# CF SS A351 CF8M TRIM 16	0	0	VB2	SOFT SEATED BALL VALVES ARE LIMITED TO MAXIMUM TEMPERATURE OF 200°C.
280							***** PIPE*****				
280											
290										VC1	SPRING PISTON CHECK VALVES ARE PREFERRED IN THE HORIZONTAL POSITION, BUT MAY BE USED IN THE VERTICAL POSITION WITH ENGINEERING APPROVAL.
290	U04		PIPE	5365140	0.5	1.5	PIPE SCH 80S SMLS SS A312 TP316/316L PE	0	0		
300			PIPE	5365138	2	8	PIPE SCH 80S SMLS SS A312 TP316/316L-S BE	0	0		
310			PIPE	5365139	10	24	PIPE SCH 80 SMLS SS A312 TP316/316L BE	0	0		
320			PIPE	5365143	26	26	PIPE WT 33.0MM EFW SS A358 TP316/316L BE	0	0		
330			PIPE	5365200	30	30	PIPE WT 38.0MM EFW SS A358 316/316L BE	0	0		
340			PIPE	5365212	36	36	PIPE WT 40.0MM EFW SS A358 316/316L BE	0	0		
350		814	PIPE	5365214	42	42	PIPE WT 45.0MM EFW SS A358 316/316L BE	0	0		
360		814	PIPE	5365213	48	48	PIPE WT 50.0MM EFW SS A358 316/316L BE	0	0		
370		814	PIPE	5365207	0.5	0.75	PIPE SCH 160 SMLS SS A312 TP316/316L PE	0	0		
380							***** FITTINGS *****				
380											
390											
390	U04		ELBOW	5449033	0.5	8	ELL 90 DEG LR SCH 80S SS A403 WP316/316L-S	0	0		
400			ELBOW	5449034	10	24	ELL 90 DEG LR SCH 80 SS A403 WP316/316L-S	0	0		
410			ELBOW	5451120	30	30	ELL 90 LR WT 38.0MM 316/316L SS A403 WP316/316L-W	0	0		
420			ELBOW	5451122	36	36	ELL 90 LR WT 40.0MM 316/316L SS A403 WP316/316L-W	0	0		
430			ELBOW	5451121	42	42	ELL 90 LR WT 45.0MM 316/316L SS A403 WP316/316L-W	0	0		
440			ELBOW	5451123	48	48	ELL 90 LR WT 50.0MM 316/316L SS A403 WP316/316L-W	0	0		
450	U04		ELBOW	5449146	0.5	8	ELL 45 DEG LR SCH 80S SS A403 WP316/316L-S	0	0		
460			ELBOW	5449145	10	24	ELL 45 DEG LR SCH 80 SS A403 WP316/316L-S	0	0		
470			ELBOW	5451110	30	30	ELL 45 LR WT 38.0MM 316/316L SS A403 WP316/316L-W	0	0		
480			ELBOW	5451102	36	36	ELL 45 LR WT 40.0MM 316/316L SS A403 WP316/316L-W	0	0		
490			ELBOW	5451103	48	48	ELL 45 LR WT 50.0MM 316/316L SS A403 WP316/316L-W	0	0		
500											
500			TEE	5449156	0.75	8	TEE SCH 80S SS A403 WP316/316L-S	0	0		
510			TEE	5449157	10	24	TEE SCH 80 SS A403 WP316/316L-S	0	0		
520			TEE	5451113	30	30	TEE 38.0MM SS A403 WP316/316L-W	0	0		
530			TEE	5451112	36	36	TEE 40.0MM SS A403 WP316/316L-W	0	0		
540			TEE	5451115	48	48	TEE 50.0MM SS A403 WP316/316L-W	0	0		

	TENGIZCHEVROIL TCO TENGIZ, KAZAKHSTAN	CONSTRUCTION	CORR.ALLOW.	SERVICE	MATERIAL	DATE	BY	REV	SHEET	PIPING LINE CLASS
		ALL SIZES - BUTT WELD SEAL WELDING - FOR THREADED CONNECTIONS ONLY PIPE BENDS - NONE THREAD SEALANT - PTFE PASTE	CORR. ALLOW. 1 MM	SOUR SERVICE - NACE MR0175/ ISO 15156, DESIGN - ASME B16.5 MG 2.2 CODE - ASME B31.3 FLUID CODES - PIM-SU-5112-TCO	MATERIAL: 316/316L SS DUAL GRADE FLANGE RATING: 600 RF TEMPERATURE RANGE: -120 / 180 °C	12/16/2024	BY OZAC	U04	Page 1 of 3	600P21

SEQ NO	REV	NOTE NO.	ITEM NAME	ITEM CODE	SIZE RANGE / SMALL END SIZES		DESCRIPTION	REFERENCE / LARGE END SIZES		NOTES
550			TEE RED	5448905	0.75	6	TEE RED SCH 80S SS A403 WP316/316L-S	1	8	
560			TEE RED	5448906	4	8	TEE RED SCH 80/80S SS A403 WP316/316L-S	10	20	
570			TEE RED	5448907	10	20	TEE RED SCH 80 SS A403 WP316/316L-S	12	24	
580		UJ2	TEE RED	5448913	12	20	TEE RED WT 33.0MM X SCH 80 SS A403 WP316/316L-S	26	26	
590										
590			CAP	5449049	0.75	8	CAP SCH 80S SS A403 WP316/316L-S	0	0	
600			CAP	5449050	10	24	CAP SCH 80 SS A403 WP316/316L-S	0	0	
610			CAP	5449261	26	26	CAP WT 33.0MM SS A403 WP316/316L-S	0	0	
620			CAP	5449260	30	30	CAP WT 38.0MM SS A403 WP316/316L-S	0	0	
630			CAP	5449262	36	36	CAP WT 40.0MM SS A403 WP316/316L-S	0	0	
640			CAP	5449263	48	48	CAP WT 50.0MM SS A403 WP316/316L-S	0	0	
650										
650		UJ2	RED CONC	5449158	0.5	6	REDUCER CONC SCH 80S SS A403 WP316/316L-S	0.75	8	
660			RED CONC	5448904	4	8	REDUCER CONC SCH 80/80S SS A403 WP316/316L-S	10	20	
670			RED CONC	5448908	10	20	REDUCER CONC SCH 80 SS A403 WP316/316L-S	12	24	
680			RED CONC	5450730	20	24	REDUCER CONC 38.0MM/SCH 80 SS A403 WP316/316L-W	30	30	
690			RED CONC	5450749	24	24	REDUCER CONC 40.0MM / SCH 80 SS A403 WP316/316L-W	36	36	
700			RED CONC	5450742	30	30	REDUCER CONC 40.0MM/ 38.0MM SS A403 WP316/316L-W	36	36	
710			RED CONC	5450741	30	30	REDUCER CONC 45.0MM/ 38.0MM SS A403 WP316/316L-W	42	42	
720			RED CONC	5450746	36	36	REDUCER CONC 45.0MM/ 40.0MM SS A403 WP316/316L-W	42	42	
730			RED CONC	5450744	42	42	REDUCER CONC 50.0MM/ 45.0MM SS A403 WP316/316L-W	48	48	
740		UJ2	RED ECC	5449159	0.5	6	REDUCER ECC SCH 80S SS A403 WP316/316L-S	0.75	8	
750			RED ECC	5449160	4	8	REDUCER ECC SCH 80/80S SS A403 WP316/316L-S	10	20	
760			RED ECC	5449161	10	20	REDUCER ECC SCH 80 SS A403 WP316/316L-S	12	24	
770			RED ECC	5450728	20	24	REDUCER ECC 38.0MM/SCH 80 SS A403 WP316/316L-W	30	30	
780			RED ECC	5450739	24	24	REDUCER ECC 40.0MM / SCH 80 SS A403 WP316/316L-W	36	36	
790			RED ECC	5450729	30	30	REDUCER ECC 40.0MM / 38.0MM SS A403 WP316/316L-W	36	36	
800			RED ECC	5450754	36	36	REDUCER ECC 45.0MM / 40.0MM SS A403 WP316/316L-W	42	42	
810			RED ECC	5450752	42	42	REDUCER ECC 50.0MM / 45.0MM SS A403 WP316/316L-W	48	48	
820										
820							***** OLETS *****			
830										
830			OLETS	5504504	0.75	2	NIPOFLANGE 600# RF SCH 80S SS A182 F316/316L	2	8	
840			OLETS	5504505	0.75	2	NIPOFLANGE 600# RF SCH 80/80S SS A182 F316/316L	10	24	
850			OLETS	5504416	0.75	2	NIPOFLANGE 600# RF WT 33.0MM/SCH 80S SS A182 F316/316L	26	26	
860			OLETS	5504506	0.75	2	NIPOFLANGE 600# RF WT 38.0MM/SCH 80S SS A182 F316/316L	30	30	
870			OLETS	5504539	0.75	2	NIPOFLANGE 600# RF SCH 40.0MM/80S SS A182 F316/316L	36	36	
880			OLETS	5504541	0.75	2	NIPOFLANGE 600# RF SCH 50.0MM/80S SS A182 F316/316L	48	48	
890		FF5	OLETS	5504613	0.75	1.5	NIPOFLANGE FLAT BOTTOM 600# RF SCH 80S SS A182 F316/316L	0	0	
900		UJ2	OLETS	5504075	1.5	1.5	NIPOFLANGE 600# RF SCH 80S/160 SS A182 F316/316L	4	8	
910		UJ2	OLETS	5504076	1.5	1.5	NIPOFLANGE 600# RF SCH 80/160 SS A182 F316/316L	10	24	
920		UJ2	OLETS	5504083	1.5	1.5	NIPOFLANGE 600# RF 33.0MM WT/SCH 160 SS A182 F316/316L	26	26	
930		UJ2	OLETS	5504080	1.5	1.5	NIPOFLANGE 600# RF 38.0MM WT/SCH 160 SS A182 F316/316L	30	30	
940		UJ2	OLETS	5504081	1.5	1.5	NIPOFLANGE 600# RF 40.0MM WT/SCH 160 SS A182 F316/316L	36	36	
950		UJ2	OLETS	5504540	1.5	1.5	NIPOFLANGE 600# RF SCH 45.0MM/160 SS A182 F316/316L	42	42	
960		UJ2	OLETS	5504082	1.5	1.5	NIPOFLANGE 600# RF 50.0MM WT/SCH 160 SS A182 F316/316L	48	48	
970										
970			OLETS	5509637	0.75	3	WELDOLET SCH 80S SS A182 F316/316L	2	8	
980			OLETS	5509638	0.75	8	WELDOLET SCH 80/80S SS A182 F316/316L	10	24	
990			OLETS	5509655	0.75	8	WELDOLET 38.0MM WT/ SCH 80S SS A182 F316/316L	30	30	
1000			OLETS	5509656	0.75	8	WELDOLET 40.0MM WT/ SCH 80S SS A182 F316/316L	36	36	
1010			OLETS	5509657	0.75	8	WELDOLET 50.0MM WT/ SCH 80S SS A182 F316/316L	48	48	
1020			OLETS	5509660	10	12	WELDOLET 38.0MM WT/ SCH 80 SS A182 F316/316L	30	30	
1030			OLETS	5509661	10	12	WELDOLET 40.0MM WT/ SCH 80 SS A182 F316/316L	36	36	
1040			OLETS	5509665	10	12	WELDOLET 50.0MM WT/ SCH 80 SS A182 F316/316L	48	48	
1050		U04	OLETS	5504375	1	1	WELDOLET FLAT BOTTOM SCH 80S SS A182 F316/F316L	0	0	
1060										
1060		UJ2	ELBOFLG	5516375	1.5	1.5	ELBOFLANGE 600# RF SCH 80S/160 SS A182 F316/316L	4	8	
1070		UJ2	ELBOFLG	5516376	1.5	1.5	ELBOFLANGE 600# RF SCH 80 /160 SS A182 F316/316L	10	24	
1080		UJ2	ELBOFLG	5516377	1.5	1.5	ELBOFLANGE 600# RF 33.0MM WT/160 SS A182 F316/316L	26	26	
1090		UJ2	ELBOFLG	5516380	1.5	1.5	ELBOFLANGE 600# RF 38.0MM WT/160 SS A182 F316/316L	30	30	
1100		UJ2	ELBOFLG	5516381	1.5	1.5	ELBOFLANGE 600# RF 40.0MM WT/160 SS A182 F316/316L	36	36	
1110		UJ2	ELBOFLG	5516383	1.5	1.5	ELBOFLANGE 600# RF 45.0MM WT/160 SS A182 F316/316L	42	42	
1120		UJ2	ELBOFLG	5516382	1.5	1.5	ELBOFLANGE 600# RF 50.0MM WT/160 SS A182 F316/316L	48	48	
1130										
1130			ELBOFLG	5509801	0.75	0.75	ELBOLET SCH 80/80S SS A182 F316/316L	16	16	
1140			ELBOFLG	5509800	2	2	ELBOLET SCH 80S/80S SS A182 F316/316L	8	8	
1150										
1150			OLETS	5537071	0.75	1.5	SOCKOLET 3000# SS A182 F316/316L	2	48	
1160			OLETS	5533235	0.75	1.5	SOCKOLET FLAT BOTTOM 3000# SS A182 F316/316L	0	0	
1170										
1170		UD7	OLETS	5515771	0.75	0.75	THREDOLET 3000# SS A182 F316/316L	2	48	
1180										

	TENGIZCHEVROIL TCO TENGIZ, KAZAKHSTAN	CONSTRUCTION	CORR.ALLOW.	SERVICE	MATERIAL	DATE	BY	REV	SHEET	PIPING LINE CLASS
		ALL SIZES - BUTT WELD SEAL WELDING - FOR THREADED CONNECTIONS ONLY PIPE BENDS - NONE THREAD SEALANT - PTFE PASTE	CORR. ALLOW. 1 MM	SOUR SERVICE - NACE MR0175/ ISO 15156, DESIGN - ASME B16.5 MG 2.2 CODE - ASME B31.3 FLUID CODES - PIM-SU-5112-TCO	MATERIAL: 316/316L SS DUAL GRADE FLANGE RATING: 600 RF TEMPERATURE RANGE: -120 / 180 °C	12/16/2024	BY OZAC	U04	Page 2 of 3	600P21

SEQ NO	REV	NOTE NO.	ITEM NAME	ITEM CODE	SIZE RANGE / SMALL END SIZES		DESCRIPTION	REFERENCE / LARGE END SIZES		NOTES
1180		816					***** FLANGES *****			
1190										
1190		FA8	TEE RED	5600660	0.5	0.5	FLG SCRD (FNPT) REDUCING 600# RF SS A182 F316/316L	0.75	1.5	
1200										
1200	U04		FLG ADAPTER	5851204	0.5	2	FLANGE ADAPTER 600# RF 316 SS X 12 MM TUBE	0	0	
1210										
1210			FLANGE	5582998	0.5	8	FLG WN 600# RF SS A182 F316/316L SCH 80S BORE	0	0	
1220			FLANGE	5582999	10	24	FLG WN 600# RF SS A182 F316/316L SCH 80 BORE	0	0	
1230			FLANGE	5583635	30	30	FLG WN 600# RF SS A182 F316/316L 38.0MM WT B16.47 SERIES A	0	0	
1240			FLANGE	5583632	36	36	FLG WN 600# RF SS A182 F316/316L 40.0MM WT B16.47 SERIES A	0	0	
1250			FLANGE	5583634	42	42	FLG WN 600# RF SS A182 F316/316L 45.0MM WT B16.47 SERIES A	0	0	
1260			FLANGE	5583633	48	48	FLG WN 600# RF SS A182 F316/316L 50.0MM WT B16.47 SERIES A	0	0	
1270	U04	817	FLANGE	5619807	26	26	FLG COMPACT 600# RJ SS A182 F316/316L WT 33.0MM	0	0	
1280	U04	817	FLANGE	5619808	30	30	FLG COMPACT 600# RJ SS A182 F316/316L WT 38.0MM	0	0	
1290	U04	817	FLANGE	5619809	36	36	FLG COMPACT 600# RJ SS A182 F316/316L WT 40.0MM	0	0	
1300	U04	817	FLANGE	5619810	42	42	FLG COMPACT 600# RJ SS A182 F316/316L WT 45.0MM	0	0	
1310	U04	817	FLANGE	5619811	48	48	FLG COMPACT 600# RJ SS A182 F316/316L WT 50.0MM	0	0	
1320		FS1	FLANGE	5583979	0.5	2	FLG WN 1500# RF SS A182 F316/316L SCH 80S BORE	0	0	
1330	U04	817	BLIND	5616567	2	2	FLG BLIND 1500# RTJ SS A182 F316/316L	0	0	
1340	U04	817	FLANGE	5583000	2	2	FLG WN 1500# RTJ SS A182 F316/316L SCH 80 BORE	0	0	
1350	U04	FS1,	FLANGE	5584167	0.5	1	FLG WN 2500# RTJ SS A182 F316/316L SCH 80S	0	0	
		817								
1360	U04	FS1	FLANGE	5583006	3	4	FLG WN 900# RF SS A182 F316/316L SCH 80S BORE	0	0	
1370	U04	817	FLANGE	5583213	3	4	FLG WN 900# RTJ SS A182 F316/316L SCH 80S BORE	0	0	
1380			BLIND	5616544	0.5	24	FLG BLIND 600# RF SS A182 F316/316L	0	0	
1390			BLIND	5616531	30	48	FLG BLIND 600# RF SS A182 F316/316L B16.47 SERIES A	0	0	
1400	U04	817	BLIND	5619715	26	48	FLG COMPACT BLIND 600# RJ SS A182 F316/316L PIPE CLASS 600P21	0	0	
1410										
1410							***** ORIFICE FLANGES *****			
1420										
1420			ORIFICE FLG	5640600	2	8	WN ORIF SET 600# RF SS A182 F316/316L SCH 80S BORE	0	0	
1430			ORIFICE FLG	5640601	10	24	WN ORIF SET 600# RF SS A182 F316/316L SCH 80 BORE	0	0	
1440										
1440							***** PIPE NIPPLES *****			
1450							***** GASKETS *****			
1460										
1460			GASKET	5673103	0.5	24	GASKET 600# 316SS SPIRAL WOUND GRAPHITE IR	0	0	
1470			GASKET	5674012	26	48	GASKET 600# 316SS KAMMPROFILE GRAPHITE ASME B16.47 SERIES A	0	0	
1480	U04	817	GASKET	5673420	26	48	GASKET 600# RJ INC 718 ENERGIZED SEALRING COMPACT FLANGE PIPE CLASS 600P21	0	0	
1490		815	GASKET	5672251	0.5	2	GASKET 1500# 316SS SPIRAL WOUND GRAPHITE IR	0	0	
1500	U04	817	GASKET	5674479	2	2	GASKET 1500# RTJ SS OCTAGONAL RING	0	0	
1510	U04	FS1,	GASKET	5674480	0.5	0.5	GASKET 2500# RTJ SS OCTAGONAL RING	0	0	
		817								
1520	U04	FS1,	GASKET	5674480	1	1	GASKET 2500# RTJ SS OCTAGONAL RING	0	0	
		817								
1530	U04	FS1	GASKET	5673117	3	4	GASKET 900# 316SS SPIRAL WOUND GRAPHITE IR	0	0	
1540	U04	817	GASKET	5674481	4	4	GASKET 900# RTJ SS OCTAGONAL RING	0	0	
1550										
1550		B1					***** BOLTING *****			
1560										
1560	U04	B22		5675770	0.5	99	STUD-BOLT A320 GR L7M/A194 GR 7M (S3) WITH 2 NUTS	0	0	
1570	U04	BA1	BOLTING	5675677	0.5	99	STUD-BOLT A320 GR B8M CLASS 2/A194 GR 8MA NUTS	0	0	
1580	U04	BA1	BOLTING	5675776	0.5	99	STUD-BOLT WITH 2 NUTS API-6A718	0	0	
1590	U04	BA5	BOLTING	5675778	26	99	STUD-BOLT C/W 2 COMPACT NUTS API-6A718	0	0	
1600										
1600							***** BLINDS & SPACERS *****			
1610										
1610			SPEC BLIND	5750423	0.75	8	SPECTACLE BLIND 600# RF SS A240 GR 316	0	0	
1620										
1620			PADDLE	5750523	10	24	PADDLE BLANK 600# RF SS A240 GR 316	0	0	
1630			PADDLE	5750528	30	48	PADDLE BLANK 600# RF SS A240 GR 316 B16.47 SERIES A	0	0	
1640			PADDLE	5750623	10	24	PADDLE SPACER 600# RF SS A240 GR 316	0	0	
1650			PADDLE	5750628	30	48	PADDLE SPACER 600# RF SS A240 GR 316 B16.47 SERIES A	0	0	
1660										
1670										
1670							***** MISCELLANEOUS *****			
1680										
1680	U04		FLG GUARD	5558883	2	6	SAFETY SHIELD PTFE SUITABLE FOR 600# FLANGE	0	0	

	TENGIZCHEVROIL TCO TENGIZ, KAZAKHSTAN	CONSTRUCTION	CORR.ALLOW.	SERVICE	MATERIAL	DATE	BY	REV	SHEET	PIPING LINE CLASS
		ALL SIZES - BUTT WELD SEAL WELDING - FOR THREADED CONNECTIONS ONLY PIPE BENDS - NONE THREAD SEALANT - PTFE PASTE	CORR. ALLOW. 1 MM	SOUR SERVICE - NACE MR0175/ ISO 15156, DESIGN - ASME B16.5 MG 2.2 CODE - ASME B31.3 FLUID CODES - PIM-SU-5112-TCO	MATERIAL: 316/316L SS DUAL GRADE FLANGE RATING: 600 RF TEMPERATURE RANGE: -120 / 180 °C	12/16/2024	BY OZAC	U04	Page 3 of 3	600P21