

SEQ NO	REV	NOTE NO.	ITEM NAME	ITEM CODE	SIZE RANGE / SMALL END SIZES		DESCRIPTION	REFERENCE / LARGE END SIZES		NOTES	
10							***** MODULAR VALVES *****			810	NIPPLE TO BE CUT FROM SCH 160 PIPE.
20										816	COMPACT FLANGES CAN BE USED FOR TIE-IN PURPOSE ONLY TO EXISTING PIPING AND EQUIPMENT.
20	U04		MODULAR DBB	K15AC02	0.5	1.5	MODULAR VALVE DB&B BALL TYPE 1500# RF LTCS A350 LF2 CL.1 INCONEL TRIM METAL LO - FULL SIZE TYPE 2BV	0	0		USE ONLY FOR TIE IN
30	U04		MODULAR DBB	K15AC06	2	2	MODULAR VALVE DB&B BALL TYPE 1500# RF LTCS A350 LF2 CL.1 INCONEL TRIM METAL LO - FULL SIZE TYPE 2BV	0	0	817	TO BE USED FOR LINES SUBJECT TO AIV OR WHERE REQUIRED BY STRESS.
40	U04	VAV	MODULAR DBB	K09AC06	3	3	MODULAR VALVE DB&B BALL TYPE 900# RF LTCS A350 LF2 CL.1 316 SS TRIM METAL LO FULL SIZE TYPE 2BV	0	0	821	
50	U04		MODULAR DBB	M15AC02	0.75	1.5	MODULAR VALVE DB&B BALL TYPE 1500# RF LTCS A350 LF2 CL.1 INCONEL TRIM METAL LO - CONTROLLED BORE TYPE 2BVR	0	0	B2	7/8" X 145MM BOLTS ONLY TO BE USED FOR 1 INCH 1500# PERAR BALL VALVES ITEM CODE B15AM10
60	U04		MODULAR DBB	M15AC06	2	2	MODULAR VALVE DB&B BALL TYPE 1500# RF LTCS A350 LF2 CL.1 INCONEL TRIM METAL LO - CONTROLLED BORE TYPE 2BVR	0	0	B5	7/8" X 155MM BOLTS ONLY TO BE USED FOR 1 INCH 1500# PERAR BALL VALVES ITEM CODE B15AC02 WHEREVER MATCHED WITH A SPECTACLE BLIND
70	U04	VAW	MODULAR DBB	M15EC02	0.75	2	MODULAR VALVE DB&B BALL TYPE 1500# RF LTCS A350 LF2 CL.1 INCONEL TRIM METAL LO REDUCING - CONTROLLED BORE TYPE R2BVR	1.5	3		
80	U04	VAW	MODULAR DBB	M09EC02	1	1	MODULAR VALVE DB&B BALL TYPE 900# X 1500# RF LTCS A350 LF2 CL.1 INCONEL TRIM METAL LO REDUCING - CONTROLLED BORE TYPE 2BVR	3	3	BA1	TO BE USED WITH RAISED FACE FLANGES ONLY.
90							***** BALL VALVES *****			BA5	TO BE USED WITH COMPACT FLANGES REQUIRING COMPACT NUTS ONLY. FOR FGP ONLY.
90		VB2									
100											
100	U04		BALL	A15AC05	2	2	BALL 1500# RF LTCS A350 LF2 CL.1 INCONEL TRIM TRUNNION SOFT RB LO	0	0	FA8	USE THREADED FLANGES FOR INSTRUMENT CONNECTIONS ONLY.
110	U04		BALL	A15AC06	2	2	BALL 1500# RF LTCS A350 LF2 CL.1 INCONEL TRIM TRUNNION METAL RB LO	0	0		
120	U04		BALL	A09AC05	3	3	BALL 900# RF LTCS A350 LF2 CL.1 316SS TRIM TRUNNION SOFT RB LO	0	0	FF5	FLAT BOTTOM NIPOF LANGES FOR USE ON WELD CAPS AND BLIND FLANGES
130	U04		BALL	A09AC06	3	3	BALL 900# RF LTCS A350 LF2 CL.1 316SS TRIM TRUNNION METAL RB LO	0	0		
140	U04		BALL	A09AC07	4	10	BALL 900# RF LTCS A350 LF2 CL.1 316SS TRIM TRUNNION SOFT RB GO	0	0	FS1	USE FLANGES, GASKETS & VALVES AS REQUIRED TO MATCH EQUIPMENT OR VESSEL NOZZLES.
150	U04		BALL	A09AC08	4	10	BALL 900# RF LTCS A350 LF2 CL.1 316SS TRIM TRUNNION METAL RB GO	0	0		
160	U04	817	BALL	A09CC07	12	24	BALL 900# CF LTCS A350 LF2 CL.1 316SS TRIM TRUNNION SOFT RB GO	0	0		
170	U04	817	BALL	A09CC08	12	24	BALL 900# CF LTCS A350 LF2 CL.1 316SS TRIM TRUNNION METAL RB GO	0	0	GA6	SPECIAL GASKET ONLY FOR USE AS SPECIFIED IN ENG-200-117
180	U04		BALL	B15AC01	0.75	1.5	BALL 1500# RF LTCS A350 LF2 CL.1 INCONEL TRIM FLOATING SOFT FB LO	0	0		
190	U04		BALL	B15AC02	0.75	1.5	BALL 1500# RF LTCS A350 LF2 CL.1 INCONEL TRIM FLOATING METAL FB LO	0	0	ND9	USE ONLY WITH CONSENT OF MATERIALS ENGINEER.
200	U04	VA5	BALL	B15AC05	2	2	BALL 1500# RF LTCS A350 LF2 CL.1 INCONEL TRIM TRUNNION SOFT FB LO	0	0		
210	U04	VA5	BALL	B15AC06	2	2	BALL 1500# RF LTCS A350 LF2 CL.1 INCONEL TRIM TRUNNION METAL FB LO	0	0	SB5	USE JACK SCREWS ONLY WHERE PIPING CAN NOT BE OPENED WITH FLANGE SPREADER.
220	U04	VA5	BALL	B09AC05	3	3	BALL 900# RF LTCS A350 LF2 CL.1 316SS TRIM TRUNNION SOFT FB GO	0	0		
230	U04	VA5	BALL	B09AC06	3	3	BALL 900# RF LTCS A350 LF2 CL.1 316SS TRIM TRUNNION METAL FB GO	0	0	UD7	USE THREDOLET AND SCREWED PLUG FOR HYDROSTATIC TEST VENTS AND DRAINS. SEAL WELD AFTER HYDROSTATIC TEST
240	U04	VA5	BALL	B09AC07	3	10	BALL 900# RF LTCS A350 LF2 CL.1 316SS TRIM TRUNNION SOFT FB GO	0	0		
250	U04	VA5	BALL	B09AC08	3	10	BALL 900# RF LTCS A350 LF2 CL.1 316SS TRIM TRUNNION METAL FB GO	0	0		
260	U04	817	BALL	B09CC07	12	24	BALL 900# CF LTCS A350 LF2 CL.1 316SS TRIM TRUNNION SOFT FB GO	0	0	UJ2	USE 1 1/2IN WITH THERMOWELL CONNECTIONS ONLY & 3/4IN (IF SHOWN) FOR DBB PRESSURE CONNECTIONS WITH CHEMICAL SEALS.
270	U04	817	BALL	B09CC08	12	24	BALL 900# CF LTCS A350 LF2 CL.1 316SS TRIM TRUNNION METAL FB GO	0	0		
280							***** GATE VALVES *****			UJ3	USE 3IN WITH THERMOWELL CONNECTIONS ONLY
290											
290	U04		GATE	G15AC48	0.75	1.5	GATE 1500# RF LTCS A350 LF2 CL.1 TRIM 16 WEDGE HW	0	0		
300			GATE	V15AC41	2	2	GATE PARALLEL SLIDE 1500# RF LTCS A352 LCC TRIM 16 HW	0	0	UK9	DO NOT USE FOR ORIFICE FLANGE TAP ASSEMBLIES.
310			GATE	V09AC41	3	4	GATE PARALLEL SLIDE 900# RF LTCS A352 LCC TRIM 16 HW	0	0		
320			GATE	V09AC42	6	8	GATE PARALLEL SLIDE 900# RF LTCS A352 LCC TRIM 16 GO	0	0	VA5	USE THESE VALVES ONLY WHERE SPECIFIED ON PIPING AND INSTRUMENT DIAGRAMS
330	U04		GATE	W09AC71	6	6	GATE 900# RF LTCS A352 LCC 316 SS TRIM THROUGH COND SOLID SLAB GO	0	0	VAV	USAGE IS LIMITED TO INSTRUMENT ISOLATION PURPOSE.
340							***** BUTTERFLY VALVES *****			VAW	VALVE ONLY TO BE USED IN ACCORDANCE WITH DOCUMENT L-ST-2055 - VENT DRAIN AND INSTRUMENT CONNECTION DETAILS.
340											
350											
350		ZA8	BUTTERFLY	T09AC61	10	10	BUTTERFLY 900# RF LTCS A352 LCC INC TRIM TOV METAL DBL FLG SHORT PAT GO	0	0		
360		ZA8	BUTTERFLY	T09CC61	12	30	BUTTERFLY 900# COMPACT FLANGE LTCS A352 LCC INC TRIM TOV METAL DBL FLG SHORT PAT GO	0	0	VB2	SOFT SEATED BALL VALVES ARE LIMITED TO MAXIMUM TEMPERATURE OF 200°C.
370							***** GLOBE VALVES *****			VC1	SPRING PISTON CHECK VALVES ARE PREFERRED IN THE HORIZONTAL POSITION, BUT MAY BE USED IN THE VERTICAL POSITION WITH ENGINEERING APPROVAL.
370											
380	U04		GLOBE	L15AC48	0.75	1.5	GLOBE 1500# RF LTCS A350 LF2 CL.1 INCONEL OS&Y HW	0	0		
390	U04		GLOBE	L15AC41	2	2	GLOBE 1500# RF LTCS A352 LCC INCONEL OS&Y HW	0	0		
400			GLOBE	L09AC41	3	3	GLOBE 900# RF LTCS A352 LCC TRIM 16 OS&Y HW	0	0		
410			GLOBE	L09AC42	4	8	GLOBE 900# RF LTCS A352 LCC TRIM 16 OS&Y GO	0	0	ZA8	*****TO BE USED IN STEAM AND CONDENSATE SERVICE ONLY*****
420							***** CHECK VALVES *****				
420											
430											
430	U04	VC1	CHECK	C15AC50	0.75	1.5	CHECK PISTON 1500# RF LTCS A350 LF2 CL.1 TRIM 16	0	0		
440	U04		CHECK	C15AC45	2	2	CHECK DUAL WAFER LUG 1500# RF LTCS A352 LCC INCONEL TRIM THROU BOLTED	0	0		
450			CHECK	C09AC45	3	8	CHECK DUAL WAFER LUG 900# RF LTCS A352 LCC TRIM 16 THROU BOLTED	0	0		
460			CHECK	C09AC52	10	10	CHECK DUAL DBL FLG 900# RF LTCS A352 LCC TRIM 16	0	0		
470	U04	817	CHECK	C09CC52	12	24	CHECK DUAL DBL FLG 900# CF LTCS A352 LCC TRIM 16	0	0		
480							*****PIPES*****				
480											
490											
490			PIPE	5358508	0.75	1.5	PIPE SCH XS SMLS LTCS A333 GR.6 PE	0	0		
500	U04	UK9	PIPE	5358511	0.75	0.75	PIPE SCH XXS SMLS LTCS A333 GR.6 PE	0	0		
510			PIPE	5358514	2	3	PIPE SCH XS SMLS LTCS A333 GR.6 BE	0	0		
520			PIPE	5358510	4	16	PIPE SCH 120 SMLS LTCS A333 GR.6 BE	0	0		
530			PIPE	5358600	18	24	PIPE SCH 120 EFW LTCS A671 CC60 CL.22 BE	0	0		

	TENGIZCHEVROIL TCO TENGIZ, KAZAKHSTAN	CONSTRUCTION	CORR.ALLOW.	SERVICE	MATERIAL	DATE	BY	REV	SHEET	PIPING LINE CLASS
		ALL SIZES - BUTT WELD PWHT FOR WT >19 MM SEAL WELDING - FOR THREADED CONNECTIONS ONLY PIPE BENDS - NONE THREAD SEALANT - PTFE PASTE	CORR. ALLOW: 1.5 MM	SOUR SERVICE - NACE MR0175/ ISO 15156 DESIGN: ASME B16.5 MG 1.1 CODE: ASME B31.3 FLUID CODES - PIM-SU-5112-TCO	MATERIAL: LTCS FLANGE RATING: 900 RF/CF TEMPERATURE RANGE: -40 / 410 °C	12/16/2024	BY OZAC	U04	Page 1 of 3	900H21

SEQ NO	REV	NOTE NO.	ITEM NAME	ITEM CODE	SIZE RANGE / SMALL END SIZES		DESCRIPTION	REFERENCE / LARGE END SIZES		NOTES
540			PIPE	5358640	30	30	PIPE WT 49.0MM EFW LTCS A671 CC60 CL.22 BE	0	0	
550		810	PIPE	5358512	0.75	1.5	PIPE SCH 160 SMLS LTCS A333 GR.6 PE	0	0	
560										
560							***** FITTINGS *****			
570										
570			ELBOW	5392600	0.75	3	ELL BW 90 DEG LR SCH XS LTCS A420 WPL6	0	0	
580	U04	ND9	ELBOW	5392816	0.75	0.75	ELL BW 90 DEG LR SCH 160 LTCS A420 WPL6	0	0	
590	U04	UK9	ELBOW	5392815	0.75	0.75	ELL BW 90 DEG LR SCH XXS LTCS A420 WPL6	0	0	
600			ELBOW	5392700	4	16	ELL 90 DEG LR SCH 120 LTCS A420 WPL6	0	0	
610			ELBOW	5392388	18	24	ELL 90 DEG LR SCH 120 LTCS A420 WPL6-W	0	0	
620			ELBOW	5392567	30	30	ELL 90 DEG LR WT 49.0MM LTCS A420 WPL6-W	0	0	
630			ELBOW	5392606	0.75	3	ELL BW 45 DEG LR SCH XS LTCS A420 WPL6	0	0	
640	U04	ND9	ELBOW	5392822	0.75	0.75	ELL BW 45 DEG LR SCH 160 LTCS A420 WPL6	0	0	
650	U04	UK9	ELBOW	5392831	0.75	0.75	ELL BW 45 DEG LR SCH XXS LTCS A420 WPL6	0	0	
660			ELBOW	5392701	4	16	ELL BW 45 DEG LR SCH 120 LTCS A420 WPL6	0	0	
670			ELBOW	5392392	18	24	ELL 45 DEG LR SCH 120 LTCS A420 WPL6-W	0	0	
680			ELBOW	5392568	30	30	ELL 45 DEG LR WT 49.0MM LTCS A420 WPL6-W	0	0	
690										
690			TEE	5392609	0.75	3	TEE BW SCH XS LTCS A420 WPL6	0	0	
700	U04	UK9	TEE	5392879	0.75	0.75	TEE SCH XXS LTCS A420 WPL6	0	0	
710			TEE	5392702	4	16	TEE BW SCH 120 LTCS A420 WPL6	0	0	
720			TEE	5392404	18	24	TEE BW SCH 120 LTCS A420 WPL6-W	0	0	
730			TEE RED	5392661	0.75	2	TEE RED BW SCH XS LTCS A420 WPL6	1	3	
740			TEE RED	5392466	1.5	3	TEE RED BW SCH 120/XS LTCS A420 WPL6	4	6	
750			TEE RED	5392603	4	14	TEE RED SCH 120 LTCS A420 WPL6	6	16	
760			TEE RED	5392878	8	20	TEE RED SCH 120 LTCS A420 WPL6-W	18	24	
770			TEE RED	5392888	10	24	TEE RED 49.0MM WT / SCH 120 LTCS A420 WPL6-W	30	30	
780										
780			CAP	5392610	0.75	3	CAP BW SCH XS LTCS A420 WPL6	0	0	
790			CAP	5392703	4	24	CAP SCH 120 LTCS A420 WPL6	0	0	
800										
800			RED CONC	5392458	0.75	2	REDUCER CONC SCH XS LTCS A420 WPL6	1	3	
810			RED CONC	5392706	2	3	REDUCER CONC SCH 120/XS LTCS A420 WPL6	4	6	
820	U04	821		5392467	2	2	REDUCER CONC SCH 120/160 LTCS A420 WPL6	4	4	
830			RED CONC	5392704	4	14	REDUCER CONC SCH 120 LTCS A420 WPL6	6	16	
840			RED CONC	5392707	10	20	REDUCER CONC SCH 120 LTCS A420 WPL6-W	18	24	
850			RED CONC	5392736	24	24	REDUCER CONC WT 49.0MM/SCH 120 LTCS A420 WPL6-W	30	30	
860			RED ECC	5392612	0.75	2	REDUCER ECC SCH XS LTCS A420 WPL6	1	3	
870	U04			5392468	2	2	REDUCER ECC SCH 120/160 LTCS A420 WPL6	4	4	
880	U04		RED ECC	5392708	2	3	REDUCER ECC SCH 120/XS LTCS A420 WPL6	4	6	
890			RED ECC	5392705	4	14	REDUCER ECC SCH 120 LTCS A420 WPL6	6	16	
900			RED ECC	5392709	10	20	REDUCER ECC SCH 120 LTCS A420 WPL6-W	18	24	
910			RED ECC	5392738	24	24	REDUCER ECC WT 49.0MM/SCH 120 LTCS A420 WPL6-W	30	30	
920										
920	U04		OLETS	5504160	0.75	1	NIPOFLANGE 1500# RF SCH XS LTCS A350 LF2 CL.1	2	3	
930	U04		OLETS	5504161	0.75	2	NIPOFLANGE 1500# RF SCH 120/XS LTCS A350 LF2 CL.1	4	24	
940	U04		OLETS	5504193	0.75	2	NIPOFLANGE 1500# RF WT 49.0MM/XS LTCS A350 LF2 CL.1	30	30	
950	U04	UJ2	OLETS	5504163	1.5	1.5	NIPOFLANGE 1500# RF SCH 120/160 LTCS A350 LF2 CL.1	4	24	
960	U04	UJ3	OLETS	5504365	3	3	NIPOFLANGE 1500# RF SCH 120/160 LTCS A350 LF2 CL.1	14	14	
970	U04	UJ2	OLETS	5504320	1.5	3	NIPOFLANGE 1500# RF WT 49.0MM/160 LTCS A350 LF2 CL.1	30	30	
980	U04		OLETS	5504030	0.75	0.75	NIPOFLANGE 1500# RTJ SCH 120/XS LTCS A350 LF2 CL.1	4	4	
990	U04			5505324	3	3	NIPOFLANGE 900# RF SCH 120/160 LTCS A350 LF2 CL.1	12	20	
1000	U04			5505326	3	3	NIPOFLANGE 900# RF SCH 120/XS LTCS A350 LF2 CL.1	12	20	
1010	U04	UJ3	OLETS	5505323	3	3	NIPOFLANGE 900# RF WT 49.0MM/160 LTCS A350 LF2 CL.1	30	30	
1020	U04	FF5	OLETS	5504000	0.75	1.5	NIPOFLANGE FLAT BOTTOM 1500# RF SCH XS LTCS A350 LF2 CL.1	0	0	
1030										
1030	U04		OLETS	5505335	0.75	1	WELDOLET SCH XS LTCS A350 LF2 CL.1	2	3	
1040	U04		OLETS	5505626	1	3	WELDOLET WT 49.0MM/SCH XS LTCS A350 LF2 CL.1	30	30	
1050	U04		OLETS	5505194	0.75	3	WELDOLET SCH 120/XS LTCS A350 LF2 CL.1	4	24	
1060	U04		OLETS	5505195	4	8	WELDOLET SCH 120 LTCS A350 LF2 CL.1	14	24	
1070	U04		OLETS	5504374	1	1.5	WELDOLET FLAT BOTTOM SCH XS LTCS A350 LF2 CL.1	0	0	
1080										
1080	U04	UJ2	ELBOFLG	5516082	1.5	1.5	ELBOFLANGE 1500# RF SCH 120/160 LTCS A350 LF2 CL.1	4	24	
1090										
1090							***** OLETS *****			
1100										
1100	U04		OLETS	5533072	0.75	1.5	SOCKOLET 3000# LTCS A350 LF2 CL.1	2	24	
1110	U04		OLETS	5533232	0.75	1.5	SOCKOLET FLAT BOTTOM 3000# LTCS A350 LF2 CL.1	0	0	
1120										
1120	U04	UD7	OLETS	5514772	0.75	0.75	THREDOLET 3000# LTCS A350 LF2 CL.1	2	24	
1130										
1140							***** COUPLINGS, UNIONS & PLUGS *****			

	TENGIZCHEVROI TCO TENGIZ, KAZAKHSTAN	CONSTRUCTION	CORR.ALLOW.	SERVICE	MATERIAL	DATE	BY	REV	SHEET	PIPING LINE CLASS
		ALL SIZES - BUTT WELD PWHT FOR WT >19 MM SEAL WELDING - FOR THREADED CONNECTIONS ONLY PIPE BENDS - NONE THREAD SEALANT - PTFE PASTE	CORR. ALLOW: 1.5 MM	SOUR SERVICE - NACE MR0175/ ISO 15156 DESIGN: ASME B16.5 MG 1.1 CODE: ASME B31.3 FLUID CODES - PIM-SU-5112-TCO	MATERIAL: LTCS FLANGE RATING: 900 RF/CF TEMPERATURE RANGE: -40 / 410 °C	12/16/2024	BY OZAC	U04	Page 2 of 3	900H21

SEQ NO	REV	NOTE NO.	ITEM NAME	ITEM CODE	SIZE RANGE / SMALL END SIZES		DESCRIPTION	REFERENCE / LARGE END SIZES		NOTES
1140			COUPLING	5478705	0.75	1.5	COUPLING 3000# SW LTCS A350 LF2	0	0	
1150	U04		TEE RED	5478709	0.75	1	COUPLING RED 3000# SW LTCS A350 LF2 CL.1	1	1.5	
1160										
1160	U04		UNION	5478706	0.75	1.5	UNION 3000# SW LTCS A350 LF2 CL.1	0	0	
1170										
1170	U04	UD7	FITTING SCRD	5491303	0.75	0.75	PLUG ROUND HEAD SCRD LTCS A350 LF2 CL.1	0	0	
1180										
1180		816					***** FLANGES *****			
1190										
1190	U04	FA8	FLANGE	5599704	0.5	0.5	FLG SCRD (FNPT) REDUCING 1500# RF LTCS A350 LF2 CL.1	0.75	1.5	
1200										
1200		VA5	FLG ADAPTER	5851205	0.75	2	FLANGE ADAPTER 1500# RF 316 SS X 12 MM TUBE	0	0	
1210										
1210	U04		FLANGE	5557393	0.75	2	FLG WN 1500# RF LTCS A350 LF2 CL.1 SCH XS	0	0	
1220	U04	FS1	FLANGE	5557395	4	4	FLG WN 1500# RF LTCS A350 LF2 CL.1 SCH 120 BORE	0	0	
1230	U04		FLANGE	5557397	0.75	2	FLG WN 1500# RF LTCS A350 LF2 CL.1 SCH 160 BORE	0	0	
1240	U04	UK9	FLANGE	5557505	0.75	0.75	FLG WN 1500# RF LTCS A350 LF2 CL.1 SCH XXS BORE	0	0	
1250	U04	817	FLANGE	5557507	1	2	FLG WN 1500# RTJ LTCS A350 LF2 CL.1 SCH XS	0	0	
1260	U04		FLANGE	5557141	3	3	FLG WN 900# RF LTCS A350 LF2 CL.1 SCH XS	0	0	
1270	U04		FLANGE	5557143	4	24	FLG WN 900# RF LTCS A350 LF2 CL.1 SCH 120 BORE	0	0	
1280	U04		FLANGE	5556499	30	30	FLG WN 900# RF LTCS A350 LF2 CL.1 WT 49.0MM B16.47 SERIES A	0	0	
1290	U04	817	FLANGE	5619821	12	24	FLG COMPACT 900# RJ LTCS A350 LF2 CL.1 SCH 120 BORE	0	0	
1300	U04	817	FLANGE	5619819	30	30	FLG COMPACT 900# RJ LTCS A350 LF2 CL.1 WT 49.0MM	0	0	
1310	U04		BLIND	5615616	0.5	2	FLG BLIND 1500# RF LTCS A350 LF2 CL.1	0	0	
1320	U04	817	BLIND	5615614	1	1	FLG BLIND 1500# RTJ LTCS A350 LF2 CL.1	0	0	
1330	U04		BLIND	5615605	3	24	FLG BLIND 900# RF LTCS A350 LF2 CL.1	0	0	
1340	U04	817	BLIND	5619770	12	30	FLG COMPACT BLIND 900# RJ LTCS A350 LF2 CL.1 PIPE CLASS 900H21	0	0	
1350	U04	817	BLIND	9619758	2	2	FLG COMPACT BLIND 10000# RJ LTCS A694 F60 PIPE CLASS 10000H5A - 2 INCH ONLY	0	0	
1360	U04	817	BLIND	5619756	6	6	FLG COMPACT BLIND 10000# RJ 2-1/4CR F22M PIPE CLASS 10000F22 FOR NPS 4 INCH & ABOVE	0	0	
1370										
1370							***** ORIFICE FLANGES *****			
1380										
1380	U04		ORIFICE FLG	5624599	2	2	WN ORIF SET 1500# RF LTCS A350 LF2 CL.1 SCH XS	0	0	
1390	U04		ORIFICE FLG	5624540	3	3	WN ORIF SET 900# RF LTCS A350 LF2 CL.1 SCH XS	0	0	
1400	U04		ORIFICE FLG	5624532	4	24	WN ORIF SET 900# RF LTCS A350 SCH 120 BORE	0	0	
1410	U04	817	ORIFICE FLG	5624538	12	24	WN ORIF SET COMPACT 900# RJ LTCS A350 SCH 120 BORE	0	0	
1420										
1420							***** PIPE NIPPLES *****			
1430										
1430		810		0			NIPPLE PBE TO BE CUT FROM PIPE			
1440										
1440							***** GASKETS *****			
1450										
1450			GASKET	5672251	0.5	4	GASKET 1500# 316SS SPIRAL WOUND GRAPHITE IR	0	0	
1460	U04	GA6	GASKET	5673021	2	2	GASKET 1500# 316SS KAMMPROFILE GRAPHITE ASME B16.5	0	0	
1470			GASKET	5673117	3	24	GASKET 900# 316SS SPIRAL WOUND GRAPHITE IR	0	0	
1480			GASKET	5674033	30	30	GASKET 900# 316SS KAMMPROFILE GRAPHITE ASME B16.47 SERIES A	0	0	
1490	U04	817	GASKET	5673440	12	30	GASKET 900# RJ INC 718 ENERGIZED SEALRING COMPACT FLANGE PIPE CLASS 900H21	0	0	
1500	U04	817	GASKET	5674479	1	2	GASKET 1500# RTJ SS OCTAGONAL RING	0	0	
1510	U04	817	GASKET	5673550	6	6	GASKET 10000# RJ INC 718 ENERGIZED SEALRING COMPACT FLANGE PIPE CLASS 10000F22 FOR NPS 4 INCH & ABOVE	0	0	
1520										
1520							***** BOLTING *****			
1530										
1530			BOLTING	5675770	0.5	20	STUD-BOLT A320 GR L7M/A194 GR 7M (S3) WITH 2 NUTS	0	0	
1540		BA1	BOLTING	5675776	24	99	STUD-BOLT WITH 2 NUTS API-6A718	0	0	
1550										
1550		BA5	BOLTING	5675778	6	99	STUD-BOLT/COMPACT NUT API-6A718	0	0	
1560										
1560		SB5					***** BLINDS & SPACERS *****			
1570										
1570			SPEC BLIND	5749595	0.75	2	SPECTACLE BLIND 1500# RF LTCS A516 GR.70	0	0	
1580			SPEC BLIND	5749596	3	8	SPECTACLE BLIND 900# RF LTCS A516 GR.70	0	0	
1590										
1590		VA5	PADDLE	5750102	10	24	PADDLE BLANK 900# RF LTCS A516 GR.70	0	0	
1600		VA5	PADDLE	5750202	10	24	PADDLE SPACER 900# RF LTCS A516 GR.70	0	0	
1610	U04	817	PADDLE	5750264	12	30	PADDLE BLANK COMPACT 900# RJ LTCS A516 GR.70	0	0	
1620	U04	817	PADDLE	5750265	12	30	PADDLE SPACER COMPACT 900# RJ LTCS A516 GR.70	0	0	
1630	U04		PADDLE	5750104	30	30	PADDLE BLANK 900# RF LTCS A516 GR.70 B16.47 SERIES A	0	0	
1640	U04		PADDLE	5750204	30	30	PADDLE SPACER 900# RF LTCS A516 GR.70 B16.47 SERIES A	0	0	
1650										

	TENGIZCHEVROI TCO TENGIZ, KAZAKHSTAN	CONSTRUCTION	CORR.ALLOW.	SERVICE	MATERIAL	DATE	BY	REV	SHEET	PIPING LINE CLASS
		ALL SIZES - BUTT WELD PWHT FOR WT >19 MM SEAL WELDING - FOR THREADED CONNECTIONS ONLY PIPE BENDS - NONE THREAD SEALANT - PTFE PASTE	CORR. ALLOW: 1.5 MM	SOUR SERVICE - NACE MR0175/ ISO 15156 DESIGN: ASME B16.5 MG 1.1 CODE: ASME B31.3 FLUID CODES - PIM-SU-5112-TCO	MATERIAL: LTCS FLANGE RATING: 900 RF/CF TEMPERATURE RANGE: -40 / 410 °C	12/16/2024	BY OZAC	U04	Page 3 of 3	900H21