

SEQ NO	REV	NOTE NO.	ITEM NAME	ITEM CODE	SIZE RANGE / SMALL END SIZES		DESCRIPTION	REFERENCE / LARGE END SIZES		NOTES	
10							***** VALVES *****			817	USE ONLY FOR TIE IN
20							***** MODULAR VALVES *****			B1	ALL BOLTS ARE METRIC DIA.
30										B2	7/8" X 145MM BOLTS ONLY TO BE USED FOR 1 INCH 1500# PERAR BALL VALVES ITEM CODE B15AM10
30	U04		MODULAR DBB	K15AC02	0.5	1.5	MODULAR VALVE DB&B BALL TYPE 1500# RF LTCS A350 LF2 CL.1 INCONEL TRIM METAL LO - FULL SIZE TYPE 2BV	0	0		
40	U04		MODULAR DBB	K15AC06	2	2	MODULAR VALVE DB&B BALL TYPE 1500# RF LTCS A350 LF2 CL.1 INCONEL TRIM METAL LO - FULL SIZE TYPE 2BV	0	0	FF5	FLAT BOTTOM NIPOFLANGES FOR USE ON WELD CAPS AND BLIND FLANGES
50	U04	VAV	MODULAR DBB	K09AC06	3	3	MODULAR VALVE DB&B BALL TYPE 900# RF LTCS A350 LF2 CL.1 316 SS TRIM METAL LO FULL SIZE TYPE 2BV	0	0	NT5	TO BE USED IN NON-PIGGED LINES ONLY
60	U04		MODULAR DBB	M15AC02	0.75	1.5	MODULAR VALVE DB&B BALL TYPE 1500# RF LTCS A350 LF2 CL.1 INCONEL TRIM METAL LO - CONTROLLED BORE TYPE 2BVR	0	0	UJ2	USE 1 1/2IN WITH THERMOWELL CONNECTIONS ONLY & 3/4IN (IF SHOWN) FOR DBB PRESSURE CONNECTIONS WITH CHEMICAL SEALS.
70	U04		MODULAR DBB	M15AC06	2	2	MODULAR VALVE DB&B BALL TYPE 1500# RF LTCS A350 LF2 CL.1 INCONEL TRIM METAL LO - CONTROLLED BORE TYPE 2BVR	0	0	VA5	USE THESE VALVES ONLY WHERE SPECIFIED ON PIPING AND INSTRUMENT DIAGRAMS
80	U04	VAW	MODULAR DBB	M15EC02	0.75	1	MODULAR VALVE DB&B BALL TYPE 1500# RF LTCS A350 LF2 CL.1 INCONEL TRIM METAL LO REDUCING - CONTROLLED BORE TYPE R2BVR	2	2	VAV	USAGE IS LIMITED TO INSTRUMENT ISOLATION PURPOSE.
90	U04	VAW	MODULAR DBB	M09EC02	1	1	MODULAR VALVE DB&B BALL TYPE 900# X 1500# RF LTCS A350 LF2 CL.1 INCONEL TRIM METAL LO REDUCING - CONTROLLED BORE TYPE 2BVR	3	3	VAW	VALVE ONLY TO BE USED IN ACCORDANCE WITH DOCUMENT L-ST-2055 - VENT DRAIN AND INSTRUMENT CONNECTION DETAILS.
100		VB2					***** BALL VALVES *****			VB2	SOFT SEATED BALL VALVES ARE LIMITED TO MAXIMUM TEMPERATURE OF 200°C.
100										VC1	SPRING PISTON CHECK VALVES ARE PREFERRED IN THE HORIZONTAL POSITION, BUT MAY BE USED IN THE VERTICAL POSITION WITH ENGINEERING APPROVAL.
110	U04		BALL	A15AC05	2	2	BALL 1500# RF LTCS A350 LF2 CL.1 INCONEL TRIM TRUNNION SOFT RB LO	0	0		
120	U04		BALL	A15AC06	2	2	BALL 1500# RF LTCS A350 LF2 CL.1 INCONEL TRIM TRUNNION METAL RB LO	0	0		
130	U04		BALL	A09AC05	3	3	BALL 900# RF LTCS A350 LF2 CL.1 316SS TRIM TRUNNION SOFT RB LO	0	0		
140	U04		BALL	A09AC06	3	3	BALL 900# RF LTCS A350 LF2 CL.1 316SS TRIM TRUNNION METAL RB LO	0	0		
150	U04		BALL	A09AC07	4	10	BALL 900# RF LTCS A350 LF2 CL.1 316SS TRIM TRUNNION SOFT RB GO	0	0		
160	U04		BALL	A09AC08	4	10	BALL 900# RF LTCS A350 LF2 CL.1 316SS TRIM TRUNNION METAL RB GO	0	0		
170	U04	VA5	BALL	B15AC01	0.75	1.5	BALL 1500# RF LTCS A350 LF2 CL.1 INCONEL TRIM FLOATING SOFT FB LO	0	0		
180	U04	VA5	BALL	B15AC02	0.75	1.5	BALL 1500# RF LTCS A350 LF2 CL.1 INCONEL TRIM FLOATING METAL FB LO	0	0		
190	U04	VA5	BALL	B15AC05	2	2	BALL 1500# RF LTCS A350 LF2 CL.1 INCONEL TRIM TRUNNION SOFT FB LO	0	0		
200	U04	VA5	BALL	B15AC06	2	2	BALL 1500# RF LTCS A350 LF2 CL.1 INCONEL TRIM TRUNNION METAL FB LO	0	0		
210	U04	VA5	BALL	B09AC07	3	10	BALL 900# RF LTCS A350 LF2 CL.1 316SS TRIM TRUNNION SOFT FB GO	0	0		
220	U04	VA5	BALL	B09AC08	3	10	BALL 900# RF LTCS A350 LF2 CL.1 316SS TRIM TRUNNION METAL FB GO	0	0		
230							***** RISING STEM BALL VALVES *****				
230											
240											
240	U04	VA5	BALL	R15AC06	2	2	BALL RISING STEM 1500# RF LTCS A352 LCC INCONEL TRIM METAL RB HO	0	0		
250		VA5	BALL	R09AC06	3	4	BALL RISING STEM 900# RF LTCS A352 LCC 316SS TRIM METAL RB HO	0	0		
260		VA5	BALL	R09AC08	6	6	BALL RISING STEM 900# RF LTCS A352 LCC 316SS TRIM METAL RB GO	0	0		
270							***** GATE VALVES *****				
270											
280	U04		GATE	G15AC48	0.75	1.5	GATE 1500# RF LTCS A350 LF2 CL.1 INCONEL TRIM WEDGE HW	0	0		
290			GATE	W09AC70	3	4	GATE 900# RF LTCS A352 LCC 316 SS TRIM THROUGH COND SOLID SLAB HW	0	0		
300			GATE	W09AC71	6	10	GATE 900# RF LTCS A352 LCC 316 SS TRIM THROUGH COND SOLID SLAB GO	0	0		
310							***** BUTTERFLY VALVES *****				
310											
320			BUTTERFLY	T09AC61	10	10	BUTTERFLY 900# RF LTCS A352 LCC INC TRIM TOV METAL DBL FLG SHORT PAT GO	0	0		
330							***** CHECK VALVES *****				
330											
340	U04	VC1	CHECK	C15AC50	0.75	1.5	CHECK PISTON 1500# RF LTCS A350 LF2 CL.1 INCONEL TRIM	0	0		
350	U04		CHECK	C15AC45	2	2	CHECK DUAL WAFER LUG 1500# RF LTCS A352 LCC INCONEL TRIM THROU BOLTED	0	0		
360			CHECK	C09AC45	3	8	CHECK DUAL WAFER LUG 900# RF LTCS A352 LCC TRIM 16 THROU BOLTED	0	0		
370			CHECK	C09AC52	10	10	CHECK DUAL DBL FLG 900# RF LTCS A352 LCC TRIM 16	0	0		
380							***** GLOBE VALVES *****				
380											
390	U04		GLOBE	L15AC48	0.75	1.5	GLOBE 1500# RF LTCS A350 LF2 CL.1 INCONEL OS&Y HW	0	0		
400	U04		GLOBE	L15AC41	2	2	GLOBE 1500# RF LTCS A352 LCC INCONEL OS&Y HW	0	0		
410			GLOBE	L09AC41	3	3	GLOBE 900# RF LTCS A352 LCC TRIM 16 OS&Y HW	0	0		
420			GLOBE	L09AC42	4	8	GLOBE 900# RF LTCS A352 LCC TRIM 16 OS&Y GO	0	0		
430							*****PIPE ABOVE GROUND*****				
430											
440			PIPE	5358512	0.75	1.5	PIPE SCH 160 SMLS LTCS A333 GR.6 PE	0	0		
450			PIPE	5358515	2	3	PIPE SCH 160 SMLS LTCS A333 GR.6 BE	0	0		
460											
460			PIPE	9001257	4	4	LINEPIPE SMLS WT= 6.02 MM API-5L X60 BE	0	0		
470			PIPE	9001255	6	6	LINEPIPE SMLS WT= 7.11 MM API-5L X60 BE	0	0		
480							***** PIPE BELOW GROUND*****				
480											

	TENGIZCHEVROI TCO TENGIZ, KAZAKHSTAN	CONSTRUCTION	CORR.ALLOW.	SERVICE	MATERIAL	DATE	BY	REV	SHEET	PIPING LINE CLASS
		ALL SIZES - BUTT WELD SEAL WELDING - REQUIRED PIPE BENDS - INDUCTION BENDS THREAD SEALANT - PTFE PASTE	CORR. ALLOW. 1.5 MM	DESIGN: ASME B16.5 MG 1.1 CODE: ASME B31.8 ABOVE GROUND FACTOR = 0.5 BELOW GROUND FACTOR = 0.6 MAX. DESIGN PARAMETER = 132 BARG. @ 80 DEG.C. (LIMITED BY PIPE WT) FLUID CODES - PIM-SU-5112-TCO	MATERIAL: LTCS FLANGE RATING: 900 RF/CF TEMPERATURE RANGE: -40 / 80 °C	12/16/2024	BY OZAC	U04	Page 1 of 3	900H5H

SEQ NO	REV	NOTE NO.	ITEM NAME	ITEM CODE	SIZE RANGE / SMALL END SIZES		DESCRIPTION	REFERENCE / LARGE END SIZES		NOTES
490										
490	U04		PIPE	9006227CTD	2	2	PIPELINE:2 INCH GR X52 5L 6.0 MM WT SMLS CS SLFBE	0	0	
500										
500			PIPE	9001257CTD	4	4	LINEPIPE SMLS WT= 6.02 MM API-5L X60 BE COATED	0	0	
510			PIPE	9001254CTD	6	6	LINEPIPE SMLS WT= 6.35 MM API-5L X60 BE COATED	0	0	
520										
520							***** FITTINGS ABOVE & BELOW GROUND*****			
530										
530			ELBOW	5392816	0.75	3	ELL BW 90 DEG LR SCH 160 LTCS A420 WPL6	0	0	
540			ELBOW	5392822	0.75	3	ELL BW 45 DEG LR SCH 160 LTCS A420 WPL6	0	0	
550			ELBOW	9006566	4	4	ELL BW 90 DEG LR WT 6.02 MM A860 WPHY 60	0	0	
560			ELBOW	9006573	4	4	ELL BW 45 DEG LR WT 6.02MM A860 WPHY 60	0	0	
570			ELBOW	9006470	6	6	ELL BW 90 DEG LR WT 7.11 MM A860 WPHY 60	0	0	
580			ELBOW	9006574	6	6	ELL BW 45 DEG LR WT 7.11MM A860 WPHY 60	0	0	
590										
590			TEE	5392825	0.75	3	TEE BW SCH 160 LTCS A420 WPL6	0	0	
600	NT5		TEE	9301610	4	4	TEE BW WT 6.02 MM LTCS A860 WPHY-60	0	0	
610	NT5		TEE	9006600	6	6	TEE BW WT 7.11MM A860 WPHY 60	0	0	
620			TEE RED	5392821	0.75	2	TEE RED BW SCH 160 LTCS A420 WPL6	1	3	
630	NT5		TEE RED	9006663	2	3	TEE RED BW WT 6.02 MM / SCH 160 LTCS A860 WPHY 60	4	4	
640	NT5		TEE RED	9006661	3	3	TEE RED BW WT 7.11 MM/SCH 160 LTCS A860 WPHY 60	6	6	
650	NT5		TEE RED	9006610	4	4	TEE RED BW WT 7.11 MM/6.02 MM LTCS A860 WPHY 60	6	6	
660										
660			CAP	5392826	0.75	3	CAP BW SCH 160 LTCS A420 WPL6	0	0	
670			CAP	9002480	4	4	CAP BW WT 6.02 MM LTCS A860 WPHY-60	0	0	
680			CAP	9005056	6	6	CAP BW WT 7.11MM LTCS A860 WPHY-60	0	0	
690										
690			RED CONC	5392827	0.75	2	REDUCER CONC SCH 160 LTCS A420 WPL6	1	3	
700			RED ECC	5392828	0.75	2	REDUCER ECC SCH 160 LTCS A420 WPL6	1	3	
710			RED CONC	9006917	1.5	3	REDUCER CONC WT 6.02MM / SCH 160 A860 WPHY 60	4	4	
720			RED ECC	9002475	1.5	3	REDUCER ECC WT 6.02MM / SCH 160 LTCS A860 WPHY-60	4	4	
730			RED CONC	9006916	3	3	REDUCER CONC WT 7.11MM / SCH 160 A860 WPHY 60	6	6	
740			RED ECC	9002433	3	3	REDUCER ECC WT 7.11MM / SCH 160 LTCS A860 WPHY-60	6	6	
750			RED CONC	9006907	4	4	REDUCER CONC WT 7.11 MM / 6.02 MM LTCS A860 WPHY-60	6	6	
760			RED ECC	9001373	4	4	REDUCER ECC WT 7.11 MM / 6.02 MM LTCS A860 WPHY-60	6	6	
770							***** INDUCTION BENDS ABOVE GROUND *****			
780										
780			INDUC BEND	9005380	4	4	INDUCTION BEND 90 DEG X 5D RADIUS WT 6.02 MM API 5L X60 C/W 1.5D TANGENT ENDS BW	0	0	
790			INDUC BEND	9001396	6	6	INDUCTION BEND 90 DEG X 5D RADIUS WT 7.11MM API 5L X60 C/W 1.5D TANGENT ENDS BW	0	0	
800			INDUC BEND	9005381	4	4	INDUCTION BEND 45DEG X 5D RADIUS WT 6.02 MM API 5L X60 C/W 1.5D TANGENT ENDS BW	0	0	
810			INDUC BEND	9001399	6	6	INDUCTION BEND 45 DEG X 5D RADIUS WT 7.11 MM API 5L X60 C/W 1.5D TANGENT ENDS BW	0	0	
820			INDUC BEND	9005382	4	4	INDUCTION BEND 22.5DEG X 5D RADIUS WT 6.02 MM API 5L X60 C/W 1.5D TANGENT ENDS BW	0	0	
830			INDUC BEND	9002000	6	6	INDUCTION BEND 22.5 DEG X 5D RADIUS WT 7.11 MM API 5L X60 C/W 1.5D TANGENT ENDS BW	0	0	
840							***** INDUCTION BENDS BELOW GROUND *****			
850										
850			INDUC BEND	9005380CTD	4	4	INDUCTION BEND 90 DEG X 5D RADIUS WT 6.02 MM API 5L X60 C/W 1.5D TANGENT ENDS BW COATED	0	0	
860			INDUC BEND	9001396CTD	6	6	INDUCTION BEND 90 DEG X 5D RADIUS WT 7.11MM API 5L X60 C/W 1.5D TANGENT ENDS BW COATED	0	0	
870	U04		INDUC BEND	9007016CTD	6	6	INDUCTION BEND 45DEG X 15D RADIUS WT 6.35 MM API 5L X60 C/W 1.5D TANGENT ENDS BW COATED	0	0	
880	U04		INDUC BEND	9007030CTD	4	4	INDUCTION BEND 90 DEG X 10D RADIUS WT 6.02 MM API 5L X60 C/W 1.5D TANGENT ENDS BW COATED	0	0	
890	U04		INDUC BEND	9007031CTD	6	6	INDUCTION BEND 90 DEG X 10D RADIUS WT 6.35 MM API 5L X60 C/W 1.5D TANGENT ENDS BW COATED	0	0	
900	U04		INDUC BEND	9007042CTD	4	4	INDUCTION BEND 90 DEG X 15D RADIUS WT 6.02 MM API 5L X60 C/W 1.5D TANGENT ENDS BW COATED	0	0	
910	U04		INDUC BEND	9007043CTD	6	6	INDUCTION BEND 90 DEG X 15D RADIUS WT 6.35 MM API 5L X60 C/W 1.5D TANGENT ENDS BW COATED	0	0	
920			INDUC BEND	9005381CTD	4	4	INDUCTION BEND 45DEG X 5D RADIUS WT 6.02 MM API 5L X60 C/W 1.5D TANGENT ENDS BW COATED	0	0	
930			INDUC BEND	9001399CTD	6	6	INDUCTION BEND 45 DEG X 5D RADIUS WT 7.11 MM API 5L X60 C/W 1.5D TANGENT ENDS BW COATED	0	0	
940	U04		INDUC BEND	9007000CTD	4	4	INDUCTION BEND 45DEG X 10D RADIUS WT 6.02 MM API 5L X60 C/W 1.5D TANGENT ENDS BW COATED	0	0	
950	U04		INDUC BEND	9007001CTD	6	6	INDUCTION BEND 45DEG X 10D RADIUS WT 6.35 MM API 5L X60 C/W 1.5D TANGENT ENDS BW COATED	0	0	
960	U04		INDUC BEND	9007015CTD	4	4	INDUCTION BEND 45DEG X 15D RADIUS WT 6.02 MM API 5L X60 C/W 1.5D TANGENT ENDS BW COATED	0	0	
970			INDUC BEND	9005382CTD	4	4	INDUCTION BEND 22.5DEG X 5D RADIUS WT 6.02 MM API 5L X60 C/W 1.5D TANGENT ENDS BW COATED	0	0	
980			INDUC BEND	9002000CTD	6	6	INDUCTION BEND 22.5 DEG X 5D RADIUS WT 7.11 MM API 5L X60 C/W 1.5D TANGENT ENDS BW COATED	0	0	
990							***** OLETS ABOVE & BELOW GROUND *****			
990										
1000										
1000			OLETS	9006400	0.75	1.5	WELDOLET WT 6.02 MM / SCH 160 LTCS A694 F60	4	4	
1010	U04		OLETS	5505335	0.75	1	WELDOLET SCH XS LTCS A350 LF2 CL.1	2	3	

	TENGIZCHEVROI TCO TENGIZ, KAZAKHSTAN	CONSTRUCTION	CORR.ALLOW.	SERVICE	MATERIAL	DATE	BY	REV	SHEET	PIPING LINE CLASS
		ALL SIZES - BUTT WELD SEAL WELDING - REQUIRED PIPE BENDS - INDUCTION BENDS THREAD SEALANT - PTFE PASTE	CORR. ALLOW. 1.5 MM	DESIGN: ASME B16.5 MG 1.1 CODE: ASME B31.8 ABOVE GROUND FACTOR = 0.5 BELOW GROUND FACTOR = 0.6 MAX. DESIGN PARAMETER = 132 BARG. @ 80 DEG.C. (LIMITED BY PIPE WT) FLUID CODES - PIM-SU-5112-TCO	MATERIAL: LTCS FLANGE RATING: 900 RF/CF TEMPERATURE RANGE: -40 / 80 °C	12/16/2024	BY OZAC	U04	Page 2 of 3	900H5H

SEQ NO	REV	NOTE NO.	ITEM NAME	ITEM CODE	SIZE RANGE / SMALL END SIZES		DESCRIPTION	REFERENCE / LARGE END SIZES		NOTES
1020			OLETS	9002072	0.75	2	WELDOLET WT 7.11MM/ SCH 160 LTCS A694 F60	6	6	
1030	U04		OLETS	5504379	1	1	WELDOLET FLAT BOTTOM SCH 160 LTCS A350 LF2 CL.1	0	0	
1040										
1040	U04		OLETS	5504170	0.75	2	NIPOFLANGE 1500# RF SCH 160 LTCS A350 LF2 CL.1	2	3	
1050			OLETS	9005388	0.75	2	NIPOFLANGE 1500# RF WT 6.02 MM/ SCH 160 LTCS A694 F60	4	4	
1060			OLETS	9002835	0.75	2	NIPOFLANGE 1500# RF WT 7.11 MM/ SCH 160 LTCS A694 F60	6	6	
1070	U04	UJ2	OLETS	9005400	1.5	1.5	NIPOFLANGE 1500# RF WT 6.02 MM/ SCH 160 LTCS A694 F60	4	4	
1080	U04	UJ2	OLETS	9005401	1.5	1.5	NIPOFLANGE 1500# RF WT 7.11 MM/ SCH 160 LTCS A694 F60	6	6	
1090		FF5	OLETS	9504523	0.75	0.75	NIPOFLANGE FLAT BOTTOM 1500# RF SCH 160 LTCS A694 F60	0	0	
1100										
1100		UJ2	ELBOFLG	9002713	1.5	1.5	ELBOFLANGE 1500# RF WT 6.02MM / SCH 160 LTCS A694 F60	4	4	
1110		UJ2	ELBOFLG	9002714	1.5	1.5	ELBOFLANGE 1500# RF WT 7.11MM / SCH 160 LTCSA694 F60	6	6	
1120										
1120							***** FLANGES ABOVE & BELOW GROUND*****			
1130										
1130	U04		FLANGE	5557397	0.75	2	FLG WN 1500# RF LTCS A350 LF2 CL.1 SCH 160 BORE	0	0	
1140	U04		FLANGE	5557145	3	3	FLG WN 900# RF LTCS A350 LF2 CL.1 SCH 160	0	0	
1150			FLANGE	9005389	4	4	FLG WN 900# RF LTCS A694 F60 WT 6.02MM	0	0	
1160			FLANGE	9002876	6	6	FLG WN 900# RF LTCS A694 F60 WT 7.11MM	0	0	
1170	U04	817	FLANGE	5557281	3	3	FLG WN 900# RTJ LTCS A350 LF2 CL.1 SCH 160 BORE	0	0	
1180	U04	817	FLANGE	9006715	4	4	FLG WN 900# RTJ LTCS A694 F60 WT 6.02MM	0	0	
1190	U04	817	FLANGE	9006700	6	6	FLG WN 900# RTJ LTCS A694 F60 WT 7.11MM	0	0	
1200	U04	817		9001544	2	2	FLG WN 1500# RF A694 F52 WT 3.9MM	0	0	
1210	U04	817		9001530	2	2	FLG WN 1500# RTJ A694 F52 WT 3.9MM	0	0	
1220	U04	817		5557511	2	2	FLG WN 1500# RTJ LTCS A350 LF2 CL.1 SCH 160 BORE	0	0	
1230	U04	817	FLANGE	5557266	4	4	FLG WN 900# RTJ LTCS A350 LF2 CL.1 SCH XS	0	0	
1240	U04		FLANGE	5599704	0.5	0.5	FLG SCRDR (FNPT) REDUCING 1500# RF LTCS A350 LF2 CL.1	0.75	1.5	
1250										
1250			FLG ADAPTER	5851205	0.75	2	FLANGE ADAPTER 1500# RF 316 SS X 12 MM TUBE	0	0	
1260										
1260	U04		BLIND	5615616	0.5	2	FLG BLIND 1500# RF LTCS A350 LF2 CL.1	0	0	
1270			BLIND	9002863	3	12	FLG BLIND 900# RF LTCS A694 F60	0	0	
1280	U04	817	BLIND	9001470	4	6	FLG BLIND 900# RTJ A694 F60	0	0	
1290										
1290							***** GASKETS *****			
1300										
1300			GASKET	5672251	0.75	2	GASKET 1500# 316SS SPIRAL WOUND GRAPHITE IR	0	0	
1310			GASKET	5673117	3	6	GASKET 900# 316SS SPIRAL WOUND GRAPHITE IR	0	0	
1320	U04	817	GASKET	5674491	3	6	GASKET 900# RTJ SOFT IRON TEFLON COATED OCTAGONAL RING	0	0	
1330	U04	817		5674492	2	2	GASKET 1500# RTJ SOFT IRON TEFLON COATED OCTAGONAL RING	0	0	
1340										
1340		B1					***** BOLTING *****			
1350	U04		BOLTING	5675770	0.5	99	STUD-BOLT A320 GR L7M/A194 GR 7M (S3) WITH 2 NUTS	0	0	
1360										
1360							*****BLINDS AND SPACERS*****			
1370										
1370			SPEC BLIND	5749595	0.75	2	SPECTACLE BLIND 1500# RF LTCS A516 GR.70	0	0	
1380			SPEC BLIND	5749596	3	6	SPECTACLE BLIND 900# RF LTCS A516 GR.70	0	0	
1390	U04	817		5749591	4	4	SPECTACLE BLIND 900# RTJ FEMALE LTCS A516-GR70	0	0	
1400										

 TENGIZCHEVROIL TCO TENGIZ, KAZAKHSTAN	CONSTRUCTION	CORR.ALLOW.	SERVICE	MATERIAL	DATE	BY	REV	SHEET	PIPING LINE CLASS
	ALL SIZES - BUTT WELD SEAL WELDING - REQUIRED PIPE BENDS - INDUCTION BENDS THREAD SEALANT - PTFE PASTE	CORR. ALLOW. 1.5 MM	DESIGN: ASME B16.5 MG 1.1 CODE: ASME B31.8 ABOVE GROUND FACTOR = 0.5 BELOW GROUND FACTOR = 0.6 MAX. DESIGN PARAMETER = 132 BARG. @ 80 DEG.C. (LIMITED BY PIPE WT) FLUID CODES - PIM-SU-5112-TCO	MATERIAL: LTCS FLANGE RATING: 900 RF/CF TEMPERATURE RANGE: -40 / 80 °C	12/16/2024	BY OZAC	U04	Page 3 of 3	900H5H