

SEQ NO	REV	NOTE NO.	ITEM NAME	ITEM CODE	SIZE RANGE / SMALL END SIZES		DESCRIPTION	REFERENCE / LARGE END SIZES		NOTES	
10							*****VALVES*****			B1	ALL BOLTS ARE METRIC DIA.
20										B6	7/8" X 145MM BOLTS ONLY TO BE USED FOR 1
20							***** BALL VALVES *****				INCH 1500# PERAR BALL VALVES ITEM CODE
30											B15AS22
30			BALL	A15AM14	2	2	BALL 1500# RF 825 INC 625 TRIM TRUNNION METAL RB LO	0	0	SB6	USE JACKSCREWS FOR PADDLE
40											BLANKS/SPACERS AND FLANGE SPREADERS
40							***** PIPE ABOVE GROUND *****				FOR SPECTACLE BLINDS.
50											
50			PIPE	9006211	6	6	LINEPIPE SMLS WT = 9.53 MM API-5L X60 BE EPOXY INTERNALLY COATED	0	0		
60			PIPE	9006226	6	6	LINEPIPE SMLS WT = 9.53 MM API-5L X60 BE EPOXY INTERNALLY COATED - BELLED ENDS	0	0		
70			PIPE	9001493	6	6	LINEPIPE SMLS WT = 9.53 MM API-5L X60 BE	0	0		
80			PIPE	9001494	8	8	LINEPIPE SMLS WT = 10.31 MM API-5L X60 BE	0	0		
90											
90							*****PIPE BELOW GROUND*****				
100											
100			PIPE	9006211CTD	6	6	LINEPIPE SMLS WT = 8.74 MM API-5L X60 BE COATED - EPOXY INTERNALLY COATED	0	0		
110			PIPE	9006226CTD	6	6	LINEPIPE SMLS WT = 8.74 MM API-5L X60 BE COATED - EPOXY INTERNALLY COATED - BELLED ENDS	0	0		
120			PIPE	9001487CTD	6	6	LINEPIPE SMLS WT = 8.74 MM API-5L X60 BE COATED	0	0		
130			PIPE	9001493CTD	8	8	LINEPIPE SMLS WT = 9.53 MM API-5L X60 BE COATED	0	0		
140											
140							*****FITTINGS ABOVE & BELOW GROUND GROUND*****				
150											
150			CAP	9005060	6	6	CAP BW WT 9.53 MM LTCS A860 WPHY-60	0	0		
160			CAP	9005061	8	8	CAP BW WT 10.31 MM LTCS A860 WPHY-60	0	0		
170											
170			RED ECC	9004137	6	6	REDUCER ECC WT 10.31 MM / 9.53 MM LTCS A860 WPHY-60-W	8	8		
180											
180			COUPLING	9005900	6	6	COUPLING INSERT SLEEVE TYPE FOR EPOXY INTERNALLY COATED CARBON STEEL PIPE	0	0		
190			COUPLING	9005901	6	6	COUPLING INSERT SLEEVE TYPE FOR EPOXY INTERNALLY COATED CARBON STEEL PIPE - BELLED END PIPE ONLY	0	0		
200											
200							***** INDUCTION BENDS ABOVE GROUND*****				
210											
210			INDUC BEND	9001817	6	6	INDUCTION BEND 90 DEG X 5D RADIUS WT 9.53 MM API 5L X60 C/W 1.5D TANGENT ENDS BW	0	0		
220			INDUC BEND	9001818	8	8	INDUCTION BEND 90 DEG X 5D RADIUS WT 10.31 MM API 5L X60 C/W 1.5D TANGENT ENDS BW	0	0		
230			INDUC BEND	9001827	6	6	INDUCTION BEND 45 DEG X 5D RADIUS WT 9.53 MM API 5L X60 C/W 1.5D TANGENT ENDS BW	0	0		
240			INDUC BEND	9001828	8	8	INDUCTION BEND 45 DEG X 5D RADIUS WT 10.31 MM API 5L X60 C/W 1.5D TANGENT ENDS BW	0	0		
250			INDUC BEND	9006591	6	6	INDUCTION BEND 22.5 DEG X 5D RADIUS 9.53 MM API 5L X60 C/W 1.5D TANGENT ENDS BW - EPOXY INTERNALLY COATED	0	0		
260			INDUC BEND	9006592	6	6	INDUCTION BEND 22.5 DEG X 5D RADIUS 9.53 MM API 5L X60 C/W 1.5D TANGENT ENDS BW - EPOXY INTERNALLY COATED - BELLED ENDS	0	0		
270			INDUC BEND	9001837	6	6	INDUCTION BEND 22.5 DEG X 5D RADIUS WT 9.53 MM API 5L X60 C/W 1.5D TANGENT ENDS BW	0	0		
280			INDUC BEND	9001838	8	8	INDUCTION BEND 22.5 DEG X 5D RADIUS WT 10.31 MM API 5L X60 C/W 1.5D TANGENT ENDS BW	0	0		
290											
290							***** INDUCTION BENDS BELOW GROUND*****				
300											
300			INDUC BEND	9001817CTD	6	6	INDUCTION BEND 90 DEG X 5D RADIUS WT 9.53 MM API 5L X60 C/W 1.5D TANGENT ENDS BW COATED	0	0		
310			INDUC BEND	9001818CTD	8	8	INDUCTION BEND 90 DEG X 5D RADIUS WT 10.31 MM API 5L X60 C/W 1.5D TANGENT ENDS BW COATED	0	0		
320			INDUC BEND	9001827CTD	6	6	INDUCTION BEND 45 DEG X 5D RADIUS WT 9.53 MM API 5L X60 C/W 1.5D TANGENT ENDS BW COATED	0	0		
330			INDUC BEND	9001828CTD	8	8	INDUCTION BEND 45 DEG X 5D RADIUS WT 10.31 MM API 5L X60 C/W 1.5D TANGENT ENDS BW COATED	0	0		
340			INDUC BEND	9006591CTD	6	6	INDUCTION BEND 22.5 DEG X 5D RADIUS 9.53 MM API 5L X60 C/W 1.5D TANGENT ENDS BW COATED - EPOXY INTERNALLY COATED	0	0		
350			INDUC BEND	9006592CTD	6	6	INDUCTION BEND 22.5 DEG X 5D RADIUS 9.53 MM API 5L X60 C/W 1.5D TANGENT ENDS BW COATED - EPOXY INTERNALLY COATED - BELLED	0	0		
360			INDUC BEND	9001837CTD	6	6	INDUCTION BEND 22.5 DEG X 5D RADIUS WT 9.53 MM API 5L X60 C/W 1.5D TANGENT ENDS BW COATED	0	0		
370			INDUC BEND	9001838CTD	8	8	INDUCTION BEND 22.5 DEG X 5D RADIUS WT 10.31 MM API 5L X60 C/W 1.5D TANGENT ENDS BW COATED	0	0		
380											
380							***** FLANGES ABOVE & BELOW GROUND*****				
390											
390			FLANGE	9004328	6	6	FLG WN 900# RF LTCS A694 F60 WT 9.53 MM	0	0		
400			FLANGE	9002848	8	8	FLG WN 900# RF LTCS A694 F60 WT 10.31MM	0	0		
410			BLIND	9002891	2	2	FLG BLIND 1500# RF LTCS A694 F60 PE COATED	0	0		
420			BLIND	9002890	6	8	FLG BLIND 900# RF LTCS A694 F60 PE COATED	0	0		
430											
430							***** GASKETS *****				
440											
440			GASKET	5672251	0.75	2	GASKET 1500# 316SS SPIRAL WOUND GRAPHITE IR	0	0		
450			GASKET	5673117	3	8	GASKET 900# 316SS SPIRAL WOUND GRAPHITE IR	0	0		

	TENGIZCHEVROIL TCO TENGIZ, KAZAKHSTAN	CONSTRUCTION	CORR.ALLOW.	SERVICE	MATERIAL	DATE	BY	REV	SHEET	PIPING LINE CLASS
		ALL SIZES - BUTT WELD EACH COMPLETED LINE TO BE INTERNALLY LINED WITH PULL THROUGH LINER BY THIRD PARTY PIPE BENDS - INDUCTION BENDS	CORR. ALLOW. 3 MM	SOUR SERVICE - NACE MR0175/ ISO 15156 DESIGN: ASME B16.5 MG 1.1 CODE: ASME B31.8 ABOVE GROUND FACTOR = 0.5 BELOW GROUND FACTOR = 0.6 MAX. DESIGN PARAMETER = 140 BARG. @ 90 DEG.C. (LIMITED BY PIPE WT) FLUID CODES - PIM-SU-5112-TCO	MATERIAL: LTCS FLANGE RATING: 900 RF/CF TEMPERATURE RANGE: -40 / 90 °C	12/16/2024	BY OZAC	U04	Page 1 of 2	900K5C

SEQ NO	REV	NOTE NO.	ITEM NAME	ITEM CODE	SIZE RANGE / SMALL END SIZES		DESCRIPTION	REFERENCE / LARGE END SIZES		NOTES
460										
460		B1					***** BOLTING *****			
470										
470	U04		BOLTING	5675770	0.5	8	STUD-BOLT A320 GR L7M/A194 GR 7M (S3) WITH 2 NUTS	0	0	
480										
480		SB6	BOLTING	5675675	10	28	JACK SCREW HEX HEAD A320 GR L7M	0	0	
490										
490			SPEC BLIND	5749596	6	8	SPECTACLE BLIND 900# RF LTCS A516 GR.70	0	0	
500										

	TENGIZCHEVROIL TCO TENGIZ, KAZAKHSTAN	CONSTRUCTION	CORR.ALLOW.	SERVICE	MATERIAL	DATE	BY	REV	SHEET	PIPING LINE CLASS
		ALL SIZES - BUTT WELD EACH COMPLETED LINE TO BE INTERNALLY LINED WITH PULL THROUGH LINER BY THIRD PARTY PIPE BENDS - INDUCTION BENDS	CORR. ALLOW. 3 MM	SOUR SERVICE - NACE MR0175/ISO 15156 DESIGN: ASME B16.5 MG 1.1 CODE: ASME B31.8 ABOVE GROUND FACTOR = 0.5 BELOW GROUND FACTOR = 0.6 MAX. DESIGN PARAMETER = 140 BARG. @ 90 DEG.C. (LIMITED BY PIPE WT) FLUID CODES - PIM-SU-5112-TCO	MATERIAL: LTCS FLANGE RATING: 900 RF/CF TEMPERATURE RANGE: -40 / 90 °C	12/16/2024	BY OZAC	U04	Page 2 of 2	900K5C