

SEQ NO	REV	NOTE NO.	ITEM NAME	ITEM CODE	SIZE RANGE / SMALL END SIZES		DESCRIPTION	REFERENCE / LARGE END SIZES		NOTES	
10	U04						*****VALVES*****			817	USE ONLY FOR TIE IN
20										B2	7/8" X 145MM BOLTS ONLY TO BE USED FOR 1 INCH 1500# PERAR BALL VALVES ITEM CODE B15AM10
20	U04						***** MODULAR VALVES *****				
30										FA8	USE THREADED FLANGES FOR INSTRUMENT CONNECTIONS ONLY.
30	U04	VA5	MODULAR DBB	K15AC02	0.5	1.5	MODULAR VALVE DB&B BALL TYPE 1500# RF LTCS A350 LF2 CL.1 316 SS TRIM METAL LO - FULL SIZE TYPE 2BV	0	0	VA5	USE THESE VALVES ONLY WHERE SPECIFIED ON PIPING AND INSTRUMENT DIAGRAMS
40	U04		MODULAR DBB	K15AC06	2	2	MODULAR VALVE DB&B BALL TYPE 1500# RF LTCS A350 LF2 CL.1 316 SS TRIM METAL LO - FULL SIZE TYPE 2BV	0	0	VAV	USAGE IS LIMITED TO INSTRUMENT ISOLATION PURPOSE.
50	U04	VAV	MODULAR DBB	K09AC06	3	3	MODULAR VALVE DB&B BALL TYPE 900# RF LTCS A350 LF2 CL.1 316 SS TRIM METAL LO FULL SIZE TYPE 2BV	0	0	VAW	VALVE ONLY TO BE USED IN ACCORDANCE WITH DOCUMENT L-ST-2055 - VENT DRAIN AND INSTRUMENT CONNECTION DETAILS.
60	U04		MODULAR DBB	M15AC02	0.75	1.5	MODULAR VALVE DB&B BALL TYPE 1500# RF LTCS A350 LF2 CL.1 316 SS TRIM METAL LO - CONTROLLED BORE TYPE 2BVR	0	0	VB2	SOFT SEATED BALL VALVES ARE LIMITED TO MAXIMUM TEMPERATURE OF 200°C.
70	U04		MODULAR DBB	M15AC06	2	2	MODULAR VALVE DB&B BALL TYPE 1500# RF LTCS A350 LF2 CL.1 316 SS TRIM METAL LO - CONTROLLED BORE TYPE 2BVR	0	0	VC1	SPRING PISTON CHECK VALVES ARE PREFERRED IN THE HORIZONTAL POSITION, BUT MAY BE USED IN THE VERTICAL POSITION WITH ENGINEERING APPROVAL.
80	U04	VAW	MODULAR DBB	M15EC02	0.75	1	MODULAR VALVE DB&B BALL TYPE 1500# RF LTCS A350 LF2 CL.1 316SS TRIM METAL LO REDUCING - CONTROLLED BORE TYPE 2BVR	2	2		
90	U04	VAW	MODULAR DBB	M09EC02	1	1	MODULAR VALVE DB&B BALL TYPE 900# RF LTCS A350 LF2 CL.1 316SS TRIM METAL LO REDUCING - CONTROLLED BORE TYPE 2BVR	3	3		
100											
100	U04	VB2					***** BALL VALVES *****				
110											
110	U04		BALL	A15AC05	2	2	BALL 1500# RF LTCS A350 LF2 CL.1 316SS TRIM TRUNNION SOFT RB LO	0	0		
120	U04		BALL	A15AC06	2	2	BALL 1500# RF LTCS A350 LF2 CL.1 316SS TRIM TRUNNION METAL RB LO	0	0		
130	U04		BALL	A09AC05	3	3	BALL 900# RF LTCS A350 LF2 CL.1 316SS TRIM TRUNNION SOFT RB LO	0	0		
140	U04		BALL	A09AC06	3	3	BALL 900# RF LTCS A350 LF2 CL.1 316SS TRIM TRUNNION METAL RB LO	0	0		
150	U04		BALL	A09AC07	4	10	BALL 900# RF LTCS A350 LF2 CL.1 316SS TRIM TRUNNION SOFT RB GO	0	0		
160	U04		BALL	A09AC08	4	10	BALL 900# RF LTCS A350 LF2 CL.1 316SS TRIM TRUNNION METAL RB GO	0	0		
170	U04		BALL	B15AC01	0.75	1.5	BALL 1500# RF LTCS A350 LF2 CL.1 316SS TRIM FLOATING SOFT FB LO	0	0		
180	U04		BALL	B15AC02	0.75	1.5	BALL 1500# RF LTCS A350 LF2 CL.1 316SS TRIM FLOATING METAL FB LO	0	0		
190	U04		BALL	B15AC05	2	2	BALL 1500# RF LTCS A350 LF2 CL.1 316SS TRIM TRUNNION SOFT FB LO	0	0		
200	U04	VA5	BALL	B15AC06	2	2	BALL 1500# RF LTCS A350 LF2 CL.1 316SS TRIM TRUNNION METAL FB LO	0	0		
210	U04	VA5	BALL	B09AC07	3	10	BALL 900# RF LTCS A350 LF2 CL.1 316SS TRIM TRUNNION SOFT FB GO	0	0		
220	U04	VA5	BALL	B09AC08	3	10	BALL 900# RF LTCS A350 LF2 CL.1 316SS TRIM TRUNNION METAL FB GO	0	0		
230	U04	817	BALL	B09CC08	12	12	BALL 900# CF LTCS A350 LF2 CL.1 316SS TRIM TRUNNION METAL FB GO	0	0		
240	U04	817	BALL	A09CC08	12	12	BALL 900# CF LTCS A350 LF2 CL.1 316SS TRIM TRUNNION METAL RB GO	0	0		
250	U04	817	BALL	B09CC07	12	12	BALL 900# CF LTCS A350 LF2 CL.1 316SS TRIM TRUNNION SOFT FB GO	0	0		
260	U04	817	BALL	A09CC07	12	12	BALL 900# CF LTCS A350 LF2 CL.1 316SS TRIM TRUNNION SOFT RB GO	0	0		
270											
270	U04						***** THROUGH CONDUIT GATE VALVES *****				
280											
280	U04		GATE	W09AC70	3	4	GATE 900# RF LTCS A352 LCC 316 SS TRIM THROUGH COND SOLID SLAB HW	0	0		
290	U04		GATE	W09AC71	6	10	GATE 900# RF LTCS A352 LCC 316 SS TRIM THROUGH COND SOLID SLAB GO	0	0		
300	U04	817	GATE	W09CC71	12	12	GATE 900# CF LTCS A352 LCC 316 SS TRIM THROUGH COND SOLID SLAB GO	0	0		
310											
310	U04						***** GLOBE VALVES *****				
320											
320	U04		GLOBE	L15AC48	0.75	1.5	GLOBE 1500# RF LTCS A350 LF2 CL.1 TRIM 16 OS&Y HW	0	0		
330	U04		GLOBE	L15AC41	2	2	GLOBE 1500# RF LTCS A352 LCC TRIM 16 OS&Y HW	0	0		
340	U04		GLOBE	L09AC41	3	3	GLOBE 900# RF LTCS A352 LCC TRIM 16 OS&Y HW	0	0		
350	U04		GLOBE	L09AC42	4	8	GLOBE 900# RF LTCS A352 LCC TRIM 16 OS&Y GO	0	0		
360											
360	U04						***** CHECK VALVES *****				
370											
370	U04	VC1	CHECK	C15AC50	0.75	1.5	CHECK PISTON 1500# RF LTCS A350 LF2 CL.1 TRIM 16	0	0		
380	U04		CHECK	C15AC45	2	2	CHECK DUAL WAFER LUG 1500# RF LTCS A352 LCC TRIM 16 THROU BOLTED	0	0		
390	U04		CHECK	C09AC45	3	8	CHECK DUAL WAFER LUG 900# RF LTCS A352 LCC TRIM 16 THROU BOLTED	0	0		
400	U04		CHECK	C09AC52	10	10	CHECK DUAL DBL FLG 900# RF LTCS A352 LCC TRIM 16	0	0		
410	U04	817	CHECK	C09CC52	12	12	CHECK DUAL 900# CF LTCS A352 LCC TRIM 16	0	0		
420											
420	U04						***** PIPE ABOVE GROUND *****				
430											
430	U04		PIPE	5358512	0.75	1.5	PIPE SCH 160 SMLS LTCS A333 GR.6 PE	0	0		
440	U04		PIPE	5358515	2	3	PIPE SCH 160 SMLS LTCS A333 GR.6 BE	0	0		
450											
450	U04		PIPE	9005240	4	4	LINEPIPE SMLS WT= 8.56 MM API-5L X60 BE	0	0		
460	U04		PIPE	9001493	6	6	LINEPIPE SMLS WT = 9.53 MM API-5L X60 BE	0	0		
470	U04		PIPE	9001338	8	8	LINEPIPE SMLS WT= 11.1 MM API-5L X60 BE	0	0		
480	U04		PIPE	9001491	10	10	LINEPIPE SMLS WT = 14.27 MM API-5L X60 BE	0	0		
490	U04		PIPE	9005244	12	12	LINEPIPE SMLS WT = 15.88 MM API-5L X60 BE	0	0		
500	U04		PIPE	9005243	16	16	LINEPIPE SMLS WT= 19.05MM API-5L X60 BE	0	0		
510											
510	U04						***** PIPE BELOW GROUND *****				

	TENGIZCHEVROI TCO TENGIZ, KAZAKHSTAN	CONSTRUCTION	CORR.ALLOW.	SERVICE	MATERIAL	DATE	BY	REV	SHEET	PIPING LINE CLASS
		ALL SIZES - BUTT WELD PWHT - SOUR SERVICE ALL WELDS ABOVE GROUND PIPE BENDS - INDUCTION BENDS	CORR. ALLOW. 3 MM	SOUR SERVICE - NACE MR0175/ ISO 15156 DESIGN: ASME B16.5 MG 1.1 CODE: ASME B31.8 ABOVE GROUND FACTOR = 0.5 BELOW GROUND FACTOR = 0.6 MAX. DESIGN PARAMETER = 132 BARG. @ 110 DEG.C. (LIMITED BY PIPE WT) FLUID CODES - PIM-SU-5112-TCO	MATERIAL: LTCS FLANGE RATING: 900 RF TEMPERATURE RANGE: -40 / 120 °C COMMENT: LTCS	12/16/2024	BY OZAC	U04	Page 1 of 3	900K5D

SEQ NO	REV	NOTE NO.	ITEM NAME	ITEM CODE	SIZE RANGE / SMALL END SIZES		DESCRIPTION	REFERENCE / LARGE END SIZES		NOTES
520										
520	U04		PIPE	9001311CTD	6	6	LINEPIPE SMLS WT= 7.92 MM API-5L X60 BE COATED	0	0	
530	U04		PIPE	9001338CTD	8	8	LINEPIPE WT 11.1 MM SMLS API 5L X60 BE DUAL COATED	0	0	
540										
540	U04						*****FITTINGS ABOVE & BELOW GROUND*****			
550										
550	U04		ELBOW	5392822	0.75	3	ELL BW 45 DEG LR SCH 160 LTCS A420 WPL6	0	0	
560	U04		ELBOW	9006570	6	6	ELL BW 45 DEG LR WT 9.53 MM A860 WPHY 60 - W	0	0	
570	U04		ELBOW	9002174	8	8	ELL BW 45 DEG LR WT 11.1MM A860 WPHY 60	0	0	
580	U04		ELBOW	9006567	16	16	ELL BW 45 DEG LR WT 19.05MM A860 WPHY 60	0	0	
590	U04		ELBOW	5392816	0.75	3	ELL BW 90 DEG LR SCH 160 LTCS A420 WPL6	0	0	
600	U04		ELBOW	9006594	4	4	ELL BW 90 DEG LR WT 8.56 MM A860 WPHY 60	0	0	
610	U04		ELBOW	9006471	6	6	ELL BW 90 DEG LR WT 9.53 MM A860 WPHY 60	0	0	
620	U04		ELBOW	9002158	8	8	ELL BW 90 DEG LR WT 11.1MM A860 WPHY 60	0	0	
630	U04		ELBOW	9006469	12	12	ELL BW 90 DEG LR WT 15.88 MM A860 WPHY 60	0	0	
640	U04		ELBOW	9006568	16	16	ELL BW 90 DEG LR WT 19.05 MM A860 WPHY 60	0	0	
650										
650	U04		RED CONC	5392827	0.75	2	REDUCER CONC SCH 160 LTCS A420 WPL6	1	3	
660	U04		RED CONC	9006924	1.5	3	REDUCER CONC WT 8.56MM / SCH 160 A860 WPHY 60	4	4	
670	U04		RED CONC	9006925	3	3	REDUCER CONC WT 9.53MM / SCH 160 A860 WPHY 60	6	6	
680	U04		RED CONC	9002201	8	8	REDUCER CONC SCH 120 / WT 11.1MM A860 WPHY 60	10	12	
690	U04		RED CONC	9006900	8	8	REDUCER CONC WT 14.27MM / 12.7MM LTCS A860 WPHY 60	10	10	
700	U04		RED ECC	5392828	0.75	2	REDUCER ECC SCH 160 LTCS A420 WPL6	1	3	
710	U04		RED ECC	9004273	1.5	3	REDUCER ECC WT 8.56MM / SCH 160 LTCS A860 WPHY-60	4	4	
720	U04		RED ECC	9004274	3	3	REDUCER ECC WT 9.53 MM / SCH 160 LTCS A860 WPHY-60	6	6	
730	U04		RED ECC	9002231	8	8	REDUCER ECC SCH 120 / WT 11.1MM LTCS A860 WPHY-60	10	12	
740	U04		RED ECC	9002410	8	8	REDUCER ECC WT 14.27 MM / 12.70 MM LTCS A860 WPHY-60	10	10	
750										
750	U04		TEE	5392825	0.75	3	TEE BW SCH 160 LTCS A420 WPL6	0	0	
760	U04		TEE	9004210	6	6	TEE BW WT 9.53MM A860 WPHY 60-W	0	0	
770	U04		TEE	9002114	8	8	TEE BW WT 11.1MM A860 WPHY 60	0	0	
780	U04		TEE	9004200	12	12	TEE BW WT 15.88MM A860 WPHY 60	0	0	
790	U04		TEE RED	5392821	0.75	2	TEE RED BW SCH 160 LTCS A420 WPL6	1	3	
800	U04		TEE RED	9006662	2	3	TEE RED BW WT 8.56 MM/SCH 160 LTCS A860 WPHY 60	4	4	
810	U04		TEE RED	9006665	3	3	TEE RED BW WT 9.53 MM/SCH 160 MM LTCS A860 WPHY 60	6	6	
820	U04		TEE RED	9004207	6	6	TEE RED BW WT 15.88 MM/9.53 MM LTCS A860 WPHY 60	12	12	
830	U04		TEE RED	9006634	6	6	TEE RED BW WT 19.05 MM/9.53 MM LTCS A860 WPHY 60	16	16	
840	U04		TEE RED	9002136	8	8	TEE RED BW SCH 120 / WT 11.1MM A860 WPHY 60	10	12	
850	U04		TEE RED	9002128	8	8	TEE RED BW WT 20.6MM/ WT 11.1MM A860 WPHY 60	20	20	
860										
860	U04		CAP	5392826	0.75	3	CAP BW SCH 160 LTCS A420 WPL6	0	0	
870	U04		CAP	9005200	4	4	CAP BW WT 8.56 MM LTCS A860 WPHY-60	0	0	
880	U04		CAP	9005060	6	6	CAP BW WT 9.53 MM LTCS A860 WPHY-60	0	0	
890	U04		CAP	9002306	8	8	CAP BW WT 11.1MM LTCS A860 WPHY 60	0	0	
900	U04		CAP	9005067	8	8	CAP BW WT 12.70 MM LTCS A860 WPHY-60	0	0	
910	U04		CAP	9005068	10	10	CAP BW WT 14.27 MM LTCS A860 WPHY-60	0	0	
920	U04		CAP	9005069	12	12	CAP BW WT 15.88 MM LTCS A860 WPHY-60	0	0	
930	U04		CAP	9005072	16	16	CAP BW WT 19.05 MM LTCS A860 WPHY-60	0	0	
940										
940	U04						***** INDUCTION BENDS BELOW GROUND*****			
950										
950	U04		INDUC BEND	9001815CTD	6	6	INDUCTION BEND 90 DEG X 5D RADIUS WT 7.92 MM API 5L X60 C/W 1.5D TANGENT ENDS BW COATED	0	0	
960	U04		INDUC BEND	9001825CTD	6	6	INDUCTION BEND 45 DEG X 5D RADIUS WT 7.92 MM API 5L X60 C/W 1.5D TANGENT ENDS BW COATED	0	0	
970	U04		INDUC BEND	9001835CTD	6	6	INDUCTION BEND 22.5 DEG X 5D RADIUS WT 7.92 MM API 5L X60 C/W 1.5D TANGENT ENDS BW COATED	0	0	
980	U04		INDUC BEND	9001938CTD	8	8	INDUCTION BEND 22.5 DEG X 5D RADIUS C/W 1.5D TANGENTS WT 11.1MM SMLS API 5L X60 BE DUAL COATED	0	0	
990										
990	U04						***** OLETS ABOVE GROUND *****			
1000										
1000	U04		OLETS	9006819	0.75	1.5	WELDOLET WT 8.56 MM / SCH 160 LTCS A694 F60	4	4	
1010	U04		OLETS	9002457	0.75	2	WELDOLET WT 9.53 MM/SCH 160 WT LTCS A694 F60	6	6	
1020	U04		OLETS	9002466	0.75	3	WELDOLET WT 12.70 MM/ SCH 160 WT LTCS A694 F60	8	8	
1030	U04		OLETS	9002470	0.75	3	WELDOLET WT 14.27 MM/ SCH 160 WT LTCS A694 F60	10	10	
1040	U04		OLETS	9002085	0.75	3	WELDOLET WT 15.88 MM/ SCH 160 LTCS A694 F60	12	12	
1050	U04		OLETS	9004335	4	4	WELDOLET WT 15.88 MM/ 8.56 MM LTCS A694 F60	12	12	
1060	U04		OLETS	9004336	0.75	3	WELDOLET WT 17.48 MM/SCH 160 LTCS A694 F60	14	14	
1070	U04		OLETS	9004337	4	4	WELDOLET WT 17.48 MM/8.56 MM LTCS A694 F60	14	14	
1080	U04		OLETS	9002089	0.75	3	WELDOLET WT 19.05 MM/ SCH 160 LTCS A694 F60	16	16	
1090	U04		OLETS	9004338	4	4	WELDOLET WT 19.05 MM/ 8.56 MM LTCS A694 F60	16	16	
1100	U04		OLETS	9004339	6	6	WELDOLET WT 19.05 MM/ 9.53 MM LTCS A694 F60	16	16	
1110										

	TENGIZCHEVROI TCO TENGIZ, KAZAKHSTAN	CONSTRUCTION	CORR.ALLOW.	SERVICE	MATERIAL	DATE	BY	REV	SHEET	PIPING LINE CLASS
		ALL SIZES - BUTT WELD PWHT - SOUR SERVICE ALL WELDS ABOVE GROUND PIPE BENDS - INDUCTION BENDS	CORR. ALLOW. 3 MM	SOUR SERVICE - NACE MR0175/ ISO 15156 DESIGN: ASME B16.5 MG 1.1 CODE: ASME B31.8 ABOVE GROUND FACTOR = 0.5 BELOW GROUND FACTOR = 0.6 MAX. DESIGN PARAMETER = 132 BARG. @ 110 DEG.C. (LIMITED BY PIPE WT) FLUID CODES - PIM-SU-5112-TCO	MATERIAL: LTCS FLANGE RATING: 900 RF TEMPERATURE RANGE: -40 / 120 °C COMMENT: LTCS	12/16/2024	BY OZAC	U04	Page 2 of 3	900K5D

SEQ NO	REV	NOTE NO.	ITEM NAME	ITEM CODE	SIZE RANGE / SMALL END SIZES		DESCRIPTION	REFERENCE / LARGE END SIZES		NOTES
1110	U04		OLETS	5504170	1	1	NIPOFLANGE 1500# RF SCH 160 LTCS A350 LF2 CL.1	2	2	
1120	U04		OLETS	9002838	0.75	2	NIPOFLANGE 1500# RF WT 12.70 MM/ SCH 160 LTCS A694 F60	8	8	
1130	U04		OLETS	9002839	0.75	2	NIPOFLANGE 1500# RF WT 14.27 MM/ SCH 160 LTCS A694 F60	10	10	
1140	U04		OLETS	9004322	0.75	2	NIPOFLANGE 1500# RF WT 15.88 MM/ SCH 160 LTCS A694 F60	12	12	
1150	U04		OLETS	9002842	0.75	2	NIPOFLANGE 1500# RF WT 19.05 MM/ SCH 160 LTCS A694 F60	16	16	
1160										
1160	U04						***** FLANGES ABOVE GROUND*****			
1170										
1170	U04		FLANGE	5557397	0.75	2	FLG WN 1500# RF LTCS A350 LF2 CL.1 SCH 160 BORE	0	0	
1180	U04		FLANGE	5557145	3	3	FLG WN 900# RF LTCS A350 LF2 CL.1 SCH 160	0	0	
1190	U04		FLANGE	9004327	4	4	FLG WN 900# RF LTCS A694 F60 WT 8.56 MM	0	0	
1200	U04		FLANGE	9004328	6	6	FLG WN 900# RF LTCS A694 F60 WT 9.53 MM	0	0	
1210	U04		FLANGE	9002857	8	8	FLG WN 900# RF LTCS A694 F60 WT 11.13 MM	0	0	
1220	U04		FLANGE	9002850	10	10	FLG WN 900# RF LTCS A694 F60 WT 14.27MM	0	0	
1230	U04	817	FLANGE	9006150	12	12	FLG COMPACT 900# RJ A694 F60 WT 15.88 MM	0	0	
1240	U04	817	FLANGE	9006154	16	16	FLG COMPACT 900# RJ A694 F60 WT 19.05 MM	0	0	
1250	U04		BLIND	5615616	0.75	2	FLG BLIND 1500# RF LTCS A350 LF2 CL.1	0	0	
1260	U04		BLIND	5615605	3	3	FLG BLIND 900# RF LTCS A350 LF2 CL.1	0	0	
1270	U04		BLIND	9002863	4	10	FLG BLIND 900# RF LTCS A694 F60	0	0	
1280	U04	817	BLIND	9619775	12	16	FLG COMPACT BLIND 900# RJ LTCS A694 F60 PIPE CLASS 900K5B	0	0	
1290	U04	FA8	TEE RED	5599704	0.5	1	FLG SCRDR (FNPT) REDUCING 1500# RF LTCS A350 LF2 CL.1	0.75	1.5	
1300	U04	817	FLANGE	5557511	2	2	FLG WN 1500# RTJ LTCS A350 LF2 CL.1 SCH 160 BORE	0	0	
1310	U04	817	FLANGE	5557281	3	3	FLG WN 900# RTJ LTCS A350 LF2 CL.1 SCH 160 BORE	0	0	
1320	U04	817	FLANGE	9001538	8	8	FLG WN 900# RTJ LTCS A694 F60 WT 11.1MM	0	0	
1330	U04	817	FLANGE	9006719	8	8	FLG WN 900# RTJ LTCS A694 F60 WT 12.70MM	0	0	
1340	U04	817	FLANGE	9006716	10	10	FLG WN 900# RTJ LTCS A694 F60 WT 14.27MM	0	0	
1350	U04	817	FLANGE	9006718	12	12	FLG WN 900# RTJ LTCS A694 F60 WT 15.88MM	0	0	
1360										
1360	U04		FLANGE	5851205	0.75	0.75	FLANGE ADAPTER 1500# RF 316 SS X 12 MM TUBE	0	0	
1370	U04		FLANGE	5851205	2	2	FLANGE ADAPTER 1500# RF 316 SS X 12 MM TUBE	0	0	
1380										
1380	U04						***** GASKETS *****			
1390										
1390	U04		GASKET	5672251	0.5	2	GASKET 1500# 316SS SPIRAL WOUND GRAPHITE IR	0	0	
1400	U04		GASKET	5673117	3	10	GASKET 900# 316SS SPIRAL WOUND GRAPHITE IR	0	0	
1410	U04	817	GASKET	5673445	12	16	GASKET 900# RJ INC 718 ENERGIZED SEALRING COMPACT FLANGE PIPE CLASS 900K5B	0	0	
1420	U04	817	GASKET	5674491	3	12	GASKET 900# RTJ SOFT IRON TEFLON COATED OCTAGONAL RING	0	0	
1430	U04	817	GASKET	5674492	2	2	GASKET 1500# RTJ SOFT IRON TEFLON COATED OCTAGONAL RING	0	0	
1440										
1440	U04						***** BOLTING *****			
1450										
1450	U04		BOLTING	5675770	0.5	16	STUD-BOLT A320 GR L7M/A194 GR 7M (S3) WITH 2 NUTS	0	0	
1460										
1460	U04						***** BLINDS & SPACERS *****			
1470										
1470	U04		SPEC BLIND	5749595	0.75	2	SPECTACLE BLIND 1500# RF LTCS A516 GR.70	0	0	
1480	U04		SPEC BLIND	5749596	3	8	SPECTACLE BLIND 900# RF LTCS A516 GR.70	0	0	
1490										
1490	U04		PADDLE	5750102	10	10	PADDLE BLANK 900# RF LTCS A516 GR.70	0	0	
1500	U04		PADDLE	5750202	10	10	PADDLE SPACER 900# RF LTCS A516 GR.70	0	0	
1510	U04	817	PADDLE	5750222	12	16	PADDLE BLANK COMPACT 900# RJ LTCS A516 GR.70	0	0	
1520	U04	817	PADDLE	5750228	12	16	PADDLE SPACER COMPACT 900# RJ LTCS A516 GR.70	0	0	
1530										

	TENGIZCHEVROI TCO TENGIZ, KAZAKHSTAN	CONSTRUCTION	CORR.ALLOW.	SERVICE	MATERIAL	DATE	BY	REV	SHEET	PIPING LINE CLASS
		ALL SIZES - BUTT WELD PWHT - SOUR SERVICE ALL WELDS ABOVE GROUND PIPE BENDS - INDUCTION BENDS	CORR. ALLOW. 3 MM	SOUR SERVICE - NACE MR0175/ ISO 15156 DESIGN: ASME B16.5 MG 1.1 CODE: ASME B31.8 ABOVE GROUND FACTOR = 0.5 BELOW GROUND FACTOR = 0.6 MAX. DESIGN PARAMETER = 132 BARG. @ 110 DEG.C. (LIMITED BY PIPE WT) FLUID CODES - PIM-SU-5112-TCO	MATERIAL: LTCS FLANGE RATING: 900 RF TEMPERATURE RANGE: -40 / 120 °C COMMENT: LTCS	12/16/2024	BY OZAC	U04	Page 3 of 3	900K5D