

| SEQ NO                                                                             | REV | NOTE NO. | ITEM NAME                                      | ITEM CODE | SIZE RANGE / SMALL END SIZES                                                                                             |      | DESCRIPTION                                                                                                 | REFERENCE / LARGE END SIZES                                                                                    |                                                                                                             | NOTES      |                                                                                                                                         |     |                |                   |
|------------------------------------------------------------------------------------|-----|----------|------------------------------------------------|-----------|--------------------------------------------------------------------------------------------------------------------------|------|-------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------|------------|-----------------------------------------------------------------------------------------------------------------------------------------|-----|----------------|-------------------|
| 10                                                                                 |     |          |                                                |           |                                                                                                                          |      | ***** MODULAR VALVES *****                                                                                  |                                                                                                                |                                                                                                             | 814        | NIPPLE TO BE CUT FROM SS SCH 160 PE PIPE.                                                                                               |     |                |                   |
| 20                                                                                 |     |          |                                                |           |                                                                                                                          |      |                                                                                                             |                                                                                                                |                                                                                                             | 815        | TO BE USED WITH COMPACT FLANGES ONLY.                                                                                                   |     |                |                   |
| 20                                                                                 |     | VA5      | MODULAR DBB                                    | K15AS02   | 0.5                                                                                                                      | 1.5  | MODULAR VALVE DB&B BALL TYPE 1500# RF SS A182 F316 316 SS TRIM METAL LO - FULL SIZE TYPE 2BV                | 0                                                                                                              | 0                                                                                                           | 816        | COMPACT FLANGES CAN BE USED FOR TIE-IN PURPOSE ONLY TO EXISTING PIPING AND EQUIPMENT.                                                   |     |                |                   |
| 30                                                                                 |     |          | MODULAR DBB                                    | K15AS06   | 2                                                                                                                        | 2    | MODULAR VALVE DB&B BALL TYPE 1500# RF SS A182 F316 316 SS TRIM METAL LO - FULL SIZE TYPE 2BV                | 0                                                                                                              | 0                                                                                                           |            |                                                                                                                                         |     |                |                   |
| 40                                                                                 |     | VAV      | MODULAR DBB                                    | K09AS06   | 3                                                                                                                        | 3    | MODULAR VALVE DB&B BALL TYPE 900# RF SS A182 F316 316SS TRIM METAL LO FULL SIZE TYPE 2BV                    | 0                                                                                                              | 0                                                                                                           |            |                                                                                                                                         |     |                |                   |
| 50                                                                                 |     |          | MODULAR DBB                                    | M15AS02   | 0.75                                                                                                                     | 1.5  | MODULAR VALVE DB&B BALL TYPE 1500# RF SS A182 F316 316 SS TRIM METAL LO - CONTROLLED BORE TYPE 2BVR         | 0                                                                                                              | 0                                                                                                           | 817        | USE ONLY FOR TIE IN                                                                                                                     |     |                |                   |
| 60                                                                                 |     |          | MODULAR DBB                                    | M15AS06   | 2                                                                                                                        | 2    | MODULAR VALVE DB&B BALL TYPE 1500# RF SS A182 F316 316 SS TRIM METAL LO - CONTROLLED BORE TYPE 2BVR         | 0                                                                                                              | 0                                                                                                           | B1         | ALL BOLTS ARE METRIC DIA.                                                                                                               |     |                |                   |
| 70                                                                                 | U04 | VAW      | MODULAR DBB                                    | M15ES02   | 0.75                                                                                                                     | 1    | MODULAR VALVE DB&B BALL TYPE 1500# RF SS A182 F316 316SS TRIM METAL LO REDUCING - CONTROLLED BORE TYPE 2BVR | 1.5                                                                                                            | 2                                                                                                           | B6         | 7/8" X 145MM BOLTS ONLY TO BE USED FOR 1 INCH 1500# PEARL BALL VALVES ITEM CODE B15AS22                                                 |     |                |                   |
| 80                                                                                 |     | VAV      | MODULAR DBB                                    | M09ES02   | 1                                                                                                                        | 1    | MODULAR VALVE DB&B BALL TYPE 900# RF SS A182 F316 316SS TRIM METAL LO REDUCING - CONTROLLED BORE TYPE 2BVR  | 3                                                                                                              | 3                                                                                                           | BA1        | TO BE USED WITH RAISED FACE FLANGES ONLY.                                                                                               |     |                |                   |
| 90                                                                                 |     |          |                                                |           |                                                                                                                          |      | ***** BALL VALVES *****                                                                                     |                                                                                                                |                                                                                                             | BA5        | TO BE USED WITH COMPACT FLANGES REQUIRING COMPACT NUTS ONLY. FOR FGP ONLY.                                                              |     |                |                   |
| 90                                                                                 |     |          |                                                |           |                                                                                                                          |      |                                                                                                             |                                                                                                                |                                                                                                             | FA8        | USE THREADED FLANGES FOR INSTRUMENT CONNECTIONS ONLY.                                                                                   |     |                |                   |
| 100                                                                                |     |          |                                                |           |                                                                                                                          |      |                                                                                                             |                                                                                                                |                                                                                                             | GA6        | SPECIAL GASKET ONLY FOR USE AS SPECIFIED IN ENG-200-117                                                                                 |     |                |                   |
| 100                                                                                |     |          | BALL                                           | A15AS05   | 2                                                                                                                        | 2    | BALL 1500# RF SS A182 F316 316SS TRIM TRUNNION SOFT RB LO                                                   | 0                                                                                                              | 0                                                                                                           | ND9        | USE ONLY WITH CONSENT OF MATERIALS ENGINEER.                                                                                            |     |                |                   |
| 110                                                                                |     |          | BALL                                           | A15AS06   | 2                                                                                                                        | 2    | BALL 1500# RF SS A182 F316 316SS TRIM TRUNNION METAL RB LO                                                  | 0                                                                                                              | 0                                                                                                           |            |                                                                                                                                         |     |                |                   |
| 120                                                                                |     |          | BALL                                           | A09AS05   | 3                                                                                                                        | 3    | BALL 900# RF SS A182 F316 316SS TRIM TRUNNION SOFT RB LO                                                    | 0                                                                                                              | 0                                                                                                           | SB6        | USE JACKSCREWS FOR PADDLE BLANKS/SPACERS AND FLANGE SPREADERS FOR SPECTACLE BLINDS.                                                     |     |                |                   |
| 130                                                                                |     |          | BALL                                           | A09AS06   | 3                                                                                                                        | 3    | BALL 900# RF SS A182 F316 316SS TRIM TRUNNION METAL RB LO                                                   | 0                                                                                                              | 0                                                                                                           |            |                                                                                                                                         |     |                |                   |
| 140                                                                                |     |          | BALL                                           | A09AS07   | 4                                                                                                                        | 10   | BALL 900# RF SS A182 F316 316SS TRIM TRUNNION SOFT RB GO                                                    | 0                                                                                                              | 0                                                                                                           | UJ2        | USE 1 1/2IN WITH THERMOWELL CONNECTIONS ONLY & 3/4IN (IF SHOWN) FOR DBB PRESSURE CONNECTIONS WITH CHEMICAL SEALS.                       |     |                |                   |
| 150                                                                                |     |          | BALL                                           | A09AS08   | 4                                                                                                                        | 10   | BALL 900# RF SS A182 F316 316SS TRIM TRUNNION METAL RB GO                                                   | 0                                                                                                              | 0                                                                                                           | UJ4        | FOR 2 INCH THERMOWELL CONNECTIONS ONLY                                                                                                  |     |                |                   |
| 160                                                                                | U04 | 817      | BALL                                           | A09CS07   | 12                                                                                                                       | 30   | BALL 900# CF SS A182 F316 316SS TRIM TRUNNION SOFT RB GO                                                    | 0                                                                                                              | 0                                                                                                           | UK9        | DO NOT USE FOR ORIFICE FLANGE TAP ASSEMBLIES.                                                                                           |     |                |                   |
| 170                                                                                | U04 | 817      | BALL                                           | A09CS08   | 12                                                                                                                       | 30   | BALL 900# CF SS A182 F316 316SS TRIM TRUNNION METAL RB GO                                                   | 0                                                                                                              | 0                                                                                                           | VA5        | USE THESE VALVES ONLY WHERE SPECIFIED ON PIPING AND INSTRUMENT DIAGRAMS                                                                 |     |                |                   |
| 180                                                                                |     |          | BALL                                           | B15AS01   | 0.75                                                                                                                     | 1.5  | BALL 1500# RF SS A182 F316 316SS TRIM FLOATING SOFT FB LO                                                   | 0                                                                                                              | 0                                                                                                           | VAV        | USAGE IS LIMITED TO INSTRUMENT ISOLATION PURPOSE.                                                                                       |     |                |                   |
| 190                                                                                |     |          | BALL                                           | B15AS02   | 0.75                                                                                                                     | 1.5  | BALL 1500# RF SS A182 F316 316SS TRIM FLOATING METAL FB LO                                                  | 0                                                                                                              | 0                                                                                                           | VAW        | VALVE ONLY TO BE USED IN ACCORDANCE WITH DOCUMENT L-ST-2055 - VENT DRAIN AND INSTRUMENT CONNECTION DETAILS.                             |     |                |                   |
| 200                                                                                |     | VA5      | BALL                                           | B15AS05   | 2                                                                                                                        | 2    | BALL 1500# RF SS A182 F316 316SS TRIM TRUNNION SOFT FB LO                                                   | 0                                                                                                              | 0                                                                                                           | VC1        | SPRING PISTON CHECK VALVES ARE PREFERED IN THE HORIZONTAL POSITION, BUT MAY BE USED IN THE VERTICAL POSITION WITH ENGINEERING APPROVAL. |     |                |                   |
| 210                                                                                |     | VA5      | BALL                                           | B15AS06   | 2                                                                                                                        | 2    | BALL 1500# RF SS A182 F316 316SS TRIM TRUNNION METAL FB LO                                                  | 0                                                                                                              | 0                                                                                                           |            |                                                                                                                                         |     |                |                   |
| 220                                                                                | U04 | VA5      | BALL                                           | B09AS07   | 3                                                                                                                        | 10   | BALL 900# RF SS A182 F316 316SS TRIM TRUNNION SOFT FB GO                                                    | 0                                                                                                              | 0                                                                                                           |            |                                                                                                                                         |     |                |                   |
| 230                                                                                |     | VA5      | BALL                                           | B09AS08   | 4                                                                                                                        | 10   | BALL 900# RF SS A182 F316 316SS TRIM TRUNNION METAL FB GO                                                   | 0                                                                                                              | 0                                                                                                           |            |                                                                                                                                         |     |                |                   |
| 240                                                                                | U04 | 817      | BALL                                           | B09CS07   | 12                                                                                                                       | 30   | BALL 900# CF SS A182 F316 316SS TRIM TRUNNION SOFT FB GO                                                    | 0                                                                                                              | 0                                                                                                           |            |                                                                                                                                         |     |                |                   |
| 250                                                                                | U04 | 817      | BALL                                           | B09CS08   | 12                                                                                                                       | 30   | BALL 900# CF SS A182 F316 316SS TRIM TRUNNION METAL FB GO                                                   | 0                                                                                                              | 0                                                                                                           |            |                                                                                                                                         |     |                |                   |
| 260                                                                                |     |          |                                                |           |                                                                                                                          |      | ***** GLOBE VALVES *****                                                                                    |                                                                                                                |                                                                                                             |            |                                                                                                                                         |     |                |                   |
| 260                                                                                |     |          |                                                |           |                                                                                                                          |      |                                                                                                             |                                                                                                                |                                                                                                             |            |                                                                                                                                         |     |                |                   |
| 270                                                                                |     |          |                                                |           |                                                                                                                          |      |                                                                                                             |                                                                                                                |                                                                                                             |            |                                                                                                                                         |     |                |                   |
| 270                                                                                |     |          | GLOBE                                          | L15AS48   | 0.75                                                                                                                     | 1.5  | GLOBE 1500# RF A182 F316 SS TRIM 16 OS&Y HW                                                                 | 0                                                                                                              | 0                                                                                                           |            |                                                                                                                                         |     |                |                   |
| 280                                                                                |     |          | GLOBE                                          | L15AS41   | 2                                                                                                                        | 2    | GLOBE 1500# RF SS A351 CF8M TRIM 16 OS&Y HW                                                                 | 0                                                                                                              | 0                                                                                                           |            |                                                                                                                                         |     |                |                   |
| 290                                                                                |     |          | GLOBE                                          | L09AS41   | 3                                                                                                                        | 3    | GLOBE 900# RF SS A351 CF8M TRIM 16 OS&Y HW                                                                  | 0                                                                                                              | 0                                                                                                           |            |                                                                                                                                         |     |                |                   |
| 300                                                                                |     |          | GLOBE                                          | L09AS42   | 4                                                                                                                        | 8    | GLOBE 900# RF SS A351 CF8M TRIM 16 OS&Y GO                                                                  | 0                                                                                                              | 0                                                                                                           |            |                                                                                                                                         |     |                |                   |
| 310                                                                                |     |          |                                                |           |                                                                                                                          |      | ***** CHECK VALVES *****                                                                                    |                                                                                                                |                                                                                                             |            |                                                                                                                                         |     |                |                   |
| 310                                                                                |     |          |                                                |           |                                                                                                                          |      |                                                                                                             |                                                                                                                |                                                                                                             |            |                                                                                                                                         |     |                |                   |
| 320                                                                                |     |          |                                                |           |                                                                                                                          |      |                                                                                                             |                                                                                                                |                                                                                                             |            |                                                                                                                                         |     |                |                   |
| 320                                                                                |     | VC1      | CHECK                                          | C15AS50   | 0.75                                                                                                                     | 1.5  | CHECK PISTON 1500# RF SS A182 F316 TRIM 16                                                                  | 0                                                                                                              | 0                                                                                                           |            |                                                                                                                                         |     |                |                   |
| 330                                                                                | U04 |          | CHECK                                          | C15AS45   | 2                                                                                                                        | 2    | CHECK DUAL WAFER LUG 1500# RF SS A351 CF8M TRIM 16 THROU BOLTED                                             | 0                                                                                                              | 0                                                                                                           |            |                                                                                                                                         |     |                |                   |
| 340                                                                                | U04 |          | CHECK                                          | C09AS45   | 3                                                                                                                        | 8    | CHECK DUAL WAFER LUG 900# RF SS A351 CF8M TRIM 16 THROU BOLTED                                              | 0                                                                                                              | 0                                                                                                           |            |                                                                                                                                         |     |                |                   |
| 350                                                                                | U04 |          | CHECK                                          | C09AS52   | 10                                                                                                                       | 10   | CHECK DUAL DBL FLG 900# RF SS A351 CF8M TRIM 16                                                             | 0                                                                                                              | 0                                                                                                           |            |                                                                                                                                         |     |                |                   |
| 360                                                                                | U04 |          | CHECK                                          | C09CS52   | 12                                                                                                                       | 30   | CHECK DUAL DBL FLG 900# CF SS A351 CF8M TRIM 16                                                             | 0                                                                                                              | 0                                                                                                           |            |                                                                                                                                         |     |                |                   |
| 370                                                                                |     |          |                                                |           |                                                                                                                          |      | *****PIPE*****                                                                                              |                                                                                                                |                                                                                                             |            |                                                                                                                                         |     |                |                   |
| 370                                                                                |     |          |                                                |           |                                                                                                                          |      |                                                                                                             |                                                                                                                |                                                                                                             |            |                                                                                                                                         |     |                |                   |
| 380                                                                                |     |          |                                                |           |                                                                                                                          |      |                                                                                                             |                                                                                                                |                                                                                                             |            |                                                                                                                                         |     |                |                   |
| 380                                                                                |     |          | PIPE                                           | 5365140   | 0.75                                                                                                                     | 1.5  | PIPE SCH 80S SMLS SS A312 TP316/316L PE                                                                     | 0                                                                                                              | 0                                                                                                           |            |                                                                                                                                         |     |                |                   |
| 390                                                                                | U04 | UK9      | PIPE                                           | 5365206   | 0.75                                                                                                                     | 0.75 | PIPE SCH XXS SMLS SS A312 316/316L SS BE                                                                    | 0                                                                                                              | 0                                                                                                           |            |                                                                                                                                         |     |                |                   |
| 400                                                                                | U04 |          | PIPE                                           | 5365138   | 2                                                                                                                        | 3    | PIPE SCH 80S SMLS SS A312 TP316/316L-S BE                                                                   | 0                                                                                                              | 0                                                                                                           |            |                                                                                                                                         |     |                |                   |
| 410                                                                                |     |          | PIPE                                           | 5365128   | 4                                                                                                                        | 24   | PIPE SCH 120 SMLS SS A312 TP316/316L BE                                                                     | 0                                                                                                              | 0                                                                                                           |            |                                                                                                                                         |     |                |                   |
| 420                                                                                |     |          | PIPE                                           | 5365217   | 26                                                                                                                       | 26   | PIPE WT 42.0MM EFW SS A358 316/316L BE                                                                      | 0                                                                                                              | 0                                                                                                           |            |                                                                                                                                         |     |                |                   |
| 430                                                                                |     |          | PIPE                                           | 5365218   | 28                                                                                                                       | 28   | PIPE WT 44.0MM EFW SS A358 316/316L BE                                                                      | 0                                                                                                              | 0                                                                                                           |            |                                                                                                                                         |     |                |                   |
| 440                                                                                |     |          | PIPE                                           | 5365216   | 30                                                                                                                       | 30   | PIPE WT 47.0MM EFW SS A358 316/316L BE                                                                      | 0                                                                                                              | 0                                                                                                           |            |                                                                                                                                         |     |                |                   |
| 450                                                                                |     |          | PIPE                                           | 5365219   | 36                                                                                                                       | 36   | PIPE WT 56.0MM EFW SS A358 316/316L BE                                                                      | 0                                                                                                              | 0                                                                                                           |            |                                                                                                                                         |     |                |                   |
| 460                                                                                |     | 814      | PIPE                                           | 5365207   | 0.75                                                                                                                     | 1.5  | PIPE SCH 160 SMLS SS A312 TP316/316L PE                                                                     | 0                                                                                                              | 0                                                                                                           |            |                                                                                                                                         |     |                |                   |
| 470                                                                                |     |          |                                                |           |                                                                                                                          |      | ***** FITTINGS *****                                                                                        |                                                                                                                |                                                                                                             |            |                                                                                                                                         |     |                |                   |
| 470                                                                                |     |          |                                                |           |                                                                                                                          |      |                                                                                                             |                                                                                                                |                                                                                                             |            |                                                                                                                                         |     |                |                   |
| 480                                                                                |     |          |                                                |           |                                                                                                                          |      |                                                                                                             |                                                                                                                |                                                                                                             |            |                                                                                                                                         |     |                |                   |
| 480                                                                                |     |          | ELBOW                                          | 5449033   | 0.75                                                                                                                     | 1.5  | ELL 90 DEG LR SCH 80S SS A403 WP316/316L-S                                                                  | 0                                                                                                              | 0                                                                                                           |            |                                                                                                                                         |     |                |                   |
| 490                                                                                |     |          | ELBOW                                          | 5449033   | 2                                                                                                                        | 3    | ELL 90 DEG LR SCH 80S SS A403 WP316/316L-S                                                                  | 0                                                                                                              | 0                                                                                                           |            |                                                                                                                                         |     |                |                   |
| 500                                                                                |     |          | ELBOW                                          | 5449570   | 4                                                                                                                        | 24   | ELL 90 DEG LR SCH 120 SS A403 WP316/316L-S                                                                  | 0                                                                                                              | 0                                                                                                           |            |                                                                                                                                         |     |                |                   |
| 510                                                                                |     |          | ELBOW                                          | 5451124   | 26                                                                                                                       | 26   | ELL 90 DEG LR WT 42.0MM SS A403 WP316/316L-W                                                                | 0                                                                                                              | 0                                                                                                           |            |                                                                                                                                         |     |                |                   |
| 520                                                                                |     |          | ELBOW                                          | 5451125   | 28                                                                                                                       | 28   | ELL 90 LR WT 44.0MM 316/316L SS A403 WP316/316L-W                                                           | 0                                                                                                              | 0                                                                                                           |            |                                                                                                                                         |     |                |                   |
| 530                                                                                |     |          | ELBOW                                          | 5451136   | 30                                                                                                                       | 30   | ELL 90 LR WT 47.0MM SS A403 WP316/316L-W                                                                    | 0                                                                                                              | 0                                                                                                           |            |                                                                                                                                         |     |                |                   |
| 540                                                                                |     |          | ELBOW                                          | 5451127   | 36                                                                                                                       | 36   | ELL 90 LR WT 56.0MM SS A403 WP316/316L-W                                                                    | 0                                                                                                              | 0                                                                                                           |            |                                                                                                                                         |     |                |                   |
| 550                                                                                |     |          | ELBOW                                          | 5449146   | 0.75                                                                                                                     | 3    | ELL 45 DEG LR SCH 80S SS A403 WP316/316L-S                                                                  | 0                                                                                                              | 0                                                                                                           |            |                                                                                                                                         |     |                |                   |
| 560                                                                                | U04 | UK9      | ELBOW                                          | 5449143   | 0.75                                                                                                                     | 0.75 | ELL 45 DEG LR XXS SS A403 WP316/316L-S                                                                      | 0                                                                                                              | 0                                                                                                           |            |                                                                                                                                         |     |                |                   |
| 570                                                                                | U04 | ND9      | ELBOW                                          | 5449142   | 0.75                                                                                                                     | 0.75 | ELL BW 45 DEG LR SCH 160 SS A403 WP316/316L-S                                                               | 0                                                                                                              | 0                                                                                                           |            |                                                                                                                                         |     |                |                   |
| 580                                                                                | U04 | ND9      | ELBOW                                          | 5449140   | 0.75                                                                                                                     | 0.75 | ELL BW 90 DEG LR SCH 160 SS A403 WP316/316L-S                                                               | 0                                                                                                              | 0                                                                                                           |            |                                                                                                                                         |     |                |                   |
|  |     |          | TENGIZCHEVROIL<br>TCO<br>TENGIZ,<br>KAZAKHSTAN |           | CONSTRUCTION                                                                                                             |      | CORR.ALLOW.                                                                                                 | SERVICE                                                                                                        | MATERIAL                                                                                                    | DATE       | BY                                                                                                                                      | REV | SHEET          | PIPING LINE CLASS |
|                                                                                    |     |          |                                                |           | ALL SIZES- BUTT WELD<br>SEAL WELDING - FOR THREADED CONNECTIONS ONLY<br>PIPE BENDS - NONE<br>THREAD SEALANT - PTFE PASTE |      | CORR. ALLOW. 1 MM                                                                                           | NACE STD. MR0175 / ISO 15156<br>DESIGN: ASME B16.5 MG 2.2<br>CODE: ASME B31.3<br>FLUID CODES - PIM-SU-5112-TCO | MATERIAL: 316/316L SS DUAL GRADE<br>FLANGE RATING: 900 RF/CF<br>TEMPERATURE RANGE: -40 / 350 °C<br>COMMENT: | 12/16/2024 | BY<br>OZAC                                                                                                                              | U04 | Page 1<br>of 4 | 900P22            |

| SEQ NO | REV | NOTE NO. | ITEM NAME | ITEM CODE | SIZE RANGE / SMALL END SIZES |      | DESCRIPTION                                             | REFERENCE / LARGE END SIZES |      | NOTES |
|--------|-----|----------|-----------|-----------|------------------------------|------|---------------------------------------------------------|-----------------------------|------|-------|
| 590    | U04 | UK9      | ELBOW     | 5449141   | 0.75                         | 0.75 | ELL BW 90 DEG LR SCH XXS SS A403 WP316/316L-S           | 0                           | 0    |       |
| 600    |     |          | ELBOW     | 5449576   | 4                            | 24   | ELL 45 DEG LR SCH 120 SS A403 WP316/316L-S              | 0                           | 0    |       |
| 610    |     |          | ELBOW     | 5449084   | 26                           | 26   | ELL 45 DEG LR WT 42.0MM SS A403 WP316/316L-W            | 0                           | 0    |       |
| 620    |     |          | ELBOW     | 5449085   | 28                           | 28   | ELL 45 DEG LR WT 44.0MM SS A403 WP316/316L-W            | 0                           | 0    |       |
| 630    |     |          | ELBOW     | 5451126   | 30                           | 30   | ELL 45 LR WT 47.0MM SS A403 WP316/316L-W                | 0                           | 0    |       |
| 640    |     |          | ELBOW     | 5449086   | 36                           | 36   | ELL 45 LR WT 56.0MM SS A403 WP316/316L-W                | 0                           | 0    |       |
| 650    |     |          |           |           |                              |      |                                                         |                             |      |       |
| 650    |     |          | TEE       | 5449156   | 0.75                         | 1.5  | TEE SCH 80S SS A403 WP316/316L-S                        | 0                           | 0    |       |
| 660    |     |          | TEE       | 5449156   | 2                            | 3    | TEE SCH 80S SS A403 WP316/316L-S                        | 0                           | 0    |       |
| 670    | U04 | UK9      | TEE       | 5449191   | 0.75                         | 0.75 | TEE SCH XXS SS A403 WP316/316L-S                        | 0                           | 0    |       |
| 680    |     |          | TEE       | 5449579   | 4                            | 24   | TEE SCH 120 SS A403 WP316/316L-S                        | 0                           | 0    |       |
| 690    | U04 | ND9      | TEE       | 5449190   | 0.75                         | 0.75 | TEE SCH 160 SS A403 WP316/316L-S                        | 0                           | 0    |       |
| 700    |     |          | TEE       | 5449087   | 26                           | 26   | TEE 42.0MM SS A403 WP316/316L-W                         | 0                           | 0    |       |
| 710    |     |          | TEE       | 5449088   | 28                           | 28   | TEE 44.0MM SS A403 WP316/316L-W                         | 0                           | 0    |       |
| 720    |     |          | TEE       | 5451116   | 30                           | 30   | TEE 47.0MM SS A403 WP316/316L-W                         | 0                           | 0    |       |
| 730    |     |          | TEE       | 5449089   | 36                           | 36   | TEE 56.0MM SS A403 WP316/316L-W                         | 0                           | 0    |       |
| 740    |     |          | TEE RED   | 5448905   | 0.75                         | 2    | TEE RED SCH 80S SS A403 WP316/316L-S                    | 1                           | 3    |       |
| 750    |     |          | TEE RED   | 5449577   | 2                            | 3    | TEE RED SCH 120/80S SS A403 WP316/316L-S                | 4                           | 6    |       |
| 760    |     |          | TEE RED   | 5449578   | 4                            | 20   | TEE RED SCH 120 SS A403 WP316/316L-S                    | 6                           | 24   |       |
| 770    |     |          | TEE RED   | 5449094   | 12                           | 24   | TEE RED WT 42.0MM X SCH 120 SS A403 WP316/316L-W        | 26                          | 26   |       |
| 780    |     |          | TEE RED   | 5449054   | 14                           | 24   | TEE RED WT 47.0MM X SCH 120 SS A403 WP316/316L-W        | 30                          | 30   |       |
| 790    | U04 |          | TEE RED   | 5392839   | 20                           | 20   | TEE RED WT 56.0MM X SCH 120 SS A403 WP316/316L-W        | 36                          | 36   |       |
| 800    |     |          |           |           |                              |      |                                                         |                             |      |       |
| 800    |     |          | CAP       | 5449049   | 0.75                         | 3    | CAP SCH 80S SS A403 WP316/316L-S                        | 0                           | 0    |       |
| 810    |     |          | CAP       | 5449052   | 4                            | 24   | CAP SCH 120 SS A403 WP316/316L-S                        | 0                           | 0    |       |
| 820    |     |          | CAP       | 5449090   | 26                           | 26   | CAP WT 42.0MM SS A403 WP316/316L                        | 0                           | 0    |       |
| 830    |     |          | CAP       | 5449091   | 28                           | 28   | CAP WT 44.0MM SS A403 WP316/316L                        | 0                           | 0    |       |
| 840    |     |          | CAP       | 5449097   | 30                           | 30   | CAP WT 47.0MM SS A403 WP316/316L                        | 0                           | 0    |       |
| 850    |     |          | CAP       | 5449093   | 36                           | 36   | CAP WT 56.0MM SS A403 WP316/316L                        | 0                           | 0    |       |
| 860    |     |          |           |           |                              |      |                                                         |                             |      |       |
| 860    | U04 |          | RED CONC  | 5449158   | 0.5                          | 0.5  | REDUCER CONC SCH 80S SS A403 WP316/316L-S               | 0.75                        | 0.75 |       |
| 870    | U04 |          | RED CONC  | 5449158   | 0.5                          | 2    | REDUCER CONC SCH 80S SS A403 WP316/316L-S               | 1                           | 3    |       |
| 880    | U04 |          | RED CONC  | 5448916   | 1.5                          | 3    | REDUCER CONC SCH 120/80S SS A403 WP316/316L-S           | 4                           | 6    |       |
| 890    |     |          | RED CONC  | 5448915   | 4                            | 20   | REDUCER CONC SCH 120 SS A403 WP316/316L-S               | 6                           | 24   |       |
| 900    |     |          | RED CONC  | 5449095   | 18                           | 24   | REDUCER CONC 42.0MM WT/SCH 120 SS A403 WP316/316L-W     | 26                          | 26   |       |
| 910    |     |          | RED CONC  | 5450766   | 24                           | 24   | REDUCER CONC 47.0MM / SCH 120 SS A403 WP316/316L-W      | 30                          | 30   |       |
| 920    | U04 |          | RED CONC  | 5450753   | 24                           | 24   | REDUCER CONC 56.0MM / SCH 120 SS A403 WP316/316L-W      | 36                          | 36   |       |
| 930    |     |          | RED CONC  | 5450757   | 30                           | 30   | REDUCER CONC 56.0MM/ 47.0MM SS A403 WP316/316L-W        | 36                          | 36   |       |
| 940    | U04 |          | RED ECC   | 5449159   | 0.5                          | 0.5  | REDUCER ECC SCH 80S SS A403 WP316/316L-S                | 1                           | 1    |       |
| 950    |     |          | RED ECC   | 5449159   | 0.75                         | 2    | REDUCER ECC SCH 80S SS A403 WP316/316L-S                | 1                           | 3    |       |
| 960    | U04 |          | RED ECC   | 5449179   | 1.5                          | 3    | REDUCER ECC SCH 120/80S SS A403 WP316/316L-S            | 4                           | 6    |       |
| 970    |     |          | RED ECC   | 5449178   | 4                            | 20   | REDUCER ECC SCH 120 SS A403 WP316/316L-S                | 6                           | 24   |       |
| 980    |     |          | RED ECC   | 5449096   | 18                           | 24   | REDUCER ECC 42.0MM WT/SCH 120 SS A403 WP316/316L-W      | 26                          | 26   |       |
| 990    |     |          | RED ECC   | 5450716   | 24                           | 24   | REDUCER ECC 47.0MM / SCH 120 SS A403 WP316/316L-W       | 30                          | 30   |       |
| 1000   |     |          | RED ECC   | 5450755   | 24                           | 24   | REDUCER ECC 56.0MM / SCH 120 SS A403 WP316/316L-W       | 36                          | 36   |       |
| 1010   |     |          | RED ECC   | 5450734   | 30                           | 30   | REDUCER ECC 56.0MM / 47.0MM SS A403 WP316/316L-W        | 36                          | 36   |       |
| 1020   |     |          |           |           |                              |      |                                                         |                             |      |       |
| 1020   |     |          | OLETS     | 5504176   | 0.75                         | 1.5  | NIPOFLANGE 1500# RF SCH 80S SS A182 F316/316L           | 2                           | 3    |       |
| 1030   |     |          | OLETS     | 5504177   | 0.75                         | 1.5  | NIPOFLANGE 1500# RF SCH 120/80S SS A182 F316/316L       | 4                           | 24   |       |
| 1040   |     |          | OLETS     | 5504178   | 0.75                         | 1.5  | NIPOFLANGE 1500# RF 42.0MM WT/SCH 80S SS A182 F316/316L | 26                          | 26   |       |
| 1050   |     |          | OLETS     | 5504179   | 0.75                         | 1.5  | NIPOFLANGE 1500# RF 47.0MM WT/SCH 80S SS A182 F316/316L | 30                          | 30   |       |
| 1060   |     |          | OLETS     | 5504189   | 0.75                         | 1.5  | NIPOFLANGE 1500# RF 56.0MM WT/SCH 80S SS A182 F316/316L | 36                          | 36   |       |
| 1070   |     | UJ2      | OLETS     | 5504180   | 1.5                          | 1.5  | NIPOFLANGE 1500# RF SCH 120/160 SS A182 F316/316L       | 4                           | 24   |       |
| 1080   |     | UJ2      | OLETS     | 5504181   | 1.5                          | 1.5  | NIPOFLANGE 1500# RF 42.0MM WT/SCH 160 SS A182 F316/316L | 26                          | 26   |       |
| 1090   |     | UJ2      | OLETS     | 5504182   | 1.5                          | 1.5  | NIPOFLANGE 1500# RF 47.0MM WT/SCH 160 SS A182 F316/316L | 30                          | 30   |       |
| 1100   |     | UJ2      | OLETS     | 5504188   | 1.5                          | 1.5  | NIPOFLANGE 1500# RF 56.0MM WT/SCH 160 SS A182 F316/316L | 36                          | 36   |       |
| 1110   |     |          | OLETS     | 5504183   | 2                            | 2    | NIPOFLANGE 1500# RF SCH 80S SS A182 F316/316L           | 3                           | 3    |       |
| 1120   |     |          | OLETS     | 5504184   | 2                            | 2    | NIPOFLANGE 1500# RF SCH 120/80S SS A182 F316/316L       | 4                           | 24   |       |
| 1130   |     |          | OLETS     | 5504185   | 2                            | 2    | NIPOFLANGE 1500# RF 42.0MM WT/SCH 80S SS A182 F316/316L | 26                          | 26   |       |
| 1140   |     |          | OLETS     | 5504186   | 2                            | 2    | NIPOFLANGE 1500# RF 47.0MM WT/SCH 80 SS A182 F316/316L  | 30                          | 30   |       |
| 1150   | U04 | UJ4      | OLETS     | 5504313   | 2                            | 2    | NIPOFLANGE 1500# RF 47.0MM WT/SCH 160 SS A182 F316/316L | 30                          | 30   |       |
| 1160   |     |          | OLETS     | 5504187   | 2                            | 2    | NIPOFLANGE 1500# RF 56.0MM WT/SCH 80 SS A182 F316/316L  | 36                          | 36   |       |
| 1170   |     |          |           |           |                              |      |                                                         |                             |      |       |
| 1170   |     |          | OLETS     | 5509637   | 0.75                         | 1    | WELDOLET SCH 80S SS A182 F316/316L                      | 2                           | 3    |       |
| 1180   |     |          | OLETS     | 5510374   | 0.75                         | 3    | WELDOLET SCH 120 /80S SS A182 316/316L                  | 4                           | 24   |       |
| 1190   |     |          | OLETS     | 5509649   | 2                            | 3    | WELDOLET 42.0MM WT/SCH 80S SS A182 F316/316L            | 26                          | 26   |       |
| 1200   |     |          | OLETS     | 5509647   | 2                            | 3    | WELDOLET 47.0MM WT/SCH 80S SS A182 F316/316L            | 30                          | 30   |       |
| 1210   |     |          | OLETS     | 5509640   | 4                            | 8    | WELDOLET SCH 120 SS A182 F316/316L                      | 12                          | 24   |       |
| 1220   |     |          | OLETS     | 5509646   | 4                            | 10   | WELDOLET 42.0MM WT/SCH 120 SS A182 F316/316L            | 26                          | 26   |       |
| 1230   |     |          | OLETS     | 5509667   | 1                            | 1    | WELDOLET 47.0MM WT/SCH 80S SS A182 F316/316L            | 30                          | 30   |       |
| 1240   |     |          | OLETS     | 5509648   | 4                            | 12   | WELDOLET 47.0MM WT/SCH 120 SS A182 F316/316L            | 30                          | 30   |       |
| 1250   |     |          | OLETS     | 5509659   | 4                            | 4    | WELDOLET 56.0MM WT/ SCH 120 SS A182 F316/316L           | 36                          | 36   |       |
| 1260   | U04 |          | OLETS     | 5509666   | 3                            | 3    | WELDOLET WT 56.0MM/SCH 80S SS A182 F316/316L            | 36                          | 36   |       |

|                                                                                    |                                      |                                                                                                                          |                   |                                                                                                                |                                                                                                             |            |            |     |                |                   |
|------------------------------------------------------------------------------------|--------------------------------------|--------------------------------------------------------------------------------------------------------------------------|-------------------|----------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------|------------|------------|-----|----------------|-------------------|
|  | TENGIZCHEVROIL<br>TCO,<br>KAZAKHSTAN | CONSTRUCTION                                                                                                             | CORR.ALLOW.       | SERVICE                                                                                                        | MATERIAL                                                                                                    | DATE       | BY         | REV | SHEET          | PIPING LINE CLASS |
|                                                                                    |                                      | ALL SIZES- BUTT WELD<br>SEAL WELDING - FOR THREADED CONNECTIONS ONLY<br>PIPE BENDS - NONE<br>THREAD SEALANT - PTFE PASTE | CORR. ALLOW. 1 MM | NACE STD. MR0175 / ISO 15156<br>DESIGN: ASME B16.5 MG 2.2<br>CODE: ASME B31.3<br>FLUID CODES - PIM-SU-5112-TCO | MATERIAL: 316/316L SS DUAL GRADE<br>FLANGE RATING: 900 RF/CF<br>TEMPERATURE RANGE: -40 / 350 °C<br>COMMENT: | 12/16/2024 | BY<br>OZAC | U04 | Page 2<br>of 4 | 900P22            |

| SEQ NO | REV | NOTE NO. | ITEM NAME   | ITEM CODE | SIZE RANGE / SMALL END SIZES |      | DESCRIPTION                                                                | REFERENCE / LARGE END SIZES |     | NOTES |
|--------|-----|----------|-------------|-----------|------------------------------|------|----------------------------------------------------------------------------|-----------------------------|-----|-------|
| 1270   |     |          |             |           |                              |      |                                                                            |                             |     |       |
| 1270   |     | UJ2      | ELBOFLG     | 5516085   | 1.5                          | 1.5  | ELBOFLANGE 1500# RF SCH 120/160 SS A182 F316/316L                          | 4                           | 24  |       |
| 1280   |     | UJ2      | ELBOFLG     | 5516086   | 1.5                          | 1.5  | ELBOFLANGE 1500# RF 42.0MM WT/SCH 160 SS A182 F316/316L                    | 26                          | 26  |       |
| 1290   |     | UJ2      | ELBOFLG     | 5516087   | 1.5                          | 1.5  | ELBOFLANGE 1500# RF 47.0MM WT/SCH 160 SS A182 F316/316L                    | 30                          | 30  |       |
| 1300   |     | UJ2      | ELBOFLG     | 5516088   | 1.5                          | 1.5  | ELBOFLANGE 1500# RF 56.0MM WT/SCH 160 SS A182 F316/316L                    | 36                          | 36  |       |
| 1310   |     |          |             |           |                              |      |                                                                            |                             |     |       |
| 1310   |     | 816      |             |           |                              |      | ***** FLANGES *****                                                        |                             |     |       |
| 1320   |     |          |             |           |                              |      |                                                                            |                             |     |       |
| 1320   |     | FA8      | TEE RED     | 5600664   | 0.5                          | 0.5  | FLG SCRDR (FNPT) REDUCING 1500# RF SS A182 F316/316L                       | 0.75                        | 1.5 |       |
| 1330   |     |          |             |           |                              |      |                                                                            |                             |     |       |
| 1330   | U04 |          | FLG ADAPTER | 5851205   | 0.75                         | 0.75 | FLANGE ADAPTER 1500# RF 316 SS X 12 MM TUBE                                | 0                           | 0   |       |
| 1340   |     |          | FLANGE      | 5851205   | 0.75                         | 0.75 | FLANGE ADAPTER 1500# RF 316 SS X 12 MM TUBE                                | 0                           | 0   |       |
| 1350   |     |          |             |           |                              |      |                                                                            |                             |     |       |
| 1350   | U04 |          | FLANGE      | 5583979   | 0.5                          | 2    | FLG WN 1500# RF SS A182 F316/316L SCH 80S BORE                             | 0                           | 0   |       |
| 1360   |     |          | FLANGE      | 5583006   | 3                            | 3    | FLG WN 900# RF SS A182 F316/316L SCH 80S BORE                              | 0                           | 0   |       |
| 1370   |     |          | FLANGE      | 5583813   | 4                            | 10   | FLG WN 900# RF SS A182 F316/316L SCH 120 BORE                              | 0                           | 0   |       |
| 1380   |     |          | FLANGE      | 5583813   | 12                           | 24   | FLG WN 900# RF SS A182 F316/316L SCH 120 BORE                              | 0                           | 0   |       |
| 1390   |     |          | FLANGE      | 5583018   | 26                           | 26   | FLG WN 900# RF SS A182 F316/316L 42.0MM WT B16.47 SERIES A                 | 0                           | 0   |       |
| 1400   |     |          | FLANGE      | 5583019   | 30                           | 30   | FLG WN 900# RF SS A182 F316/316L 47.0MM WT B16.47 SERIES A                 | 0                           | 0   |       |
| 1410   | U04 | 817      | FLANGE      | 5619824   | 12                           | 24   | FLG COMPACT 900# RJ SS A182 F316/316L SCH 120 BORE LINE CLASS 900P21/P22   | 0                           | 0   |       |
| 1420   | U04 | 817      | FLANGE      | 5619825   | 26                           | 26   | FLG COMPACT 900# RJ SS A182 F316/316L WT 42.0MM LINE CLASS 900P21/P22      | 0                           | 0   |       |
| 1430   | U04 | 817      | FLANGE      | 5619826   | 28                           | 28   | FLG COMPACT 900# RJ SS A182 F316/316L WT 44.0MM LINE CLASS 900P21/P22      | 0                           | 0   |       |
| 1440   | U04 | 817      | FLANGE      | 5619827   | 30                           | 30   | FLG COMPACT 900# RJ SS A182 F316/316L WT 47.0MM LINE CLASS 900P21/P22      | 0                           | 0   |       |
| 1450   | U04 | 817      | FLANGE      | 5619828   | 36                           | 36   | FLG COMPACT 900# RJ SS A182 F316/316L WT 56.0MM LINE CLASS 900P21/P22      | 0                           | 0   |       |
| 1460   | U04 | 817      | FLANGE      | 5583022   | 3                            | 3    | FLG WN 900# RJ SS A182 F316/316L SCH XS BORE                               | 0                           | 0   |       |
| 1470   | U04 | ND9      | FLANGE      | 5583003   | 0.75                         | 0.75 | FLG WN 1500# RF SS A182 F316/316L SCH 160 BORE                             | 0                           | 0   |       |
| 1480   | U04 |          | FLANGE      | 5583980   | 0.75                         | 0.75 | FLG WN 1500# RF SS A182 F316/316L SCH XXS BORE                             | 0                           | 0   |       |
| 1490   | U04 |          | FLANGE      | 5583020   | 36                           | 36   | FLG WN 900# RF SS A182 F316/316L 56.0MM WT B16.47 SERIES A                 | 0                           | 0   |       |
| 1500   |     |          | BLIND       | 5616564   | 0.5                          | 2    | FLG BLIND 1500# RF SS A182 F316/316L                                       | 0                           | 0   |       |
| 1510   |     |          | BLIND       | 5616556   | 3                            | 10   | FLG BLIND 900# RF SS A182 F316/316L                                        | 0                           | 0   |       |
| 1520   |     |          | BLIND       | 5616556   | 12                           | 24   | FLG BLIND 900# RF SS A182 F316/316L                                        | 0                           | 0   |       |
| 1530   |     |          | BLIND       | 5616533   | 26                           | 30   | FLG BLIND 900# RF SS A182 F316/316L B16.47 SERIES A                        | 0                           | 0   |       |
| 1540   | U04 | 817      | BLIND       | 5619753   | 12                           | 36   | FLG COMPACT BLIND 900# RJ SS A182 F316/316L PIPE CLASS 900P22              | 0                           | 0   |       |
| 1550   |     |          |             |           |                              |      |                                                                            |                             |     |       |
| 1550   |     |          |             |           |                              |      | ***** ORIFICE FLANGES *****                                                |                             |     |       |
| 1560   |     |          |             |           |                              |      |                                                                            |                             |     |       |
| 1560   |     |          | ORIFICE FLG | 5641519   | 2                            | 2    | WN ORIF SET 1500# RF SS A182 F316/316L SCH 80S BORE                        | 0                           | 0   |       |
| 1570   |     |          | ORIFICE FLG | 5641287   | 3                            | 3    | WN ORIF SET 900# RF SS A182 F316/316L SCH 80S BORE                         | 0                           | 0   |       |
| 1580   |     |          | ORIFICE FLG | 5641293   | 4                            | 24   | WN ORIF SET 900# RF SS A182 F316/316L SCH 120 BORE                         | 0                           | 0   |       |
| 1590   |     |          | ORIFICE FLG | 5640609   | 26                           | 26   | WN ORIF SET 900# RF A182 F316/316L 42.0MM WT B16.47 SERIES A               | 0                           | 0   |       |
| 1600   |     |          | ORIFICE FLG | 5640614   | 30                           | 30   | WN ORIF SET 900# RF A182 F316/316L 47.0MM WT B16.47 SERIES A               | 0                           | 0   |       |
| 1610   |     |          |             |           |                              |      |                                                                            |                             |     |       |
| 1610   |     |          |             |           |                              |      | ***** PIPE NIPPLES *****                                                   |                             |     |       |
| 1620   |     |          |             |           |                              |      |                                                                            |                             |     |       |
| 1620   | U04 | 814      |             |           |                              |      | NIPPLE PBE CUT FROM PIPE                                                   |                             |     |       |
| 1630   |     | 814      |             | 0         |                              |      | NIPPLE PBE CUT FROM PIPE                                                   |                             |     |       |
| 1640   |     |          |             |           |                              |      |                                                                            |                             |     |       |
| 1640   |     |          |             |           |                              |      | ***** GASKETS *****                                                        |                             |     |       |
| 1650   |     |          |             |           |                              |      |                                                                            |                             |     |       |
| 1650   |     |          | GASKET      | 5672251   | 0.5                          | 2    | GASKET 1500# 316SS SPIRAL WOUND GRAPHITE IR                                | 0                           | 0   |       |
| 1660   |     |          | GASKET      | 5673117   | 3                            | 24   | GASKET 900# 316SS SPIRAL WOUND GRAPHITE IR                                 | 0                           | 0   |       |
| 1670   |     |          | GASKET      | 5674033   | 26                           | 30   | GASKET 900# 316SS KAMMPROFILE GRAPHITE ASME B16.47 SERIES A                | 0                           | 0   |       |
| 1680   | U04 | 817      | GASKET      | 5673451   | 12                           | 36   | GASKET 900# RJ INC 718 ENERGIZED SEALRING COMPACT FLANGE PIPE CLASS 900P22 | 0                           | 0   |       |
| 1690   | U04 | 815, 817 | GASKET      | 5674481   | 3                            | 3    | GASKET 900# RTJ SS OCTAGONAL RING                                          | 0                           | 0   |       |
| 1700   | U04 | GA6      | GASKET      | 5673021   | 2                            | 2    | GASKET 1500# 316SS KAMMPROFILE GRAPHITE ASME B16.5                         | 0                           | 0   |       |
| 1710   | U04 | GA6      | GASKET      | 5673020   | 3                            | 3    | GASKET 900# 316SS KAMMPROFILE GRAPHITE ASME B16.5                          | 0                           | 0   |       |
| 1720   |     |          |             |           |                              |      |                                                                            |                             |     |       |
| 1720   |     | B1       |             |           |                              |      | ***** BOLTING *****                                                        |                             |     |       |
| 1730   |     |          |             |           |                              |      |                                                                            |                             |     |       |
| 1730   | U04 | BA1      | BOLTING     | 5675770   | 0.5                          | 10   | STUD-BOLT A320 GR L7M/A194 GR 7M (S3) WITH 2 NUTS                          | 0                           | 0   |       |
| 1740   |     | BA1      | BOLTING     | 5675770   | 12                           | 20   | STUD-BOLT A320 GR L7M/A194 GR 7M (S3) WITH 2 NUTS                          | 0                           | 0   |       |
| 1750   | U04 | BA5      | BOLTING     | 5675778   | 12                           | 99   | STUD-BOLT C/W 2 COMPACT NUTS API-6A718                                     | 0                           | 0   |       |
| 1760   |     | BA1      | BOLTING     | 5675776   | 24                           | 99   | STUD-BOLT WITH 2 NUTS API-6A718                                            | 0                           | 0   |       |
| 1770   |     |          |             |           |                              |      |                                                                            |                             |     |       |
| 1770   |     | SB6      | BOLTING     | 5675675   | 10                           | 30   | JACK SCREW HEX HEAD A320 GR L7M                                            | 0                           | 0   |       |
| 1780   |     |          |             |           |                              |      |                                                                            |                             |     |       |
| 1780   |     |          |             |           |                              |      | ***** BLINDS AND SPACERS *****                                             |                             |     |       |
| 1790   |     |          |             |           |                              |      |                                                                            |                             |     |       |
| 1790   |     |          | SPEC BLIND  | 5749757   | 0.75                         | 2    | SPECTACLE BLIND 1500# RF SS A240 GR 316                                    | 0                           | 0   |       |
| 1800   |     |          | SPEC BLIND  | 5749755   | 3                            | 6    | SPECTACLE BLIND 900# RF SS A240 GR 316                                     | 0                           | 0   |       |
| 1810   |     |          |             |           |                              |      |                                                                            |                             |     |       |
| 1810   |     |          | PADDLE      | 5750048   | 8                            | 10   | PADDLE BLANK 900# RF SS A240 GR 316                                        | 0                           | 0   |       |

|  | <b>TENGIZCHEVROIL TCO TENGIZ, KAZAKHSTAN</b> | CONSTRUCTION                                                                                                             | CORR.ALLOW.       | SERVICE                                                                                                        | MATERIAL                                                                                                    | DATE       | BY      | REV | SHEET       | PIPING LINE CLASS |
|------------------------------------------------------------------------------------|----------------------------------------------|--------------------------------------------------------------------------------------------------------------------------|-------------------|----------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------|------------|---------|-----|-------------|-------------------|
|                                                                                    |                                              | ALL SIZES- BUTT WELD<br>SEAL WELDING - FOR THREADED CONNECTIONS ONLY<br>PIPE BENDS - NONE<br>THREAD SEALANT - PTFE PASTE | CORR. ALLOW. 1 MM | NACE STD. MR0175 / ISO 15156<br>DESIGN: ASME B16.5 MG 2.2<br>CODE: ASME B31.3<br>FLUID CODES - PIM-SU-5112-TCO | MATERIAL: 316/316L SS DUAL GRADE<br>FLANGE RATING: 900 RF/CF<br>TEMPERATURE RANGE: -40 / 350 °C<br>COMMENT: | 12/16/2024 | BY OZAC | U04 | Page 3 of 4 | <b>900P22</b>     |

| SEQ NO | REV | NOTE NO. | ITEM NAME | ITEM CODE | SIZE RANGE / SMALL END SIZES |    | DESCRIPTION                                          | REFERENCE / LARGE END SIZES |   | NOTES |
|--------|-----|----------|-----------|-----------|------------------------------|----|------------------------------------------------------|-----------------------------|---|-------|
| 1820   |     |          | PADDLE    | 5750048   | 12                           | 24 | PADDLE BLANK 900# RF SS A240 GR 316                  | 0                           | 0 |       |
| 1830   |     |          | PADDLE    | 5750282   | 8                            | 10 | PADDLE SPACER 900# RF SS A240 GR 316                 | 0                           | 0 |       |
| 1840   |     |          | PADDLE    | 5750282   | 12                           | 24 | PADDLE SPACER 900# RF SS A240 GR 316                 | 0                           | 0 |       |
| 1850   | U04 |          | PADDLE    | 5750532   | 26                           | 36 | PADDLE BLANK 900# RF SS A240 GR 316 B16.47 SERIES A  | 0                           | 0 |       |
| 1860   | U04 |          | PADDLE    | 5750632   | 26                           | 36 | PADDLE SPACER 900# RF SS A240 GR 316 B16.47 SERIES A | 0                           | 0 |       |
| 1870   | U04 | 817      | PADDLE    | 5750274   | 12                           | 36 | PADDLE BLANK COMPACT 900# RJ SS A240 GR 316          | 0                           | 0 |       |
| 1880   | U04 | 817      | PADDLE    | 5750275   | 12                           | 36 | PADDLE SPACER COMPACT 900# RJ SS A240 GR 316         | 0                           | 0 |       |

|                                                                                    |                                                |                                                                                                                          |                   |                                                                                                                |                                                                                                             |            |            |     |                |                   |
|------------------------------------------------------------------------------------|------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------|-------------------|----------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------|------------|------------|-----|----------------|-------------------|
|  | TENGIZCHEVROIL<br>TCO<br>TENGIZ,<br>KAZAKHSTAN | CONSTRUCTION                                                                                                             | CORR.ALLOW.       | SERVICE                                                                                                        | MATERIAL                                                                                                    | DATE       | BY         | REV | SHEET          | PIPING LINE CLASS |
|                                                                                    |                                                | ALL SIZES- BUTT WELD<br>SEAL WELDING - FOR THREADED CONNECTIONS ONLY<br>PIPE BENDS - NONE<br>THREAD SEALANT - PTFE PASTE | CORR. ALLOW. 1 MM | NACE STD. MR0175 / ISO 15156<br>DESIGN: ASME B16.5 MG 2.2<br>CODE: ASME B31.3<br>FLUID CODES - PIM-SU-5112-TCO | MATERIAL: 316/316L SS DUAL GRADE<br>FLANGE RATING: 900 RF/CF<br>TEMPERATURE RANGE: -40 / 350 °C<br>COMMENT: | 12/16/2024 | BY<br>OZAC | U04 | Page 4<br>of 4 | 900P22            |