

SEQ NO	REV	NOTE NO.	ITEM NAME	ITEM CODE	SIZE RANGE / SMALL END SIZES		DESCRIPTION	REFERENCE / LARGE END SIZES		NOTES
10	U04	VAX, 817	MODULAR DBB	M10TL14-X22	2	2	MODULAR VALVE DB&B BALL TYPE 10000 CF X RTJ (BX TYPE) INCONEL 625 BODY AND TRIM METAL LO - CONTROLLED BORE TYPE 2BVR	0	0	817 USE ONLY FOR TIE IN B1 ALL BOLTS ARE METRIC DIA. B6 7/8" X 145MM BOLTS ONLY TO BE USED FOR 1 INCH 1500# PERAR BALL VALVES ITEM CODE B15AS22 BA3 TO BE USED WITH API 6A FLANGES ONLY. BA5 TO BE USED WITH COMPACT FLANGES REQUIRING COMPACT NUTS ONLY. FOR FGP ONLY. FA1 API 6BX FLANGE TO NB PIPE DESIGNATION SEE PIM-SU-5112-TCO SB6 USE JACKSCREWS FOR PADDLE BLANKS/SPACERS AND FLANGE SPREADERS FOR SPECTACLE BLINDS. VAX VALVE ONLY TO BE USED IN ACCORDANCE WITH DOCUMENT L-ST-2055 - VENT DRAIN AND INSTRUMENT CONNECTION DETAILS. RTJ(BX TYPE) END IS SIDE MATING WITH INSTRUMENTATION
20							*****PIPE ABOVE GROUND*****			
20										
30										
30	U04		PIPE	9005277	14	14	PIPE WT 55.00 MM ID 250 MM (245.6 MM ACTUAL) SMLS 2-1/4CR F22M BE	0	0	
40			PIPE	9005277	14	14	PIPE WT 55.00 MM ID 250 MM SMLS 2-1/4CR F22M BE	0	0	
50	U04			9005277CTD	14	14	PIPE WT 55.00 MM ID 250 MM (245.6 MM ACTUAL) SMLS 2-1/4CR F22M BE COATED	0	0	
60										
60							***** FITTINGS ABOVE GROUND*****			
70										
70			ELBOW	9002726	14	14	BEND FORGED 90 DEG 5D WT 55.0MM 2-1/4CR F22M	0	0	
80			ELBOW	9002737	14	14	BEND FORGED 45 DEG 5D WT 55.0MM 2-1/4CR F22M	0	0	
90	U04		ELBOW	9002748	14	14	BEND FORGED 22.5 DEG 5D WT 55.0 MM, ID 245.6 MM, 2-1/4CR F22M	0	0	
100										
100	U04		TEE RED	9002380	2	2	TEE RED 250.0MM ID (245.6 ACTUAL), 55.0MM WT / 60.30 OD 12.5MM 2-1/4CR F22M	14	14	
110			CAP	9006194	14	14	CAP WT 55.0MM SMLS 2-1/4CR F22M	0	0	
110										
120	U04		ELBOW	9006596	14	14	ELL 90 DEG LR WT 55.0MM 2-1/4CR F22M	0	0	
130										
130							***** FITTINGS BELOW GROUND*****			
140										
140	U04		ELBOW	9002748CTD	14	14	BEND FORGED 22.5 DEG 5D WT 55.0 MM, ID 245.6 MM, 2-1/4CR F22M COATED	0	0	
150										
150							***** FLANGES ABOVE GROUND*****			
160										
160	U04	817	FLANGE	9005279	14	14	FLG COMPACT 10000# RJ BORE 245.6MM 2-1/4CR F22M	0	0	
170	U04	817	FLANGE	9005276	2	2	FLG COMPACT 10000# RJ BORE 35.3MM 2-1/4CR F22M LINE CLASS 10000X22	0	0	
180			FLANGE	9006192	14	14	FLG WN 10000 API 6A TYPE 6BX 11" (14" NB) NS RTJ BORE 249.0MM 2-1/4CR F22M	0	0	
190			BLIND	5407435	14	14	FLG BLIND 10000 API 6A TYPE 6BX 11" NS RTJ 2-1/4CR F22M	0	0	
200	U04	817	BLIND	9619757	14	14	FLG COMPACT BLIND 10000# RJ 2-1/4CR F22M LINE CLASS 10000X22	0	0	
210										
210		FA1					***** GASKETS *****			
220										
220			GASKET	5674483	14	14	GASKET 10000 API 6A BX 158 11" NS 316SS RING	0	0	
230	U04	817	GASKET	5673551	14	14	GASKET 10000# RJ INC 718 ENERGIZED SEALRING COMPACT FLANGE LINE CLASS 10000X22	0	0	
240										
240		B1					***** BOLTING *****			
250										
250	U04	BA5	BOLTING	5675778	14	14	STUD-BOLT C/W 2 COMPACT NUTS API-6A718	0	0	
260		BA3	BOLTING	5675770	14	14	STUD-BOLT A320 GR L7M/A194 GR 7M (S3) WITH 2 NUTS	0	0	
270										
270		SB6	BOLTING	5675675	14	14	JACK SCREW HEX HEAD A320 GR L7M	0	0	
280										
280		FA1					***** BLINDS & SPACERS *****			
290										
290			PADDLE	5407747	14	14	PADDLE BLANK 10000 API 6A 11" NS FOR 14" PIPE RTJ FEMALE 2-1/4CR F22M	0	0	
300			PADDLE	5407845	14	14	PADDLE SPACER 10000 API 6A 9" NS FOR 10" PIPE RTJ FEMALE 2-1/4CR F22M	0	0	
310										

	TENGIZCHEVROI TCO TENGIZ, KAZAKHSTAN	CONSTRUCTION	CORR.ALLOW.	SERVICE	MATERIAL	DATE	BY	REV	SHEET	PIPING LINE CLASS
		ALL SIZES - BUTT WELD PWHT - ALL SIZES.	CORR. ALLOW. 3 MM	SOUR SERVICE NACE STD. MR0175 / ISO 15156 DESIGN CODE ASME B31.8 / API 6A DESIGN PRESSURE - 600 BARG FLUID CODES - PIM-SU-5112-TCO	MATERIAL: 2-1/4CR F22 MODIFIED FLANGE RATING: 10000 RJ/CF TEMPERATURE RANGE: -40 / 110 °C	12/16/2024	BY OZAC	U04	Page 1 of 1	10000X22