

SEQ NO	REV	NOTE NO.	ITEM NAME	ITEM CODE	SIZE RANGE / SMALL END SIZES		DESCRIPTION	REFERENCE / LARGE END SIZES		NOTES	
10		VA5					***** MODULAR VALVES *****			810	NIPPLE TO BE CUT FROM SCH 160 PIPE.
20										820	ALLOY 825 INTERNAL CLADDING IS
20			MODULAR DBB	K01AM10	0.5	2	MODULAR VALVE DB&B BALL TYPE 150# RF INC 825 INC TRIM 625 METAL LO - FULL SIZE TYPE 2BV	0	0		ACCEPTABLE FOR PIPES MANUFACTURED
30	U04	VAV	MODULAR DBB	K03AM10	1.5	2	MODULAR VALVE DB&B BALL TYPE 300# RF INC 825 INC TRIM 625 METAL LO - FULL SIZE TYPE 2BV	0	0		FROM METALLURGICALLY ROLL-BONDED OR
40		VAV	MODULAR DBB	K03AM10	3	3	MODULAR VALVE DB&B BALL TYPE 300# RF INC 825 INC TRIM 625 METAL LO - FULL SIZE TYPE 2BV	0	0		EXPLOSION BONDED CLAD PLATES. ALLOY 625
50		FS1	MODULAR DBB	M01AM10	0.5	2	MODULAR VALVE DB&B BALL TYPE 150# RF INC 825 INC TRIM 625 METAL LO - CONTROLLED BORE TYPE 2BVR	0	0		MATERIAL TO BE USED FOR PIPES
											MANUFACTURED WITH INTERNAL WELD
60	U04	FS1	MODULAR DBB	M03AM10	0.75	3	MODULAR VALVE DB&B BALL TYPE 300# RF INC 825 INC TRIM 625 METAL LO - CONTROLLED BORE TYPE 2BVR	0	0		OVERLAY.
70		VAW	MODULAR DBB	M03EM10	0.75	1	MODULAR VALVE DB&B BALL TYPE 300# RF INC 825 INC TRIM 625 METAL LO REDUCING - CONTROLLED BORE TYPE 2BVR	2	2	B1	ALL BOLTS ARE METRIC DIA.
80		VAW	MODULAR DBB	M03EM10	1	1	MODULAR VALVE DB&B BALL TYPE 300# RF INC 825 INC TRIM 625 METAL LO REDUCING - CONTROLLED BORE TYPE 2BVR	3	3	B2	7/8" X 145MM BOLTS ONLY TO BE USED FOR 1 INCH 1500# PERAR BALL VALVES ITEM CODE B15AM10
90	U04	VAW	MODULAR DBB	M03EM10L	0.75	1	MODULAR VALVE DB&B BALL TYPE 300# RF INC 825 INC TRIM 625 METAL LO REDUCING - CONTROLLED BORE TYPE 2BVR	2	2	B6	7/8" X 145MM BOLTS ONLY TO BE USED FOR 1 INCH 1500# PERAR BALL VALVES ITEM CODE B15AS22
100	U04	VAW	MODULAR DBB	M03EM10L	1	1	MODULAR VALVE DB&B BALL TYPE 300# RF INC 825 INC TRIM 625 METAL LO REDUCING - CONTROLLED BORE TYPE 2BVR	3	3	DS5	USE THIS COMPONENT ONLY FOR RADAR TYPE LEVEL TRANSMITTERS LIT 1003-1,1003-2,1003-3 AND LT 1004
110		VB2					***** BALL VALVES *****			DS6	TO SHIFT COMPLETE SPOOL FABRICATION TO DSME
110											
120										FA8	USE THREADED FLANGES FOR INSTRUMENT CONNECTIONS ONLY.
120			BALL	A01AM09	3	3	BALL 150# RF INC 825 INC TRIM 625 FLOATING SOFT RB LO	0	0		
130			BALL	A01AR09	4	6	BALL 150# RF LTCS + CLAD INC 825 INC 625 TRIM FLOATING SOFT RB LO	0	0		
140	U04		BALL	A01AR10	4	4	BALL 150# RF LTCS + CLAD INC 825 INC TRIM 625 FLOATING METAL RB LO	0	0	FF5	FLAT BOTTOM NIPOF LANGES FOR USE ON WELD CAPS AND BLIND FLANGES
150	U04		BALL	A01AR16	6	8	BALL 150# RF LTCS + CLAD INC 825 INC TRIM 625 TRUNNION METAL RB GO	0	0		
160	U04		BALL	A01AR15	6	8	BALL 150# RF LTCS + CLAD INC 825 INC TRIM 625 TRUNNION SOFT RB GO	0	0	FS1	USE FLANGES, GASKETS & VALVES AS REQUIRED TO MATCH EQUIPMENT OR VESSEL NOZZLES.
170			BALL	B01AM09	0.75	2	BALL 150# RF INC 825 INC TRIM 625 FLOATING SOFT FB LO	0	0		
180		VA5	BALL	B01AM09	3	3	BALL 150# RF INC 825 INC TRIM 625 FLOATING SOFT FB LO	0	0		
190	U04		BALL	B01AM10	0.75	2	BALL 150# RF INC 825 INC TRIM 625 FLOATING METAL FB LO	0	0	GA6	SPECIAL GASKET ONLY FOR USE AS SPECIFIED IN ENG-200-117
200	U04		BALL	A01AM10	3	3	BALL 150# RF INC 825 INC TRIM 625 FLOATING METAL RB LO	0	0		
210	U04	VA5	BALL	B01AR11	4	4	BALL 150# RF LTCS + CLAD INC 825 INC TRIM 625 FLOATING SOFT FB GO	0	0	ND9	USE ONLY WITH CONSENT OF MATERIALS ENGINEER.
220	U04	VA5	BALL	B01AR15	6	20	BALL 150# RF LTCS + CLAD INC 825 INC TRIM 625 TRUNNION SOFT FB GO	0	0		
230		FS1	BALL	B03AM09	0.75	2	BALL 300# RF INC 825 INC 625 TRIM FLOATING SOFT FB LO	0	0	PS1	PIPE ONLY TO BE USED AS TRUNNION SUPPORTS
240	U04	FS1	BALL	B03AM10	0.75	2	BALL 300# RF INC 825 INC 625 TRIM FLOATING METAL FB LO	0	0		
250		FS1	BALL	A03AM09	3	3	BALL 300# RF INC 825 INC TRIM 625 FLOATING SOFT RB LO	0	0	SB6	USE JACKSCREWS FOR PADDLE BLANKS/SPACERS AND FLANGE SPREADERS FOR SPECTACLE BLINDS.
260											
260			BUTTERFLY	T01AR63	10	24	BUTTERFLY 150# RF LTCS + CLAD INC 825 INC TRIM 625 TOV METAL DBL FLG SHORT PAT GO	0	0	UJ2	USE 1 1/2IN WITH THERMOWELL CONNECTIONS ONLY & 3/4IN (IF SHOWN) FOR DBB PRESSURE CONNECTIONS WITH CHEMICAL SEALS.
270											
270		VQ2					***** GATE VALVES *****				
280											
280	U04		GATE	G01AM49	0.75	3	GATE 150# RF INC 825 INC TRIM 625 WEDGE HW	0	0		
290	U04	VA5	GATE	G01AR43	10	16	GATE 150# RF LTCS + CLAD INC 825 INC TRIM 625 WEDGE HW	0	0	VA5	USE THESE VALVES ONLY WHERE SPECIFIED ON PIPING AND INSTRUMENT DIAGRAMS
300			GATE	G01AR43	4	8	GATE 150# RF LTCS + CLAD INC 825 INC TRIM 625 WEDGE HW	0	0		
310		VA5	GATE	G01AR44	12	24	GATE 150# RF LTCS + CLAD INC 825 INC TRIM 625 WEDGE GO	0	0	VAV	USAGE IS LIMITED TO INSTRUMENT ISOLATION PURPOSE.
320	U04	VA5	GATE	G01AR44	18	24	GATE 150# RF LTCS + CLAD INC 825 INC TRIM 625 WEDGE GO	0	0		
330										VAW	VALVE ONLY TO BE USED IN ACCORDANCE WITH DOCUMENT L-ST-2055 - VENT DRAIN AND INSTRUMENT CONNECTION DETAILS.
330							***** GLOBE VALVES *****				
340											
340			GLOBE	L01AM49	0.75	3	GLOBE 150# RF INC 825 INC TRIM 625 OS&Y HW	0	0	VB2	SOFT SEATED BALL VALVES ARE LIMITED TO MAXIMUM TEMPERATURE OF 200°C.
350			GLOBE	L01AR49	4	6	GLOBE 150# RF LTCS + CLAD INC 825 INC TRIM 625 OS&Y HW	0	0		
360			GLOBE	L01AR44	8	10	GLOBE 150# RF LTCS + CLAD INC 825 INC TRIM 625 OS&Y GO	0	0	VC1	SPRING PISTON CHECK VALVES ARE PREFERRED IN THE HORIZONTAL POSITION, BUT MAY BE USED IN THE VERTICAL POSITION WITH ENGINEERING APPROVAL.
370											
370							***** CHECK VALVES *****				
380											
380		VC1	CHECK	C01AM51	0.75	1.5	CHECK PISTON 150# RF INC 825 INC TRIM 625	0	0	VQ2	QUARTER TURN VALVES ARE TO BE SELECTED FOR PROCESS APPLICATIONS.
390	U04		CHECK	C01AM46	2	3	CHECK DUAL WAFER LUG 150# RF INC 825 TRIM INC 625 THROU BOLTED	0	0		
400	U04		CHECK	C01AR46	4	6	CHECK DUAL WAFER LUG 150# RF LTCS + CLAD INC 825 TRIM INC 625 THROU BOLTED	0	0		
410	U04		CHECK	C01AR53	8	24	CHECK DUAL DBL FLG 150# RF LTCS + CLAD INC 825 INC TRIM 625	0	0		
420											
420							***** PIPES *****				
430											
430			PIPE	5732001	0.75	1	PIPE SCH 80S SMLS ALLOY 825 B423 UNS N08825 PE	0	0		
440			PIPE	5732002	1.5	1.5	PIPE SCH 40S SMLS ALLOY 825 B423 UNS N08825 PE	0	0		
450			PIPE	5361603	2	3	PIPE SCH 40S SMLS ALLOY 825 B423 UNS N08825 BE	0	0		
460	U04		PIPE	5358505_C60	10	16	PIPE SCH STD SMLS LTCS A333 GR.6 WITH 3MM INC 625 INTERNAL CLADDING	0	0		
470			PIPE	5358505_C80	4	6	PIPE SCH STD SMLS LTCS A333 GR.6 WITH 3MM INC 825 INTERNAL CLADDING	0	0		
480			PIPE	5358501_C80	8	16	PIPE SCH 20 SMLS LTCS A333 GR.6 WITH 3MM INC 825 INTERNAL CLADDING	0	0		
490			PIPE	5358597_C80	18	18	PIPE SCH 20 EFW LTCS A671 CC60 CL.22 WITH 3MM INC 825 INTERNAL CLADDING	0	0		
500	U04	820	PIPE	5358576_C60	18	24	PIPE SCH STD EFW LTCS A671 CC60 CL.22 WITH 3MM INC 825/625 INTERNAL CLADDING	0	0		
510		820	PIPE	5358577_C60	48	48	PIPE SCH XS EFW LTCS A671 CC60 CL.22 WITH 3 MM INC 825/625 INTERNAL CLADDING	0	0		
520	U04		PIPE	5358506_C60	8	8	PIPE SCH 60 SMLS LTCS A333 GR.6 BE WITH 3 MM INC 625 INTERNAL CLADDING	0	0		
530	U04		PIPE	5358510_C60	4	4	PIPE SCH 120 SMLS LTCS A333 GR.6 BE WITH 3MM INC 625 INTERNAL CLADDING	0	0		
540	U04		PIPE	5358514_C60	6	6	PIPE SCH XS SMLS LTCS A333 GR.6 WITH 3 MM INC 625 INTERNAL CLADDING	0	0		
550		810	PIPE	5732003	0.5	0.5	PIPE SCH 160 SMLS ALLOY 825 B423 UNS N08825 PE	0	0		

	TENGIZCHEVROI TCO TENGIZ, KAZAKHSTAN	CONSTRUCTION	CORR.ALLOW.	SERVICE	MATERIAL	DATE	BY	REV	SHEET	PIPING LINE CLASS
		ALL SIZES - BUTT WELD PWHT FOR SIZES 4" AND LARGER SEAL WELDING - FOR THREADED CONNECTIONS ONLY PIPE BENDS - NONE THREAD SEALANT - PTFE PASTE	CORR. ALLOW. 1 MM	DESIGN: ASME B16.5 MG 1.1 CODE: ASME B31.3 FLUID CODES - PIM-SU-5112-TCO	MATERIAL: LTCS + CRA FLANGE RATING: 150 RF TEMPERATURE RANGE: -40 / 200 °C	12/16/2024	BY OZAC	U04	Page 1 of 5	150C80

SEQ NO	REV	NOTE NO.	ITEM NAME	ITEM CODE	SIZE RANGE / SMALL END SIZES		DESCRIPTION	REFERENCE / LARGE END SIZES		NOTES
560							***** TRUNNION PIPE SUPPORTS *****			
570										
570	U04	PS1	PIPE	5358506	8	8	PIPE SCH 60 SMLS LTCS A333 GR.6 BE	0	0	
580	U04	PS1	PIPE	5358510	4	4	PIPE SCH 120 SMLS LTCS A333 GR.6 BE	0	0	
590	U04	PS1	PIPE	5358514	6	6	PIPE SCH XS SMLS LTCS A333 GR.6 BE	0	0	
600	U04	PS1	PIPE	5358576	20	24	PIPE SCH STD EFW LTCS A671 CC60 CL.22 BE	0	0	
610							***** FITTINGS *****			
610										
620										
620			ELBOW	5425111	0.75	1	ELL 90 DEG LR SCH 80S ALLOY 825 B366-WPS UNS N08825	0	0	
630			ELBOW	5424722	1.5	3	ELL 90 DEG LR SCH 40S ALLOY 825 B366-WPS UNS N08825	0	0	
640			ELBOW	5392438_C80	4	6	ELL BW 90 DEG LR SCH STD LTCS A420 WPL6 WITH 3MM INC 825 INTERNAL CLADDING	0	0	
650	U04		ELBOW	5392438_C60	10	16	ELL BW 90 DEG LR SCH STD LTCS A420 WPL6 WITH 3MM INC 625 INTERNAL CLADDING	0	0	
660			ELBOW	5392276_C80	8	16	ELL BW 90 DEG LR SCH 20 LTCS A420 WPL6 WITH 3 MM INC 825 INTERNAL CLADDING	0	0	
670			ELBOW	5392280_C80	18	18	ELL BW 90 DEG LR SCH 20 LTCS A420 WPL6-W WITH 3MM INC 825 INTERNAL CLADDING	0	0	
680	U04		ELBOW	5392496_C60	18	24	ELL 90 DEG LR SCH STD LTCS A420 WPL6-W WITH 3MM INC 625 INTERNAL CLADDING	0	0	
690	U04		ELBOW	5392700_C60	4	4	ELL BW 90 DEG LR SCH 120 LTCS A420 WPL6 WITH 3MM INC 625 INTERNAL CLADDING	0	0	
700	U04		ELBOW	5392492_C60	8	8	ELL BW 90 DEG LR SCH 60 LTCS A420 WPL6 WITH 3MM INC 625 INTERNAL CLADDING	0	0	
710	U04		ELBOW	5392600_C60	6	6	ELL BW 90 DEG LR SCH XS LTCS A420 WPL6 WITH 3 MM INC 625 INTERNAL CLADDING	0	0	
720	U04		ELBOW	5392497_C60	48	48	ELL BW 90 DEG LR SCH XS LTCS A420 WPL6-W WITH 3 MM INC 625 INTERNAL CLADDING	0	0	
730			ELBOW	5425113	0.75	1	ELL 45 DEG SCH 80S ALLOY 825 B366-WPS UNS N08825	0	0	
740			ELBOW	5424727	1.5	3	ELL 45 DEG SCH 40S ALLOY 825 B366-WPS UNS N08825	0	0	
750			ELBOW	5392444_C80	4	6	ELL BW 45 DEG LR SCH STD LTCS A420 WPL6 WITH 3MM INC 825 INTERNAL CLADDING	0	0	
760			ELBOW	5392282_C80	8	16	ELL BW 45 DEG LR SCH 20 LTCS A420 WPL6 WITH 3 MM INC 825 INTERNAL CLADDING	0	0	
770			ELBOW	5392281_C80	18	18	ELL BW 45 DEG LR SCH20 LTCS A420 WPL6-W WITH 3 MM INC 825 INTERNAL CLADDING	0	0	
780	U04		ELBOW	5392701_C60	4	4	ELL BW 45 DEG LR SCH 120 LTCS A420 WPL6 WITH 3MM INC 625 INTERNAL CLADDING	0	0	
790	U04		ELBOW	5392498_C60	8	8	ELL BW 45 DEG LR SCH 60 LTCS A420 WPL6 WITH 3MM INC 625 INTERNAL CLADDING	0	0	
800	U04		ELBOW	5392444_C60	10	16	ELL BW 45 DEG LR SCH STD LTCS A420 WPL6 WITH 3MM INC 625 INTERNAL CLADDING	0	0	
810	U04		ELBOW	5392607_C60	18	24	ELL BW 45 DEG LR SCH STD LTCS A420 WPL6-W WITH 3MM INC 625 INTERNAL CLADDING	0	0	
820	U04		ELBOW	5392606_C60	6	6	ELL BW 45 DEG LR SCH XS LTCS A420 WPL6 WITH 3 MM INC 625 INTERNAL CLADDING	0	0	
830										
830			TEE	5425119	0.75	1	TEE SCH 80S ALLOY 825 B366-WPS UNS N08825	0	0	
840			TEE	5424725	1.5	3	TEE SCH 40S ALLOY 825 B366-WPS UNS N08825	0	0	
850	U04		TEE	5392447_C60	10	16	TEE BW SCH STD LTCS A420 WPL6 WITH 3MM INC 625 INTERNAL CLADDING	0	0	
860			TEE	5392447_C80	4	6	TEE BW SCH STD LTCS A420 WPL6 WITH 3MM INC 825 INTERNAL CLADDING	0	0	
870			TEE	5392285_C80	8	16	TEE BW SCH 20 LTCS A420 WPL6 WITH 3 MM INC 825 INTERNAL CLADDING	0	0	
880			TEE	5392295_C80	18	18	TEE BW SCH 20 LTCS A420 WPL6-W WITH 3 MM INC 825 INTERNAL CLADDING	0	0	
890	U04		TEE	5392405_C60	18	24	TEE SCH STD LTCS A420 WPL6-W WITH 3MM INC 625 INTERNAL CLADDING	0	0	
900			TEE	5392405_C80	20	24	TEE SCH STD LTCS A420 WPL6-W WITH 3MM INC 825 INTERNAL CLADDING	0	0	
910	U04		TEE	5392501_C60	8	8	TEE BW SCH 60 LTCS A420 WPL6 WITH 3 MM INC 625 INTERNAL CLADDING	0	0	
920	U04		TEE	5392609_C60	6	6	TEE BW SCH XS LTCS A420 WPL6 WITH 3 MM INC 625 INTERNAL CLADDING	0	0	
930	U04		TEE	5392702_C60	4	4	TEE BW SCH 120 LTCS A420 WPL6 WITH 3MM INC 625 INTERNAL CLADDING	0	0	
940			FLANGE	5425126	0.75	0.75	TEE RED SCH 80S ALLOY 825 B366-WPS UNS N08825	1	1	
950			FLANGE	5425124	0.75	1	TEE RED SCH 40S/80S ALLOY 825 B366-WPS UNS N08825	1.5	2	
960			FLANGE	5424724	1.5	2	TEE RED SCH 40S ALLOY 825 B366-WPS UNS N08825	2	3	
970			FLANGE	5425128	1.5	3	TEE RED SCH STD/SCH 40S ALLOY 825 B366-WPS UNS N08825	4	6	
980	U04		TEE RED	5392445_C60	10	14	TEE RED BW SCH STD LTCS A420 WPL6 WITH 3 MM INC 625 INTERNAL CLADDING	12	16	
990			FLANGE	5392445_C80	4	4	TEE RED BW SCH STD LTCS A420 WPL6 WITH 3 MM INC 825 INTERNAL CLADDING	6	6	
1000			FLANGE	5392289_C80	4	6	TEE RED BW SCH 20/STD LTCS A420 WPL6 WITH 3 MM INC 825 INTERNAL CLADDING	8	16	
1010			FLANGE	5392209_C80	8	14	TEE RED BW SCH 20 LTCS A420 WPL6 WITH 3 MM INC 825 INTERNAL CLADDING	10	16	
1020			FLANGE	5392292_C80	8	16	TEE RED BW SCH 20 STD LTCS A420 WPL6-W WITH 3 MM INC 825 INTERNAL CLADDING	18	18	
1030			TEE RED	5556912_C80	8	18	TEE RED BW SCH STD/ SCH 20 LTCS A420 WPL6-W WITH 3 MM INC 825 INTERNAL INTERNAL CLADDING	20	24	
1040	U04		TEE RED	5392901_C60	8	8	TEE RED SCH STD/SCH 60 LTCS A420 WPL6-W WITH 3 MM INC 625 INTERNAL CLADDING	18	20	
1050	U04		TEE RED	5425179_C60	6	6	TEE RED BW SCH 60/SCH XS LTCS A420 WPL6 WITH 3 MM INC 625 INTERNAL CLADDING	8	8	
1060			FLANGE	5392428_C80	20	20	TEE RED BW SCH STD LTCS A420 WPL6 -W WITH 3 MM INC 825 INTERNAL CLADDING	24	24	
1070	U04		TEE RED	5392428_C60	10	18	TEE RED BW SCH STD LTCS A420 WPL6-W WITH 3MM INC 625 INTERNAL CLADDING	18	24	
1080	U04		TEE RED	5392428_C60	20	20	TEE RED BW SCH STD LTCS A420 WPL6 -W WITH 3MM INC 625 INTERNAL CLADDING	24	24	
1090	U04		TEE RED	5392348_C60	8	8	TEE RED BW SCH STD/SCH 60 LTCS A420 WPL6 WITH 3 MM INC 625 INTERNAL CLADDING	10	16	
1100	U04		TEE RED	5392427_C60	4	4	TEE RED BW SCH 60/SCH 120 LTCS A420 WPL6 WITH 3 MM INC 625 INTERNAL CLADDING	8	8	
1110	U04		TEE RED	5392442_C60	2	2	TEE RED SCH 120/XXS LTCS A420 WPL6 WITH 3MM INC 625 INTERNAL CLADDING	4	4	
1120	U04		TEE RED	5392451_C60	4	4	TEE RED BW SCH STD/SCH 120 LTCS A420 WPL6 WITH 3 MM INC 625 INTERNAL CLADDING	10	10	
1130	U04		TEE RED	5392454_C60	6	6	TEE RED BW SCH STD/XS LTCS A420 WPL6 WITH 3MM INC 625 INTERNAL CLADDING	10	16	
1140	U04		TEE RED	5392469_C60	3	3	TEE RED SCH XS/160 LTCS A420 WPL6 WITH 3MM INC 625 INTERNAL CLADDING	6	6	
1150	U04		TEE RED	5392471_C60	3	3	TEE RED SCH 120/160 LTCS A420 WPL6 WITH 3MM INC 625 INTERNAL CLADDING	4	4	
1160	U04		TEE RED	5392626_C60	4	4	TEE RED BW SCH XS/SCH 120 LTCS A420 WPL6 WITH 3 MM INC 625 INTERNAL CLADDING	6	6	
1170										
1170			CAP	5424270	0.75	1	CAP SCH 80S ALLOY 825 B366 UNS N08825	0	0	
1180			CAP	5424219	1.5	3	CAP SCH 40S ALLOY 825 B366 UNS N08825	0	0	
1190			CAP	5392448_C80	4	6	CAP BW SCH STD LTCS A420 WPL6 WITH 3 MM INC 825 INTERNAL CLADDING	0	0	
1200			CAP	5392448_C80	20	24	CAP BW SCH STD LTCS A420 WPL6 WITH 3 MM INC 825 INTERNAL CLADDING	0	0	
1210	U04		CAP	5392448_C60	4	24	CAP BW SCH STD LTCS A420 WPL6 WITH 3 MM INC 625 INTERNAL CLADDING	0	0	

	TENGIZCHEVROI TCO TENGIZ, KAZAKHSTAN	CONSTRUCTION	CORR.ALLOW.	SERVICE	MATERIAL	DATE	BY	REV	SHEET	PIPING LINE CLASS
		ALL SIZES - BUTT WELD PWHT FOR SIZES 4" AND LARGER SEAL WELDING - FOR THREADED CONNECTIONS ONLY PIPE BENDS - NONE THREAD SEALANT - PTFE PASTE	CORR. ALLOW. 1 MM	DESIGN: ASME B16.5 MG 1.1 CODE: ASME B31.3 FLUID CODES - PIM-SU-5112-TCO	MATERIAL: LTCS + CRA FLANGE RATING: 150 RF TEMPERATURE RANGE: -40 / 200 °C	12/16/2024	BY OZAC	U04	Page 2 of 5	150C80

SEQ NO	REV	NOTE NO.	ITEM NAME	ITEM CODE	SIZE RANGE / SMALL END SIZES		DESCRIPTION	REFERENCE / LARGE END SIZES		NOTES
1220			CAP	5392286_C80	8	18	CAP BW SCH 20 LTCS A420 WPL6 WITH 3 MM INC 825 INTERNAL CLADDING	0	0	
1230	U04		CAP	5392502_C60	8	8	CAP BW SCH 60 LTCS A420 WPL6 WITH 3 MM INC 625 INTERNAL CLADDING	0	0	
1240	U04		CAP	5392610_C60	6	6	CAP BW SCH XS LTCS A420 WPL6 WITH 3 MM INC 625 INTERNAL CLADDING	0	0	
1250	U04		CAP	5392703_C60	4	4	CAP SCH 120 LTCS A420 WPL6 WITH 3MM INC 625 INTERNAL CLADDING	0	0	
1260										
1260			RED CONC	5425122	0.75	0.75	REDUCER CONC SCH 80S ALLOY 825 B366-WPS N08825	1	1	
1270			RED CONC	5425143	0.75	1	REDUCER CONC SCH 40S/80S ALLOY 825 B366-WPS N08825	1.5	2	
1280			RED CONC	5424733	1.5	3	REDUCER CONC SCH 40S ALLOY 825 B366-WPS N08825	2	6	
1290			RED CONC	5425146	1.5	3	REDUCER CONC SCH STD/40S ALLOY 825 B366-WPS N08825	4	6	
1300	U04		RED CONC	5392741	1.5	3	REDUCER CONC SCH 160/40S ALLOY 825 B366-WPS N08825	4	4	
1310	U04		RED CONC	5392599_C80	4	4	REDUCER CONC SCH STD/120 LTCS A420 WPL6 WITH 3 MM INC 625 INTERNAL CLADDING	10	10	
1320	U04		RED CONC	5425161	3	3	REDUCER CONC SCH 120/40S ALLOY 825 B366-WPS N08825	6	6	
1330			RED CONC	5392449_C60	4	14	REDUCER CONC SCH STD LTCS A420 WPL6 WITH 3 MM INC 625 INTERNAL CLADDING	6	16	
1340			RED CONC	5392449_C80	4	4	REDUCER CONC SCH STD LTCS A420 WPL6 WITH 3 MM INC 825 INTERNAL CLADDING	6	6	
1350			RED CONC	5392290_C80	4	6	REDUCER CONC SCH 20/STD LTCS A420 WPL6 WITH 3 MM INC 825 INTERNAL CLADDING	8	14	
1360			RED CONC	5392211_C80	8	14	REDUCER CONC SCH 20 LTCS A420 WPL6 WITH 3 MM INC 825 INTERNAL CLADDING	10	16	
1370			RED CONC	5392287_C80	10	16	REDUCER CONC SCH 20 LTCS A420 WPL6-W WITH 3 MM INC 825 INTERNAL CLADDING	18	18	
1380			RED CONC	5392500_C80	12	18	REDUCER CONC SCH STD/20 LTCS A420 WPL6-W WITH 3 MM INC 825 INTERNAL CLADDING	20	24	
1390			RED CONC	5392505_C60	10	20	REDUCER CONC SCH STD LTCS A420 WPL6-W WITH 3 MM INC 625 INTERNAL CLADDING	18	24	
1400			RED CONC	5392505_C80	20	20	REDUCER CONC SCH STD LTCS A420 WPL6-W WITH 3 MM INC 825 INTERNAL CLADDING	24	24	
1410	U04		RED CONC	5392343_C80	4	4	REDUCER CONC SCH 60/SCH 120 LTCS A420 WPL6 WITH 3 MM INC 625 INTERNAL CLADDING	8	8	
1420	U04		RED CONC	5392344_C80	6	6	REDUCER CONC SCH 60/SCH XS LTCS A420 WPL6 WITH 3 MM INC 625 INTERNAL CLADDING	8	8	
1430	U04		RED CONC	5392452_C80	6	6	REDUCER CONC SCH STD/XS LTCS A420 WPL6 WITH 3 MM INC 625 INTERNAL CLADDING	10	16	
1440	U04		RED CONC	5392629_C80	8	8	REDUCER CONC SCH STD/SCH 60 LTCS A420 WPL6 WITH 3 MM INC 625 INTERNAL CLADDING	10	16	
1450	U04		RED CONC	5392740_C80	4	4	REDUCER CONC SCH XS/120 LTCS A420 WPL6 WITH 3 MM INC 625 INTERNAL CLADDING	6	6	
1460			RED ECC	5425123	0.75	0.75	REDUCER ECC SCH 80S ALLOY 825 B366-WPS N08825	1	1	
1470			RED ECC	5425145	0.75	1	REDUCER ECC SCH 40S/80S ALLOY 825 B366-WPS N08825	1.5	2	
1480			RED ECC	5424734	1.5	2	REDUCER ECC SCH 40S ALLOY 825 B366-WPS N08825	2	3	
1490			RED ECC	5425148	1.5	3	REDUCER ECC SCH STD/40S ALLOY 825 B366-WPS N08825	4	6	
1500	U04		RED ECC	5392450_C60	10	14	REDUCER ECC SCH STD LTCS A420 WPL6 WITH 3 MM INC 625 INTERNAL CLADDING	12	16	
1510	U04		RED ECC	5392450_C60	4	4	REDUCER ECC SCH STD LTCS A420 WPL6 WITH 3 MM INC 625 INTERNAL CLADDING	6	6	
1520			RED ECC	5392450_C80	4	4	REDUCER ECC SCH STD LTCS A420 WPL6 WITH 3 MM INC 825 INTERNAL CLADDING	6	6	
1530			RED ECC	5392291_C80	4	6	REDUCER ECC SCH 20/STD LTCS A420 WPL6 WITH 3 MM INC 825 INTERNAL CLADDING	8	16	
1540			RED ECC	5392212_C80	8	14	REDUCER ECC SCH 20 LTCS A420 WPL6-W WITH 3 MM INC 825 INTERNAL CLADDING	10	16	
1550			RED ECC	5392288_C80	10	16	REDUCER ECC SCH 20 LTCS A420 WPL6-W WITH 3 MM INC 825 INTERNAL CLADDING	18	18	
1560										
1560			RED ECC	5392508_C80	12	18	REDUCERECC SCH STD/20 LTCS A420 WPL6-W WITH 3 MM INC 825 INTERNAL CLADDING	20	24	
1570										
1570			RED ECC	5392509_C60	10	20	REDUCER ECC SCH STD LTCS A420 WPL6-W WITH 3 MM INC 625 INTERNAL CLADDING	18	24	
1580			RED ECC	5392509_C80	20	20	REDUCER ECC SCH STD LTCS A420 WPL6-W WITH 3 MM INC 825 INTERNAL CLADDING	24	24	
1590	U04		RED ECC	5392453_C80	6	6	REDUCER ECC SCH STD/XS LTCS A420 WPL6 WITH 3 MM INC 625 INTERNAL CLADDING	10	16	
1600	U04		RED ECC	5425159	1.5	3	REDUCER ECC SCH 160/40S ALLOY 825 B366-WPS N08825	4	4	
1610	U04		RED ECC	5425162	3	3	REDUCER ECC SCH 120/40S ALLOY 825 B366-WPS N08825	6	6	
1620	U04		RED ECC	5392643_C80	4	4	REDUCER ECC SCH 60/120 LTCS A420 WPL6 WITH 3 MM INC 625 INTERNAL CLADDING	8	8	
1630	U04		RED ECC	5392644_C80	4	4	REDUCER ECC SCH STD/120 LTCS A420 WPL6 WITH 3 MM INC 625 INTERNAL CLADDING	10	10	
1640	U04		RED ECC	5392645_C80	6	6	REDUCER ECC SCH 60/XS LTCS A420 WPL6 WITH 3 MM INC 625 INTERNAL CLADDING	8	8	
1650	U04		RED ECC	5392820_C80	4	4	REDUCER ECC SCH XS/SCH 120 LTCS A420 WPL6 WITH 3 MM INC 625 INTERNAL CLADDING	6	6	
1660	U04		RED ECC	5392839_C80	8	8	REDUCER ECC SCH STD/SCH 60 LTCS A420 WPL6 WITH 3 MM INC 625 INTERNAL CLADDING	10	16	
1670										
1670			OLETS	5504121	0.75	1	NIPOFLANGE 150# RF SCH 40S/80S ALLOY 825 B564 UNS N08825	2	3	
1680			OLETS	5504123	0.75	1	NIPOFLANGE 150# RF SCH STD/80S ALLOY 825 B564 UNS N08825	4	24	
1690			OLETS	5504150	0.75	1	NIPOFLANGE 150# RF SCH 20/80S ALLOY 825 B564 UNS N08825	8	18	
1700			OLETS	5504122	1.5	2	NIPOFLANGE 150# RF SCH 40S ALLOY 825 B564 UNS N08825	3	3	
1710			OLETS	5504124	1.5	2	NIPOFLANGE 150# RF SCH STD/40S ALLOY 825 B564 UNS N08825	4	24	
1720			OLETS	5504155	1.5	2	NIPOFLANGE 150# RF SCH 20/40S ALLOY 825 B564 UNS N08825	8	18	
1730	U04		OLETS	5513474	1.5	2	NIPOFLANGE 150# RF SCH 120/40S ALLOY 825 B564 UNS N08825	4	4	
1740	U04		OLETS	5513475	0.75	1	NIPOFLANGE 150# RF SCH 120/80S ALLOY 825 B564 UNS N08825	4	4	
1750	U04		OLETS	5513523	0.75	1	NIPOFLANGE 150# RF SCH XS/80S ALLOY 825 B564 UNS N08825	6	6	
1760	U04		OLETS	5513524	1.5	2	NIPOFLANGE 150# RF SCH XS/40S ALLOY 825 B564 UNS N08825	6	6	
1770	U04		OLETS	5513525	1.5	2	NIPOFLANGE 150# RF SCH 60/40S ALLOY 825 B564 UNS N08825	8	8	
1780	U04		OLETS	5514642	0.75	1	NIPOFLANGE 150# RF SCH 60/80S ALLOY 825 B564 UNS N08825	8	8	
1790	U04	FS1	OLETS	5513491	1	1	NIPOFLANGE 300# RF SCH 40S/80S ALLOY 825 B564 UNS N08825	1.5	3	
1800		FS1	OLETS	5513495	1.5	1.5	NIPOFLANGE 300# RF SCH 40S ALLOY 825 B564 UNS N08825	2	3	
1810		UJ2	OLETS	5513479	1.5	1.5	NIPOFLANGE 300# RF SCH STD/160 ALLOY 825 B564 UNS N08825	4	6	
1820		UJ2	OLETS	5513479	1.5	1.5	NIPOFLANGE 300# RF SCH STD/160 ALLOY 825 B564 UNS N08825	20	24	
1830	U04	UJ2	OLETS	5513479	1.5	1.5	NIPOFLANGE 300# RF SCH STD/160 ALLOY 825 B564 UNS N08825	10	24	
1840		UJ2	OLETS	5513420	1.5	1.5	NIPOFLANGE 300# RF SCH 20/160 ALLOY 825 B564 UNS N08825	8	18	
1850	U04	UJ2	OLETS	5513478	1.5	1.5	NIPOFLANGE 300# RF SCH XS/160 ALLOY 825 B564 UNS N08825	6	6	
1860	U04	FS1	OLETS	5513520	1.5	1.5	NIPOFLANGE 300# RF SCH 120/40S ALLOY 825 B564 UNS N08825	4	4	
1870	U04	UJ2	OLETS	5513522	1.5	1.5	NIPOFLANGE 300# RF SCH 60/160 ALLOY 825 B564 UNS N08825	8	8	
1880	U04	UJ2	OLETS	5513579	1.5	1.5	NIPOFLANGE 300# RF SCH 120/160 ALLOY 825 B564 UNS N08825	4	4	
1890		FF5	OLETS	5504198	0.75	1	NIPOFLANGE FLAT BOTTOM 150# RF SCH 80S ALLOY 825 B564 UNS N08825	0	0	
1900		FF5	OLETS	5504199	1.5	1.5	NIPOFLANGE FLAT BOTTOM 150# RF SCH 40S ALLOY 825 B564 UNS N08825	0	0	

	TENGIZCHEVROI TCO TENGIZ, KAZAKHSTAN	CONSTRUCTION	CORR.ALLOW.	SERVICE	MATERIAL	DATE	BY	REV	SHEET	PIPING LINE CLASS
		ALL SIZES - BUTT WELD PWHT FOR SIZES 4" AND LARGER SEAL WELDING - FOR THREADED CONNECTIONS ONLY PIPE BENDS - NONE THREAD SEALANT - PTFE PASTE	CORR. ALLOW. 1 MM	DESIGN: ASME B16.5 MG 1.1 CODE: ASME B31.3 FLUID CODES - PIM-SU-5112-TCO	MATERIAL: LTCS + CRA FLANGE RATING: 150 RF TEMPERATURE RANGE: -40 / 200 °C	12/16/2024	BY OZAC	U04	Page 3 of 5	150C80

SEQ NO	REV	NOTE NO.	ITEM NAME	ITEM CODE	SIZE RANGE / SMALL END SIZES		DESCRIPTION	REFERENCE / LARGE END SIZES		NOTES
1910		FF5	OLETS	5504518	0.75	1	NIPOFLANGE FLAT BOTTOM 300# RF SCH 80S ALLOY 825 B564 UNS N08825	0	0	
1920		FF5	OLETS	5504519	1.5	1.5	NIPOFLANGE FLAT BOTTOM 300# RF SCH 40S ALLOY 825 B564 UNS N08825	0	0	
1930										
1930			OLETS	5513437	0.75	1	WELDOLET SCH 40S/80S ALLOY 825 B564 UNS N08825	2	3	
1940			OLETS	5513417	0.75	1	WELDOLET SCH STD/80S ALLOY 825 B564 UNS N08825	4	24	
1950			OLETS	5513442	0.75	1	WELDOLET SCH 20/80S ALLOY 825 B564 UNS N08825	8	18	
1960			OLETS	5513418	1.5	3	WELDOLET SCH STD/ 40S ALLOY 825 B564 UNS N08825	4	24	
1970			OLETS	5513441	1.5	3	WELDOLET SCH 20/ 40S ALLOY 825 B564 UNS N08825	8	18	
1980			OLETS	5513440	4	6	WELDOLET SCH 20/ STD ALLOY 825 B564 UNS N08825	12	18	
1990			OLETS	5513439	4	6	WELDOLET SCH STD ALLOY 825 B564 UNS N08825	20	24	
2000			OLETS	5513444	8	8	WELDOLET SCH STD/ 20 ALLOY 825 B564 UNS N08825	24	24	
2010	U04		OLETS	5504381_C60	4	4	WELDOLET FLAT BOTTOM SCH 120 LTCS A350 LF2 CL.1 WITH 3MM INC 625 INTERNAL CLADDING	0	0	
2020	U04		OLETS	5509610	1.5	1.5	WELDOLET SCH 120 /40S ALLOY 825 B564 UNS N08825	4	4	
2030	U04		OLETS	5513406	0.75	0.75	WELDOLET FLAT BOTTOM SCH 80S ALLOY 825 B564 UNS N08825	0	0	
2040	U04		OLETS	5509620	0.75	1	WELDOLET SCH 120 /80S ALLOY 825 B564 UNS N08825	4	4	
2050	U04		OLETS	5513415	0.75	1	WELDOLET SCH XS/80S ALLOY 825 B564 UNS N08825	6	6	
2060	U04		OLETS	5513419	1.5	2	WELDOLET SCH XS/ 40S ALLOY 825 B564 UNS N08825	6	6	
2070	U04		OLETS	5513419	2	2	WELDOLET SCH XS/ 40S ALLOY 825 B564 UNS N08825	48	48	
2080	U04		OLETS	5513432	1.5	3	WELDOLET SCH 60/40S ALLOY 825 B564 UNS N08825	8	8	
2090	U04		OLETS	5513433	0.75	1	WELDOLET SCH 60/80S ALLOY 825 B564 UNS N08825	8	8	
2100	U04		OLETS	5505179_C60	6	6	WELDOLET SCH STD/ XS LTCS A350 LF2 CL.1 WITH 3MM INC 625 INTERNAL CLADDING	18	24	
2110	U04		OLETS	5513530_C60	4	4	WELDOLET SCH STD/120 LTCS A350 LF2 CL.1 WITH 3MM INC 625 INTERNAL CLADDING	12	24	
2120	U04		OLETS	5513535_C60	8	8	WELDOLET SCH STD/ 60 LTCS A350 LF2 CL.1 WITH 3MM INC 625 INTERNAL CLADDING	24	24	
2130										
2130		UJ2	ELBOFLG	5516626	1.5	1.5	ELBOFLANGE 300# RF SCH STD/160 ALLOY 825 B564 UNS N08825	4	6	
2140		UJ2	ELBOFLG	5516626	1.5	1.5	ELBOFLANGE 300# RF SCH STD/160 ALLOY 825 B564 UNS N08825	20	24	
2150	U04	UJ2	ELBOFLG	5516626	1.5	1.5	ELBOFLANGE 300# RF SCH STD/160 ALLOY 825 B564 UNS N08825	10	24	
2160		UJ2	ELBOFLG	5516629	1.5	1.5	ELBOFLANGE 300# RF SCH 20/160 ALLOY 825 B564 UNS N08825	8	18	
2170	U04		ELBOFLG	5516631	1.5	1.5	ELBOFLANGE 300# RF SCH 120/160 ALLOY 825 B564 UNS N08825	4	4	
2180	U04		ELBOFLG	5516632	1.5	1.5	ELBOFLANGE 300# RF SCH 60/160 ALLOY 825 B564 UNS N08825	8	8	
2190	U04		ELBOFLG	5516627	1.5	1.5	ELBOFLANGE 300# RF SCH XS/160 ALLOY 825 B564 UNS N08825	6	6	
2200										
2200		FS1					***** FLANGES *****			
2210										
2210		FA8	FLANGE	5614311	0.5	0.5	FLG SCRDR (FNPT) REDUCING 150# RF ALLOY 825 B564 UNS N08825	0.75	1.5	
2220		FA8	FLANGE	5614310	0.5	0.5	FLG SCRDR (FNPT) REDUCING 300# RF ALLOY 825 B564 UNS N08825	0.75	1.5	
2230										
2230			FLANGE	5851200	0.5	0.75	FLANGE ADAPTER 150# RF 316 SS X 12 MM TUBE	0	0	
2240			FLANGE	5851200	2	2	FLANGE ADAPTER 150# RF 316 SS X 12 MM TUBE	0	0	
2250			FLANGE	5851203	0.75	0.75	FLANGE ADAPTER 300# RF 316 SS X 12 MM TUBE	0	0	
2260			FLANGE	5851209	1	1	FLANGE ADAPTER 150# RF 316 SS X 25 MM TUBE	0	0	
2270	U04	ND9	FLG ADAPTER	5851223	0.5	1	FLANGE ADAPTER 150# RF ALLOY 825 B564 UNS N08825 X 12 MM TUBE	0	0	
2280	U04	ND9	FLG ADAPTER	5851223	1.5	2	FLANGE ADAPTER 150# RF ALLOY 825 B564 UNS N08825 X 12 MM TUBE	0	0	
2290	U04	ND9	FLG ADAPTER	5851222	0.75	0.75	FLANGE ADAPTER 300# RF ALLOY 825 B564 UNS N08825 X 12 MM TUBE	0	0	
2300										
2300			FLANGE	5569030	0.5	1	FLG WN 150# RF ALLOY 825 SCH 80S B564 UNS N08825	0	0	
2310			FLANGE	5569026	1.5	3	FLG WN 150# RF ALLOY 825 SCH 40S B564 UNS N08825	0	0	
2320	U04	DS6	FLANGE	5569026	6	6	FLG WN 150# RF ALLOY 825 SCH 40S B564 UNS N08825	0	0	
2330	U04		FLANGE	5556266_C80	48	48	FLG WN 150# RF LTCS A350 LF2 CL.1 SCH XS B16.47 SERIES A WITH 3MM INC 825 CLAD FACE & BORE	0	0	
2340	U04		FLANGE	5556251_C60	4	4	FLG WN 150# RF LTCS A350 LF2 CL.1 SCH 120 WITH 3MM INC 625 CLAD FACE & BORE	0	0	
2350	U04		FLANGE	5556252_C60	8	8	FLG WN 150# RF LTCS A350 LF2 CL.1 SCH 60 WITH 3MM INC 625 CLAD FACE & BORE	0	0	
2360	U04		FLANGE	5556261_C60	10	24	FLG WN 150# RF LTCS A350 LF2 CL.1 SCH STD WITH 3MM INC 625 CLAD FACE & BORE	0	0	
2370	U04		FLANGE	5556261_C80	4	6	FLG WN 150# RF LTCS A350 LF2 CL.1 SCH STD WITH 3MM INC 825 CLAD FACE & BORE	0	0	
2380	U04		FLANGE	5556261_C80	20	24	FLG WN 150# RF LTCS A350 LF2 CL.1 SCH STD WITH 3MM INC 825 CLAD FACE & BORE	0	0	
2390	U04		FLANGE	5556264_C60	6	6	FLG WN 150# RF LTCS A350 LF2 CL.1 SCH XS WITH 3MM INC 625 CLAD FACE & BORE	0	0	
2400	U04		FLANGE	5556265_C80	8	18	FLG WN 150# RF LTCS A350 LF2 CL.1 SCH 20 WITH 3MM INC 825 CLAD FACE & BORE	0	0	
2410	U04		FLANGE	5556266_C60	48	48	FLG WN 150# RF LTCS A350 LF2 CL.1 SCH XS B16.47 SERIES A WITH 3MM INC 625 CLAD FACE & BORE	0	0	
2420			FLANGE	5569290	0.5	1	FLG WN 300# RF ALLOY 825 SCH 80S B564 UNS N08825	0	0	
2430			FLANGE	5569276	1.5	3	FLG WN 300# RF ALLOY 825 SCH 40S B564 UNS N08825	0	0	
2440	U04	DS5	FLANGE	5569276	4	4	FLG WN 300# RF ALLOY 825 SCH 40S B564 UNS N08825	0	0	
2450	U04		FLANGE	5556473_C60	10	24	FLG WN 300# RF LTCS A350 LF2 CL.1 SCH STD WITH 3MM INC 625 CLAD FACE & BORE	0	0	
2460	U04		FLANGE	5556473_C80	4	6	FLG WN 300# RF LTCS A350 LF2 CL.1 SCH STD WITH 3MM INC 825 CLAD FACE & BORE	0	0	
2470	U04		FLANGE	5556473_C80	20	24	FLG WN 300# RF LTCS A350 LF2 CL.1 SCH STD WITH 3MM INC 825 CLAD FACE & BORE	0	0	
2480	U04		FLANGE	5556474_C80	8	18	FLG WN 300# RF LTCS A350 LF2 CL.1 SCH 20 WITH 3MM INC 825 CLAD FACE & BORE	0	0	
2490	U04		FLANGE	5556477_C60	48	48	FLG WN 300# RF LTCS A350 LF2 CL.1 SCH XS B16.47 SERIES A WITH 3MM INC 625 CLAD FACE & BORE	0	0	
2500	U04		FLANGE	5556477_C80	48	48	FLG WN 300# RF LTCS A350 LF2 CL.1 SCH XS B16.47 SERIES A WITH 3MM INC 825 CLAD FACE & BORE	0	0	
2510	U04		FLANGE	5556451_C60	4	4	FLG WN 300# RF LTCS A350 LF2 CL.1 SCH 120 WITH 3MM INC 625 CLAD FACE & BORE	0	0	
2520	U04		FLANGE	5556452_C60	8	8	FLG WN 300# RF LTCS A350 LF2 CL.1 SCH 60 WITH 3MM INC 625 CLAD FACE & BORE	0	0	
2530	U04		FLANGE	5556476_C60	6	6	FLG WN 300# RF LTCS A350 LF2 CL.1 SCH XS WITH 3MM INC 625 CLAD FACE & BORE	0	0	
2540			FLANGE	5570276	2	2	FLG WN 1500# RF ALLOY 825 SCH 40S B564 UNS N08825	0	0	
2550			FLANGE	5557400	3	3	FLG WN 900# RF ALLOY 825 SCH 40S B564 UNS N08825	0	0	
2560			BLIND	5617150	0.5	3	FLG BLIND 150# RF ALLOY 825 B564 UNS N08825	0	0	
2570	U04		BLIND	5615566_C80	4	24	FLG BLIND 150# RF LTCS A350 LF2 CL.1 WITH 3MM INC 825 CLAD FACE	0	0	

	TENGIZCHEVROI TCO TENGIZ, KAZAKHSTAN	CONSTRUCTION	CORR.ALLOW.	SERVICE	MATERIAL	DATE	BY	REV	SHEET	PIPING LINE CLASS
		ALL SIZES - BUTT WELD PWHT FOR SIZES 4" AND LARGER SEAL WELDING - FOR THREADED CONNECTIONS ONLY PIPE BENDS - NONE THREAD SEALANT - PTFE PASTE	CORR. ALLOW. 1 MM	DESIGN: ASME B16.5 MG 1.1 CODE: ASME B31.3 FLUID CODES - PIM-SU-5112-TCO	MATERIAL: LTCS + CRA FLANGE RATING: 150 RF TEMPERATURE RANGE: -40 / 200 °C	12/16/2024	BY OZAC	U04	Page 4 of 5	150C80

SEQ NO	REV	NOTE NO.	ITEM NAME	ITEM CODE	SIZE RANGE / SMALL END SIZES		DESCRIPTION	REFERENCE / LARGE END SIZES		NOTES
2580	U04		BLIND	5615566_C60	4	24	FLG BLIND 150# RF LTCS A350 LF2 CL.1 WITH 3MM INC 625 CLAD FACE	0	0	
2590			BLIND	5617159	0.5	3	FLG BLIND 300# RF ALLOY 825 B564 UNS N08825	0	0	
2600	U04		BLIND	5615576_C60	4	24	FLG BLIND 300# RF LTCS A350 LF2 CL.1 WITH 3 MM INC 625 CLAD FACE	0	0	
2610	U04		BLIND	5615576_C80	4	24	FLG BLIND 300# RF LTCS A350 LF2 CL.1 WITH 3 MM INC 825 CLAD FACE	0	0	
2620	U04		FLANGE	5557143_C60	4	4	FLG WN 900# RF LTCS A350 LF2 CL.1 SCH 120 WITH 3MM INC 625 CLAD FACE & BORE	0	0	
2630										
2630							*****ORIFICE FLANGES*****			
2640										
2640			ORIFICE FLG	5650830	2	3	WN ORIF SET 300# RF ALLOY 825 B564 UNS N08825 SCH 40S	0	0	
2650	U04		ORIFICE FLG	5623944_C60	4	24	WN ORIF SET 300# RF LTCS A350 LF2 CL.1 SCH STD WITH 3MM INC 625 CLAD FACE & BORE	0	0	
2660	U04		ORIFICE FLG	5623944_C80	4	6	WN ORIF SET 300# RF LTCS A350 LF2 CL.1 SCH STD WITH 3MM INC 825 CLAD FACE & BORE	0	0	
2670	U04		ORIFICE FLG	5623944_C80	20	24	WN ORIF SET 300# RF LTCS A350 LF2 CL.1 SCH STD WITH 3MM INC 825 CLAD FACE & BORE	0	0	
2680	U04		ORIFICE FLG	5623941_C80	8	18	WN ORIF SET 300# RF LTCS A350 LF2 CL.1 SCH 20 WITH 3MM INC 825 CLAD FACE & BORE	0	0	
2690	U04		ORIFICE FLG	5623930_C60	4	4	WN ORIF SET 300# RF LTCS A350 LF2 CL.1 SCH 120 WITH 3MM INC 625 CLAD FACE & BORE	0	0	
2700	U04		ORIFICE FLG	5623931_C60	8	8	WN ORIF SET 300# RF LTCS A350 LF2 CL.1 SCH 60 WITH 3MM INC 625 CLAD FACE & BORE	0	0	
2710	U04		ORIFICE FLG	5623947_C60	6	6	WN ORIF SET 300# RF LTCS A350 LF2 CL.1 SCH XS WITH 3MM INC 625 CLAD FACE & BORE	0	0	
2720										
2720							***** PIPE NIPPLES *****			
2730										
2730	U04	810					NIPPLE PBE CUT FROM PIPE			
2740										
2740		FS1					***** GASKETS *****			
2750										
2750			GASKET	5673653	0.5	24	GASKET 150# ALLOY 825 SPIRAL WOUND GRAPHITE IR	0	0	
2760			GASKET	5674016	48	48	GASKET 150# ALLOY 825 KAMMPROFILE GRAPHITE ASME B16.47 SERIES A	0	0	
2770			GASKET	5673657	0.5	24	GASKET 300# ALLOY 825 SPIRAL WOUND GRAPHITE IR	0	0	
2780	U04	GA6	GASKET	5673019	2	3	GASKET 300# ALLOY 825 KAMMPROFILE GRAPHITE ASME B16.5	0	0	
2790			GASKET	5674034	48	48	GASKET 300# ALLOY 825 KAMMPROFILE GRAPHITE ASME B16.47 SERIES A	0	0	
2800			GASKET	5673800	2	2	GASKET 1500# ALLOY 825 SPIRAL WOUND GRAPHITE IR	0	0	
2810	U04		GASKET	5673700	3	4	GASKET 900# ALLOY 825 SPIRAL WOUND GRAPHITE IR	0	0	
2820										
2820		B1					***** BOLTING *****			
2830										
2830	U04		BOLTING	5675770	0.5	99	STUD-BOLT A320 GR L7M/A194 GR 7M (S3) WITH 2 NUTS	0	0	
2840										
2840		SB6	BOLTING	5675675	12	48	JACK SCREW HEX HEAD A320 GR L7M	0	0	
2850										
2850		FS1					**** BLINDS & SPACERS ****			
2860										
2860			SPEC BLIND	5749681	0.75	3	SPECTACLE BLIND 150# RF ALLOY 825 B424 UNS N08825	0	0	
2870	U04		SPEC BLIND	5749580_C60	4	14	SPECTACLE BLIND 150# RF LTCS A 516 GR.70 WITH 3MM INC 625 CLAD FACE & BORE	0	0	
2880			SPEC BLIND	5749580_C80	4	14	SPECTACLE BLIND 150# RF LTCS A 516 GR.70 WITH 3MM INC 825 CLAD FACE & BORE	0	0	
2890			SPEC BLIND	5749683	0.75	3	SPECTACLE BLIND 300# RF ALLOY 825 B424 UNS N08825	0	0	
2900	U04		SPEC BLIND	5749581_C60	4	10	SPECTACLE BLIND 300# RF LTCS A516 GR.70 WITH 3MM INC 625 CLAD FACE & BORE	0	0	
2910			SPEC BLIND	5749581_C80	4	10	SPECTACLE BLIND 300# RF LTCS A516 GR.70 WITH 3MM INC 825 CLAD FACE & BORE	0	0	
2920										
2920	U04		PADDLE	5750023_C60	16	24	PADDLE BLANK 150# RF LTCS A516 GR.70 WITH 3MM INC 625 CLAD FACE	0	0	
2930			PADDLE	5750023_C80	16	24	PADDLE BLANK 150# RF LTCS A516 GR.70 WITH 3MM INC 825 CLAD FACE & BORE	0	0	
2940	U04		PADDLE	5750100_C60	12	24	PADDLE BLANK 300# RF LTCS A516 GR.70 WITH 3MM INC 625 CLAD FACE	0	0	
2950			PADDLE	5750100_C80	12	24	PADDLE BLANK 300# RF LTCS A516 GR.70 WITH 3MM INC 825 CLAD FACE & BORE	0	0	
2960	U04		PADDLE	5750028_C60	48	48	PADDLE BLANK 300# RF LTCS A516 GR70 B16.47 SERIES A WITH 3MM INC 625 CLAD FACE	0	0	
2970			PADDLE	5750028_C80	48	48	PADDLE BLANK 300# RF LTCS A516 GR70 B16.47 SERIES A WITH 3MM INC 825 CLAD FACE	0	0	
2980	U04		PADDLE	5750240_C80	16	24	PADDLE SPACER 150# RF LTCS A516 GR.70 WITH 3MM INC 625 CLAD FACE & BORE	0	0	
2990			PADDLE	5750240_C80	16	24	PADDLE SPACER 150# RF LTCS A516 GR.70 WITH 3MM INC 825 CLAD FACE & BORE	0	0	
3000	U04		PADDLE	5750200_C80	12	24	PADDLE SPACER 300# RF LTCS A516 GR.70 WITH 3MM INC 625 CLAD FACE & BORE	0	0	
3010			PADDLE	5750200_C80	12	24	PADDLE SPACER 300# RF LTCS A516 GR.70 WITH 3MM INC 825 CLAD FACE & BORE	0	0	
3020	U04		PADDLE	5750198_C80	48	48	PADDLE SPACER 300# RF LTCS A516 GR70 B16.47 SERIES A WITH 3MM INC 625 CLAD FACE & BORE	0	0	
3030			PADDLE	5750198_C80	48	48	PADDLE SPACER 300# RF LTCS A516 GR70 B16.47 SERIES A WITH 3MM INC 825 CLAD FACE & BORE	0	0	

	TENGIZCHEVROI TCO TENGIZ, KAZAKHSTAN	CONSTRUCTION	CORR.ALLOW.	SERVICE	MATERIAL	DATE	BY	REV	SHEET	PIPING LINE CLASS
		ALL SIZES - BUTT WELD PWHT FOR SIZES 4" AND LARGER SEAL WELDING - FOR THREADED CONNECTIONS ONLY PIPE BENDS - NONE THREAD SEALANT - PTFE PASTE	CORR. ALLOW. 1 MM	DESIGN: ASME B16.5 MG 1.1 CODE: ASME B31.3 FLUID CODES - PIM-SU-5112-TCO	MATERIAL: LTCS + CRA FLANGE RATING: 150 RF TEMPERATURE RANGE: -40 / 200 °C	12/16/2024	BY OZAC	U04	Page 5 of 5	150C80