

SEQ NO	REV	NOTE NO.	ITEM NAME	ITEM CODE	SIZE RANGE / SMALL END SIZES		DESCRIPTION	REFERENCE / LARGE END SIZES		NOTES	
10	U04						***** PIPE *****			B1	ALL BOLTS ARE METRIC DIA.
20											
20	U04		PIPE	5722001	0.75	2	PIPE STD WT SMLS MONEL 400 B165 UNS N04400 BE	0	0		
30											
30	U04						***** FITTINGS *****				
40											
40	U04		ELBOW	5722002	0.75	0.75	ELL BW 90 DEG LR STD WT MONEL 400 B366 UNS N04400	0	0		
50											
50	U04		RED CONC	5722004	0.75	1.5	REDUCER CONC STD WT MONEL 400 B366 UNS N04400	2	2		
60											
60	U04						***** FLANGES *****				
70											
70	U04		FLANGE	5722003	0.75	2	FLG WN 150# RF MONEL 400 B564 UNS N04400 STD WT	0	0		
80											
80	U04						***** GASKETS *****				
90											
90	U04		GASKET	5673060	0.75	2	GASKET 150# MONEL 400 SPIRAL WOUND GRAPHITE FILLED	0	0		
100											
100	U04						***** BOLTING *****				
110											
110	U04	B1	BOLTING	5675770	0.5	99	STUD-BOLT A320 GR L7M/A194 GR 7M (S3) WITH 2 NUTS	0	0		

	TENGIZCHEVROI TCO TENGIZ, KAZAKHSTAN	CONSTRUCTION	CORR.ALLOW.	SERVICE	MATERIAL	DATE	BY	REV	SHEET	PIPING LINE CLASS
		ALL SIZES - BUTT WELD SEAL WELDING - NONE PIPE BENDS - NONE THREAD SEALANT - NONE	CORR. ALLOW. 0 MM	SOUR SERVICE - NACE MR0175 / ISO 15156 DESIGN: ASME B16.5 MG 3.4 CODE: ASME B31.3 FLUID CODES - PIM-SU-5112-TCO	MATERIAL: MONEL 400 FLANGE RATING: 150 RF TEMPERATURE RANGE: -40 / 215 °C	12/16/2024	BY OZAC	U04	Page 1 of 1	150M40