

SEQ NO	REV	NOTE NO.	ITEM NAME	ITEM CODE	SIZE RANGE / SMALL END SIZES		DESCRIPTION	REFERENCE / LARGE END SIZES		NOTES	
10							*****VALVES*****			810	NIPPLE TO BE CUT FROM SCH 160 PIPE.
20										817	USE ONLY FOR TIE IN
20							***** MODULAR VALVES *****			821	TO BE USED FOR LINES SUBJECT TO AIV OR WHERE REQUIRED BY STRESS.
30										824	FOR FLARE & BLOWDOWN SERVICES (BD, BF, BFH & BHL) OR WHERE STRESS REQUIRE LINES SUBJECT TO AIV
30			MODULAR DBB	K01AS22	0.5	2	MODULAR VALVE DB&B BALL TYPE 150# RF SS A182 F316 316 SS TRIM METAL LO 718 BOLT - FULL SIZE TYPE 2BV	0	0		
40		VAV	MODULAR DBB	K03AS22	3	3	MODULAR VALVE DB&B BALL TYPE 300# RF SS A182 F316 316 SS TRIM METAL LO 718 BOLT - FULL SIZE TYPE 2BV	0	0	B1	ALL BOLTS ARE METRIC DIA.
50			MODULAR DBB	M01AS22	0.5	2	MODULAR VALVE DB&B BALL TYPE 150# RF SS A182 F316 316 SS TRIM METAL LO 718 BOLT - CONTROLLED BORE TYPE 2BVR	0	0	B2	7/8" X 145MM BOLTS ONLY TO BE USED FOR 1 INCH 1500# PERAR BALL VALVES ITEM CODE B15AM10
60		FS1	MODULAR DBB	M03AS22	0.75	3	MODULAR VALVE DB&B BALL TYPE 300# RF SS A182 F316 316 SS TRIM METAL LO 718 BOLT - CONTROLLED BORE TYPE 2BVR	0	0	B6	7/8" X 145MM BOLTS ONLY TO BE USED FOR 1 INCH 1500# PERAR BALL VALVES ITEM CODE B15AS22
70		VAW	MODULAR DBB	M03ES22	0.75	1	MODULAR VALVE DB&B BALL TYPE 300# RF SS A182 F316SS TRIM METAL LO 718 BOLT REDUCING - CONTROLLED BORE TYPE 2BVR	1.5	3	FA3	FLAT FACE FLANGES & FULL FACE GASKETS SHALL ONLY BE USED WHEN MATING WITH FLAT FACE EQUIPMENT.
80							***** BALL VALVES *****			FA8	USE THREADED FLANGES FOR INSTRUMENT CONNECTIONS ONLY.
80		VB2								FF5	FLAT BOTTOM NIPPOFLANGES FOR USE ON WELD CAPS AND BLIND FLANGES
90										FS1	USE FLANGES, GASKETS & VALVES AS REQUIRED TO MATCH EQUIPMENT OR VESSEL NOZZLES.
90			BALL	A01AS21	3	4	BALL 150# RF SS A182 F316 316SS TRIM FLOATING SOFT RB LO 718 BOLT	0	0	GA6	SPECIAL GASKET ONLY FOR USE AS SPECIFIED IN ENG-200-117
100			BALL	A01AS22	3	4	BALL 150# RF SS A182 F316 316SS TRIM FLOATING METAL RB LO 718 BOLT	0	0	ND9	USE ONLY WITH CONSENT OF MATERIALS ENGINEER.
110	U04		BALL	A01AS23	6	6	BALL 150# RF SS A182 F316 316SS TRIM FLOATING SOFT RB GO 718 BOLT	0	0	PE1	SCHEDULE 10 PIPING SHALL NOT BE USED IN FLARE & BLOWDOWN (BD, BF, BFH & BFL) SERVICES.
120	U04		BALL	A01AS24	6	6	BALL 150# RF SS A182 F316 316SS TRIM FLOATING METAL RB GO 718 BOLT	0	0	PS1	PIPE ONLY TO BE USED AS TRUNNION SUPPORTS
130			BALL	A01AS27	8	8	BALL 150# RF SS A182 F316 316SS TRIM TRUNNION SOFT RB GO 718 BOLT	0	0	SB6	USE JACKSCREWS FOR PADDLE BLANKS/SPACERS AND FLANGE SPREADERS FOR SPECTACLE BLINDS.
140			BALL	A01AS28	8	8	BALL 150# RF SS A182 F316 316SS TRIM TRUNNION METAL RB GO 718 BOLT	0	0	UD7	USE THREDOLET AND SCREWED PLUG FOR HYDROSTATIC TEST VENTS AND DRAINS. SEAL WELD AFTER HYDROSTATIC TEST
150			BALL	B01AS21	0.5	2	BALL 150# RF SS A182 F316 316SS TRIM FLOATING SOFT FB LO 718 BOLT	0	0	UDC	FOR USE WITH PRESSURE CONNECTIONS ONLY
160		VA5	BALL	B01AS21	3	3	BALL 150# RF SS A182 F316 316SS TRIM FLOATING SOFT FB LO 718 BOLT	0	0	UJ2	USE 1 1/2IN WITH THERMOWELL CONNECTIONS ONLY & 3/4IN (IF SHOWN) FOR DBB PRESSURE CONNECTIONS WITH CHEMICAL SEALS.
170			BALL	B01AS22	0.5	2	BALL 150# RF SS A182 F316 316SS TRIM FLOATING METAL FB LO 718 BOLT	0	0	UK9	DO NOT USE FOR ORIFICE FLANGE TAP ASSEMBLIES.
180		VA5	BALL	B01AS22	3	3	BALL 150# RF SS A182 F316 316SS TRIM FLOATING METAL FB LO 718 BOLT	0	0	VA5	USE THESE VALVES ONLY WHERE SPECIFIED ON PIPING AND INSTRUMENT DIAGRAMS
190	U04	VA5	BALL	B01AS23	4	4	BALL 150# RF SS A182 F316 316SS TRIM FLOATING SOFT FB GO 718 BOLT	0	0	VAV	USAGE IS LIMITED TO INSTRUMENT ISOLATION PURPOSE.
200	U04	VA5	BALL	B01AS24	4	4	BALL 150# RF SS A182 F316 316SS TRIM FLOATING METAL FB GO 718 BOLT	0	0	VAW	VALVE ONLY TO BE USED IN ACCORDANCE WITH DOCUMENT L-ST-2055 - VENT DRAIN AND INSTRUMENT CONNECTION DETAILS.
210		VA5	BALL	B01AS27	6	24	BALL 150# RF SS A182 F316 316SS TRIM TRUNNION SOFT FB GO 718 BOLT	0	0	VB2	SOFT SEATED BALL VALVES ARE LIMITED TO MAXIMUM TEMPERATURE OF 200°C.
220	U04	VA5	BALL	B01AS28	6	24	BALL 150# RF SS A182 F316 316SS TRIM TRUNNION METAL FB GO 718 BOLT	0	0	VC1	SPRING PISTON CHECK VALVES ARE PREFERED IN THE HORIZONTAL POSITION, BUT MAY BE USED IN THE VERTICAL POSITION WITH ENGINEERING APPROVAL.
230		VA5	BALL	B01JS28	26	42	BALL 150# RF SS A182 F316 316SS TRIM TRUNNION METAL FB GO B16.47 SERIES A 718 BOLT	0	0		
240		FS1	BALL	B03AS21	0.5	2	BALL 300# RF SS A182 F316 316SS TRIM FLOATING SOFT FB LO 718 BOLT	0	0		
250		FS1	BALL	B03AS22	0.5	2	BALL 300# RF SS A182 F316 316SS TRIM FLOATING METAL FB LO 718 BOLT	0	0		
260	U04	FS1	BALL	A03AS21	3	4	BALL 300# RF SS A182 F316 316SS TRIM FLOATING SOFT RB LO 718 BOLT	0	0		
270		FS1	BALL	A03AS22	3	3	BALL 300# RF SS A182 F316 316SS TRIM FLOATING METAL RB LO 718 BOLT	0	0		
280							***** BUTTERFLY VALVES *****				
280											
290			BUTTERFLY	T01AS65	10	24	BUTTERFLY 150# RF SS A351 CF8M 316SS TRIM TOV METAL DBL FLG SHORT PAT GO 718 BOLT	0	0		
300			BUTTERFLY	T01JS65	26	42	BUTTERFLY 150# RF SS A351 CF8M 316SS TRIM TOV METAL DBL FLG SHORT PAT GO ASME B16.47 SERIES A 718 BOLT	0	0		
310							***** GLOBE VALVES *****				
310											
320											
320	U04		GLOBE	L01AS55	0.5	1.5	GLOBE 150# RF SS A182 F316 TRIM 16 OS&Y HW 718 BOLT	0	0		
330	U04		GLOBE	L06AS55	0.75	1.5	GLOBE 600# RF SS A182 F316 TRIM 16 OS&Y HW 718 BOLT	0	0		
340			GLOBE	L01AS56	2	6	GLOBE 150# RF SS A351 CF8M TRIM 16 OS&Y HW 718 BOLT	0	0		
350	U04		GLOBE	L06AS57	6	10	GLOBE 600# RF SS A351 CF8M TRIM 16 OS&Y GO 718 BOLT	0	0		
360	U04		GLOBE	L06AS56	2	4	GLOBE 600# RF SS A351 CF8M TRIM 16 OS&Y HW 718 BOLT	0	0		
370			GLOBE	L01AS57	8	10	GLOBE 150# RF SS A351 CF8M TRIM 16 OS&Y GO 718 BOLT	0	0		
380							***** CHECK VALVES *****				
380											
390											
390		VC1	CHECK	C01AS54	0.75	1.5	CHECK PISTON 150# RF SS A182 F316 TRIM 16 718 BOLT	0	0		
400	U04		CHECK	C01AS45	2	6	CHECK DUAL WAFER LUG 150# RF SS A351 CF8M TRIM 16 THROU BOLTED	0	0		
410	U04		CHECK	C01AS52	8	24	CHECK DUAL DBL FLG 150# RF SS A351 CF8M TRIM 16	0	0		
420	U04		CHECK	C01JS52	26	42	CHECK DUAL DBL FLG 150# RF SS A351 CF8M TRIM 16 B16.47 SERIES A	0	0		
430							***** PIPE *****				
430											
440											
440			PIPE	5365140	0.75	1.5	PIPE SCH 80S SMLS SS A312 TP316/316L PE	0	0		
450			PIPE	5365136	2	6	PIPE SCH 40S SMLS SS A312 TP316/316L BE	0	0		
460	U04	824	PIPE	5365136	8	18	PIPE SCH 40S SMLS SS A312 TP316/316L BE	0	0		
470			PIPE	5365119	8	12	PIPE SCH 30 SMLS SS A312 TP316/316L BE	0	0		
480	U04	PE1	PIPE	5365117	14	18	PIPE SCH 10 SMLS SS A312 TP316/316L BE	0	0		
490			PIPE	5365118	20	24	PIPE SCH 20 SMLS SS A312 TP316/316L BE	0	0		
500			PIPE	5365193	26	36	PIPE SCH STD EFW SS A358 316/316L BE	0	0		
510			PIPE	5365193	42	42	PIPE SCH STD EFW SS A358 316/316L BE	0	0		
520		810	PIPE	5365207	0.5	0.5	PIPE SCH 160 SMLS SS A312 TP316/316L PE	0	0		
530	U04	824	PIPE	5365137	14	24	PIPE SCH 40 SMLS SS A312 TP316/316L BE	0	0		
540	U04	824	PIPE	5365144	16	24	PIPE SCH 60 SMLS SS A312 TP316/316L BE	0	0		
550	U04	ND9	PIPE	5365139	10	10	PIPE SCH 80 SMLS SS A312 TP316/316L BE	0	0		

	TENGIZCHEVROIL TCO TENGIZ, KAZAKHSTAN	CONSTRUCTION	CORR.ALLOW.	SERVICE	MATERIAL	DATE	BY	REV	SHEET	PIPING LINE CLASS
		ALL SIZES - BUTT WELD SEAL WELDING - FOR THREADED CONNECTIONS ONLY PIPE BENDS - NONE THREAD SEALANT - PTFE PASTE	CORR. ALLOW. 1 MM	SOUR SERVICE - NACE MR0175/ ISO 15156 DESIGN: ASME B16.5 MG 2.2 CODE - ASME B31.3 FLUID CODES - PIM-SU-5112-TCO	MATERIAL: 316/316L SS DUAL GRADE FLANGE RATING: 150 RF TEMPERATURE RANGE: -120 / 180 °C COMMENT: LOW TEMP BLOW DOWN	12/16/2024	BY OZAC	U04	Page 1 of 6	150P21

SEQ NO	REV	NOTE NO.	ITEM NAME	ITEM CODE	SIZE RANGE / SMALL END SIZES		DESCRIPTION	REFERENCE / LARGE END SIZES		NOTES
560	U04	PS1	PIPE	5365138	6	6	PIPE SCH 80S SMLS SS A312 TP316/316L-S BE	0	0	
570	U04	821		5365138	10	10	PIPE SCH 80S SMLS SS A312 TP316/316L-S BE	0	0	
580	U04	824	PIPE	5365138	18	24	PIPE SCH 80S SMLS SS A312 TP316/316L-S BE	0	0	
590	U04	UK9	PIPE	5365202	0.5	0.75	PIPE SCH XXS SMLS SS A312 316/316L SS PE	0	0	
600										
600							***** FITTINGS *****			
610										
610	U04		ELBOW	5449033	0.5	1.5	ELL 90 DEG LR SCH 80S SS A403 WP316/316L-S	0	0	
620	U04	824	ELBOW	5449033	18	20	ELL 90 DEG LR SCH 80S SS A403 WP316/316L-S	0	0	
630	U04	821		5449033	10	10	ELL 90 DEG LR SCH 80S SS A403 WP316/316L-S	0	0	
640	U04	824	ELBOW	5449138	10	10	ELL 90 DEG LR SCH 40S SS A403 WP316/316L-S	0	0	
650	U04	824	ELBOW	5449138	18	18	ELL 90 DEG LR SCH 40S SS A403 WP316/316L-S	0	0	
660			ELBOW	5449138	2	6	ELL 90 DEG LR SCH 40S SS A403 WP316/316L-S	0	0	
670			ELBOW	5449031	8	12	ELL 90 DEG LR SCH 30 SS A403 WP316/316L-S	0	0	
680			ELBOW	5448890	14	18	ELL 90 DEG LR SCH 10 SS A403 WP316/316L-S	0	0	
690			ELBOW	5449030	20	24	ELL 90 DEG LR SCH 20 SS A403 WP316/316L-S	0	0	
700			ELBOW	5451100	26	36	ELL 90 DEG LR SCH STD 316/316L SS A403 WP316/316L-W	0	0	
710			ELBOW	5451100	42	42	ELL 90 DEG LR SCH STD 316/316L SS A403 WP316/316L-W	0	0	
720	U04	824	ELBOW	5449032	14	24	ELL 90 DEG LR SCH 40 SS A403 WP316/316L-S	0	0	
730	U04	824	ELBOW	5449573	18	24	ELL 90 DEG LR SCH 60 SS A403 WP316/316L-S	0	0	
740	U04	ND9		5449034	10	10	ELL 90 DEG LR SCH 80 SS A403 WP316/316L-S	0	0	
750	U04	UK9	ELBOW	5449572	0.5	0.75	ELL 90 DEG LR SCH XXS SS A403 WP316/316L-S	0	0	
760	U04	821		5449146	10	10	ELL 45 DEG LR SCH 80S SS A403 WP316/316L-S	0	0	
770			ELBOW	5449146	0.75	1.5	ELL 45 DEG LR SCH 80S SS A403 WP316/316L-S	0	0	
780	U04	824	ELBOW	5449144	10	10	ELL 45 SCH 40S SS A403 WP316/316L-S	0	0	
790			ELBOW	5449144	2	6	ELL 45 SCH 40S SS A403 WP316/316L-S	0	0	
800			ELBOW	5449037	8	12	ELL 45 SCH 30 SS A403 WP316/316L-S	0	0	
810			ELBOW	5448891	14	18	ELL 45 DEG SCH 10 A403 WP316/316L-S	0	0	
820			ELBOW	5449036	20	24	ELL 45 DEG SCH 20 A403 WP316/316L-S	0	0	
830			ELBOW	5451106	26	36	ELL 45 DEG SCH STD 316/316L SS A403 WP316/316L-W	0	0	
840			ELBOW	5451106	42	42	ELL 45 DEG SCH STD 316/316L SS A403 WP316/316L-W	0	0	
850	U04	UK9	ELBOW	5449143	0.5	0.75	ELL 45 DEG LR XXS SS A403 WP316/316L-S	0	0	
860	U04	824	ELBOW	5449038	14	24	ELL 45 SCH 40 SS A403 WP316/316L-S	0	0	
870										
870	U04		TEE	5449156	0.5	1.5	TEE SCH 80S SS A403 WP316/316L-S	0	0	
880	U04	824	TEE	5449156	20	24	TEE SCH 80S SS A403 WP316/316L-S	0	0	
890			TEE	5449147	2	6	TEE SCH 40S SS A403 WP316/316L-S	0	0	
900			TEE	5449043	8	12	TEE SCH 30 SS A403 WP316/316L-S	0	0	
910			TEE	5448892	14	18	TEE SCH 10 SS A403 WP316/316L-S	0	0	
920			TEE	5449039	20	24	TEE SCH 20 SS A403 WP316/316L-S	0	0	
930			TEE	5451109	26	36	TEE SCH STD 316/316L SS A403 WP316/316L-W	0	0	
940			TEE	5451109	42	42	TEE SCH STD 316/316L SS A403 WP316/316L-W	0	0	
950	U04	824	TEE	5449045	18	18	TEE SCH 40 SS A403 WP316/316L-S	0	0	
960	U04	824	TEE	5449045	24	24	TEE SCH 40 SS A403 WP316/316L-S	0	0	
970	U04	UK9	TEE	5449191	0.5	0.75	TEE SCH XXS SS A403 WP316/316L-S	0	0	
980			TEE RED	5448905	0.75	1	TEE RED SCH 80S SS A403 WP316/316L-S	1	1.5	
990			TEE RED	5449250	1	1.5	TEE RED SCH 40S/80S SS A403 WP316/316L-S	2	3	
1000			TEE RED	5449184	2	4	TEE RED SCH 40S SS A403 WP316/316L-S	3	6	
1010			TEE RED	5448889	4	6	TEE RED SCH 30/40S SS A403 WP316/316L-S	8	12	
1020	U04	PE1	TEE RED	5448880	6	6	TEE RED SCH 10/40S SS A403 WP316/316L-S	14	16	
1030			TEE RED	5449053	8	10	TEE RED SCH 30 SS A403 WP316/316L-S	10	12	
1040			TEE RED	5448896	8	12	TEE RED SCH 10/30 SS A403 WP316/316L-S	14	18	
1050			TEE RED	5449167	8	12	TEE RED SCH 20/30 SS A403 WP316/316L-S	20	24	
1060			TEE RED	5448898	14	16	TEE RED SCH 10 SS A403 316/316L-S	16	18	
1070	U04	PE1	TEE RED	5449168	14	18	TEE RED SCH 20/10 SS A403 WP316/316L-S	20	24	
1080			TEE RED	5449041	20	20	TEE RED SCH 20 SS A403 WP316/316L-S	24	24	
1090			TEE RED	5449131	16	16	TEE RED SCH STD/10 SS A403 WP316/316L-W	30	30	
1100			TEE RED	5449169	20	24	TEE RED SCH STD/20 SS A403 WP316/316L-W	26	30	
1110			TEE RED	5449042	26	36	TEE RED SCH STD SS A403 WP316/316L-W	28	42	
1120	U04	824	TEE RED	5449251	12	12	TEE RED SCH 40S/30 SS A403 WP316/316L-S	18	18	
1130	U04	824	TEE RED	5448917	12	12	TEE RED SCH 60/30 SS A403 WP316/316L-S	24	24	
1140	U04	PE1	TEE RED	5448909	18	18	TEE RED SCH 80S/10 SS A403 WP316/316L-S	24	24	
1150	U04	824	TEE RED	5449185	18	18	TEE RED SCH 80S/40S SS A403 WP316/316L-S	24	24	
1160	U04	824	TEE RED	5449197	18	18	TEE RED SCH 80S/SCH40 SS A403 WP316/316L-S	24	24	
1170										
1170			CAP	5449049	0.75	1.5	CAP SCH 80S SS A403 WP316/316L-S	0	0	
1180			CAP	5449148	2	6	CAP SCH 40S SS A403 WP316/316L-S	0	0	
1190			CAP	5449044	8	12	CAP SCH 30 SS A403 WP316/316L-S	0	0	
1200			CAP	5448893	14	18	CAP SCH 10 SS ASTM A403 WP316/316L-S	0	0	
1210			CAP	5449040	20	24	CAP SCH 20 SS A403 WP316/316L-S	0	0	
1220			CAP	5449256	26	36	CAP SCH STD SS A403 WP316/316L-S	0	0	
1230			CAP	5449256	42	42	CAP SCH STD SS A403 WP316/316L-S	0	0	
1240										

	TENGIZCHEVROIL TCO TENGIZ, KAZAKHSTAN	CONSTRUCTION	CORR.ALLOW.	SERVICE	MATERIAL	DATE	BY	REV	SHEET	PIPING LINE CLASS
		ALL SIZES - BUTT WELD SEAL WELDING - FOR THREADED CONNECTIONS ONLY PIPE BENDS - NONE THREAD SEALANT - PTFE PASTE	CORR. ALLOW. 1 MM	SOUR SERVICE - NACE MR0175/ ISO 15156 DESIGN: ASME B16.5 MG 2.2 CODE - ASME B31.3 FLUID CODES - PIM-SU-5112-TCO	MATERIAL: 316/316L SS DUAL GRADE FLANGE RATING: 150 RF TEMPERATURE RANGE: -120 / 180 °C COMMENT: LOW TEMP BLOW DOWN	12/16/2024	BY OZAC	U04	Page 2 of 6	150P21

SEQ NO	REV	NOTE NO.	ITEM NAME	ITEM CODE	SIZE RANGE / SMALL END SIZES		DESCRIPTION	REFERENCE / LARGE END SIZES		NOTES
1240			RED CONC	5449158	0.5	1	REDUCER CONC SCH 80S SS A403 WP316/316L-S	0.75	1.5	
1250			RED CONC	5549110	0.75	1.5	REDUCER CONC SCH 40S/80S SS A403 WP316/316L-S	2	4	
1260			RED CONC	5449149	2	4	REDUCER CONC SCH 40S SS A403 WP316/316L-S	3	6	
1270	U04	824	RED CONC	5449149	4	6	REDUCER CONC SCH 40S SS A403 WP316/316L-S	10	10	
1280			RED CONC	5448899	4	6	REDUCER CONC SCH 30/40S SS A403 WP316/316L-S	8	12	
1290	U04	PE1	RED CONC	5448881	6	6	REDUCER CONC SCH 10/40S SS A403 WP316/316L-S	14	14	
1300			RED CONC	5448900	8	10	REDUCER CONC SCH 30 SS A403 WP316/316L-S	10	12	
1310	U04	PE1	RED CONC	5448901	8	12	REDUCER CONC SCH 10/30 SS A403 WP316/316L-S	14	18	
1320			RED CONC	5449173	12	12	REDUCER CONC SCH 20/30 SS A403 WP316/316L-S	20	20	
1330			RED CONC	5448894	14	16	REDUCER CONC SCH 10 SS A403 WP316/316L-S	16	18	
1340	U04	PE1	RED CONC	5450720	18	18	REDUCER CONC SCH STD/10 SS A403 WP316/316L-W	26	28	
1350	U04	PE1	RED CONC	5449174	14	18	REDUCER CONC SCH 20/10 SS A403 WP316/316L-S	20	24	
1360			RED CONC	5449175	20	20	REDUCER CONC SCH 20 SS A403 WP316/316L-S	24	24	
1370			RED CONC	5450721	20	24	REDUCER CONC SCH STD/20 SS A403 WP316/316L-W	26	36	
1380			RED CONC	5450722	26	36	REDUCER CONC SCH STD SS A403 WP316/316L-W	28	42	
1390			RED ECC	5449159	0.5	1	REDUCER ECC SCH 80S SS A403 WP316/316L-S	0.75	1.5	
1400			RED ECC	5549310	0.75	1.5	REDUCER ECC SCH 40S/80S SS A403 WP316/316L-S	2	4	
1410	U04	824		5549310	2	2	REDUCER ECC SCH 40S/80S SS A403 WP316/316L-S	3	3	
1420			RED ECC	5449150	2	4	REDUCER ECC SCH 40S SS A403 WP316/316L-S	3	6	
1430	U04	824	RED ECC	5449150	16	16	REDUCER ECC SCH 40S SS A403 WP316/316L-S	18	18	
1440			RED ECC	5449151	4	6	REDUCER ECC SCH 30/40S SS A403 WP316/316L-S	8	12	
1450	U04	PE1	RED ECC	5448882	6	6	REDUCER ECC SCH 10/40S SS A403 WP316/316L-S	14	14	
1460			RED ECC	5449152	8	10	REDUCER ECC SCH 30 SS A403 WP316/316L-S	10	12	
1470	U04	PE1	RED ECC	5449153	8	12	REDUCER ECC SCH 10/30 SS A403 WP316/316L-S	14	18	
1480			RED ECC	5449170	12	12	REDUCER ECC SCH 20/30 SS A403 WP316/316L-S	20	20	
1490			RED ECC	5448895	14	16	REDUCER ECC SCH 10 SS A403 WP316/316L-S	16	18	
1500			RED ECC	5449171	14	18	REDUCER ECC SCH 20/10 SS A403 WP316/316L-S	20	24	
1510	U04	PE1	RED ECC	5450723	18	18	REDUCER ECC SCH STD/10 SS A403 WP316/316L-W	26	28	
1520			RED ECC	5449172	20	20	REDUCER ECC SCH 20 SS A403 WP316/316L-S	24	24	
1530			RED ECC	5450724	20	24	REDUCER ECC SCH STD/20 SS A403 WP316/316L-W	26	36	
1540			RED ECC	5450725	26	36	REDUCER ECC SCH STD SS A403 WP316/316L-W	28	42	
1550	U04	824	RED ECC	5449176	18	18	REDUCER ECC SCH 20/SCH 80S SS A403 WP316/316L-S	24	24	
1560	U04	824	RED ECC	5449155	18	18	REDUCER ECC SCH 40 SS A403 WP316/316L-S	20	20	
1570	U04	824	RED ECC	5449195	12	12	REDUCER ECC SCH 40/30 SS A403 WP316/316L-S	20	20	
1580	U04	824	RED ECC	5449154	6	6	REDUCER ECC SCH 40/40S SS A403 WP316/316L-S	12	12	
1590	U04	824	RED ECC	5449193	20	20	REDUCER ECC SCH 40/80S SS A403 WP316/316L-S	24	24	
1600	U04	824	RED ECC	5449691	12	12	REDUCER ECC SCH 40S/30 SS A403 WP316/316L-S	16	16	
1610	U04	824	RED ECC	5448883	18	18	REDUCER ECC SCH 60 SS A403 WP316/316L-S	24	24	
1620	U04	824	RED ECC	5449112	12	12	REDUCER ECC SCH 60/30 SS A403 WP316/316L-S	20	20	
1630	U04	824	RED ECC	5449111	12	12	REDUCER ECC SCH 60/40 SS A403 WP316/316L-S	18	18	
1640	U04	824	RED ECC	5449194	20	20	REDUCER ECC SCH 80S/SCH 20 SS A403 WP316/316L-S	24	24	
1650										
1650			OLETS	5504311	0.75	1.5	NIPOFLANGE 150# RF SCH 40S/80S SS A182 F316/316L	2	6	
1660			OLETS	5504331	0.75	1.5	NIPOFLANGE 150# RF SCH 30/80S SS A182 F316/316L	8	12	
1670	U04	PE1	OLETS	5504312	0.75	1.5	NIPOFLANGE 150# RF SCH 10/80S SS A182 F316/316L	14	18	
1680			OLETS	5504334	0.75	1.5	NIPOFLANGE 150# RF SCH 20/80S SS A182 F316/316L	20	24	
1690			OLETS	5504343	0.75	1.5	NIPOFLANGE 150# RF SCH STD/80S SS A182 F316/316L	26	42	
1700			OLETS	5504011	2	2	NIPOFLANGE 150# RF SCH 40S/40S SS A182 F316/316L	3	6	
1710			OLETS	5504031	2	2	NIPOFLANGE 150# RF SCH 30/40S SS A182 F316/316L	8	12	
1720	U04	PE1	OLETS	5504012	2	2	NIPOFLANGE 150# RF SCH 10/40S SS A182 F316/316L	14	18	
1730			OLETS	5504034	2	2	NIPOFLANGE 150# RF SCH 20/40S SS A182 F316/316L	20	24	
1740			OLETS	5504043	2	2	NIPOFLANGE 150# RF SCH STD/40S SS A182 F316/316L	26	42	
1750	U04	824	OLETS	5504344	2	2	NIPOFLANGE 150# RF SCH 40/40S SS A182 F316/316L	14	14	
1760	U04	FS1	OLETS	5504960	2	2	NIPOFLANGE 1500# RF SCH 30/40S SS A182 F316/316L	8	8	
1770	U04	FS1	OLETS	5504961	2	2	NIPOFLANGE 1500# RF SCH 40S SS A182 F316/316L	6	6	
1780	U04	824	OLETS	5504421	1.5	1.5	NIPOFLANGE 300# RF SCH 40/80S SS A182 F316/316L	14	14	
1790	U04		OLETS	5504482	1.5	1.5	NIPOFLANGE 300# RF SCH STD/80S SS A182 F316/316L	30	36	
1800	U04	FF5	OLETS	5504523	0.75	0.75	NIPOFLANGE FLAT BOTTOM 150# RF SCH 80S SS A182 F316/316L	0	0	
1810			OLETS	5504411	0.75	1.5	NIPOFLANGE 300# RF SCH 40S/80S SS A182 F316/316L	2	3	
1820			OLETS	5504412	1	1	NIPOFLANGE 300# RF SCH 80S SS A182 F316/316L	1.5	1.5	
1830	UJ2		OLETS	5504132	0.75	1.5	NIPOFLANGE 300# RF SCH 40S/160 SS A182 F316/316L	4	6	
1840	UJ2		OLETS	5504145	0.75	1.5	NIPOFLANGE 300# RF SCH 30/160 SS A182 F316/316L	8	12	
1850	UJ2		OLETS	5504146	0.75	1.5	NIPOFLANGE 300# RF SCH 10/160 SS A182 F316/316L	14	18	
1860	UJ2		OLETS	5504147	0.75	1.5	NIPOFLANGE 300# RF SCH 20/160 SS A182 F316/316L	20	24	
1870	UJ2		OLETS	5504144	0.75	1.5	NIPOFLANGE 300# RF SCH STD/160 SS A182 F316/316L	26	42	
1880										
1880			OLETS	5510354	0.75	1.5	WELDOLET SCH 40S/80S SS A182 F316/316L	2	6	
1890	U04	824	OLETS	5510354	0.75	0.75	WELDOLET SCH 40S/80S SS A182 F316/316L	10	10	
1900			OLETS	5510355	0.75	1.5	WELDOLET SCH 30/80S SS A182 F316/316L	8	12	
1910	U04	PE1	OLETS	5510356	0.75	1.5	WELDOLET SCH 10/80S SS A182 F316/316L	14	18	
1920			OLETS	5510357	0.75	1.5	WELDOLET SCH 20/80S SS A182 F316/316L	20	24	
1930			OLETS	5510358	0.75	1.5	WELDOLET STD/80S SS A182 F316/316L	26	42	
1940			OLETS	5509631	2	3	WELDOLET SCH 40S/40S SS A182 F316/316L	4	6	

	TENGIZCHEVROIL TCO TENGIZ, KAZAKHSTAN	CONSTRUCTION	CORR.ALLOW.	SERVICE	MATERIAL	DATE	BY	REV	SHEET	PIPING LINE CLASS
		ALL SIZES - BUTT WELD SEAL WELDING - FOR THREADED CONNECTIONS ONLY PIPE BENDS - NONE THREAD SEALANT - PTFE PASTE	CORR. ALLOW. 1 MM	SOUR SERVICE - NACE MR0175/ ISO 15156 DESIGN: ASME B16.5 MG 2.2 CODE - ASME B31.3 FLUID CODES - PIM-SU-5112-TCO	MATERIAL: 316/316L SS DUAL GRADE FLANGE RATING: 150 RF TEMPERATURE RANGE: -120 / 180 °C COMMENT: LOW TEMP BLOW DOWN	12/16/2024	BY OZAC	U04	Page 3 of 6	150P21

SEQ NO	REV	NOTE NO.	ITEM NAME	ITEM CODE	SIZE RANGE / SMALL END SIZES		DESCRIPTION	REFERENCE / LARGE END SIZES		NOTES
1950	U04	824	OLETS	5509631	2	2	WELDOLET SCH 40S/40S SS A182 F316/316L	10	10	
1960	U04	824	OLETS	5509631	2	4	WELDOLET SCH 40S/40S SS A182 F316/316L	18	18	
1970			OLETS	5509634	2	4	WELDOLET SCH 30/40S SS A182 F316/316L	8	12	
1980	U04	PE1	OLETS	5509630	2	6	WELDOLET SCH 10/40S SS A182 F316/316L	14	18	
1990			OLETS	5509633	2	6	WELDOLET SCH 20/40S SS A182 F316/316L	20	24	
2000			OLETS	5509650	2	6	WELDOLET STD/40S SS A182 F316/316L	26	42	
2010			OLETS	5509641	8	8	WELDOLET SCH 20/30 SS A182 F316/316L	24	24	
2020			OLETS	5509642	8	12	WELDOLET STD/30 SS A182 F316/316L	26	42	
2030										
2030	U04	PE1	OLETS	5509710	2	4	SWEEPOLET SCH 10/SCH 40S SS A182 F316/316L	18	18	
2040										
2040	U04	824	OLETS	5509636	3	3	WELDOLET SCH 40/40S SS A182 F316/316L	14	14	
2050										
2050	U04	PE1	OLETS	5509711	1.5	1.5	SWEEPOLET SCH 10/SCH 80S SS A182 F316/316L	18	18	
2060										
2060	U04	821		5509637	0.75	0.75	WELDOLET SCH 80S SS A182 F316/316L	10	10	
2070										
2070	U04		OLETS	5509709	2	6	SWEEPOLET SCH 20/SCH 40S SS A182 F316/316L	20	24	
2080										
2080	U04	821		5509632	2	2	WELDOLET SCH 80S/40S SS A182 F316/316L	10	10	
2090										
2090	U04		OLETS	5509712	1.5	1.5	SWEEPOLET SCH 20/SCH 80S SS A182 F316/316L	20	20	
2100	U04		OLETS	5509715	1.5	1.5	SWEEPOLET SCH 30/SCH 80S SS A182 F316/316L	8	8	
2110	U04	824	OLETS	5509716	2	2	SWEEPOLET SCH 40/SCH 40S SS A182 F316/316L	18	20	
2120	U04	824	OLETS	5509716	4	4	SWEEPOLET SCH 40/SCH 40S SS A182 F316/316L	18	18	
2130	U04	824	OLETS	5509716	4	4	SWEEPOLET SCH 40/SCH 40S SS A182 F316/316L	24	24	
2140	U04	824	OLETS	5509736	1.5	1.5	SWEEPOLET SCH 40/SCH 80S SS A182 F316/316L	20	20	
2150	U04	824	OLETS	5509737	2	2	SWEEPOLET SCH 60/SCH 40S SS A182 F316/316L	18	18	
2160	U04	824	OLETS	5509737	4	4	SWEEPOLET SCH 60/SCH 40S SS A182 F316/316L	18	18	
2170	U04	824	OLETS	5509737	2	2	SWEEPOLET SCH 60/SCH 40S SS A182 F316/316L	24	24	
2180	U04	824	OLETS	5509737	6	6	SWEEPOLET SCH 60/SCH 40S SS A182 F316/316L	24	24	
2190	U04	824	OLETS	5509735	1.5	1.5	SWEEPOLET SCH 60/SCH 80S SS A182 F316/316L	18	24	
2200	U04	824	OLETS	5509738	2	2	SWEEPOLET SCH 80S/SCH 40S SS A182 F316/316L	20	20	
2210	U04	824	OLETS	5509738	4	4	SWEEPOLET SCH 80S/SCH 40S SS A182 F316/316L	20	24	
2220	U04		OLETS	5509713	8	12	SWEEPOLET SCH STD/SCH 30 SS A182 F316/316L	30	30	
2230	U04		OLETS	5509714	4	4	SWEEPOLET SCH STD/SCH 40S SS A182 F316/316L	30	30	
2240										
2240		UJ2	ELBOFLG	5516152	1.5	1.5	ELBOFLANGE 300# RF SCH 40S/160 SS A182 F316/316L	4	6	
2250		UJ2	ELBOFLG	5516153	1.5	1.5	ELBOFLANGE 300# RF SCH 30/160 SS A182 316/316L	8	12	
2260		UJ2	ELBOFLG	5516154	1.5	1.5	ELBOFLANGE 300# RF SCH 10/160 SS A182 316/316L	14	18	
2270		UJ2	ELBOFLG	5516155	1.5	1.5	ELBOFLANGE 300# RF SCH 20/160 SS A182 316/316L	20	24	
2280		UJ2	ELBOFLG	5516157	1.5	1.5	ELBOFLANGE 300# RF STD/160 SS A182 316/316L	26	42	
2290										
2290			COUPLING	5480142	0.5	1.5	COUPLING 3000# SW SS A182 F316/316L	0	0	
2300			TEE RED	5480134	0.75	1	COUPLING RED 3000# SW SS A182 F316/316L	1	1.5	
2310										
2310			UNION	5480146	0.75	1.5	UNION 3000# SW SS A182 F316/316L	0	0	
2320										
2320		UD7	FITTING SCRD	5498383	0.75	0.75	PLUG ROUND HEAD SCRD SS A182 F316/316L	0	0	
2330	U04	UDC	FITTING SCRD	5498383	0.5	0.5	PLUG ROUND HEAD SCRD SS A182 F316/316L	0	0	
2340										
2340			OLETS	5537071	0.75	1.5	SOCKOLET 3000# SS A182 F316/316L	2	42	
2350			OLETS	5533235	0.75	1.5	SOCKOLET FLAT BOTTOM 3000# SS A182 F316/316L	0	0	
2360										
2360		UD7	OLETS	5515771	0.75	0.75	THREDOLET 3000# SS A182 F316/316L	2	42	
2370										
2370		FS1					***** FLANGES *****			
2380										
2380			FLANGE	5582724	0.5	1.5	FLG WN 150# RF SS A182 F316/316L SCH 80S BORE	0	0	
2390	U04	821		5582724	6	6	FLG WN 150# RF SS A182 F316/316L SCH 80S BORE	0	0	
2400			FLANGE	5582725	2	6	FLG WN 150# RF SS A182 F316/316L SCH 40S BORE	0	0	
2410			FLANGE	5582726	8	12	FLG WN 150# RF SS A182 F316/316L SCH 30 BORE	0	0	
2420	U04	PE1	FLANGE	5582722	14	18	FLG WN 150# RF SS A182 F316/316L SCH 10 BORE	0	0	
2430			FLANGE	5582723	20	24	FLG WN 150# RF SS A182 F316/316L SCH 20 BORE	0	0	
2440			FLANGE	5583005	26	36	FLG WN 150# RF SS A182 F316/316L STD B16.47 SERIES A	0	0	
2450			FLANGE	5583005	42	42	FLG WN 150# RF SS A182 F316/316L STD B16.47 SERIES A	0	0	
2460		FA3	FLANGE	5582729	2	6	FLG WN 150# FF SS A182 F316/316L SCH 40S BORE	0	0	
2470	U04	824	FLANGE	5582720	14	20	FLG WN 150# RF SS A182 F316/316L SCH 40 BORE	0	0	
2480	U04	824	FLANGE	5582727	20	20	FLG WN 150# RF SS A182 F316/316L SCH 60 BORE	0	0	
2490			TEE RED	5556281	2	2	FLG WN REDUCING 150# RF A182 F316/316L BORED TO SUIT SCH 40S	3	3	
2500			FLANGE	5582991	0.5	1.5	FLG WN 300# RF SS A182 F316/316L SCH 80S BORE	0	0	
2510			FLANGE	5582995	2	6	FLG WN 300# RF SS A182 F316/316L SCH 40S BORE	0	0	
2520			FLANGE	5582996	8	12	FLG WN 300# RF SS A182 F316/316L SCH 30 BORE	0	0	

	TENGIZCHEVROIL TCO TENGIZ, KAZAKHSTAN	CONSTRUCTION	CORR.ALLOW.	SERVICE	MATERIAL	DATE	BY	REV	SHEET	PIPING LINE CLASS
		ALL SIZES - BUTT WELD SEAL WELDING - FOR THREADED CONNECTIONS ONLY PIPE BENDS - NONE THREAD SEALANT - PTFE PASTE	CORR. ALLOW. 1 MM	SOUR SERVICE - NACE MR0175/ ISO 15156 DESIGN: ASME B16.5 MG 2.2 CODE - ASME B31.3 FLUID CODES - PIM-SU-5112-TCO	MATERIAL: 316/316L SS DUAL GRADE FLANGE RATING: 150 RF TEMPERATURE RANGE: -120 / 180 °C COMMENT: LOW TEMP BLOW DOWN	12/16/2024	BY OZAC	U04	Page 4 of 6	150P21

SEQ NO	REV	NOTE NO.	ITEM NAME	ITEM CODE	SIZE RANGE / SMALL END SIZES		DESCRIPTION	REFERENCE / LARGE END SIZES		NOTES
2530			FLANGE	5582993	14	18	FLG WN 300# RF SS A182 F316 SCH 10S BORE	0	0	
2540	U04	824	FLANGE	5582997	14	14	FLG WN 300# RF SS A182 F316/316L SCH 40 BORE	0	0	
2550	U04	824	FLANGE	5583533	18	18	FLG WN 600# RF SS A182 F316/316L SCH 60 BORE	0	0	
2560	U04		FLANGE	5583023	8	8	FLG WN 900# RF SS A182 F316/316L SCH 30 BORE	0	0	
2570	U04	ND9	FLANGE	5583007	18	18	FLG WN 900# RF SS A182 F316/316L SCH 60 BORE	0	0	
2580			FLANGE	5582992	20	24	FLG WN 300# RF SS A182 F316/316L SCH 20 BORE	0	0	
2590			FLANGE	5583010	26	36	FLG WN 300# RF SS A182 F316/316L STD B16.47 SERIES A	0	0	
2600			FLANGE	5583010	42	42	FLG WN 300# RF SS A182 F316/316L STD B16.47 SERIES A	0	0	
2610	U04		FLANGE	5582998	0.5	1.5	FLG WN 600# RF SS A182 F316/316L SCH 80S BORE	0	0	
2620	U04	824	FLANGE	5582998	18	18	FLG WN 600# RF SS A182 F316/316L SCH 80S BORE	0	0	
2630			FLANGE	5583535	2	6	FLG WN 600# RF SS A182 F316/316L SCH 40S BORE	0	0	
2640			FLANGE	5583534	10	12	FLG WN 600# RF SS A182 F316/316L SCH 30 BORE	0	0	
2650			FLANGE	5583537	18	18	FLG WN 600# RF SS A182 F316/316L SCH 10 BORE	0	0	
2660	U04		FLANGE	5583021	3	6	FLG WN 900# RF SS A182 F316/316L SCH 40S BORE	0	0	
2670	U04		FLANGE	5583970	2	6	FLG WN 1500# RF SS A182 F316/316L SCH 40S BORE	0	0	
2680	U04		FLANGE	5583972	8	12	FLG WN 1500# RF SS A182 F316/316L SCH 30 BORE	0	0	
2690	U04		FLANGE	5583979	0.5	1.5	FLG WN 1500# RF SS A182 F316/316L SCH 80S BORE	0	0	
2700	U04	817	FLANGE	5584157	2	2	FLG WN 1500# RTJ SS A182 F316/316L SCH 40S BORE	0	0	
2710	U04	824, 817		5584061	2	2	FLG WN 1500# RTJ SS A182 F316/316L SCH 80S BORE	0	0	
2720	U04	817	FLANGE	5584167	1	1.5	FLG WN 2500# RTJ SS A182 F316/316L SCH 80S	0	0	
2730	U04	817	FLANGE	5584169	2	2	FLG WN 2500# RTJ SS A182 F316/316L SCH 40S	0	0	
2740			BLIND	5616520	0.5	24	FLG BLIND 150# RF SS A182 F316/316L	0	0	
2750			BLIND	5616521	26	36	FLG BLIND 150# RF SS A182 F316/316L B16.47 SERIES A	0	0	
2760			BLIND	5616521	42	42	FLG BLIND 150# RF SS A182 F316/316L B16.47 SERIES A	0	0	
2770			BLIND	5616529	0.5	24	FLG BLIND 300# RF SS A182 F316/316L	0	0	
2780			BLIND	5616530	26	36	FLG BLIND 300# RF SS A182 F316/316L B16.47 SERIES A	0	0	
2790			BLIND	5616530	42	42	FLG BLIND 300# RF SS A182 F316/316L B16.47 SERIES A	0	0	
2800	U04	817	BLIND	5616567	2	2	FLG BLIND 1500# RTJ SS A182 F316/316L	0	0	
2810	U04		BLIND	5616544	4	4	FLG BLIND 600# RF SS A182 F316/316L	0	0	
2820	U04		BLIND	5616556	3	8	FLG BLIND 900# RF SS A182 F316/316L	0	0	
2830		FA8	TEE RED	5600655	0.5	0.5	FLG SCRD (FNPT) REDUCING 150# RF SS A182 F316/316L	0.75	1.5	
2840	U04	FA8	FLANGE	5600656	0.5	0.5	FLG SCRD (FNPT) REDUCING 300# RF SS A182 F316/316L	0.75	2	
2850										
2850			FLANGE	5851200	0.5	2	FLANGE ADAPTER 150# RF 316 SS X 12 MM TUBE	0	0	
2860			FLANGE	5851203	0.75	2	FLANGE ADAPTER 300# RF 316 SS X 12 MM TUBE	0	0	
2870										
2870							***** ORIFICE FLANGES *****			
2880										
2880			ORIFICE FLG	5640598	2	6	WN ORIF SET 300# RF SS A182 F316/316L SCH 40S BORE	0	0	
2890			ORIFICE FLG	5640597	8	12	WN ORIF SET 300# RF SS A182 F316/316L SCH 30 BORE	0	0	
2900			ORIFICE FLG	5640596	14	18	WN ORIF SET 300# RF SS A182 F316/316L SCH 10 BORE	0	0	
2910			ORIFICE FLG	5640595	20	24	WN ORIF SET 300# RF SS A182 F316/316L SCH 20 BORE	0	0	
2920			ORIFICE FLG	5640610	26	36	WN ORIF SET 300# RF SS A182 F316/316L STD WT B16.47 SERIES A	0	0	
2930			ORIFICE FLG	5640610	42	42	WN ORIF SET 300# RF SS A182 F316/316L STD WT B16.47 SERIES A	0	0	
2940										
2940							***** PIPE NIPPLES *****			
2950										
2950		810		0			NIPPLE PBE CUT FROM PIPE			
2960										
2960		FS1					***** GASKETS *****			
2970										
2970			GASKET	5673043	0.5	24	GASKET 150# 316SS SPIRAL WOUND GRAPHITE IR	0	0	
2980			GASKET	5674011	26	42	GASKET 150# 316SS KAMMPROFILE GRAPHITE ASME B16.47 SERIES A	0	0	
2990			GASKET	5664562	0.75	16	GASKET 150# FF RING EPDM 3MM THK	0	0	
3000			GASKET	5673034	0.5	24	GASKET 150# 316SS SPIRAL WOUND GRAPHITE LOW STRESS	0	0	
3010			GASKET	5673033	0.5	24	GASKET 300# 316SS SPIRAL WOUND GRAPHITE IR	0	0	
3020			GASKET	5674032	26	42	GASKET 300# 316SS KAMMPROFILE GRAPHITE ASME B16.47 SERIES A	0	0	
3030	U04	GA6	GASKET	5673017	2	3	GASKET 300# 316SS KAMMPROFILE GRAPHITE ASME B16.5	0	0	
3040	U04		GASKET	5673103	0.5	18	GASKET 600# 316SS SPIRAL WOUND GRAPHITE IR	0	0	
3050	U04		GASKET	5673117	3	8	GASKET 900# 316SS SPIRAL WOUND GRAPHITE IR	0	0	
3060	U04	ND9	GASKET	5673117	18	18	GASKET 900# 316SS SPIRAL WOUND GRAPHITE IR	0	0	
3070	U04		GASKET	5672251	0.5	12	GASKET 1500# 316SS SPIRAL WOUND GRAPHITE IR	0	0	
3080	U04	817	GASKET	5674479	2	2	GASKET 1500# RTJ SS OCTAGONAL RING	0	0	
3090	U04	817	GASKET	5674480	1	2	GASKET 2500# RTJ SS OCTAGONAL RING	0	0	
3100										
3100		B1					***** BOLTING *****			
3110										
3110				5675770	0.5	99	STUD-BOLT A320 GR L7M/A194 GR 7M (S3) WITH 2 NUTS	0	0	
3120			BOLTING	5675776	0.5	99	STUD-BOLT WITH 2 NUTS API-6A718	0	0	
3130			BOLTING	5675677	0.5	99	STUD-BOLT A320 GR B8M CLASS 2/A194 GR 8MA NUTS	0	0	
3140										
3140		SB6	BOLTING	5675676	10	42	JACK SCREW HEX HEAD A320 B8M - CLASS 2	0	0	

	TENGIZCHEVROI TCO TENGIZ, KAZAKHSTAN	CONSTRUCTION	CORR.ALLOW.	SERVICE	MATERIAL	DATE	BY	REV	SHEET	PIPING LINE CLASS
		ALL SIZES - BUTT WELD SEAL WELDING - FOR THREADED CONNECTIONS ONLY PIPE BENDS - NONE THREAD SEALANT - PTFE PASTE	CORR. ALLOW. 1 MM	SOUR SERVICE - NACE MR0175/ ISO 15156 DESIGN: ASME B16.5 MG 2.2 CODE - ASME B31.3 FLUID CODES - PIM-SU-5112-TCO	MATERIAL: 316/316L SS DUAL GRADE FLANGE RATING: 150 RF TEMPERATURE RANGE: -120 / 180 °C COMMENT: LOW TEMP BLOW DOWN	12/16/2024	BY OZAC	U04	Page 5 of 6	150P21

SEQ NO	REV	NOTE NO.	ITEM NAME	ITEM CODE	SIZE RANGE / SMALL END SIZES		DESCRIPTION	REFERENCE / LARGE END SIZES		NOTES
3150							***** BLINDS & SPACERS *****			
3150										
3160										
3160			SPEC BLIND	5750421	0.75	14	SPECTACLE BLIND 150# RF SS A240 GR 316	0	0	
3170			SPEC BLIND	5750422	0.75	10	SPECTACLE BLIND 300# RF SS A240 GR 316	0	0	
3180										
3180			PADDLE	5750521	16	24	PADDLE BLANK 150# RF SS A240 GR 316	0	0	
3190			PADDLE	5750526	26	36	PADDLE BLANK 150# RF SS A240 GR 316 B16.47 SERIES A	0	0	
3200			PADDLE	5750526	42	42	PADDLE BLANK 150# RF SS A240 GR 316 B16.47 SERIES A	0	0	
3210			PADDLE	5750522	12	24	PADDLE BLANK 300# RF SS A240 GR 316	0	0	
3220			PADDLE	5750527	26	36	PADDLE BLANK 300# RF SS A240 GR 316 B16.47 SERIES A	0	0	
3230			PADDLE	5750621	16	24	PADDLE SPACER 150# RF SS A240 GR 316	0	0	
3240			PADDLE	5750626	26	36	PADDLE SPACER 150# RF SS A240 GR 316 B16.47 SERIES A	0	0	
3250			PADDLE	5750626	42	42	PADDLE SPACER 150# RF SS A240 GR 316 B16.47 SERIES A	0	0	
3260			PADDLE	5750622	12	24	PADDLE SPACER 300# RF SS A240 GR 316	0	0	
3270			PADDLE	5750627	26	36	PADDLE SPACER 300# RF SS A240 GR 316 B16.47 SERIES A	0	0	
3280										
3290										
3290							***** MISCELLANEOUS *****			
3300										
3300	U04		FLG GUARD	5558881	0.5	10	SAFETY SHIELD PTFE SUITABLE FOR 150# FLANGE	0	0	
3310	U04		FLG GUARD	5558882	6	6	SAFETY SHIELD PTFE SUITABLE FOR 300# FLANGE	0	0	

	TENGIZCHEVROIL TCO TENGIZ, KAZAKHSTAN	CONSTRUCTION	CORR.ALLOW.	SERVICE	MATERIAL	DATE	BY	REV	SHEET	PIPING LINE CLASS
		ALL SIZES - BUTT WELD SEAL WELDING - FOR THREADED CONNECTIONS ONLY PIPE BENDS - NONE THREAD SEALANT - PTFE PASTE	CORR. ALLOW. 1 MM	SOUR SERVICE - NACE MR0175/ ISO 15156 DESIGN: ASME B16.5 MG 2.2 CODE - ASME B31.3 FLUID CODES - PIM-SU-5112-TCO	MATERIAL: 316/316L SS DUAL GRADE FLANGE RATING: 150 RF TEMPERATURE RANGE: -120 / 180 °C COMMENT: LOW TEMP BLOW DOWN	12/16/2024	BY OZAC	U04	Page 6 of 6	150P21