

SEQ NO	REV	NOTE NO.	ITEM NAME	ITEM CODE	SIZE RANGE / SMALL END SIZES		DESCRIPTION	REFERENCE / LARGE END SIZES		NOTES	
10	U04						***** PIPE*****			B1 PA5 ALL BOLTS ARE METRIC DIA. EQUIVALENT HDPE PIPE TO NOMINAL PIPE SIZES SEE PIM-SU-5112	
20	U04	PA5	PIPE	9004126	6	6	PIPE SDR 7.4 PE-RT POLYETHYLENE ASTM-D3350 / ISO 4427	0	0		
30	U04		PIPE	9004126	18	20	PIPE SDR 7.4 PE-RT POLYETHYLENE ASTM-D3350 / ISO 4427	0	0		
40	U04						***** FITTINGS *****				
50	U04		ELBOW	9004128	18	20	BEND 45 DEG LONG RADIUS SDR 7.4 PE-RT POLYETHYLENE SOUR WATER ASTM-D3350 / ISO 4427	0	0		
60	U04		ELBOW	9004127	18	20	BEND 90 DEG LONG RADIUS SDR 7.4 PE-RT POLYETHYLENE SOUR WATER ASTM-D3350 / ISO 4427	0	0		
70	U04		TEE	9004173	18	20	TEE EQUAL ELONGATED TYPE SDR 7.4 PE-RT POLYETHYLENE SOUR WATER ASTM-D3350 / ISO 4427	0	0		
80	U04		Coupling	9004174	18	20	COUPLING ELECTRO FUSION SDR 7.4 PE-RT POLYETHYLENE SOUR WATER ASTM-D3350 / ISO 4427	0	0		
90	U04						***** FLANGES*****				
100	U04		FLANGE	9004175	6	6	STUB FLG ELONGATED TYPE SDR 7.4 PE-RT POLYETHYLENE C/W BACKING RING PE SOUR WATER ASTM-D3350 / ISO 4427	0	0		
110	U04		FLANGE	9004175	18	20	STUB FLG ELONGATED TYPE SDR 7.4 PE-RT POLYETHYLENE C/W BACKING RING PE SOUR WATER ASTM-D3350 / ISO 4427	0	0		
120	U04		BLIND	9004176	18	20	FLG BLIND FF 150# PE-RT POLYETHYLENE SOUR WATER ASTM-D3350 / ISO 4427 WITH STEEL INSERT	0	0		
130	U04						***** GASKETS *****				
140	U04		GASKET	5664201	6	6	GASKET 150# RF FLAT RING PTFE	0	0		
150	U04		GASKET	5664201	18	20	GASKET 150# RF FLAT RING PTFE	0	0		
160	U04						***** BOLTING *****				
170	U04	B1	BOLTING	5675768	6	6	STUD-BOLT A320 GR L7M/A194 GR 7M (S3) W/ 2 NUTS + LTCS WASHERS	0	0		
180	U04	B1	BOLTING	5675768	18	20	STUD-BOLT A320 GR L7M/A194 GR 7M (S3) W/ 2 NUTS + LTCS WASHERS	0	0		
190	U04						*****BOLTING BELOW GROUND*****				
200	U04		BOLTING	9004177	18	20	STUD-BOLT A320 GR L7M/A194 GR 7M NUTS + LTCS WASHERS PTFE COATED	0	0		
210											

	TENGIZCHEVROIL TCO TENGIZ, KAZAKHSTAN	CONSTRUCTION	CORR.ALLOW.	SERVICE	MATERIAL	DATE	BY	REV	SHEET	PIPING LINE CLASS
		ALL SIZES - BUTT FUSION SEAL WELDING - NONE PIPE BENDS - NONE THREAD SEALANT - NONE ELECTRIC SOCKET WELDING OR BUTT WELDING AS APPLICABLE	CORR. ALLOW. 0 MM	DESIGN: DESIGN PRESSURE RANGE AS PER PIM-SU-5112-TCO CODE - SHALL BE ADVISED BY TCO SME FLUID CODES - PIM-SU-5112-TCO	MATERIAL: HDPE PERT TYPE 2 SDR 7.4 ID COLOR: RED FLANGE RATING: 150 RF TEMPERATURE RANGE: -40 / 75 °C	12/16/2024	BY OZAC	U04	Page 1 of 1	150PE7