

SEQ NO	REV	NOTE NO.	ITEM NAME	ITEM CODE	SIZE RANGE / SMALL END SIZES		DESCRIPTION	REFERENCE / LARGE END SIZES		NOTES	
10							*****VALVES*****			814	NIPPLE TO BE CUT FROM SS SCH 160 PE PIPE.
20										816	COMPACT FLANGES CAN BE USED FOR TIE-IN PURPOSE ONLY TO EXISTING PIPING AND EQUIPMENT.
20							***** MODULAR VALVES *****				
30										817	USE ONLY FOR TIE IN
30		VA5	MODULAR DBB	K25RL10	0.5	2	MODULAR VALVE DB&B BALL TYPE 2500# RTJ INCONEL 625 BODY AND TRIM METAL LO - FULL SIZE TYPE 2BV	0	0	B1	ALL BOLTS ARE METRIC DIA.
40			MODULAR DBB	K25RL16	2	2	MODULAR VALVE DB&B BALL TYPE 2500# RTJ INCONEL 625 BODY AND TRIM METAL GO - FULL SIZE TYPE 2BV	0	0	B2	7/8" X 145MM BOLTS ONLY TO BE USED FOR 1 INCH 1500# PERAR BALL VALVES ITEM CODE B15AM10
50		VAV, 817	MODULAR DBB	K25CL16	3	3	MODULAR VALVE DB&B BALL TYPE 2500# CF INCONEL 625 BODY AND TRIM METAL GO - FULL SIZE TYPE 2BV	0	0		
60	U04	VAW	MODULAR DBB	M25RL10	0.75	2	MODULAR VALVE DB&B BALL TYPE 2500# RTJ INCONEL 625 BODY AND TRIM METAL LO - CONTROLLED BORE TYPE R2BVR	0	0	BA4	TO BE USED WITH COMPACT FLANGES REQUIRING STANDARD NUTS ONLY.
70			MODULAR DBB	M25RL16	2	2	MODULAR VALVE DB&B BALL TYPE 2500# RTJ INCONEL 625 BODY AND TRIM METAL GO - CONTROLLED BORE TYPE R2BVR	0	0	FA8	USE THREADED FLANGES FOR INSTRUMENT CONNECTIONS ONLY.
80	U04	VAW	MODULAR DBB	M25HL10	0.75	1	MODULAR VALVE DB&B BALL TYPE 2500# RTJ INC 625 INC TRIM 625 METAL LO REDUCING - CONTROLLED BORE TYPE R2BVR	2	2	UJ2	USE 1 1/2IN WITH THERMOWELL CONNECTIONS ONLY & 3/4IN (IF SHOWN) FOR DBB PRESSURE CONNECTIONS WITH CHEMICAL SEALS.
90	U04	VAW	MODULAR DBB	M25HL10	2	2	MODULAR VALVE DB&B BALL TYPE 2500# RTJ INC 625 INC TRIM 625 METAL LO REDUCING - CONTROLLED BORE TYPE R2BVR	3	3	VA5	USE THESE VALVES ONLY WHERE SPECIFIED ON PIPING AND INSTRUMENT DIAGRAMS
100	U04	VAU, 817	MODULAR DBB	M25YL10	1	1	MODULAR VALVE DB&B BALL TYPE 2500# CF x RTJ INC 625 INC TRIM 625 METAL LO REDUCING - CONTROLLED BORE TYPE R2BVR	3	3	VAU	COMPACT FLANGE AT LARGE END RING TYPE JOINT AT SMALL END
110	U04	VAV, 817	MODULAR DBB	K25NL16	3	3	MODULAR VALVE DB&B BALL TYPE 2500# CF X RTJ INCONEL 625 BODY AND TRIM METAL GO - FULL SIZE TYPE 2BV	0	0	VAV	USAGE IS LIMITED TO INSTRUMENT ISOLATION PURPOSE.
120							***** BALL VALVES *****			VAW	VALVE ONLY TO BE USED IN ACCORDANCE WITH DOCUMENT L-ST-2055 - VENT DRAIN AND INSTRUMENT CONNECTION DETAILS.
120		VB2									
130											
130			BALL	A25RL15	2	2	BALL 2500# RTJ INCONEL 625 BODY AND TRIM TRUNNION SOFT RB GO	0	0		
140	U04	817	BALL	A25CL15	3	3	BALL 2500# CF INCONEL 625 BODY AND TRIM TRUNNION SOFT RB GO	0	0		
150	U04		BALL	B25RL09	0.75	1.5	BALL 2500# RTJ INCONEL 625 BODY AND TRIM FLOATING SOFT FB LO	0	0	VB2	SOFT SEATED BALL VALVES ARE LIMITED TO MAXIMUM TEMPERATURE OF 200°C.
160		VA5	BALL	B25RL15	2	3	BALL 2500# RTJ INCONEL 625 BODY AND TRIM TRUNNION SOFT FB GO	0	0		
170	U04	817	BALL	B25CL15	3	3	BALL 2500# CF INCONEL 625 BODY AND TRIM TRUNNION SOFT FB GO	0	0	VC1	SPRING PISTON CHECK VALVES ARE PREFERED IN THE HORIZONTAL POSITION, BUT MAY BE USED IN THE VERTICAL POSITION WITH ENGINEERING APPROVAL.
180							***** GLOBE VALVES *****				
180											
190											
190			GLOBE	L25RL43	0.75	2	GLOBE 2500# RTJ INC 625 B564 INC 625 TRIM OS&Y HW	0	0		
200	U04	817	GLOBE	L25CL44	3	3	GLOBE 2500# CF INC 625 B564 INC 625 TRIM OS&Y GO	0	0		
210							***** CHECK VALVES *****				
210											
220											
220		VC1	CHECK	C25RL51	0.75	1.5	CHECK PISTON 2500# RTJ INC 625 TRIM 625	0	0		
230	U04		CHECK	C25RL53	2	2	CHECK DUAL 2500# RTJ INC 625 TRIM 625	0	0		
240	U04	817	CHECK	C25CL53	3	3	CHECK DUAL DBL FLG 2500# CF INC 625 TRIM 625	0	0		
250							***** PIPE *****				
250											
260											
260			PIPE	5362274	0.75	1.5	PIPE SCH 80S SMLS ALLOY 625 B444 UNS N06625 PE	0	0		
270			PIPE	5362284	2	4	PIPE SCH 80S SMLS ALLOY 625 B444 UNS N06625 BE	0	0		
280		814	PIPE	5362289	0.75	0.75	PIPE SCH 160 SMLS ALLOY 625 B444 UNS N06625 BE	0	0		
290	U04		PIPE	5362287	4	6	PIPE SCH 120 SMLS ALLOY 625 B444 UNS N06625 BE	0	0		
300							***** FITTINGS *****				
300											
310											
310			ELBOW	5426552	0.75	3	ELL BW 90 DEG LR SCH 80S ALLOY 625 B366-WPS UNS N06625	0	0		
320			ELBOW	5426557	0.75	3	ELL BW 45 DEG LR SCH 80S ALLOY 625 B366-WPS UNS N06625	0	0		
330											
330			TEE	5426560	0.75	3	TEE BW SCH 80S ALLOY 625 B366-WPS UNS N06625	0	0		
340			TEE RED	5426559	0.75	2	TEE RED SCH 80S ALLOY 625 B366-WPS UNS N06625	1	3		
350											
350			CAP	5426561	0.75	3	CAP SCH 80S ALLOY 625 B366 UNS N06625	0	0		
360											
360			RED CONC	5426562	0.75	3	REDUCER CONC SCH 80S ALLOY 625 B366-WPS N06625	1	4		
370	U04		RED CONC	5426590	3	3	REDUCER CONC SCH 120/SCH 80S ALLOY 625 B366-WPS N06625	6	6		
380			RED ECC	5426563	0.75	3	REDUCER ECC SCH 80S ALLOY 625 B366-WPS N06625	1	4		
390	U04		RED ECC	5426591	3	3	REDUCER ECC SCH 120/SCH 80S ALLOY 625 B366-WPS N06625	6	6		
400							***** OLETS*****				
400											
410											
410			OLETS	5513887	0.75	1.5	NIPOFLANGE 2500# RTJ WT SCH 80S ALLOY 625 B564 UNS N06625	2	3		
420		UJ2	OLETS	5513888	1.5	1.5	NIPOFLANGE 2500# RTJ WT SCH 80S/160 ALLOY 625 B564 UNS N06625	3	4		
430											
430			OLETS	5513557	0.75	1.5	WELDOLET SCH 80S ALLOY 625 B564 UNS N06625	2	3		
440											
440		816					***** FLANGES *****				
450											

	TENGIZCHEVROIL TCO TENGIZ, KAZAKHSTAN	CONSTRUCTION	CORR.ALLOW.	SERVICE	MATERIAL	DATE	BY	REV	SHEET	PIPING LINE CLASS
		ALL SIZES - BUTT WELD	CORR. ALLOW. 1 MM	SOUR SERVICE - NACE MR0175/ ISO 15156 DESIGN: ASME B16.5 MG 3.8 CODE: ASME B31.3 FLUID CODES - PIM-SU-5112-TCO	MATERIAL: ALLOY 625 FLANGE RATING: 2500 RF/CF TEMPERATURE RANGE: -100 / 180 °C	12/16/2024	BY OZAC	U04	Page 1 of 2	2500A60

SEQ NO	REV	NOTE NO.	ITEM NAME	ITEM CODE	SIZE RANGE / SMALL END SIZES		DESCRIPTION	REFERENCE / LARGE END SIZES		NOTES
450		FA8	TEE RED	5599725	0.5	0.75	FLG SCRDR (FNPT) REDUCING 2500# RTJ ALLOY 625 B564 UNS N06625	0.75	1.5	
460										
460			FLANGE	5851212	0.75	0.75	FLANGE ADAPTER RTJ 2500# ALLOY 625 B564 UNS N06625 X 12 MM TUBE	0	0	
470			FLANGE	5851212	2	2	FLANGE ADAPTER RTJ 2500# ALLOY 625 B564 UNS N06625 X 12 MM TUBE	0	0	
480										
480			FLANGE	5619951	0.75	2	FLG WN 2500# RTJ ALLOY 625 SCH 80S B564 UNS N06625	0	0	
490	U04	817	FLANGE	5619950	3	3	FLG COMPACT 2500# RJ ALLOY 625 SCH 80S B564 UNS N06625	0	0	
500			BLIND	5619735	0.75	2	FLG BLIND 2500# RTJ ALLOY 625 B564 UNS N06625	0	0	
510	U04	817	BLIND	5619790	3	3	FLG COMPACT BLIND 2500# RJ ALLOY 625 B564 UNS N06625 PIPE CLASS 2500A60	0	0	
520	U04	817	FLANGE	5619953	6	6	FLG COMPACT 2500# RJ ALLOY 625 SCH 120 B564 UNS N06625 LINE CLASS 2500A60	0	0	
530										
530							***** PIPE NIPPLES *****			
540										
540		814		0			NIPPLES BBE TO BE CUT FROM PIPE			
550										
550							***** GASKETS *****			
560										
560			GASKET	5674460	0.5	2	GASKET 2500# ALLOY INC 625 OCTAGONAL RING	0	0	
570	U04	817	GASKET	5673500	3	3	GASKET 2500# RJ INC 718 ENERGIZED SEALRING COMPACT FLANGE LINE CLASS 2500A60	0	0	
580	U04	817	GASKET	5673500	6	6	GASKET 2500# RJ INC 718 ENERGIZED SEALRING COMPACT FLANGE LINE CLASS 2500A60	0	0	
590										
590		B1					***** BOLTING *****			
600										
600			BOLTING	5675770	0.5	99	STUD-BOLT A320 GR L7M/A194 GR 7M (S3) WITH 2 NUTS	0	0	
610		BA4	BOLTING	5675776	0.5	3	STUD-BOLT WITH 2 NUTS API-6A718	0	0	
620										
620							***** LINE BLANKS *****			
630										
630			SPEC BLIND	5750416	0.75	2	SPECTACLE BLIND 2500# RTJ ALLOY 625 B443 UNS N06625	0	0	
640	U04	817	SPEC BLIND	5750415	3	3	SPECTACLE BLIND COMPACT 2500# RJ ALLOY 625 B443 UNS N06625	0	0	
650			SPEC BLIND	5750315	0.75	3	SPECTACLE BLIND 2500# RF ALLOY 625 B443 UNS N06625	0	0	
660										
660	U04	817	PADDLE	5407810	3	3	PADDLE BLANK COMPACT 2500# RJ ALLOY 625 B443 UNS N06625	0	0	
670	U04	817	PADDLE	5407809	3	3	PADDLE SPACER COMPACT 2500# RJ ALLOY 625 B443 UNS N06625	0	0	
680										

	TENGIZCHEVROIL TCO TENGIZ, KAZAKHSTAN	CONSTRUCTION	CORR.ALLOW.	SERVICE	MATERIAL	DATE	BY	REV	SHEET	PIPING LINE CLASS
		ALL SIZES - BUTT WELD	CORR. ALLOW. 1 MM	SOUR SERVICE - NACE MR0175/ ISO 15156 DESIGN: ASME B16.5 MG 3.8 CODE: ASME B31.3 FLUID CODES - PIM-SU-5112-TCO	MATERIAL: ALLOY 625 FLANGE RATING: 2500 RF/CF TEMPERATURE RANGE: -100 / 180 °C	12/16/2024	BY OZAC	U04	Page 2 of 2	2500A60