

SEQ NO	REV	NOTE NO.	ITEM NAME	ITEM CODE	SIZE RANGE / SMALL END SIZES		DESCRIPTION	REFERENCE / LARGE END SIZES		NOTES	
10							***** MODULAR VALVES *****			810	NIPPLE TO BE CUT FROM SCH 160 PIPE.
20										815	TO BE USED WITH COMPACT FLANGES ONLY.
20	U04		MODULAR DBB	K06AC02	0.5	1.5	MODULAR VALVE DB&B BALL TYPE 600# RF LTCS A350 LF2 CL.1 316 SS TRIM METAL LO - FULL SIZE TYPE 2BV	0	0	816	COMPACT FLANGES CAN BE USED FOR TIE-IN PURPOSE ONLY TO EXISTING PIPING AND EQUIPMENT.
30	U04		MODULAR DBB	K06AC06	2	2	MODULAR VALVE DB&B BALL TYPE 600# RF LTCS A350 LF2 CL.1 316 SS TRIM METAL LO - FULL SIZE TYPE 2BV	0	0	817	USE ONLY FOR TIE IN
40	U04	VAV	MODULAR DBB	K06AC06	3	3	MODULAR VALVE DB&B BALL TYPE 600# RF LTCS A350 LF2 CL.1 316 SS TRIM METAL LO - FULL SIZE TYPE 2BV	0	0	B2	7/8" X 145MM BOLTS ONLY TO BE USED FOR 1 INCH 1500# PERAR BALL VALVES ITEM CODE B15AM10
50	U04		MODULAR DBB	M06AC02	0.5	1.5	MODULAR VALVE DB&B BALL TYPE 600# RF LTCS A350 LF2 CL.1 316 SS TRIM METAL LO - CONTROLLED BORE TYPE 2BVR	0	0	B6	7/8" X 145MM BOLTS ONLY TO BE USED FOR 1 INCH 1500# PERAR BALL VALVES ITEM CODE B15AS22
60	U04		MODULAR DBB	M06AC06	2	2	MODULAR VALVE DB&B BALL TYPE 600# RF LTCS A350 LF2 CL.1 316 SS TRIM METAL LO - CONTROLLED BORE TYPE 2BVR	0	0	BA6	FOR TURN AROUND TIE-INS ONLY
70	U04	VAW	MODULAR DBB	M06EC02	0.75	1	MODULAR VALVE DB&B BALL TYPE 600# RF LTCS A350 LF2 CL.1 316 SS TRIM METAL LO REDUCING - CONTROLLED BORE TYPE 2BVR	2	2	FA8	USE THREADED FLANGES FOR INSTRUMENT CONNECTIONS ONLY.
80	U04	VAW	MODULAR DBB	M06EC02	2	2	MODULAR VALVE DB&B BALL TYPE 600# RF LTCS A350 LF2 CL.1 316 SS TRIM METAL LO REDUCING - CONTROLLED BORE TYPE 2BVR	3	3	FF5	FLAT BOTTOM NIPOFLANGES FOR USE ON WELD CAPS AND BLIND FLANGES
90	U04	VAQ	MODULAR DBB	MC5C1	1	1	MODULAR VALVE DB&B BALL TYPE 600# RF LTCS A350 LF2 CL.1 316 SS TRIM	0	0	GA5	USE THIS GASKET ONLY WHERE STAINLESS STEEL MATING GASKET IS REQUIRED
100	U04	VAW	MODULAR DBB	M06EC02L	0.75	1	MODULAR VALVE DB&B BALL TYPE 600# RF LTCS A350 LF2 CL.1 316 SS TRIM METAL LO REDUCING - CONTROLLED BORE TYPE 2BVR	2	2	GA6	SPECIAL GASKET ONLY FOR USE AS SPECIFIED IN ENG-200-117
110	U04	VAW	MODULAR DBB	M06EC02L	2	2	MODULAR VALVE DB&B BALL TYPE 600# RF LTCS A350 LF2 CL.1 316 SS TRIM METAL LO REDUCING - CONTROLLED BORE TYPE 2BVR	3	3	SB6	USE JACKSCREWS FOR PADDLE BLANKS/SPACERS AND FLANGE SPREADERS FOR SPECTACLE BLINDS.
120		VB2					***** BALL VALVES *****			UD7	USE THREDOLET AND SCREWED PLUG FOR HYDROSTATIC TEST VENTS AND DRAINS. SEAL WELD AFTER HYDROSTATIC TEST
130											
130	U04		BALL	A06AC05	2	4	BALL 600# RF LTCS A350 LF2 CL.1 316SS TRIM TRUNNION SOFT RB LO	0	0		
140	U04		BALL	A06AC06	2	4	BALL 600# RF LTCS A350 LF2 CL.1 316SS TRIM TRUNNION METAL RB LO	0	0		
150	U04		BALL	A06AC07	6	8	BALL 600# RF LTCS A350 LF2 CL.1 316SS TRIM TRUNNION SOFT RB GO	0	0		
160	U04		BALL	A06AC08	6	8	BALL 600# RF LTCS A350 LF2 CL.1 316SS TRIM TRUNNION METAL RB GO	0	0	UJ2	USE 1 1/2IN WITH THERMOWELL CONNECTIONS ONLY & 3/4IN (IF SHOWN) FOR DBB PRESSURE CONNECTIONS WITH CHEMICAL SEALS.
170	U04		BALL	B06AC01	0.75	1.5	BALL 600# RF LTCS A350 LF2 CL.1 316SS TRIM FLOATING SOFT FB LO	0	0		
180	U04		BALL	B06AC02	0.75	1.5	BALL 600# RF LTCS A350 LF2 CL.1 316SS TRIM FLOATING METAL FB LO	0	0		
190	U04	VA5	BALL	B06AC05	2	4	BALL 600# RF LTCS A350 LF2 CL.1 316SS TRIM TRUNNION SOFT FB LO	0	0		
200	U04	VA5	BALL	B06AC06	2	4	BALL 600# RF LTCS A350 LF2 CL.1 316SS TRIM TRUNNION METAL FB LO	0	0	UJ3	USE 3IN WITH THERMOWELL CONNECTIONS ONLY
210	U04	VA5	BALL	B06AC07	4	24	BALL 600# RF LTCS A350 LF2 CL.1 316SS TRIM TRUNNION SOFT FB GO	0	0		
220	U04	VA5	BALL	B06AC08	4	24	BALL 600# RF LTCS A350 LF2 CL.1 316SS TRIM TRUNNION METAL FB GO	0	0	UJ4	FOR 2 INCH THERMOWELL CONNECTIONS ONLY
230	U04	817	BALL	B06CC07	30	30	BALL 600# CF LTCS A350 LF2 CL.1 316SS TRIM TRUNNION SOFT FB GO	0	0		
240	U04	817	BALL	B06CC08	30	30	BALL 600# CF LTCS A350 LF2 CL.1 316SS TRIM TRUNNION METAL FB GO	0	0	UK9	DO NOT USE FOR ORIFICE FLANGE TAP ASSEMBLIES.
250							***** RISING STEM BALL VALVES *****			VA5	USE THESE VALVES ONLY WHERE SPECIFIED ON PIPING AND INSTRUMENT DIAGRAMS
250											
260		VA5	BALL	R06AC06	0.75	6	BALL RISING STEM 600# RF LTCS A352 LCC 316SS TRIM METAL RB HO	0	0	VAQ	FOR TURN AROUND TIE-INS ONLY
260		VA5	BALL	R06AC08	8	10	BALL RISING STEM 600# RF LTCS A352 LCC 316SS TRIM METAL RB GO	0	0	VAV	USAGE IS LIMITED TO INSTRUMENT ISOLATION PURPOSE.
270							***** BUTTERFLY VALVES *****			VAV	VALVE ONLY TO BE USED IN ACCORDANCE WITH DOCUMENT L-ST-2055 - VENT DRAIN AND INSTRUMENT CONNECTION DETAILS.
280											
280											
290											
290			BUTTERFLY	T06AC61	8	24	BUTTERFLY 600# RF LTCS A352 LCC 316SS TRIM TOV METAL DBL FLG SHORT PAT GO	0	0		
300	U04	817	BUTTERFLY	T06CC61	30	30	BUTTERFLY 600# CF LTCS A352 LCC 316SS TRIM TOV METAL DBL FLG SHORT PAT GO	0	0	VB2	SOFT SEATED BALL VALVES ARE LIMITED TO MAXIMUM TEMPERATURE OF 200°C.
310							***** GATE VALVES *****			VC1	SPRING PISTON CHECK VALVES ARE PREFERED IN THE HORIZONTAL POSITION, BUT MAY BE USED IN THE VERTICAL POSITION WITH ENGINEERING APPROVAL.
310											
320											
320	U04		GATE	G06AC48	0.75	1.5	GATE 600# RF LTCS A350 LF2 CL.1 TRIM 16 WEDGE HW	0	0		
330	U04		GATE	G06AC41	2	6	GATE 600# RF LTCS A352 LCC TRIM 16 WEDGE HW	0	0		
340			GATE	G06AC42	6	24	GATE 600# RF LTCS A352 LCC TRIM 16 WEDGE GO	0	0		
350	U04		GATE	W06AC71	18	18	GATE 600# RF LTCS A352 LCC 316 SS TRIM THROUGH COND SOLID SLAB GO	0	0		
360	U04		GATE	W06AC71	24	24	GATE 600# RF LTCS A352 LCC 316 SS TRIM THROUGH COND SOLID SLAB GO	0	0		
370	U04		GATE	W06AC70	4	4	GATE 600# RF LTCS A352 LCC 316 SS TRIM THROUGH COND SOLID SLAB HW	0	0		
380							***** GLOBE VALVES *****				
380											
390											
390	U04		GLOBE	L06AC48	0.75	1.5	GLOBE 600# RF LTCS A350 LF2 CL.1 TRIM 16 OS&Y HW	0	0		
400			GLOBE	L06AC41	2	4	GLOBE 600# RF LTCS A352 LCC TRIM 16 OS&Y HW	0	0		
410			GLOBE	L06AC42	6	10	GLOBE 600# RF LTCS A352 LCC TRIM 16 OS&Y GO	0	0		
420							***** CHECK VALVES *****				
420											
430											
430	U04	VC1	CHECK	C06AC50	0.75	1.5	CHECK PISTON 600# RF LTCS A350 LF2 CL.1 TRIM 16	0	0		
440	U04		CHECK	C06AC45	2	8	CHECK DUAL WAFER LUG 600# RF LTCS A352 LCC TRIM 16 THROU BOLTED	0	0		
450	U04		CHECK	C06AC52	10	24	CHECK DUAL DBL FLG 600# RF LTCS A352 LCC TRIM 16	0	0		
460	U04	817	CHECK	C06CC52	30	30	CHECK DUAL DBL FLG 600# CF LTCS A352 LCC TRIM 16	0	0		
470							***** PIPE *****				
470											
480											
480	U04		PIPE	5358508	0.5	1.5	PIPE SCH XS SMLS LTCS A333 GR.6 PE	0	0		
490			PIPE	5358514	2	2	PIPE SCH XS SMLS LTCS A333 GR.6 BE	0	0		

	TENGIZCHEVROIL TCO TENGIZ, KAZAKHSTAN	CONSTRUCTION	CORR.ALLOW.	SERVICE	MATERIAL	DATE	BY	REV	SHEET	PIPING LINE CLASS
		ALL SIZES - BUTT WELD PWHT FOR WT >19 MM SEAL WELDING - FOR THREADED CONNECTIONS ONLY PIPE BENDS - NONE THREAD SEALANT - PTFE PASTE	CORR. ALLOW: 1.5 MM	SOUR SERVICE - NACE MR0175/ ISO 15156 DESIGN: ASME B16.5 MG 1.1 CODE: ASME B31.3 FLUID CODES - PIM-SU-5112-TCO	MATERIAL: LTCS FLANGE RATING: 600 RF TEMPERATURE RANGE: -40 / 343 °C	12/16/2024	BY OZAC	U04	Page 1 of 4	600H21

SEQ NO	REV	NOTE NO.	ITEM NAME	ITEM CODE	SIZE RANGE / SMALL END SIZES		DESCRIPTION	REFERENCE / LARGE END SIZES		NOTES
500			PIPE	5358514	4	8	PIPE SCH XS SMLS LTCS A333 GR.6 BE	0	0	
510	U04	UK9	PIPE	5358511	0.5	0.75	PIPE SCH XXS SMLS LTCS A333 GR.6 PE	0	0	
520			PIPE	5358505	3	3	PIPE SCH STD SMLS LTCS A333 GR.6 BE	0	0	
530			PIPE	5358507	10	16	PIPE SCH 80 SMLS LTCS A333 GR.6 BE	0	0	
540			PIPE	5358599	18	24	PIPE SCH 80 EFW LTCS A671 CC60 CL.22 BE	0	0	
550			PIPE	5358616	30	30	PIPE WT 34.0MM EFW LTCS A671 CC60 CL.22 BE	0	0	
560		810	PIPE	5358512	0.5	0.5	PIPE SCH 160 SMLS LTCS A333 GR.6 PE	0	0	
570		810	PIPE	5358512	0.75	0.75	PIPE SCH 160 SMLS LTCS A333 GR.6 PE	0	0	
580										
580							***** FITTINGS *****			
590										
590	U04		ELBOW	5392600	0.5	2	ELL BW 90 DEG LR SCH XS LTCS A420 WPL6	0	0	
600			ELBOW	5392600	4	8	ELL BW 90 DEG LR SCH XS LTCS A420 WPL6	0	0	
610	U04	UK9	ELBOW	5392815	0.5	0.75	ELL BW 90 DEG LR SCH XXS LTCS A420 WPL6	0	0	
620			ELBOW	5392438	3	3	ELL BW 90 DEG LR SCH STD LTCS A420 WPL6	0	0	
630			ELBOW	5392546	10	16	ELL BW 90 DEG LR SCH 80 LTCS A420 WPL6	0	0	
640			ELBOW	5392387	18	24	ELL BW 90 DEG LR SCH 80 LTCS A420 WPL6-W	0	0	
650			ELBOW	5392606	0.75	2	ELL BW 45 DEG LR SCH XS LTCS A420 WPL6	0	0	
660			ELBOW	5392606	4	8	ELL BW 45 DEG LR SCH XS LTCS A420 WPL6	0	0	
670	U04	UK9	ELBOW	5392831	0.5	0.75	ELL BW 45 DEG LR SCH XXS LTCS A420 WPL6	0	0	
680			ELBOW	5392444	3	3	ELL BW 45 DEG LR SCH STD LTCS A420 WPL6	0	0	
690			ELBOW	5392552	10	16	ELL BW 45 DEG LR SCH 80 LTCS A420 WPL6	0	0	
700			ELBOW	5392391	18	24	ELL 45 DEG SCH 80 LTCS A420 WPL6-W	0	0	
710										
710			TEE	5392609	4	8	TEE BW SCH XS LTCS A420 WPL6	0	0	
720	U04		TEE	5392609	0.5	2	TEE BW SCH XS LTCS A420 WPL6	0	0	
730			TEE	5392447	3	3	TEE BW SCH STD LTCS A420 WPL6	0	0	
740			TEE	5392555	10	16	TEE BW SCH 80 LTCS A420 WPL6	0	0	
750	U04	UK9	TEE	5392879	0.5	0.75	TEE SCH XXS LTCS A420 WPL6	0	0	
760			TEE	5392402	18	24	TEE SCH 80 LTCS A420 WPL6-W	0	0	
770			TEE RED	5392661	0.75	1.5	TEE RED BW SCH XS LTCS A420 WPL6	1	2	
780			TEE RED	5392661	2	2	TEE RED BW SCH XS LTCS A420 WPL6	4	4	
790			TEE RED	5392661	4	6	TEE RED BW SCH XS LTCS A420 WPL6	6	8	
800			TEE RED	5392454	1	2	TEE RED BW SCH STD/XS LTCS A420 WPL6	3	3	
810			TEE RED	5392460	3	3	TEE RED BW SCH XS/STD LTCS A420 WPL6	4	8	
820			TEE RED	5392463	4	8	TEE RED BW SCH 80/XS LTCS A420 WPL6	10	16	
830			TEE RED	5392403	8	8	TEE RED BW SCH 80/XS LTCS A420 WPL6-W	18	24	
840			TEE RED	5392464	10	14	TEE RED BW SCH 80 LTCS A420 WPL6	12	16	
850			TEE RED	5392353	10	20	TEE RED BW SCH 80 LTCS A420 WPL6-W	18	24	
860										
860	U04		CAP	5392610	0.5	2	CAP BW SCH XS LTCS A420 WPL6	0	0	
870			CAP	5392610	4	8	CAP BW SCH XS LTCS A420 WPL6	0	0	
880			CAP	5392448	3	3	CAP BW SCH STD LTCS A420 WPL6	0	0	
890			CAP	5392556	10	24	CAP SCH 80 LTCS STL A420 WPL6	0	0	
900										
900			RED CONC	5392458	0.75	1.5	REDUCER CONC SCH XS LTCS A420 WPL6	1	2	
910			RED CONC	5392458	1.5	2	REDUCER CONC SCH XS LTCS A420 WPL6	4	4	
920			RED CONC	5392458	4	6	REDUCER CONC SCH XS LTCS A420 WPL6	6	8	
930			RED CONC	5392452	1.5	2	REDUCER CONC SCH STD/XS LTCS A420 WPL6	3	3	
940			RED CONC	5392455	3	3	REDUCER CONC SCH XS/STD LTCS A420 WPL6	4	8	
950			RED CONC	5392309	4	8	REDUCER CONC SCH 80/XS LTCS A420 WPL6	10	16	
960			RED CONC	5392557	10	14	REDUCER CONC SCH 80 LTCS A420 WPL6	12	16	
970			RED CONC	5392559	10	20	REDUCER CONC SCH 80 LTCS A420 WPL6-W	18	24	
980	U04		RED CONC	5392419	18	24	REDUCER CONC WT 34.0MM/SCH 80 LTCS A420 WPL6-W	30	30	
990			RED ECC	5392461	0.75	1.5	REDUCER ECC SCH XS LTCS A420 WPL6	1	2	
1000			RED ECC	5392461	1.5	2	REDUCER ECC SCH XS LTCS A420 WPL6	4	4	
1010			RED ECC	5392453	1.5	2	REDUCER ECC SCH STD/XS LTCS A420 WPL6	3	3	
1020			RED ECC	5392456	3	3	REDUCER ECC SCH XS/STD LTCS A420 WPL6	4	8	
1030			RED ECC	5392612	4	6	REDUCER ECC SCH XS LTCS A420 WPL6	6	8	
1040			RED ECC	5392311	4	8	REDUCER ECC SCH 80/XS LTCS A420 WPL6	10	16	
1050			RED ECC	5392558	10	14	REDUCER ECC SCH 80 LTCS A420 WPL6	12	16	
1060			RED ECC	5392313	10	20	REDUCER ECC SCH 80 LTCS A420 WPL6-W	18	24	
1070	U04		RED ECC	5392613	18	24	REDUCER ECC WT 34.0MM/SCH 80 LTCS A420 WPL6-W	30	30	
1080										
1080	U04		OLETS	5504006	0.75	1.5	NIPOFLANGE 600# RF SCH XS LTCS A350 LF2 CL.1	2	2	
1090	U04		OLETS	5504006	0.75	2	NIPOFLANGE 600# RF SCH XS LTCS A350 LF2 CL.1	4	8	
1100	U04		OLETS	5504007	0.75	2	NIPOFLANGE 600# RF SCH STD/XS LTCS A350 LF2 CL.1	3	3	
1110	U04		OLETS	5504026	0.75	2	NIPOFLANGE 600# RF SCH 80/XS LTCS A350 LF2 CL.1	10	24	
1120	U04		OLETS	5504095	0.75	2	NIPOFLANGE 600# RF SCH 34.0MM/XS LTCS A350 LF2 CL.1	30	30	
1130	U04	FF5	OLETS	5504502	0.75	1.5	NIPOFLANGE FLAT BOTTOM 600# RF SCH XS LTCS A350 LF2 CL.1	0	0	
1140	U04	UJ2	OLETS	5504028	1.5	1.5	NIPOFLANGE 600# RF SCH XS/160 LTCS A350 LF2 CL.1	4	8	
1150	U04	UJ2	OLETS	5504029	1.5	1.5	NIPOFLANGE 600# RF SCH 80/160 LTCS A350 LF2 CL.1	10	24	
1160	U04	UJ2	OLETS	5504096	1.5	1.5	NIPOFLANGE 600# RF WT 34.0MM/160 LTCS A350 LF2 CL.1	30	30	

	TENGINZCHEVROIL TCO TENGINZ, KAZAKHSTAN	CONSTRUCTION	CORR.ALLOW.	SERVICE	MATERIAL	DATE	BY	REV	SHEET	PIPING LINE CLASS
		ALL SIZES - BUTT WELD PWHT FOR WT >19 MM SEAL WELDING - FOR THREADED CONNECTIONS ONLY PIPE BENDS - NONE THREAD SEALANT - PTFE PASTE	CORR. ALLOW: 1.5 MM	SOUR SERVICE - NACE MR0175/ ISO 15156 DESIGN: ASME B16.5 MG 1.1 CODE: ASME B31.3 FLUID CODES - PIM-SU-5112-TCO	MATERIAL: LTCS FLANGE RATING: 600 RF TEMPERATURE RANGE: -40 / 343 °C	12/16/2024	BY OZAC	U04	Page 2 of 4	600H21

SEQ NO	REV	NOTE NO.	ITEM NAME	ITEM CODE	SIZE RANGE / SMALL END SIZES		DESCRIPTION	REFERENCE / LARGE END SIZES		NOTES
1170	U04	UJ3	OLETS	5504735	3	3	NIPOFLANGE 600# RF SCH 80/160 LTCS A350 LF2 CL.1	16	16	
1180	U04	UJ4	OLETS	5504736	2	2	NIPOFLANGE 600# RF SCH 80/160 LTCS A350 LF2 CL.1	12	12	
1190	U04	UJ4		5504736	2	2	NIPOFLANGE 600# RF SCH 80/160 LTCS A350 LF2 CL.1	18	18	
1200	U04	UJ4		5503999	2	2	NIPOFLANGE 600# RF SCH XS/160 LTCS A350 LF2 CL.1	4	4	
1210	U04	UJ3	OLETS	5504732	3	3	NIPOFLANGE 600# RF SCH XS/160 LTCS A350 LF2 CL.1	6	6	
1220	U04		OLETS	5504207	0.75	0.75	NIPOFLANGE 600# RTJ SCH STD/XS LTCS A350 LF2 CL.1	3	3	
1230	U04		OLETS	5504206	0.75	0.75	NIPOFLANGE 600# RTJ SCH XS LTCS A350 LF2 CL.1	6	6	
1240	U04		OLETS	5504160	1.5	1.5	NIPOFLANGE 1500# RF SCH XS LTCS A350 LF2 CL.1	6	6	
1250										
1250	U04		OLETS	5505335	0.75	1	WELDOLET SCH XS LTCS A350 LF2 CL.1	2	2	
1260	U04		OLETS	5505179	0.75	1	WELDOLET SCH STD/XS LTCS A350 LF2 CL.1	3	3	
1270	U04		OLETS	5505333	0.75	2	WELDOLET SCH XS LTCS A350 LF2 CL.1	4	8	
1280	U04		OLETS	5505262	0.75	2	WELDOLET SCH 80/XS LTCS A350 LF2 CL.1	10	24	
1290	U04		OLETS	5505262	4	8	WELDOLET SCH 80/XS LTCS A350 LF2 CL.1	10	24	
1300	U04		OLETS	5505334	3	3	WELDOLET SCH XS/STD LTCS A350 LF2 CL.1	8	8	
1310	U04		OLETS	5505274	3	3	WELDOLET SCH 80/STD LTCS A350 LF2 CL.1	10	24	
1320	U04	817	OLETS	9002555	3	3	WELDOLET WT 7.9MM/SCH STD LTCS A694 F65	24	24	
1330										
1330	U04	UJ2	ELBOFLG	5516659	1.5	1.5	ELBOFLANGE 600# RF SCH XS/160 LTCS A350 LF2 CL.1	4	8	
1340	U04	UJ2	ELBOFLG	5516660	1.5	1.5	ELBOFLANGE 600# RF SCH 80/160 LTCS A350 LF2 CL.1	10	24	
1350	U04	UJ2	ELBOFLG	5516655	1.5	1.5	ELBOFLANGE 600# RF WT 34.0MM/160 LTCS A350 LF2 CL.1	30	30	
1360										
1360	U04		OLETS	5533072	0.75	1.5	SOCKOLET 3000# LTCS A350 LF2 CL.1	2	24	
1370										
1370	U04	UD7	OLETS	5514772	0.75	0.75	THREDOLET 3000# LTCS A350 LF2 CL.1	2	24	
1380										
1380							***** COUPLINGS, UNIONS & PLUGS *****			
1390										
1390			COUPLING	5478705	0.75	1.5	COUPLING 3000# SW LTCS A 350 LF2	0	0	
1400	U04		TEE RED	5478709	0.75	1	COUPLING RED 3000# SW LTCS A350 LF2 CL.1	1	1.5	
1410										
1410	U04		UNION	5478706	0.75	1.5	UNION 3000# SW LTCS A350 LF2 CL.1	0	0	
1420										
1420	U04	UD7	FITTING SCRD	5491303	0.75	0.75	PLUG ROUND HEAD SCRD LTCS A350 LF2 CL.1	0	0	
1430										
1430		816					***** FLANGES *****			
1440										
1440	U04	FA8	TEE RED	5599705	0.5	0.5	FLG SCRD (FNPT) REDUCING 600# RF A350 LF2 CL.1	0.75	1.5	
1450										
1450			FLANGE	5851204	0.5	2	FLANGE ADAPTER 600# RF 316 SS X 12 MM TUBE	0	0	
1460	U04		FLG ADAPTER	5851224	0.5	2	FLANGE ADAPTER 600# RF 316 SS X 6 MM TUBE	0	0	
1470										
1470	U04		FLANGE	5557036	0.5	2	FLG WN 600# RF LTCS A350 LF2 CL.1 SCH XS	0	0	
1480	U04		FLANGE	5557036	4	8	FLG WN 600# RF LTCS A350 LF2 CL.1 SCH XS	0	0	
1490	U04		FLANGE	5557033	3	3	FLG WN 600# RF LTCS A350 LF2 CL.1 SCH STD	0	0	
1500	U04		FLANGE	5557040	10	24	FLG WN 600# RF LTCS A350 LF2 CL.1 SCH 80	0	0	
1510	U04		FLANGE	5556545	30	30	FLG WN 600# RF LTCS A350 LF2 CL.1 WT 34.0MM B16.47 SERIES A	0	0	
1520	U04		FLANGE	5555935	3	3	FLG WN 900# RF LTCS A350 LF2 CL.1 SCH STD	0	0	
1530	U04		FLANGE	5557141	4	8	FLG WN 900# RF LTCS A350 LF2 CL.1 SCH XS	0	0	
1540	U04		FLANGE	5557393	0.75	2	FLG WN 1500# RF LTCS A350 LF2 CL.1 SCH XS	0	0	
1550	U04	817	FLANGE	5558036	1	1	FLG WN 600# RTJ LTCS A350 LF2 CL.1 SCH XS	0	0	
1560	U04	817	FLANGE	5558036	4	4	FLG WN 600# RTJ LTCS A350 LF2 CL.1 SCH XS	0	0	
1570	U04	817	FLANGE	5558036	2	2	FLG WN 600# RTJ LTCS A350 LF2 CL.1 SCH XS	0	0	
1580	U04	817	FLANGE	5558040	20	24	FLG WN 600# RTJ LTCS A350 LF2 CL.1 SCH 80	0	0	
1590	U04	817	FLANGE	5558033	3	3	FLG WN 600# RTJ LTCS A350 LF2 CL.1 SCH STD	0	0	
1600	U04		FLANGE	5557147	10	10	FLG WN 900# RF LTCS A350 LF2 CL.1 SCH 80	0	0	
1610	U04		FLANGE	5555933	2	2	FLG WN 900# RF LTCS A350 LF2 CL.1 SCH XS	0	0	
1620	U04	817	FLANGE	9001632	3	3	FLG WN 600# RF LTCS A694 F65 SCH STD	0	0	
1630	U04	817	FLANGE	5619845	30	30	FLG COMPACT 600# RJ LTCS A350 LF2 CL.1 WT 34.0MM	0	0	
1640	U04	817	FLANGE	5557704	1	2	FLG WN 2500# RTJ LTCS A350 LF2 CL.1 SCH XS	0	0	
1650	U04		BLIND	5615598	0.5	24	FLG BLIND 600# RF LTCS A350 LF2 CL.1	0	0	
1660	U04		BLIND	5615580	30	30	FLG BLIND 600# RF LTCS A350 LF2 CL.1 B16.47 SERIES A	0	0	
1670	U04	817	BLIND	5615698	0.5	0.5	FLG BLIND 600# RTJ LTCS A350 LF2 CL.1	0	0	
1680	U04	817	BLIND	5615698	2	2	FLG BLIND 600# RTJ LTCS A350 LF2 CL.1	0	0	
1690	U04	817	BLIND	5615698	24	24	FLG BLIND 600# RTJ LTCS A350 LF2 CL.1	0	0	
1700	U04		BLIND	5615605	2	10	FLG BLIND 900# RF LTCS A350 LF2 CL.1	0	0	
1710	U04		BLIND	5615616	2	2	FLG BLIND 1500# RF LTCS A350 LF2 CL.1	0	0	
1720	U04	817	BLIND	5619756	4	4	FLG COMPACT BLIND 10000# RJ 2-1/4CR F22M LINE CLASS 10000F22 FOR NPS 4 INCH & ABOVE	0	0	
1730	U04	817	BLIND	5619760	30	30	FLG COMPACT BLIND 600# RJ LTCS A350 LF2 CL.1	0	0	
1740										
1740							***** ORIFICE FLANGES *****			
1750										
1750	U04		ORIFICE FLG	5624352	2	2	WN ORIF SET 600# RF LTCS A350 LF2 CL.1 SCH XS BORE	0	0	

	TENGIZCHEVROIL TCO TENGIZ, KAZAKHSTAN	CONSTRUCTION	CORR.ALLOW.	SERVICE	MATERIAL	DATE	BY	REV	SHEET	PIPING LINE CLASS
		ALL SIZES - BUTT WELD PWHT FOR WT >19 MM SEAL WELDING - FOR THREADED CONNECTIONS ONLY PIPE BENDS - NONE THREAD SEALANT - PTFE PASTE	CORR. ALLOW: 1.5 MM	SOUR SERVICE - NACE MR0175/ ISO 15156 DESIGN: ASME B16.5 MG 1.1 CODE: ASME B31.3 FLUID CODES - PIM-SU-5112-TCO	MATERIAL: LTCS FLANGE RATING: 600 RF TEMPERATURE RANGE: -40 / 343 °C	12/16/2024	BY OZAC	U04	Page 3 of 4	600H21

SEQ NO	REV	NOTE NO.	ITEM NAME	ITEM CODE	SIZE RANGE / SMALL END SIZES		DESCRIPTION	REFERENCE / LARGE END SIZES		NOTES
1760	U04		ORIFICE FLG	5624352	4	8	WN ORIF SET 600# RF LTCS A350 LF2 CL.1 SCH XS BORE	0	0	
1770	U04		ORIFICE FLG	5624349	3	3	WN ORIF SET 600# RF LTCS A350 LF2 CL.1 STD WT BORE	0	0	
1780	U04		ORIFICE FLG	5624353	10	24	WN ORIF SET 600# RF LTCS A350 LF2 CL.1 SCH 80 BORE	0	0	
1790										
1790							***** PIPE NIPPLES *****			
1800										
1800	U04	810					NIPPLE PBE TO BE CUT FROM PIPE			
1810		810		0			NIPPLE PBE TO BE CUT FROM PIPE			
1820										
1820							***** GASKETS *****			
1830										
1830			GASKET	5673103	0.5	24	GASKET 600# 316SS SPIRAL WOUND GRAPHITE IR	0	0	
1840			GASKET	5674012	30	30	GASKET 600# 316SS KAMMPROFILE GRAPHITE ASME B16.47 SERIES A	0	0	
1850	U04	GA6	GASKET	5673018	2	3	GASKET 600# 316SS KAMMPROFILE GRAPHITE ASME B16.5	0	0	
1860	U04	817	GASKET	5673202	0.5	1	GASKET 600# RTJ SOFT IRON TEFLON COATED OCTAGONAL RING	0	0	
1870	U04	817	GASKET	5673202	2	4	GASKET 600# RTJ SOFT IRON TEFLON COATED OCTAGONAL RING	0	0	
1880	U04	817	GASKET	5673202	20	24	GASKET 600# RTJ SOFT IRON TEFLON COATED OCTAGONAL RING	0	0	
1890	U04	815, 817	GASKET	5673202	2	2	GASKET 600# RTJ SOFT IRON TEFLON COATED OCTAGONAL RING	0	0	
1900	U04	817	GASKET	5673202	20	20	GASKET 600# RTJ SOFT IRON TEFLON COATED OCTAGONAL RING	0	0	
1910	U04	817	GASKET	5673410	30	30	GASKET 600# RJ INC 718 ENERGIZED SEALRING COMPACT FLANGE PIPE CLASS 600H21	0	0	
1920	U04		GASKET	5673117	2	10	GASKET 900# 316SS SPIRAL WOUND GRAPHITE IR	0	0	
1930			GASKET	5674460	1	2	GASKET 2500# ALLOY INC 625 OCTAGONAL RING	0	0	
1940	U04		GASKET	5672251	0.5	2	GASKET 1500# 316SS SPIRAL WOUND GRAPHITE IR	0	0	
1950	U04	GA5, 817	GASKET	5674480	1	1	GASKET 2500# RTJ SS OCTAGONAL RING	0	0	
1960										
1960		B2					***** BOLTING *****			
1970										
1970	U04		BOLTING	5675770	0.5	30	STUD-BOLT A320 GR L7M/A194 GR 7M (S3) WITH 2 NUTS	0	0	
1980	U04	BA6	BOLTING	5675669	0.5	99	STUD-BOLT A320 GR L7M/A194 GR 7M NUTS	0	0	
1990										
1990		SB6	BOLTING	5675675	10	24	JACK SCREW HEX HEAD A320 GR L7M	0	0	
2000										
2000							**** BLINDS & SPACERS ****			
2010										
2010			SPEC BLIND	5749587	0.75	8	SPECTACLE BLIND 600# RF LTCS A516-GR70	0	0	
2020										
2020			PADDLE	5750040	10	24	PADDLE BLANK 600# RF LTCS A516-GR70	0	0	
2030			PADDLE	5750030	30	30	PADDLE BLANK 600# RF LTCS A516 GR70 B16.47 SERIES A	0	0	
2040			PADDLE	5750251	10	24	PADDLE SPACER 600# RF LTCS A516-GR70	0	0	
2050			PADDLE	5750252	30	30	PADDLE SPACER 600# RF LTCS A516 GR70 B16.47 SERIES A	0	0	
2060										
2060	U04	817	SPEC BLIND	5751587	2	2	SPECTACLE BLIND 600# RTJ LTCS A516-GR70	0	0	
2070	U04	817		5751587	4	4	SPECTACLE BLIND 600# RTJ LTCS A516-GR70	0	0	
2080										

	TENGIZCHEVROIL TCO TENGIZ, KAZAKHSTAN	CONSTRUCTION	CORR.ALLOW.	SERVICE	MATERIAL	DATE	BY	REV	SHEET	PIPING LINE CLASS
		ALL SIZES - BUTT WELD PWHT FOR WT >19 MM SEAL WELDING - FOR THREADED CONNECTIONS ONLY PIPE BENDS - NONE THREAD SEALANT - PTFE PASTE	CORR. ALLOW. 1.5 MM	SOUR SERVICE - NACE MR0175/ ISO 15156 DESIGN: ASME B16.5 MG 1.1 CODE: ASME B31.3 FLUID CODES - PIM-SU-5112-TCO	MATERIAL: LTCS FLANGE RATING: 600 RF TEMPERATURE RANGE: -40 / 343 °C	12/16/2024	BY OZAC	U04	Page 4 of 4	600H21