

SEQ NO	REV	NOTE NO.	ITEM NAME	ITEM CODE	SIZE RANGE / SMALL END SIZES		DESCRIPTION	REFERENCE / LARGE END SIZES		NOTES	
10	U04						***** MODULAR VALVES *****			B1 FA8	ALL BOLTS ARE METRIC DIA. USE THREADED FLANGES FOR INSTRUMENT CONNECTIONS ONLY.
20											
20	U04		MODULAR DBB	M06AM10	0.75	1.5	MODULAR VALVE DB&B BALL TYPE 600# RF INC 825 INC 625 TRIM METAL LO - CONTROLLED BORE TYPE 2BVR	0	0		
30											
30	U04						***** BALL VALVES *****				
40											
40	U04		BALL	B06AM10	0.75	1.5	BALL 600# RF 825 INCONEL 625 TRIM FLOATING METAL FB LO	0	0		
50	U04		BALL	A06AM14	2	2	BALL 600# RF 825 INCONEL 625 TRIM TRUNNION METAL RB LO	0	0		
60	U04		BALL	A06AR16	8	8	BALL 600# RF LTCS + CLAD 825 INCONEL 625 TRIM TRUNNION METAL RB GO	0	0		
70											
70	U04						***** THROUGH CONDUIT GATE VALVES *****				
80											
80	U04		GATE	W06AM71	8	16	GATE 600# RF INCONEL 825 N08825 THROUGH COND SOLID SLAB GO	0	0		
90											
90	U04						***** GATE VALVES *****				
100											
100	U04		GATE	G06AM48	0.75	2	GATE 600# RF INCONEL 825 N08825 WEDGE HW	0	0		
110											
110	U04						***** CHECK VALVES *****				
120											
120	U04		CHECK	C06AR46	8	8	CHECK DUAL WAFER LUG 600# RF LTCS + CLAD INC 825 TRIM 625 THROU BOLTED	0	0		
130											
130	U04						***** PIPE *****				
140											
140	U04		PIPE	5361607	0.75	3	PIPE SCH 80S SMLS ALLOY 825 B423 UNS N08825 BE	0	0		
150	U04		PIPE	9002671	6	8	PIPE STD WT SMLS API 5L X60 WITH 3 MM INCONEL 825 INTERNAL CLADDING	0	0		
160	U04		PIPE	9002765	16	16	PIPE SCH XS SMLS API 5L X60 WITH 3 MM INCONEL 825 INTERNAL CLADDING	0	0		
170											
170	U04						***** FITTINGS *****				
180											
180	U04		ELBOW	5425111	0.75	3	ELL 90 DEG LR SCH 80S ALLOY 825 B366-WPS UNS N08825	0	0		
190	U04		ELBOW	9002672	6	8	ELL BW 90 DEG LR STD WT A860 WPHY 60 WITH 3 MM INCONEL 825 INTERNAL CLADDING	0	0		
200	U04		ELBOW	9002699	16	16	ELL BW 90 DEG LR SCH XS WT A860 WPHY 60 WITH 3 MM INCONEL 825 INTERNAL CLADDING	0	0		
210	U04		ELBOW	5425113	0.75	2	ELL 45 DEG SCH 80S ALLOY 825 B366-WPS UNS N08825	0	0		
220	U04		ELBOW	9002673	8	8	ELL BW 45 DEG LR STD WT A860 WPHY 60 WITH 3 MM INCONEL 825 INTERNAL CLADDING	0	0		
230	U04		ELBOW	9006576	16	16	ELL BW 45 DEG LR SCH XS WT A860 WPHY 60 WITH 3 MM INCONEL 825 INTERNAL CLADDING	0	0		
240											
240	U04		TEE	5425119	2	2	TEE SCH 80S ALLOY 825 B366-WPS UNS N08825	0	0		
250	U04		TEE	9002674	8	8	TEE BW STD WT A860 WPHY 60 WITH 3 MM INCONEL 825 INTERNAL CLADDING	0	0		
260	U04		TEE	9002767	16	16	TEE BW SCH XS A860 WPHY 60 WITH 3 MM INCONEL 825 INTERNAL CLADDING	0	0		
270	U04		TEE RED	9002698	6	6	TEE RED BW SCH STD WT A860 WPHY 60 WITH 3 MM INCONEL 825 INTERNAL CLADDING	8	8		
280	U04		TEE RED	9002766	6	8	TEE RED BW SCH XS/STD WT A860 WPHY 60 WITH 3 MM INCONEL 825 INTERNAL CLADDING	16	16		
290											
290	U04		CAP	9002675	8	8	CAP BW STD WT A860 WPHY60 WITH 3 MM INCONEL 825 INTERNAL CLADDING	0	0		
300											
300	U04						***** OLETS *****				
310											
310	U04		OLETS	9002676	0.75	2	NIPOFLANGE 600# RF STD WT/80S INCONEL 825 N08825	8	8		
320	U04		OLETS	9002762	0.75	2	NIPOFLANGE 600# RF SCH XS WT/80S INCONEL 825 N08825	16	16		
330											
330	U04		OLETS	9002677	0.75	2	WELDOLET STD WT/80S INCONEL 825 N08825	8	8		
340	U04		OLETS	9002761	0.75	2	WELDOLET SCH XS/80S INCONEL 825 N08825	16	16		
350											
350	U04						**** FLANGES ****				
360											
360	U04	FA8	FLANGE	5600660	0.5	0.5	FLG SCRD (FNPT) REDUCING 600# RF SS A182 F316/316L	0.75	1.5		
370	U04		FLANGE	5569391	0.75	3	FLG WN 600# RF ALLOY 825 SCH 80S B564 UNS N08825	0	0		
380	U04		FLANGE	9002678	6	8	FLG WN 600# RF STD WT A694 F60 WITH 3MM INCONEL 825 INTERNAL CLAD BORE & FACE	0	0		
390	U04		FLANGE	9002760	16	16	FLG WN 600# RF SCH XS WT A694 F60 WITH 3 MM INCONEL 825 CLAD FACE & BORE	0	0		
400	U04		BLIND	9002682	0.75	16	FLG BLIND 600# RF A694 F60 WITH 3 MM INCONEL 825 CLAD FACE	0	0		
410											
410	U04						***** PIPE NIPPLES *****				
420	U04						***** GASKETS *****				
430											
430	U04		GASKET	5673661	0.75	16	GASKET 600# ALLOY 825 SPIRAL WOUND GRAPHITE IR	0	0		
440											
440	U04						***** BOLTING *****				
450											
450	U04	B1	BOLTING	5675770	0.5	99	STUD-BOLT A320 GR L7M/A194 GR 7M (S3) WITH 2 NUTS	0	0		
460											
460	U04						***** BLINDS AND SPACERS *****				
470											

	TENGIZCHEVROI TCO TENGIZ, KAZAKHSTAN	CONSTRUCTION	CORR.ALLOW.	SERVICE	MATERIAL	DATE	BY	REV	SHEET	PIPING LINE CLASS
		ALL SIZES - BUTT WELD PWHT - SOUR SERVICE ALL WELDS ABOVE GROUND	CORR. ALLOW. 0 MM	SOUR SERVICE - NACE MR0175/ ISO 15156, DESIGN: ASME B16.5 MG 1.1 CODE: ASME B31.8 FLUID CODES - PIM-SU-5112-TCO	MATERIAL: LTCS + CRA FLANGE RATING: 600 RF TEMPERATURE RANGE: -40 / 95 °C	12/16/2024	BY OZAC	U04	Page 1 of 2	600K5G

SEQ NO	REV	NOTE NO.	ITEM NAME	ITEM CODE	SIZE RANGE / SMALL END SIZES	DESCRIPTION	REFERENCE / LARGE END SIZES	NOTES
470 480			SPEC BLIND	5749587_C80	4 8	SPECTACLE BLIND 600# RF LTCS A516-GR70 WITH 3MM INC 825 CLAD FACE & BORE	0 0	

	TENGIZCHEVROIL TCO TENGIZ, KAZAKHSTAN	CONSTRUCTION	CORR.ALLOW.	SERVICE	MATERIAL	DATE	BY	REV	SHEET	PIPING LINE CLASS
		ALL SIZES - BUTT WELD PWHT - SOUR SERVICE ALL WELDS ABOVE GROUND	CORR. ALLOW. 0 MM	SOUR SERVICE - NACE MR0175/ ISO 15156, DESIGN: ASME B16.5 MG 1.1 CODE: ASME B31.8 FLUID CODES - PIM-SU-5112-TCO	MATERIAL: LTCS + CRA FLANGE RATING: 600 RF TEMPERATURE RANGE: -40 / 95 °C	12/16/2024	BY OZAC	U04	Page 2 of 2	600K5G