

SEQ NO	REV	NOTE NO.	ITEM NAME	ITEM CODE	SIZE RANGE / SMALL END SIZES		DESCRIPTION	REFERENCE / LARGE END SIZES		NOTES							
10							***** MODULAR VALVES *****			814	NIPPLE TO BE CUT FROM SS SCH 160 PE PIPE.						
20										817	USE ONLY FOR TIE IN						
20			MODULAR DBB	K06AS02	0.5	1.5	MODULAR VALVE DB&B BALL TYPE 600# RF SS A182 F316 316 SS TRIM METAL LO - FULL SIZE TYPE 2BV	0	0	B1	ALL BOLTS ARE METRIC DIA.						
30		VAV	MODULAR DBB	K06AS06	2	3	MODULAR VALVE DB&B BALL TYPE 600# RF SS A182 F316 316 SS TRIM METAL LO - FULL SIZE TYPE 2BV	0	0	B2	7/8" X 145MM BOLTS ONLY TO BE USED FOR 1						
40			MODULAR DBB	M06AS02	0.5	1.5	MODULAR VALVE DB&B BALL TYPE 600# RF SS A182 F316 316 SS TRIM METAL LO - CONTROLLED BORE TYPE 2BVR	0	0		INCH 1500# PERAR BALL VALVES ITEM CODE B15AM10						
50			MODULAR DBB	M06AS06	2	2	MODULAR VALVE DB&B BALL TYPE 600# RF SS A182 F316 316 SS TRIM METAL LO - CONTROLLED BORE TYPE 2BVR	0	0	BA1	TO BE USED WITH RAISED FACE FLANGES ONLY.						
60		VAW	MODULAR DBB	M06ES02	0.75	2	MODULAR VALVE DB&B BALL TYPE 600# RF SS A182 F316 316 SS TRIM METAL LO REDUCING - CONTROLLED BORE TYPE 2BVR	2	3	BA5	TO BE USED WITH COMPACT FLANGES REQUIRING COMPACT NUTS ONLY. FOR FGP ONLY.						
70							***** BALL VALVES *****			FA8	USE THREADED FLANGES FOR INSTRUMENT CONNECTIONS ONLY.						
70		VB2								FF5	FLAT BOTTOM NIPOFLANGES FOR USE ON WELD CAPS AND BLIND FLANGES						
80										FS1	USE FLANGES, GASKETS & VALVES AS REQUIRED TO MATCH EQUIPMENT OR VESSEL NOZZLES.						
80			BALL	A06AS05	2	4	BALL 600# RF SS A182 F316 316SS TRIM TRUNNION SOFT RB LO	0	0	GA6	SPECIAL GASKET ONLY FOR USE AS SPECIFIED IN ENG-200-117						
90			BALL	A06AS06	2	4	BALL 600# RF SS A182 F316 316SS TRIM TRUNNION METAL RB LO	0	0								
100			BALL	A06AS07	6	8	BALL 600# RF SS A182 F316 316SS TRIM TRUNNION SOFT RB GO	0	0	UJ2	USE 1 1/2IN WITH THERMOWELL CONNECTIONS ONLY & 3/4IN (IF SHOWN) FOR DBB PRESSURE CONNECTIONS WITH CHEMICAL SEALS.						
110			BALL	A06AS08	6	8	BALL 600# RF SS A182 F316 316SS TRIM TRUNNION METAL RB GO	0	0	UJ3	USE 3IN WITH THERMOWELL CONNECTIONS ONLY						
120			BALL	B06AS01	0.75	1.5	BALL 600# RF SS A182 F316 316SS TRIM FLOATING SOFT FB LO	0	0	UJ4	FOR 2 INCH THERMOWELL CONNECTIONS ONLY						
130			BALL	B06AS02	0.75	1.5	BALL 600# RF SS A182 F316 316SS TRIM FLOATING METAL FB LO	0	0	UK9	DO NOT USE FOR ORIFICE FLANGE TAP ASSEMBLIES.						
140		VA5	BALL	B06AS05	2	4	BALL 600# RF SS A182 F316 316SS TRIM TRUNNION SOFT FB LO	0	0	VA5	USE THESE VALVES ONLY WHERE SPECIFIED ON PIPING AND INSTRUMENT DIAGRAMS						
150		VA5	BALL	B06AS06	2	4	BALL 600# RF SS A182 F316 316SS TRIM TRUNNION METAL FB LO	0	0	VAV	USAGE IS LIMITED TO INSTRUMENT ISOLATION PURPOSE.						
160		VA5	BALL	B06AS07	4	24	BALL 600# RF SS A182 F316 316SS TRIM TRUNNION SOFT FB GO	0	0	VAW	VALVE ONLY TO BE USED IN ACCORDANCE WITH DOCUMENT L-ST-2055 - VENT DRAIN AND INSTRUMENT CONNECTION DETAILS.						
170	U04	VA5	BALL	B06AS08	4	24	BALL 600# RF SS A182 F316 316SS TRIM TRUNNION METAL FB GO	0	0	VB2	SOFT SEATED BALL VALVES ARE LIMITED TO MAXIMUM TEMPERATURE OF 200°C.						
180	U04	817	BALL	B06CS07	30	30	BALL 600# CF SS A182 F316 316SS TRIM TRUNNION SOFT FB GO	0	0	VC1	SPRING PISTON CHECK VALVES ARE PREFERED IN THE HORIZONTAL POSITION, BUT MAY BE USED IN THE VERTICAL POSITION WITH ENGINEERING APPROVAL.						
190	U04	817	BALL	B06CS08	30	30	BALL 600# CF SS A182 F316 316SS TRIM TRUNNION METAL FB GO	0	0	VGA	FOR USE IN MAKE-UP WATER ONLY						
200							***** BUTTERFLY VALVES *****										
200																	
210																	
210			BUTTERFLY	T06AS61	10	24	BUTTERFLY 600# RF SS A351 CF8M 316SS TRIM TOV METAL DBL FLG SHORT PAT GO	0	0								
220			BUTTERFLY	T06CS61	30	30	BUTTERFLY 600# CF SS A351 CF8M 316SS TRIM TOV METAL DBL FLG SHORT PAT GO	0	0								
230							*****GLOBE VALVE*****										
230																	
240																	
240			GLOBE	L06AS48	0.75	1.5	GLOBE 600# RF SS A182 F316 TRIM 16 OS&Y HW	0	0								
250			GLOBE	L06AS41	2	4	GLOBE 600# RF SS A351 CF8M TRIM 16 OS&Y HW	0	0								
260			GLOBE	L06AS42	6	10	GLOBE 600# RF SS A351 CF8M TRIM 16 OS&Y GO	0	0								
270							***** CHECK VALVES *****										
270																	
280																	
280		VC1	CHECK	C06AS50	0.75	1.5	CHECK PISTON 600# RF SS A182 F316 TRIM 16	0	0								
290			CHECK	C06AS45	2	8	CHECK DUAL WAFER LUG 600# RF SS A351 CF8M TRIM 16 THROU BOLTED	0	0								
300			CHECK	C06AS52	10	24	CHECK DUAL DBL FLG 600# RF SS A351 CF8M TRIM 16	0	0								
310	U04	817	CHECK	C06CS52	30	30	CHECK DUAL DBL FLG 600# CF SS A351 CF8M TRIM 16	0	0								
320							***** GATE VALVES *****										
320																	
330																	
330		VGA, 817	GATE	G06AS41	2	6	GATE 600# RF SS A351 CF8M TRIM 16 WEDGE HW	0	0								
340	U04	VGA	GATE	G06AS48	0.5	1	GATE 600# RF SS A182 F316 TRIM 16 WEDGE HW	0	0								
350							****PIPE*****										
350																	
360																	
360	U04		PIPE	5365140	0.5	1.5	PIPE SCH 80S SMLS SS A312 TP316/316L PE	0	0								
370	U04	UK9	PIPE	5365202	0.5	0.75	PIPE SCH XXS SMLS SS A312 316/316L SS PE	0	0								
380			PIPE	5365138	2	8	PIPE SCH 80S SMLS SS A312 TP316/316L-S BE	0	0								
390			PIPE	5365139	10	24	PIPE SCH 80 SMLS SS A312 TP316/316L BE	0	0								
400			PIPE	5365143	26	26	PIPE WT 33.0MM EFW SS A358 TP316/316L BE	0	0								
410			PIPE	5365200	30	30	PIPE WT 38.0MM EFW SS A358 316/316L BE	0	0								
420			PIPE	5365212	36	36	PIPE WT 40.0MM EFW SS A358 316/316L BE	0	0								
430			PIPE	5365214	42	42	PIPE WT 45.0MM EFW SS A358 316/316L BE	0	0								
440			PIPE	5365213	48	48	PIPE WT 50.0MM EFW SS A358 316/316L BE	0	0								
450		814	PIPE	5365207	0.5	0.75	PIPE SCH 160 SMLS SS A312 TP316/316L PE	0	0								
460							***** FITTINGS *****										
460																	
470																	
470	U04		ELBOW	5449033	0.5	8	ELL 90 DEG LR SCH 80S SS A403 WP316/316L-S	0	0								
480	U04	UK9	ELBOW	5449572	0.5	0.75	ELL 90 DEG LR SCH XXS SS A403 WP316/316L-S	0	0								
490			ELBOW	5449034	10	24	ELL 90 DEG LR SCH 80 SS A403 WP316/316L-S	0	0								
500			ELBOW	5451120	30	30	ELL 90 LR WT 38.0MM 316/316L SS A403 WP316/316L-W	0	0								
510			ELBOW	5451122	36	36	ELL 90 LR WT 40.0MM 316/316L SS A403 WP316/316L-W	0	0								
520			ELBOW	5451121	42	42	ELL 90 LR WT 45.0MM 316/316L SS A403 WP316/316L-W	0	0								
530			ELBOW	5451123	48	48	ELL 90 LR WT 50.0MM 316/316L SS A403 WP316/316L-W	0	0								
540			ELBOW	5449146	0.75	8	ELL 45 DEG LR SCH 80S SS A403 WP316/316L-S	0	0								
			TENGIZCHEVROIL TCO TENGIZ, KAZAKHSTAN		CONSTRUCTION		CORR.ALLOW.		SERVICE		MATERIAL		DATE	BY	REV	SHEET	PIPING LINE CLASS
					ALL SIZES - BUTT WELD SEAL WELDING - FOR THREADED CONNECTIONS ONLY PIPE BENDS - NONE THREAD SEALANT - PTFE PASTE		CORR. ALLOW. 1 MM		SOUR SERVICE - NACE MR0175/ ISO 15156 DESIGN - ASME B16.5 MG 2.2 CODE - ASME B31.3 FLUID CODES - PIM-SU-5112-TCO		MATERIAL: 316/316L SS DUAL GRADE FLANGE RATING: 600 RF TEMPERATURE RANGE: -40 / 350 °C		12/16/2024	BY OZAC	U04	Page 1 of 3	600P22

SEQ NO	REV	NOTE NO.	ITEM NAME	ITEM CODE	SIZE RANGE / SMALL END SIZES		DESCRIPTION	REFERENCE / LARGE END SIZES		NOTES				
550	U04	UK9	ELBOW	5449143	0.5	0.75	ELL 45 DEG LR XXS SS A403 WP316/316L-S	0	0					
560			ELBOW	5449145	10	24	ELL 45 DEG LR SCH 80 SS A403 WP316/316L-S	0	0					
570			ELBOW	5451110	30	30	ELL 45 LR WT 38.0MM 316/316L SS A403 WP316/316L-W	0	0					
580			ELBOW	5451102	36	36	ELL 45 LR WT 40.0MM 316/316L SS A403 WP316/316L-W	0	0					
590			ELBOW	5451103	48	48	ELL 45 LR WT 50.0MM 316/316L SS A403 WP316/316L-W	0	0					
600														
600	U04		TEE	5449156	0.5	8	TEE SCH 80S SS A403 WP316/316L-S	0	0					
610	U04	UK9	TEE	5449191	0.5	0.75	TEE SCH XXS SS A403 WP316/316L-S	0	0					
620			TEE	5449157	10	24	TEE SCH 80 SS A403 WP316/316L-S	0	0					
630			TEE	5451113	30	30	TEE 38.0MM SS A403 WP316/316L-W	0	0					
640			TEE	5451112	36	36	TEE 40.0MM SS A403 WP316/316L-W	0	0					
650			TEE	5451115	48	48	TEE 50.0MM SS A403 WP316/316L-W	0	0					
660			TEE RED	5448905	0.75	6	TEE RED SCH 80S SS A403 WP316/316L-S	1	8					
670			TEE RED	5448906	4	8	TEE RED SCH 80/80S SS A403 WP316/316L-S	10	20					
680			TEE RED	5448907	10	20	TEE RED SCH 80 SS A403 WP316/316L-S	12	24					
690			TEE RED	5448913	12	20	TEE RED WT 33.0MM X SCH 80 SS A403 WP316/316L-S	26	26					
700														
700			CAP	5449049	0.75	8	CAP SCH 80S SS A403 WP316/316L-S	0	0					
710			CAP	5449050	10	24	CAP SCH 80 SS A403 WP316/316L-S	0	0					
720			CAP	5449261	26	26	CAP WT 33.0MM SS A403 WP316/316L-S	0	0					
730			CAP	5449260	30	30	CAP WT 38.0MM SS A403 WP316/316L-S	0	0					
740			CAP	5449262	36	36	CAP WT 40.0MM SS A403 WP316/316L-S	0	0					
750			CAP	5449263	48	48	CAP WT 50.0MM SS A403 WP316/316L-S	0	0					
760														
760	U04		RED CONC	5449158	0.5	6	REDUCER CONC SCH 80S SS A403 WP316/316L-S	0.75	8					
770			RED CONC	5448904	4	8	REDUCER CONC SCH 80/80S SS A403 WP316/316L-S	10	20					
780			RED CONC	5448908	10	20	REDUCER CONC SCH 80 SS A403 WP316/316L-S	12	24					
790			RED CONC	5450730	20	24	REDUCER CONC 38.0MM/SCH 80 SS A403 WP316/316L-W	30	30					
800			RED CONC	5450749	24	24	REDUCER CONC 40.0MM / SCH 80 SS A403 WP316/316L-W	36	36					
810			RED CONC	5450742	30	30	REDUCER CONC 40.0MM/ 38.0MM SS A403 WP316/316L-W	36	36					
820			RED CONC	5450741	30	30	REDUCER CONC 45.0MM/ 38.0MM SS A403 WP316/316L-W	42	42					
830			RED CONC	5450746	36	36	REDUCER CONC 45.0MM/ 40.0MM SS A403 WP316/316L-W	42	42					
840			RED CONC	5450744	42	42	REDUCER CONC 50.0MM/ 45.0MM SS A403 WP316/316L-W	48	48					
850	U04		RED ECC	5449159	0.5	6	REDUCER ECC SCH 80S SS A403 WP316/316L-S	1	8					
860			RED ECC	5449160	4	8	REDUCER ECC SCH 80/80S SS A403 WP316/316L-S	10	20					
870			RED ECC	5449161	10	20	REDUCER ECC SCH 80 SS A403 WP316/316L-S	12	24					
880			RED ECC	5450728	20	24	REDUCER ECC 38.0MM/SCH 80 SS A403 WP316/316L-W	30	30					
890			RED ECC	5450739	24	24	REDUCER ECC 40.0MM / SCH 80 SS A403 WP316/316L-W	36	36					
900			RED ECC	5450729	30	30	REDUCER ECC 40.0MM / 38.0MM SS A403 WP316/316L-W	36	36					
910			RED ECC	5450754	36	36	REDUCER ECC 45.0MM / 40.0MM SS A403 WP316/316L-W	42	42					
920			RED ECC	5450752	42	42	REDUCER ECC 50.0MM / 45.0MM SS A403 WP316/316L-W	48	48					
930														
930							***** OLETS *****							
940														
940			OLETS	5504504	0.75	2	NIPOFLANGE 600# RF SCH 80S SS A182 F316/316L	2	8					
950			OLETS	5504505	0.75	2	NIPOFLANGE 600# RF SCH 80/80S SS A182 F316/316L	10	24					
960			OLETS	5504416	0.75	2	NIPOFLANGE 600# RF WT 33.0MM/SCH 80S SS A182 F316/316L	26	26					
970			OLETS	5504506	0.75	2	NIPOFLANGE 600# RF WT 38.0MM/SCH 80S SS A182 F316/316L	30	30					
980			OLETS	5504539	0.75	2	NIPOFLANGE 600# RF SCH 40.0MM/80S SS A182 F316/316L	36	36					
990			OLETS	5504541	0.75	2	NIPOFLANGE 600# RF SCH 50.0MM/80S SS A182 F316/316L	48	48					
1000		FF5	OLETS	5504613	0.75	1.5	NIPOFLANGE FLAT BOTTOM 600# RF SCH 80S SS A182 F316/316L	0	0					
1010		UJ2	OLETS	5504075	1.5	1.5	NIPOFLANGE 600# RF SCH 80S/160 SS A182 F316/316L	4	8					
1020		UJ2	OLETS	5504076	1.5	1.5	NIPOFLANGE 600# RF SCH 80/160 SS A182 F316/316L	10	24					
1030		UJ2	OLETS	5504083	1.5	1.5	NIPOFLANGE 600# RF 33.0MM WT/SCH 160 SS A182 F316/316L	26	26					
1040		UJ2	OLETS	5504080	1.5	1.5	NIPOFLANGE 600# RF 38.0MM WT/SCH 160 SS A182 F316/316L	30	30					
1050		UJ2	OLETS	5504081	1.5	1.5	NIPOFLANGE 600# RF 40.0MM WT/SCH 160 SS A182 F316/316L	36	36					
1060		UJ2	OLETS	5504540	1.5	1.5	NIPOFLANGE 600# RF SCH 45.0MM/160 SS A182 F316/316L	42	42					
1070		UJ2	OLETS	5504082	1.5	1.5	NIPOFLANGE 600# RF 50.0MM WT/SCH 160 SS A182 F316/316L	48	48					
1080	U04	UJ4	OLETS	5504113	2	2	NIPOFLANGE 600# RF 38.0MM WT/SCH 160 SS A182 F316/316L	30	30					
1090	U04	UJ3	OLETS	5504526	3	3	NIPOFLANGE 600# RF 38.0MM WT/SCH 160 SS A182 F316/316L	30	30					
1100	U04	UJ4	OLETS	5504027	2	2	NIPOFLANGE 600# RF SCH 80/160 SS A182 F316/316L	16	16					
1110	U04	UJ3	OLETS	5504525	3	3	NIPOFLANGE 600# RF SCH 80/160 SS A182 F316/316L	16	16					
1120														
1120			OLETS	5509637	0.75	3	WELDOLET SCH 80S SS A182 F316/316L	2	8					
1130			OLETS	5509638	0.75	8	WELDOLET SCH 80/80S SS A182 F316/316L	10	24					
1140			OLETS	5509655	0.75	8	WELDOLET 38.0MM WT/ SCH 80S SS A182 F316/316L	30	30					
1150			OLETS	5509656	0.75	8	WELDOLET 40.0MM WT/ SCH 80S SS A182 F316/316L	36	36					
1160			OLETS	5509657	0.75	8	WELDOLET 50.0MM WT/ SCH 80S SS A182 F316/316L	48	48					
1170			OLETS	5509660	10	12	WELDOLET 38.0MM WT/ SCH 80 SS A182 F316/316L	30	30					
1180			OLETS	5509661	10	12	WELDOLET 40.0MM WT/ SCH 80 SS A182 F316/316L	36	36					
1190			OLETS	5509665	10	12	WELDOLET 50.0MM WT/ SCH 80 SS A182 F316/316L	48	48					
1200														
1200														
1200	UJ2		ELBOFLG	5516375	1.5	1.5	ELBOFLANGE 600# RF SCH 80S/160 SS A182 F316/316L	4	8					

	TENGIZCHEVROI TCO TENGIZ, KAZAKHSTAN	CONSTRUCTION	CORR.ALLOW.	SERVICE	MATERIAL	DATE	BY	REV	SHEET	PIPING LINE CLASS
		ALL SIZES - BUTT WELD SEAL WELDING - FOR THREADED CONNECTIONS ONLY PIPE BENDS - NONE THREAD SEALANT - PTFE PASTE	CORR. ALLOW. 1 MM	SOUR SERVICE - NACE MR0175/ ISO 15156 DESIGN - ASME B16.5 MG 2.2 CODE - ASME B31.3 FLUID CODES - PIM-SU-5112-TCO	MATERIAL: 316/316L SS DUAL GRADE FLANGE RATING: 600 RF TEMPERATURE RANGE: -40 / 350 °C	12/16/2024	BY OZAC	U04	Page 2 of 3	600P22

SEQ NO	REV	NOTE NO.	ITEM NAME	ITEM CODE	SIZE RANGE / SMALL END SIZES		DESCRIPTION	REFERENCE / LARGE END SIZES		NOTES
1210		UJ2	ELBOFLG	5516376	1.5	1.5	ELBOFLANGE 600# RF SCH 80 /160 SS A182 F316/316L	10	24	
1220		UJ2	ELBOFLG	5516377	1.5	1.5	ELBOFLANGE 600# RF 33.0MM WT/160 SS A182 F316/316L	26	26	
1230		UJ2	ELBOFLG	5516380	1.5	1.5	ELBOFLANGE 600# RF 38.0MM WT/160 SS A182 F316/316L	30	30	
1240		UJ2	ELBOFLG	5516381	1.5	1.5	ELBOFLANGE 600# RF 40.0MM WT/160 SS A182 F316/316L	36	36	
1250		UJ2	ELBOFLG	5516383	1.5	1.5	ELBOFLANGE 600# RF 45.0MM WT/160 SS A182 F316/316L	42	42	
1260		UJ2	ELBOFLG	5516382	1.5	1.5	ELBOFLANGE 600# RF 50.0MM WT/160 SS A182 F316/316L	48	48	
1270										
1270			ELBOFLG	5509801	0.75	0.75	ELBOLET SCH 80/80S SS A182 F316/316L	16	16	
1280			ELBOFLG	5509800	2	2	ELBOLET SCH 80S/80S SS A182 F316/316L	8	8	
1290										
1290							***** FLANGES *****			
1300										
1300	U04	FA8	FLANGE	5600660	0.5	0.5	FLG SCRD (FNPT) REDUCING 600# RF SS A182 F316/316L	0.75	1.5	
1310										
1310	U04		FLG ADAPTER	5851204	0.5	2	FLANGE ADAPTER 600# RF 316 SS X 12 MM TUBE	0	0	
1320										
1320			FLANGE	5582998	0.5	8	FLG WN 600# RF SS A182 F316/316L SCH 80S BORE	0	0	
1330			FLANGE	5582999	10	24	FLG WN 600# RF SS A182 F316/316L SCH 80 BORE	0	0	
1340			FLANGE	5583635	30	30	FLG WN 600# RF SS A182 F316/316L 38.0MM WT B16.47 SERIES A	0	0	
1350			FLANGE	5583632	36	36	FLG WN 600# RF SS A182 F316/316L 40.0MM WT B16.47 SERIES A	0	0	
1360			FLANGE	5583634	42	42	FLG WN 600# RF SS A182 F316/316L 45.0MM WT B16.47 SERIES A	0	0	
1370			FLANGE	5583633	48	48	FLG WN 600# RF SS A182 F316/316L 50.0MM WT B16.47 SERIES A	0	0	
1380		FS1	FLANGE	5583006	3	3	FLG WN 900# RF SS A182 F316/316L SCH 80S BORE	0	0	
1390		FS1	FLANGE	5583979	0.75	2	FLG WN 1500# RF SS A182 F316/316L SCH 80S BORE	0	0	
1400	U04	817	FLANGE	5619808	30	30	FLG COMPACT 600# RJ SS A182 F316/316L WT 38.0MM	0	0	
1410			BLIND	5616544	0.5	24	FLG BLIND 600# RF SS A182 F316/316L	0	0	
1420			BLIND	5616531	30	48	FLG BLIND 600# RF SS A182 F316/316L B16.47 SERIES A	0	0	
1430	U04	817	BLIND	5619716	30	30	FLG COMPACT BLIND 600# RJ SS A182 F316/316L PIPE CLASS 600P22	0	0	
1440										
1440							***** ORIFICE FLANGES *****			
1450										
1450			ORIFICE FLG	5640600	2	8	WN ORIF SET 600# RF SS A182 F316/316L SCH 80S BORE	0	0	
1460			ORIFICE FLG	5640601	10	24	WN ORIF SET 600# RF SS A182 F316/316L SCH 80 BORE	0	0	
1470										
1470							***** PIPE NIPPLES *****			
1480										
1480		814		0			NIPPLE PBE CUT FROM PIPE			
1490										
1490							***** GASKETS *****			
1500										
1500			GASKET	5673103	0.5	24	GASKET 600# 316SS SPIRAL WOUND GRAPHITE IR	0	0	
1510			GASKET	5674012	30	48	GASKET 600# 316SS KAMMPROFILE GRAPHITE ASME B16.47 SERIES A	0	0	
1520	U04	GA6	GASKET	5673018	2	3	GASKET 600# 316SS KAMMPROFILE GRAPHITE ASME B16.5	0	0	
1530	U04	817	GASKET	5673421	26	48	GASKET 600# RJ INC 718 ENERGIZED SEALRING COMPACT FLANGE PIPE CLASS 600P22	0	0	
1540			GASKET	5673117	3	3	GASKET 900# 316SS SPIRAL WOUND GRAPHITE IR	0	0	
1550			GASKET	5672251	0.75	2	GASKET 1500# 316SS SPIRAL WOUND GRAPHITE IR	0	0	
1560										
1560		B1					***** BOLTING *****			
1570										
1570	U04	BA1	BOLTING	5675770	0.5	99	STUD-BOLT A320 GR L7M/A194 GR 7M (S3) WITH 2 NUTS	0	0	
1580	U04	BA5	BOLTING	5675778	26	99	STUD-BOLT C/W 2 COMPACT NUTS API-6A718	0	0	
1590		BA1	BOLTING	5675776	36	99	STUD-BOLT WITH 2 NUTS API-6A718	0	0	
1600										
1600							***** BLINDS AND SPACERS *****			
1610										
1610			SPEC BLIND	5750423	0.75	8	SPECTACLE BLIND 600# RF SS A240 GR 316	0	0	
1620										
1620			PADDLE	5750523	10	24	PADDLE BLANK 600# RF SS A240 GR 316	0	0	
1630			PADDLE	5750528	30	48	PADDLE BLANK 600# RF SS A240 GR 316 B16.47 SERIES A	0	0	
1640	U04	817	PADDLE	5750269	30	48	PADDLE BLANK COMPACT 600# RJ SS A240 GR 316	0	0	
1650			PADDLE	5750623	10	24	PADDLE SPACER 600# RF SS A240 GR 316	0	0	
1660			PADDLE	5750628	30	48	PADDLE SPACER 600# RF SS A240 GR 316 B16.47 SERIES A	0	0	
1670	U04	817	PADDLE	5750258	30	48	PADDLE SPACER COMPACT 600# RJ SS A240 GR 316	0	0	
1680										
1690										
1690							*****MISCELLANEOUS*****			
1700										
1700	U04		FLG GUARD	5558883	2	6	SAFETY SHIELD PTFE SUITABLE FOR 600# FLANGE	0	0	

	TENGIZCHEVROIL TCO TENGIZ, KAZAKHSTAN	CONSTRUCTION	CORR.ALLOW.	SERVICE	MATERIAL	DATE	BY	REV	SHEET	PIPING LINE CLASS
		ALL SIZES - BUTT WELD SEAL WELDING - FOR THREADED CONNECTIONS ONLY PIPE BENDS - NONE THREAD SEALANT - PTFE PASTE	CORR. ALLOW. 1 MM	SOUR SERVICE - NACE MR0175/ ISO 15156 DESIGN - ASME B16.5 MG 2.2 CODE - ASME B31.3 FLUID CODES - PIM-SU-5112-TCO	MATERIAL: 316/316L SS DUAL GRADE FLANGE RATING: 600 RF TEMPERATURE RANGE: -40 / 350 °C	12/16/2024	BY OZAC	U04	Page 3 of 3	600P22