

SEQ NO	REV	NOTE NO.	ITEM NAME	ITEM CODE	SIZE RANGE / SMALL END SIZES		DESCRIPTION	REFERENCE / LARGE END SIZES		NOTES	
10							*****VALVES*****			810	NIPPLE TO BE CUT FROM SCH 160 PIPE.
20										816	COMPACT FLANGES CAN BE USED FOR TIE-IN PURPOSE ONLY TO EXISTING PIPING AND EQUIPMENT.
20							***** MODULAR VALVES *****				
30										817	USE ONLY FOR TIE IN
30		VA5	MODULAR DBB	K15AM10	0.5	1.5	MODULAR VALVE DB&B BALL TYPE 1500# RF INC 825 INC 625 TRIM METAL LO - FULL SIZE TYPE 2BV	0	0	B1	ALL BOLTS ARE METRIC DIA.
40			MODULAR DBB	K15AM14	2	2	MODULAR VALVE DB&B BALL TYPE 1500# RF INC 825 INC 625 TRIM METAL LO - FULL SIZE TYPE 2BV	0	0	B2	7/8" X 145MM BOLTS ONLY TO BE USED FOR 1 INCH 1500# PERAR BALL VALVES ITEM CODE B15AM10
50		VAV	MODULAR DBB	K09AM14	3	3	MODULAR VALVE DB&B BALL TYPE 900# RF INC 825 INC 625 TRIM METAL LO FULL SIZE TYPE 2BV	0	0		
60			MODULAR DBB	M15AM10	0.75	1.5	MODULAR VALVE DB&B BALL TYPE 1500# RF INC 825 INC 625 TRIM METAL LO - CONTROLLED BORE TYPE 2BVR	0	0		
70			MODULAR DBB	M15AM14	2	2	MODULAR VALVE DB&B BALL TYPE 1500# RF INC 825 INC 625 TRIM METAL LO - CONTROLLED BORE TYPE 2BVR	0	0	BA1	TO BE USED WITH RAISED FACE FLANGES ONLY.
80		VAW	MODULAR DBB	M15EM10	0.75	1	MODULAR VALVE DB&B BALL TYPE 1500# RF INC 825 INC 625 TRIM METAL LO REDUCING - CONTROLLED BORE TYPE 2BVR	1.5	2	BA5	TO BE USED WITH COMPACT FLANGES REQUIRING COMPACT NUTS ONLY. FOR FGP ONLY.
90	U04	VAW	MODULAR DBB	M09EM10	1	1	MODULAR VALVE DB&B BALL TYPE 900# X 1500# RF INC 825 INC 625 TRIM METAL LO REDUCING - CONTROLLED BORE TYPE 2BVR	3	3	FF5	FLAT BOTTOM NIPPOFLANGES FOR USE ON WELD CAPS AND BLIND FLANGES
100										GA6	SPECIAL GASKET ONLY FOR USE AS SPECIFIED IN ENG-200-117
100		VB2					***** BALL VALVES *****				
110										ND8	USE ONLY WHERE SPACE IS LIMITED AND WITH APPROVAL BY MATERIALS ENGINEER.
110			BALL	A15AM14	2	2	BALL 1500# RF 825 INC 625 TRIM TRUNNION METAL RB LO	0	0		
120			BALL	A09AM14	3	3	BALL 900# RF 825 INC 625 TRIM TRUNNION METAL RB LO	0	0	ND9	USE ONLY WITH CONSENT OF MATERIALS ENGINEER.
130			BALL	A09AM16	4	10	BALL 900# RF 825 INC 625 TRIM TRUNNION METAL RB GO	0	0		
140	U04	817	BALL	A09CM16	12	30	BALL 900# CF 825 INC 625 TRIM TRUNNION METAL RB GO	0	0		
150			BALL	B15AM10	0.75	1.5	BALL 1500# RF 825 INC 625 INC TRIM FLOATING METAL FB LO	0	0	UJ2	USE 1 1/2IN WITH THERMOWELL CONNECTIONS ONLY & 3/4IN (IF SHOWN) FOR DBB PRESSURE CONNECTIONS WITH CHEMICAL SEALS.
160		VA5	BALL	B15AM14	2	2	BALL 1500# RF 825 INC 625 INC TRIM TRUNNION METAL FB LO	0	0		
170	U04	VA5	BALL	B09AM16	3	10	BALL 900# RF 825 INC 625 TRIM TRUNNION METAL FB GO	0	0	UK9	DO NOT USE FOR ORIFICE FLANGE TAP ASSEMBLIES.
180	U04	817	BALL	B09CM16	12	24	BALL 900# CF 825 INC 625 TRIM TRUNNION METAL FB GO	0	0	VA5	USE THESE VALVES ONLY WHERE SPECIFIED ON PIPING AND INSTRUMENT DIAGRAMS
190							***** GLOBE VALVES *****			VAV	USAGE IS LIMITED TO INSTRUMENT ISOLATION PURPOSE.
200										VAW	VALVE ONLY TO BE USED IN ACCORDANCE WITH DOCUMENT L-ST-2055 - VENT DRAIN AND INSTRUMENT CONNECTION DETAILS.
200			GLOBE	L15AM43	0.75	2	GLOBE 1500# RF INC 825 INC TRIM 625 OS&Y HW	0	0	VB2	SOFT SEATED BALL VALVES ARE LIMITED TO MAXIMUM TEMPERATURE OF 200°C.
210			GLOBE	L09AM43	3	3	GLOBE 900# RF INC 825 INC TRIM 625 OS&Y HW	0	0	VC1	SPRING PISTON CHECK VALVES ARE PREFERED IN THE HORIZONTAL POSITION, BUT MAY BE USED IN THE VERTICAL POSITION WITH ENGINEERING APPROVAL.
220			GLOBE	L09AM44	4	8	GLOBE 900# RF INC 825 INC 625 TRIM OS&Y GO	0	0		
230							***** CHECK VALVES *****				
230											
240											
240		VC1	CHECK	C15AM51	0.75	1.5	CHECK PISTON 1500# RF INC 825 TRIM 625	0	0		
250			CHECK	C15AM46	2	2	CHECK DUAL WAFER LUG 1500# RF INC 825 TRIM 625 THROU BOLTED	0	0		
260			CHECK	C09AM46	3	8	CHECK DUAL WAFER LUG 900# RF INC 825 TRIM 625 THROU BOLTED	0	0		
270			CHECK	C09AM53	10	10	CHECK DUAL DBL FLG 900# RF INC 825 TRIM 625	0	0		
280	U04	817	CHECK	C09CM53	12	24	CHECK DUAL DBL FLG 900# CF INC 825 TRIM 625	0	0		
290							***** PIPE *****				
290											
300											
300			PIPE	5732001	0.75	1	PIPE SCH 80S SMLS ALLOY 825 B423 UNS N08825 PE	0	0		
310			PIPE	5732002	1.5	1.5	PIPE SCH 40S SMLS ALLOY 825 B423 UNS N08825 PE	0	0		
320			PIPE	5361603	2	4	PIPE SCH 40S SMLS ALLOY 825 B423 UNS N08825 BE	0	0		
330			PIPE	5361607	6	8	PIPE SCH 80S SMLS ALLOY 825 B423 UNS N08825 BE	0	0		
340			PIPE	5361635	10	10	PIPE SCH 80S WLD ALLOY 825 B705 CL.2 N08825 BE	0	0		
350			PIPE	5361637	12	24	PIPE SCH 60 WLD ALLOY 825 B705 CL.2 N08825 BE	0	0		
360			PIPE	5361641	30	30	PIPE NOM. WT 30MM WLD ALLOY 825 B705 CL.2 N08825 BE	0	0		
370		810	PIPE	5361608	0.75	1.5	PIPE SCH 160 SMLS ALLOY 825 B423 UNS N08825 BE	0	0		
380	U04	UK9	PIPE	5361609	0.75	0.75	PIPE SCH XXS SMLS ALLOY 825 B423 UNS N08825 BE	0	0		
390							*****TRUNNION PIPE SUPPORTS*****				
390											
400											
400	U04	ND9	PIPE	5365128	4	24	PIPE SCH 120 SMLS SS A312 TP316/316L BE	0	0		
410	U04	ND9	PIPE	5365138	2	3	PIPE SCH 80S SMLS SS A312 TP316/316L-S BE	0	0		
420							***** FITTINGS *****				
420											
430											
430			ELBOW	5425111	0.75	8	ELL 90 DEG LR SCH 80S ALLOY 825 B366-WPS UNS N08825	0	0		
440	U04	UK9	ELBOW	5425112	0.75	0.75	ELL 90 DEG LR SCH XXS ALLOY 825 B366-WPS UNS N08825	0	0		
450			ELBOW	5424722	1.5	4	ELL 90 DEG LR SCH 40S ALLOY 825 B366-WPS UNS N08825	0	0		
460			ELBOW	5425109	10	10	ELL 90 DEG LR SCH 80S ALLOY 825 B366-WPW UNS N08825	0	0		
470			ELBOW	5425130	12	24	ELL 90 DEG LR SCH 60 ALLOY 825 B366-WPW UNS N08825	0	0		
480			ELBOW	5425147	30	30	ELL 90 DEG LR WT 30MM ALLOY 825 B366-WPW UNS N08825	0	0		
490			ELBOW	5425113	0.75	8	ELL 45 DEG SCH 80S ALLOY 825 B366-WPS UNS N08825	0	0		
500	U04	UK9	ELBOW	5425116	0.75	0.75	ELL 45 DEG SCH XXS ALLOY 825 B366-WPS UNS N08825	0	0		
510			ELBOW	5424727	1.5	4	ELL 45 DEG SCH 40S ALLOY 825 B366-WPS UNS N08825	0	0		
520			ELBOW	5425115	10	10	ELL 45 DEG SCH 80S ALLOY 825 B366-WPW UNS N08825	0	0		
530			ELBOW	5425131	12	24	ELL 45 DEG SCH 60 ALLOY 825 B366-WPW UNS N08825	0	0		
540											
540			TEE	5425119	0.75	8	TEE SCH 80S ALLOY 825 B366-WPS UNS N08825	0	0		

	TENGIZCHEVROIL TCO TENGIZ, KAZAKHSTAN	CONSTRUCTION	CORR.ALLOW.	SERVICE	MATERIAL	DATE	BY	REV	SHEET	PIPING LINE CLASS
		ALL SIZES - BUTT WELD SEAL WELDING - FOR THREADED CONNECTIONS ONLY PIPE BENDS - NONE THREAD SEALANT - PTFE PASTE	CORR. ALLOW. 1 MM	SOUR SERVICE - NACE MR0175/ ISO 15156 DESIGN PRESSURE: 103.4 BARG CODE: ASME B31.3 FLUID CODES - PIM-SU-5112-TCO	MATERIAL: ALLOY 825 FLANGE RATING: 900 RF/CF TEMPERATURE RANGE: -40 / 300 °C	12/16/2024	BY OZAC	U04	Page 1 of 3	900A80

SEQ NO	REV	NOTE NO.	ITEM NAME	ITEM CODE	SIZE RANGE / SMALL END SIZES		DESCRIPTION	REFERENCE / LARGE END SIZES		NOTES
550	U04	UK9	TEE	5425164	0.75	0.75	TEE SCH XXS ALLOY 825 B366-WPS UNS N08825	0	0	
560			TEE	5424725	1.5	4	TEE SCH 40S ALLOY 825 B366-WPS UNS N08825	0	0	
570			TEE	5425118	10	10	TEE SCH 80S ALLOY 825 B366-WPW UNS N08825	0	0	
580			TEE	5425132	12	24	TEE SCH 60 ALLOY 825 B366-WPW UNS N08825	0	0	
590			TEE	5425152	30	30	TEE WT 30MM ALLOY 825 B366-WPW UNS N08825	0	0	
600			TEE RED	5425126	0.75	6	TEE RED SCH 80S ALLOY 825 B366-WPS UNS N08825	1	8	
610			TEE RED	5425124	0.75	1	TEE RED SCH 40S/80S ALLOY 825 B366-WPS UNS N08825	1.5	2	
620			TEE RED	5424724	1.5	3	TEE RED SCH 40S ALLOY 825 B366-WPS UNS N08825	2	4	
630			TEE RED	5425125	3	4	TEE RED SCH 80S/40S ALLOY 825 B366-WPS UNS N08825	6	8	
640			TEE RED	5425134	3	4	TEE RED SCH 80S/40S ALLOY 825 B366-WPW UNS N08825	10	10	
650			TEE RED	5425117	6	8	TEE RED SCH 80S ALLOY 825 B366-WPW UNS N08825	10	10	
660			TEE RED	5425135	6	10	TEE RED SCH 60/80S ALLOY 825 B366-WPW UNS N08825	12	24	
670			TEE RED	5425133	12	20	TEE RED SCH 60 ALLOY 825 B366-WPW UNS N08825	14	24	
680	U04		TEE RED	5425129	16	16	TEE RED 30MM/SCH 60 ALLOY 825 B366-WPW UNS N08825	30	30	
690										
690			CAP	5424270	0.75	10	CAP SCH 80S ALLOY 825 B366 UNS N08825	0	0	
700			CAP	5424219	1.5	4	CAP SCH 40S ALLOY 825 B366 UNS N08825	0	0	
710			CAP	5425136	12	24	CAP SCH 60 ALLOY 825 B366 UNS N08825	0	0	
720										
720			RED CONC	5425122	0.5	6	REDUCER CONC SCH 80S ALLOY 825 B366-WPS N08825	0.75	8	
730			RED CONC	5425143	0.75	1	REDUCER CONC SCH 40S/80S ALLOY 825 B366-WPS N08825	1.5	2	
740			RED CONC	5424733	1.5	3	REDUCER CONC SCH 40S ALLOY 825 B366-WPS N08825	2	4	
750			RED CONC	5425142	3	4	REDUCER CONC SCH 80S/40S ALLOY 825 B366-WPS N08825	6	8	
760			RED CONC	5425100	4	4	REDUCER CONC SCH 80S/40S ALLOY 825 B366-WPW N08825	10	10	
770			RED CONC	5425120	6	8	REDUCER CONC SCH 80S ALLOY 825 B366-WPW N08825	10	10	
780			RED CONC	5425141	6	10	REDUCER CONC SCH 60/80S ALLOY 825 B366-WPW N08825	12	18	
790			RED CONC	5425137	12	18	REDUCER CONC SCH 60 ALLOY 825 B366-WPW N08825	14	24	
800			RED CONC	5424150	20	24	REDUCER CONC WT 30MM/SCH 60 ALLOY 825 B366-WPW N08825	30	30	
810	U04		RED ECC	5425123	0.5	0.75	REDUCER ECC SCH 80S ALLOY 825 B366-WPS N08825	1	1	
820			RED ECC	5425145	0.75	1	REDUCER ECC SCH 40S/80S ALLOY 825 B366-WPS N08825	1.5	2	
830			RED ECC	5424734	1.5	3	REDUCER ECC SCH 40S ALLOY 825 B366-WPS N08825	2	4	
840			RED ECC	5425101	3	4	REDUCER ECC SCH 80S/40S ALLOY 825 B366-WPS N08825	6	8	
850			RED ECC	5425121	6	6	REDUCER ECC SCH 80S ALLOY 825 B366-WPS N08825	8	8	
860			RED ECC	5425139	4	4	REDUCER ECC SCH 80S/40S ALLOY 825 B366-WPW N08825	10	10	
870			RED ECC	5424732	6	8	REDUCER ECC SCH 80S ALLOY 825 B366-WPW N08825	10	10	
880			RED ECC	5425140	6	10	REDUCER ECC SCH 60/80S ALLOY 825 B366-WPW N08825	12	18	
890			RED ECC	5425138	12	20	REDUCER ECC SCH 60 ALLOY 825 B366-WPW N08825	14	24	
900										
900							***** OLETS *****			
910										
910			OLETS	5513581	0.75	1	NIPOFLANGE 1500# RF SCH 40S/80S ALLOY 825 B564 UNS N08825	2	4	
920			OLETS	5514631	0.75	1	NIPOFLANGE 1500# RF SCH 80S ALLOY 825 B564 UNS N08825	6	10	
930			OLETS	5514641	0.75	1	NIPOFLANGE 1500# RF SCH 60/80S ALLOY 825 B564 UNS N08825	12	24	
940			OLETS	5513680	1.5	2	NIPOFLANGE 1500# RF SCH 40S ALLOY 825 B564 UNS N08825	2	4	
950			OLETS	5514630	1.5	2	NIPOFLANGE 1500# RF SCH 80S/40S ALLOY 825 B564 UNS N08825	6	10	
960			OLETS	5514640	1.5	2	NIPOFLANGE 1500# RF SCH 60/40S ALLOY 825 B564 UNS N08825	12	24	
970		UJ2	OLETS	5516680	1.5	1.5	NIPOFLANGE 1500# RF SCH 40S/160 ALLOY 825 B564 UNS N08825	2	4	
980		UJ2	OLETS	5516630	1.5	1.5	NIPOFLANGE 1500# RF SCH 80S/160 ALLOY 825 B564 UNS N08825	6	10	
990		UJ2	OLETS	5516640	1.5	1.5	NIPOFLANGE 1500# RF SCH 60/160 ALLOY 825 B564 UNS N08825	12	24	
1000	U04		OLETS	5516698	0.75	0.75	NIPOFLANGE 1500# RF WT 30.0MM /80S ALLOY 825 B564 UNS N08825	30	30	
1010	U04		OLETS	5516699	2	2	NIPOFLANGE 1500# RF WT 30.0MM/40S ALLOY 825 B564 UNS N08825	30	30	
1020		FF5	OLETS	5504591	0.75	1	NIPOFLANGE FLAT BOTTOM 1500# RF SCH 80S ALLOY 825 B564 UNS N08825	0	0	
1030		FF5	OLETS	5504590	1.5	1.5	NIPOFLANGE FLAT BOTTOM 1500# RF SCH 40S ALLOY 825 B564 UNS N08825	0	0	
1040										
1040			OLETS	5513413	0.75	1	WELDOLET SCH 40S/80S ALLOY 825 B564 UNS N08825	3	4	
1050			OLETS	5513414	0.75	1	WELDOLET SCH 80S ALLOY 825 B564 UNS N08825	6	10	
1060		UJ2	OLETS	5513433	0.75	8	WELDOLET SCH 60/80S ALLOY 825 B564 UNS N08825	12	24	
1070			OLETS	5513412	1.5	4	WELDOLET SCH 80S/40S ALLOY 825 B564 UNS N08825	6	10	
1080			OLETS	5513432	1.5	4	WELDOLET SCH 60/40S ALLOY 825 B564 UNS N08825	12	24	
1090	U04		OLETS	5513447	1.5	3	WELDOLET WT 30MM/40S ALLOY 825 B564 UNS N08825	30	30	
1100										
1100		UJ2	ELBOFLG	5516178	1.5	1.5	ELBOFLANGE 1500# RF SCH 40S/160 ALLOY 825 B564 UNS N08825	4	4	
1110		UJ2	ELBOFLG	5516179	1.5	1.5	ELBOFLANGE 1500# RF SCH 80S/160 ALLOY 825 B564 UNS N08825	6	10	
1120		UJ2	ELBOFLG	5516180	1.5	1.5	ELBOFLANGE 1500# RF SCH 60/160 ALLOY 825 B564 UNS N08825	12	24	
1130										
1130	U04	ND8	ELBOFLG	5509806	1.5	1.5	ELBOLET SCH 60/40S ALLOY 825 B564 UNS N08825	12	12	
1140	U04	ND8	ELBOFLG	5509803	1.5	1.5	ELBOLET WT 30MM/40S ALLOY 825 B564 UNS N08825	30	30	
1150	U04	ND8	ELBOFLG	5509805	0.75	0.75	ELBOLET WT 30MM/80S ALLOY 825 B564 UNS N08825	30	30	
1160										
1160							***** FLANGES *****			
1170										
1170			TEE RED	5614400	0.5	0.5	FLG SCRD (FNPT) REDUCING 1500# RF ALLOY 825 B564 UNS N08825	0.75	0.75	
1180										

	TENGIZCHEVROIL TCO TENGIZ, KAZAKHSTAN	CONSTRUCTION	CORR.ALLOW.	SERVICE	MATERIAL	DATE	BY	REV	SHEET	PIPING LINE CLASS
		ALL SIZES - BUTT WELD SEAL WELDING - FOR THREADED CONNECTIONS ONLY PIPE BENDS - NONE THREAD SEALANT - PTFE PASTE	CORR. ALLOW. 1 MM	SOUR SERVICE - NACE MR0175/ ISO 15156 DESIGN PRESSURE: 103.4 BARG CODE: ASME B31.3 FLUID CODES - PIM-SU-5112-TCO	MATERIAL: ALLOY 825 FLANGE RATING: 900 RF/CF TEMPERATURE RANGE: -40 / 300 °C	12/16/2024	BY OZAC	U04	Page 2 of 3	900A80

SEQ NO	REV	NOTE NO.	ITEM NAME	ITEM CODE	SIZE RANGE / SMALL END SIZES		DESCRIPTION	REFERENCE / LARGE END SIZES		NOTES
1180			FLG ADAPTER	5851205	0.75	2	FLANGE ADAPTER 1500# RF 316 SS X 12 MM TUBE	0	0	
1190			FLG ADAPTER	5851221	0.75	2	FLANGE ADAPTER 1500# RF ALLOY 825 B564 UNS N08825 X 12 MM TUBE	0	0	
1200										
1200	U04		FLANGE	5570286	0.5	1	FLG WN 1500# RF ALLOY 825 SCH 80S B564 UNS N08825	0	0	
1210			FLANGE	5570276	1.5	2	FLG WN 1500# RF ALLOY 825 SCH 40S B564 UNS N08825	0	0	
1220			FLANGE	5557400	3	4	FLG WN 900# RF ALLOY 825 SCH 40S B564 UNS N08825	0	0	
1230			FLANGE	5557401	6	10	FLG WN 900# RF ALLOY 825 SCH 80S B564 UNS N08825	0	0	
1240			FLANGE	5557402	12	24	FLG WN 900# RF ALLOY 825 SCH 60 B564 UNS N08825	0	0	
1250	U04	817	FLANGE	5619820	12	24	FLG COMPACT 900# RJ ALLOY 825 SCH 60 B564 UNS N08825	0	0	
1260	U04	817	FLANGE	5619903	30	30	FLG COMPACT 900# RJ ALLOY 825 WT 30MM B564 UNS N08825	0	0	
1270			BLIND	5617185	0.5	2	FLG BLIND 1500# RF ALLOY 825 B564 UNS N08825	0	0	
1280		816	BLIND	5617190	3	24	FLG BLIND 900# RF ALLOY 825 B564 UNS N08825	0	0	
1290	U04	817	BLIND	5619725	12	30	FLG COMPACT BLIND 900# RJ ALLOY 825 B564 UNS N08825 PIPE CLASS 900A80	0	0	
1300										
1300							***** ORIFICE FLANGES *****			
1310										
1310			ORIFICE FLG	5651000	2	2	WN ORIF SET 1500# RF ALLOY 825 B564 UNS N08825 SCH 40S	0	0	
1320			ORIFICE FLG	5650940	3	4	WN ORIF SET 900# RF ALLOY 825 B564 UNS N08825 SCH 40S	0	0	
1330			ORIFICE FLG	5650941	6	10	WN ORIF SET 900# RF ALLOY 825 B564 UNS N08825 SCH 80S	0	0	
1340			ORIFICE FLG	5650942	12	24	WN ORIF SET 900# RF ALLOY 825 B564 UNS N08825 SCH 60	0	0	
1350										
1350							***** NIPPLES *****			
1360										
1360				0			NIPPLE CUT FROM PIPE			
1370										
1370							***** GASKETS *****			
1380										
1380			GASKET	5673800	0.5	2	GASKET 1500# ALLOY 825 SPIRAL WOUND GRAPHITE IR	0	0	
1390	U04	GA6	GASKET	5673023	2	2	GASKET 1500# ALLOY 825 KAMMPROFILE GRAPHITE ASME B16.5	0	0	
1400	U04	GA6	GASKET	5673022	3	3	GASKET 900# ALLOY 825 KAMMPROFILE GRAPHITE ASME B16.5	0	0	
1410			GASKET	5673700	3	24	GASKET 900# ALLOY 825 SPIRAL WOUND GRAPHITE IR	0	0	
1420	U04	817	GASKET	5673430	12	30	GASKET 900# RJ INC 718 ENERGIZED SEALRING COMPACT FLANGE PIPE CLASS 900A80	0	0	
1430										
1430		B1					***** BOLTING *****			
1440										
1440	U04	BA1	BOLTING	5675770	0.5	20	STUD-BOLT A320 GR L7M/A194 GR 7M (S3) WITH 2 NUTS	0	0	
1450	U04	BA5	BOLTING	5675778	12	99	STUD-BOLT C/W 2 COMPACT NUTS API-6A718	0	0	
1460		BA1	BOLTING	5675776	24	99	STUD-BOLT WITH 2 NUTS API-6A718	0	0	
1470										
1470							***** BLINDS & SPACERS *****			
1480										
1480			SPEC BLIND	5750300	0.75	2	SPECTACLE BLIND 1500# RF ALLOY 825 B424 UNS N08825	0	0	
1490			SPEC BLIND	5750400	3	8	SPECTACLE BLIND 900# RF ALLOY 825 B424 UNS N08825	0	0	
1500										
1500			PADDLE	5750540	10	24	PADDLE BLANK 900# RF ALLOY 825 B424 UNS N08825	0	0	
1510			PADDLE	5750640	10	24	PADDLE SPACER 900# RF ALLOY 825 B424 UNS N08825	0	0	
1520	U04	817	PADDLE	5750266	12	24	PADDLE BLANK COMPACT 900# RJ ALLOY 825 B424 UNS N08825	0	0	
1530	U04	817	PADDLE	5750267	12	24	PADDLE SPACER COMPACT 900# RJ ALLOY 825 B424 UNS N08825	0	0	
1540										

	TENGIZCHEVROIL TCO TENGIZ, KAZAKHSTAN	CONSTRUCTION	CORR.ALLOW.	SERVICE	MATERIAL	DATE	BY	REV	SHEET	PIPING LINE CLASS
		ALL SIZES - BUTT WELD SEAL WELDING - FOR THREADED CONNECTIONS ONLY PIPE BENDS - NONE THREAD SEALANT - PTFE PASTE	CORR. ALLOW. 1 MM	SOUR SERVICE - NACE MR0175/ ISO 15156 DESIGN PRESSURE: 103.4 BARG CODE: ASME B31.3 FLUID CODES - PIM-SU-5112-TCO	MATERIAL: ALLOY 825 FLANGE RATING: 900 RF/CF TEMPERATURE RANGE: -40 / 300 °C	12/16/2024	BY OZAC	U04	Page 3 of 3	900A80