



03/08/2023

RNN → Sequential

CNN

Hyper parameter → Higher level parameters of the model eg. learning rate in Perceptron Learning Algorithm
There are various kinds of hyper parameters.

2-layers neural network:




$$f(x) = w_1x + w_2x^2 + \dots + w_{10}x^{10}$$

w_{10} has more significance.

05/08/2023

K-Fold:




Then we find E_k .

$$\frac{\partial \mathcal{L}}{\partial w_{j1}^{(2)}} = \frac{\partial (-y \log(y^*) - (1-y) \log(1-y^*))}{\partial w_{j1}^{(2)}} = \frac{\partial \mathcal{L}}{\partial y^*} \cdot \frac{\partial y^*}{\partial w_{j1}^{(2)}}$$

$$= \left(-\frac{y}{y^*} + \frac{(1-y)}{1-y^*} \right) \cdot \frac{\partial A\left(\sum_{j=1}^2 w_{j1}^{(2)} z_j\right)}{\partial w_{j1}^{(2)}}$$



$$\delta(z)(1-\delta(z))$$



$$\frac{\partial}{\partial x} f(a_1 h(x) + a_2 f(x)) = f'(\cdot) a_2 f'(x)$$

4 hidden layer:

2 layer → 3 layer



10/08/2023

12/08/2023


Computational Resource needed \rightarrow ① Storage, ② Time

Mini Batch Gradient Decent \rightarrow Many updates for a batch at a time.


Batch Gradient Decent \rightarrow Updates are made after processing the whole batch of data.

We can't reach any global minima in Deep Learning in Reality.

The problems of saddle point (Since geometry is complex).



Gradient Decent




$$W^{(t+1)} = W^{(t)} - \xi \nabla_{W^{(t)}} \mathcal{L}(y^*(W), y) \leftarrow \text{Updating the weight for Gradient Decent}$$

14/08/2023

Tensorflow

$$\begin{bmatrix} \vdots \\ \vdots \\ \vdots \end{bmatrix}_{28 \times 28} = [\dots]_{784}$$

flattening



PyTorch (PyTorch FMNIST).

17/08/2023


$$z_1 = A(W_{11}^{(1)} X_1 + W_{21}^{(1)} X_2) = A(W_0 X_1 + W_0 X_2)$$

$$z_2 = A(W_{21}^{(1)} X_1 + W_{22}^{(1)} X_2) = A(W_0 X_1 + W_0 X_2) = z_1$$

$$y^* = A(W_{11}^{(2)} z_1 + W_{21}^{(2)} z_2) = A(W_0 z_1 + W_0 z_2)$$

$$\frac{\partial y^*}{\partial W_{11}^{(2)}} = A'(\cdot) z_1 \quad \text{and} \quad \frac{\partial y^*}{\partial W_{21}^{(2)}} = A'(\cdot) z_2$$


$$z_1 = A(W_0 X_1 + W_0 X_2) \Rightarrow \frac{\partial z_1}{\partial W_{11}^{(1)}} = A'(\cdot) X_1$$



$$\begin{aligned} z_1 &= W^{(1)} X \\ z_2 &= W^{(2)} z_1 \\ &\vdots \\ y^* = z_n &= W^{(n)} W^{(n-1)} \dots W^{(1)} X \end{aligned}$$


for large $w^{(i)}$, $y^* \rightarrow \infty / -\infty$
for small $w^{(i)}$, $y^* \rightarrow 0$

Exploding Gradient or Vanishing Gradient problem




$$z^{(K)} = [z_1^{(K)} \quad z_2^{(K)} \quad \dots \quad z_j^{(K)} \quad \dots \quad z_{H_K}^{(K)}]$$



21/08/2023



Dropout:




Red one's are the dropouts. The renewed model is forced to learn from dataset.



24/08/2023



Batch Normalization:



Exploding & Vanishing Gradient Solution:


- ① Change Activation Function
- ② Regularization.

28/08/2023



Padding and Pooling

$$\left. \begin{array}{l} 30 \times 30 \times 32, \quad 32 \times 3 \times 3 \times 3 = 288 \times 3 = 864 \\ 13 \times 13 \times 64, \quad 64 \times (3 \times 3) \times 32 + 64 = 1849 \end{array} \right\} \text{After this, } 864 + 32 = 896$$




$$g(t) = \int x(\tau) k(t-\tau) d\tau = \int k(\tau) x(t-\tau) d\tau \quad [\text{taking } t-\tau = \tau]$$

$$= \int k(\tau) x(t-\tau) d\tau \Leftrightarrow (k * x)(t) = (x * k)(t)$$

Again, $\sum_{\alpha} \sum_{\beta} \kappa(\alpha, \beta) k(i-\alpha, j-\beta) = \sum_{\alpha} \sum_{\beta} \kappa(i-\alpha, j-\beta) k(\alpha, \beta)$

But we have, $\sum_{\alpha} \sum_{\beta} x(i+\alpha, j+\beta) \cdot K(\alpha, \beta) \leftarrow \text{Cross Correlation}$




Again, for $5 (1 \times 1 \times D)$ filter, if $D=10$ we have, $(K \times K \times 5)$

RNN:

09/09/2023

$h_t = f(x_t, h_{t-1})$, Note that, $h_1 = f(x_1, h_0)$ then we have to put a value to h_0 such that we get a better result and faster output.



What is the dimension of $\omega_1, \omega_{11}, \omega_2$?

$$\begin{aligned} X_t^{(n)} &= 5 \times 1 \\ \omega_1 &= 10 \times 5 \\ \omega_{11} &= 10 \times 10 \\ \omega_2 &= 20 \times 10 \end{aligned}$$


11/09/2023

For RNN we have sequential inputs and get an output per time period.

$$h_{T,i}^{(n)} = A(z_{i,T,i}^{(n)}), \quad z_{i,T,i}^{(n)} = \sum_i \omega_{1,ij} x_{T,i} + \sum_i \omega_{11,ij} h_{T-1,j} + b_j, \quad \frac{\partial z_{i,T,i}^{(n)}}{\partial \omega_{1,ij}} = x_{T,i}$$

$$\frac{\partial z_{i,T,i}^{(n)}}{\partial \omega_{11,ij}} = h_{T-1,i}$$

$$W_{F,1} h_{t-1} + W_{F,2} X_t + b$$






14/09/2023

Layers
Embedding
LSTM

Output Shape
(None, None, 64)
(None, 128)

Parameters
 $64 \times 1000 = 64000$

$$\underbrace{W_L X}_{128 \times 64} + \underbrace{W_R R_{t-1}}_{128 \times 128} + \underbrace{b}_{128} = 24704 (x4) (\because \text{there are 4 networks}) = 98816$$



GRU

LSTM

Layers

Return Sequence

Return State

→ Bidirectional (LSTM(10))

→ Conv 1D (TCN)

→ Time Distributed

→ Time 2Vec