Microelectrode electrophysiology: Extending the Brain Imaging Data Structure to intracellular and extracellular recordings in animal models

First Author

ABSTRACT

The Brain Imaging Data Structure (BIDS) has facilitated data sharing and tool development in human neuroimaging. We present an extension for microelectrode electrophysiology recordings in animals, specifically addressing the unique requirements of intracellular and extracellular recordings. This extension introduces two new data types: `icephys` for intracellular and `ecephys` for extracellular recordings, supporting diverse recording modalities from patch-clamp to high-density silicon probes. Building on existing BIDS principles and the prior electrophysiology extensions for EEG and iEEG, we specify metadata for probes, electrodes, and channels, with particular attention to metadata required for spike sorting analysis. The extension adopts NWB (Neurodata Without Borders) and NIX (Neuroscience Information Exchange) as data formats, ensuring comprehensive metadata capture while maintaining compatibility with existing analysis ecosystems. We provide example datasets covering common use cases and discuss integration with established tools. This standardization enables reproducible analysis pipelines, facilitates data sharing through repositories like DANDI, G-Node and EBRAINS, and bridges different scales from cellular to systems neuroscience.

Introduction

Microelectrode electrophysiology encompasses techniques for recording electrical activity from individual neurons to local field potentials, providing crucial insights into neural computation at high spatial and temporal resolution, often with the ability to track individual neuronal action potentials. Recent technological advances, including high-density silicon probes such as Neuropixels[1], have dramatically increased data acquisition rates, with single probes now capable of recording from hundreds of neurons simultaneously. Intracellular techniques such as patch clamp recordings[2] provide direct access to cellular membrane dynamics, enabling detailed characterization of synaptic transmission and intrinsic neuronal properties. These methods are primarily used in animal research but generate data of increasing complexity that demands standardized organization.

A key challenge in the microelectrode electrophysiology community has been the proliferation of proprietary data formats. Different acquisition systems, such as Blackrock, Plexon, TDT, Open Ephys, and SpikeGLX, each produce data in their own formats, creating barriers to data sharing and tool interoperability. This fragmentation complicates data sharing and long-term archival: custom readers must be maintained for each format. Undocumented specifications, unmaintained programmatic interfaces, and language lock-in risk rendering data inaccessible.

Two major community efforts have emerged to address this challenge at the session level. Neurodata Without Borders (NWB)[3,4] is an open data standard for neurophysiology developed as part of the National Institute of Health BRAIN Initiative by a community of researchers over the last 10 years. NWB uses HDF5 or Zarr as its backend and provides a comprehensive schema for storing electrophysiology data alongside stimulus information, behavioral data, and metadata. The Neuroscience Information Exchange Format (NIX)[5] is a data model for annotated scientific datasets that provides a HDF5 file backend for the Neo library[6]. Both standards are widely adopted in the neuroscience community and supported by major analysis toolkits such as SpikeInterface[7], and both have been endorsed by the International Neuroinformatics Coordinating Facility (INCF) as community standards for electrophysiology data. Both NWB and NIX have been successful in standardizing data representation at the single-session level, enabling tool developers to build analysis pipelines that work across laboratories[8–10]. However, neither standard provides organizational guidance at the project level. That is, how to organize data across multiple sessions, subjects, and experimental conditions within a study. Researchers must still make ad-hoc decisions about directory structures, naming conventions, and where to place study-level metadata such as participant information or experimental protocols.

The Brain Imaging Data Structure (BIDS)[11] is a community-driven standard for organizing and sharing neuroscience data. In a BIDS dataset, all data from each subject are organized hierarchically in subject-specific directories, with optional session subdirectories containing modality-specific folders for the data files themselves. Files follow a structured naming scheme that encodes relevant metadata such as subject, session, and task. JSON sidecar files provide detailed metadata for each data file, while TSV files capture tabular information such as participant demographics and channel properties. A `dataset_description.json` file describes the dataset as a whole, and JSON metadata at higher directory levels are

inherited by lower levels unless overridden. Originally developed for MRI, BIDS has been extended through community-driven proposals to additional modalities including MEG[12], EEG[13], iEEG[14], PET, and microscopy. With over a thousand public datasets on OpenNeuro and endorsement by the INCF, BIDS has become a widely adopted framework for FAIR neuroscience data. The electrophysiology extensions established patterns for organizing time-series neural data that we build upon here. This extension bridges the gap between session-level data standardization (NWB/NIX) and study-level organization (BIDS), combining the strengths of both approaches. BIDS provides the organizational framework for datasets containing multiple subjects and sessions, consistent with existing modalities, while NWB and NIX handle the complex internal structure of electrophysiology recordings within each session. This complementary relationship mirrors how BIDS for neuroimaging organizes NIfTI files. BIDS does not replace the data format but provides the organizational context around it.

While we tried wherever possible to maintain consistency with existing datatypes, we also designed this enhancement proposal to address the unique challenges of microelectrode electrophysiology:

1. Electrode scales spanning orders of magnitude (sub-micron tips to millimeter arrays).
2. Diverse target species, which have different brain atlases, often including entirely different brain areas.
3. Large data volumes, which can be over 100 GB for an individual session.
4. Diverse probe geometries requiring specialized coordinate systems.
5. Spike sorting as an essential preprocessing step requires specific metadata.

Here we present BIDS Extension Proposal 032 (BEP032), extending BIDS to microelectrode electrophysiology with a focus on animal models. This extension:

- introduces two datatypes (`ecephys` for extracellular and `icephys` for intracellular recordings),
- defines metadata across three levels: probes, electrodes, and channels,
- standardizes probe and electrode metadata including stereotaxic surgical coordinates,
- integrates with the ProbeInterface library[15] for probe geometry definitions, and
- defines coordinate systems for multiple species including rodent and primate brain atlases.

Other ephys standardization efforts

Methods

Development Process

The BEP032 effort grew out of the Animal Data Organization (AnDO) project, initiated at the Institut de Neurosciences de la Timone in Marseille in early 2020 to standardize experimental data recorded in animal models. Following the initial development, the effort was opened to the broader community through the launch of an INCF-endorsed Working Group on Standardized Data. The working group, comprising approximately 40 members from institutions across Europe and North America, held monthly teleconferences and made progress in subgroups on well-defined issues between meetings. After discussions within the group, a specific standardization effort for electrophysiology was initiated as BIDS Extension Proposal 032. The proposal was developed in the open on a Google Document following the standard BEP process, with the community invited to comment directly on the specification.

Several design decisions required coordination with other BIDS extension efforts and with developers of related tools. The active participation of developers of other BEPs and of BIDS maintainers was critical to the resolution of design issues, particularly the three-level metadata hierarchy and the dual coordinate system approach.

Upon reaching community consensus, the proposal was submitted as a pull request to the BIDS specification repository, concurrently with the preparation of example datasets and the update of the BIDS validator schema.

Creating a BIDS-compliant microephys dataset

Results

Microephys-BIDS Summary

The microephys extension introduces two datatypes: `ecephys` for extracellular recordings (silicon probes, tetrode arrays, Utah arrays) and `icephys` for intracellular recordings (patch-clamp, sharp electrode). Both use NWB or NIX as raw data

formats. Data files reside in modality-specific folders (`ecephys/` or `icephys/`) with accompanying TSV/JSON metadata following standard BIDS inheritance principles.

Extracellular recordings present a spatial metadata challenge: a multi-channel probe is both a manufactured device with fixed electrode geometry and an implanted object at a specific brain location. Spike sorting algorithms require the formerinter-electrode spacing, shank arrangement, contact impedancesto reconstruct spike waveforms and assign them to recording sites. Anatomical interpretation requires the latterstereotaxic coordinates, brain region labels, atlas registrationto relate spiking activity to circuit function. The extension therefore organizes metadata in a three-level hierarchy: `probes.tsv` describes devices and their surgical placement, `electrodes.tsv` provides contact positions in probe-relative coordinates (required), and `channels.tsv` links recorded signals to those contacts. Anatomical coordinates are optional and distinguished by `space-<label>` prefixes (for example, `space-AllenCCFv3_electrodes.tsv`). For intracellular recordings, `samples.tsv` links individual recordings to characterized cells or tissue slices, inheriting animal metadata conventions from Microscopy-BIDS.

The following subsections detail these components.

Updates to Participant Files

Specific Microephys-BIDS Considerations

Intracellular vs Extracellular Datatypes

Data Format Requirements

Following the approach of prior BIDS electrophysiology extensions[13,14], our selection of data formats was governed by three requirements:

1. address the needs of a substantial portion of the electrophysiology community,
2. satisfy FAIR principles with open documentation and implementations in widely-used programming languages, and
3. meet the technical demands of neurophysiological workflows: high numerical precision, efficient storage of large data volumes, efficient access to subsets of large files, and the capacity to store rich metadata alongside raw signals.

We require data to be stored in NWB (Neurodata Without Borders, RRID:SCR_015242)[3] or NIX (Neuroscience Information Exchange, RRID:SCR_016196)[5]. Both are HDF5-based, open-source (BSD-3 licensed), and self-documenting: the file itself contains the schema needed to interpret its contents. HDF5 offers practical advantages for multi-gigabyte recordings: hierarchical organization, built-in compression, and lazy loading without reading entire files into memory.

These two formats represent complementary design philosophies. NWB provides a well-defined schema with extensive validation, ensuring consistency across datasets. NIX uses a minimal, generic data model that gives users more freedom in how they organize data, and serves as a storage backend for the Neo electrophysiology library (RRID:SCR_000634)[6]. Both have been reviewed and endorsed by the INCF as standard practices[16,17], and a dedicated archival repository (DANDI, RRID:SCR_017571) exists for neurophysiology data stored in these formats.

In iEEG-BIDS[14], NWB was listed as an unofficially-supported format due to its then-nascent ecosystem. The maturation of NWB 2.0 and its subsequent INCF endorsement justify its promotion to fully compliant status here. Unlike iEEG-BIDS, which maintains separate tiers of compliant and unofficially-supported formats, we adopt a simpler two-format approach. Both NWB and NIX are fully supported with no unofficial tier.

BIDS provides dataset-level organization: directory structure, naming conventions, and human-readable TSV/JSON files that allow inspection without specialized tools. The NWB or NIX file ensures complete provenance within a self-contained container. Metadata may appear in both places; analysis tools such as SpikeInterface (RRID:SCR_021150) can already extract probe geometry from NWB files, and future integration with BIDS sidecars will provide an alternative pathway.

Probes, Electrodes, and Channels

Although the NIX and NWB files can contain all information about the channels, electrode placement and probe design, in the BIDS representation these are explicitly made available in human- and machine-readable format in tabular TSV and in JSON files. Microephys uses three tables to capture the metadata of an experiment: `probes.tsv`, `electrodes.tsv`, and `channels.tsv` (and the corresponding `.json` files). The `probes.tsv` file lists each probe with its type and surgical placement. The `electrodes.tsv` file enumerates contact sites, linking each to its probe and specifying probe-relative coordinates for spike sorting. The `channels.tsv` file documents recorded signals: sampling frequency, units, source electrode, and reference. Channels without electrodes (sync, stimulus) use `n/a`; ground, typically hardware like a skull screw or ear clip, is defined globally in the sidecar JSON and can be overridden per-channel if it differs. A `stream_id` column links channels to data objects within the NWB or NIX file.

The iEEG-BIDS and EEG-BIDS extensions distinguish electrodes from channels: an electrode is a contact point with tissue, a channel is the amplifier and digitizer that produces a stored time series. These are not equivalent and are not always one-to-one. A differential recording derives one channel from two electrodes, a Neuropixels electrode may yield separate highpass and LFP channels at different sampling rates, and a sync signal is a channel with no electrode at all. The prior extensions noted that electrodes can be "organized into arrays, grids, or probes," but their metadata captured only electrodes and channels, not this grouping.

We add an explicit probe level. A probe is the physical device—Neuropixels, tetrode bundle, patch pipette—carrying one or more electrodes. The Probe table stores metadata about a single or multiple probes, such as manufacturer, surgical coordinates, and insertion angle. It provides a mechanism to link to formal probe model specifications.

ProbeInterface Integration

In extracellular electrophysiology, the spatial layout of the electrodes (i.e. contacts) on the probe is important for processing such as spike sorting, particularly on high-density probes[7]. The positions of the electrodes on a template brain can be useful as well, but often the relative positions of the electrodes are substantially warped in the registration process, so microephys needs to also store relative positions of the electrodes on the probe. The ProbeInterface library[15] provides a JSON-based schema for specifying electrode layout on the probe, as well as specifying the shapes of the electrodes and the geometry of the probe itself, which may be used for further visualization and analysis (Figure 2).

The `ecephys` datatype provides three possible mechanisms to provide the layout of the electrodes:

1. **`electrodes.tsv` (required):** An `electrodes.tsv` file without the use of a `space` entity is required, and this file uses `x`, `y`, and sometimes `z` to specify the positions of each electrode relative to the probe tip. This data is present for every electrophysiology data stream, and can be used by downstream tools. Electrodes in an alternative space may be defined in `electrodes.tsv` files with the `space` entity defined.

2. **Link to probeinterface_library:** ProbeInterface maintains a library of popular probes. If the `ecephys` is recorded from a probe that is defined in this library, the user is encouraged to link to the formal ProbeInterface definition of the probe, which contains additional information about the probe, including the electrode shape, and probe shape. This link uses the `Levels` mechanism with `TermURL` to link from values of the `probe_model` column of the `probes.tsv` table to the URL of the probe definition on GitHub.

3. **Define custom ProbeInterface files:** If probeinterface_library does not have the probe used, users are encouraged to create a probe definition JSON file. This file can be placed in `/probes`, and the `probe_model` column of the `probes.tsv` table can use `Levels` with a BIDS URI to direct to the file. The user may also consider submitting this probe configuration file to the probeinterface_library for use in future datasets.

Coordinate Systems

Like other datatypes, including iEEG, MEG, and EEG, microelectrode electrophysiology must provide a way to report the anatomical localization of electrodes. However, this standard has four key differences in microephys experiments:

1. They often use stereotaxic coordinates to represent the surgical placement of the probe.

2. Anatomical localization is not always known.

3. Processing of the data requires understanding of real (unwarped) electrode spacing.

4. The experiments are often done on various non-human species.

Stereotaxic coordinates

When inserting microelectrode probes in vivo, experimenters often use stereotaxic instruments to target a desired brain region. The position and angle of the inserted probe are the stereotaxic coordinates, and describe the surgical positioning procedure. We reviewed the field thoroughly, and found that the systems for notating stereotaxic coordinates were often varied, inconsistent, and poorly documented. BrainSTEM[18] provides very clear and unambiguous definitions of stereotaxic coordinates along with clear illustrations. We have adopted this convention and encourage others to do the same.

In microephys, the stereotaxic coordinates are stored as columns of the `probes.tsv` table. This includes 3 axes of direction: anterior/posterior (AP), medial/lateral (ML), and dorsal/ventral (DV); and 3 rotational axes: AP Angle, ML Angle, and rotation (i.e. twist).

In non-human neuroanatomy, the direction towards the top of the brain is usually referred to as dorsal (D) and the bottom ventral (V). In human neuroanatomy, these directions are usually called superior and inferior, respectively. We note that we are

using the animal convention (D/V), here, as we expect the majority of stereotaxic microelectrode electrophysiology experiments to be done in non-humans.

Stereotaxic instruments are not always used. For example, placement of Utah array probes in non-human primates and in humans is often done without a stereotaxic instrument. They are often simply manually placed in the desired brain area based on gyral patterns observed on the surface of the brain. In these cases, there are no stereotaxic coordinates to report.

Stereotaxic coordinates are valuable information, as it reveals the intent of the surgical probe placement, and it is often the best estimate the experimenter has until histological probe localization can be conducted post mortem, however, a recent analysis has revealed that stereotaxic reproducibility can be quite poor, even in ideal circumstances, and substantial, meaningful variance exists between surgeries[19]. Stereotaxic coordinates also fail to capture inter-individual variability in brain structure. Therefore, while this information is valuable, it is incomplete.

Anatomical localization of electrodes

The precise anatomical positioning of probes and electrodes can be determined using neuroimaging or histology. The most common method is to take histological slices of the brain where the probe was inserted and visually inspect them to determine where the electrodes were.

The gold standard for anatomical localization in microephys experiments is to register the probe to a 3-dimensional coordinate system. This technique registers electrodes implanted in different subjects onto a common brain, analogous to registration procedures that are commonplace in MRI. Most microelectrode electrophysiology data is from non-human animal subjects, so we must provide a new set of coordinate systems for different species. The most popular coordinate system for mice is the Allen Institute Common Coordinate Framework (CCF) v3[20]. Other atlases have been developed for mice and a variety of other species, though complete coverage of species will require new coordinate systems and atlases to be added as they are developed.

Expressing localization of electrodes on an individual, group, or common coordinate system requires an additional `electrodes.tsv` file with a `space` entity, and a corresponding `MicroephysCoordinateSystem.json` file. Here we deviate from the iEEG datatype—the main `electrodes.tsv` file must store the real physical coordinates of electrodes in relative probe-space, as this is important information for downstream processing.

Discussion

Data Availability

Two example datasets are provided in the BIDS examples repository (https://github.com/bids-standard/bids-examples). The first is a conversion of the Reach-to-Grasp multi-electrode array dataset[21], originally published on the G-Node repository (DOI: 10.12751/g-node.f83565). It contains extracellular recordings from two macaque subjects using 96-channel Utah arrays, with both local field potential (1 kHz) and high-pass (30 kHz) data streams, behavioral channels, and task events. The second is a synthetic dataset demonstrating both `ecephys` and `icephys` datatypes, including registration to the Allen CCF v3 coordinate system, multiple simultaneous probes, and both ProbeInterface library references and custom probe definition files.

Code Availability

Using NWB and NIX as the underlying data format allows microephys BIDS data to utilize the sophisticated software ecosystems associated with these data standards.

The NWB software ecosystem contains a suite of tools to convert data from the various common electrophysiology data formats to NWB. PyNWB and MatNWB provide flexible APIs for writing NWB files[3]. NeuroConv automates conversion from 60+ formats, guiding the user in best practices[22]. NWB Inspector provides automated checks to validate NWB files against best practices, and NWB GUIDE provides a graphical interface that provides the features of NeuroConv and NWB Inspector to non-programmers.

30+ popular analysis tools support NWB as an input and/or output format, many of which are relevant to microephys data. SpikeInterface provides tools for creating spike sorting pipelines[7]. Neurosift provides interactive dashboards for visualizing NWB data[10], and Pynapple[9] provides tools for common neurophysiology analyses.

NIX can be written from NEO[6], which supports reading diverse electrophysiology data formats. NIX also supports data analysis libraries, such as Elephant[8].

References

1. Jun, J. J. *et al.* Fully integrated silicon probes for high-density recording of neural activity. *Nature* **551**, 232–236, 10.1038/nature24636 (2017).

2. Sakmann, B. & Neher, E. Patch Clamp Techniques for Studying Ionic Channels in Excitable Membranes. *Annu. Rev. Physiol.* **46**, 455–472, 10.1146/annurev.ph.46.030184.002323 (1984). Publisher: Annual Reviews.

3. Rübel, O. *et al.* The Neurodata Without Borders ecosystem for neurophysiological data science. *eLife* **11**, e78362, 10.7554/eLife.78362 (2022). Publisher: eLife Sciences Publications, Ltd.

4. Teeters, J. L. *et al.* Neurodata Without Borders: Creating a Common Data Format for Neurophysiology. *Neuron* **88**, 629–634, 10.1016/j.neuron.2015.10.025 (2015).

5. Stoewer, A., Kellner, C., Benda, J., Wachtler, T. & Grewe, J. File format and library for neuroscience data and metadata. *Front. Neuroinformatics* **8**, 10.3389/conf.fninf.2014.18.00027 (2014).

6. Garcia, S. *et al.* Neo: an object model for handling electrophysiology data in multiple formats. *Front. Neuroinformatics* **8**, 10.3389/fninf.2014.00010 (2014).

7. Buccino, A. P. *et al.* SpikeInterface, a unified framework for spike sorting. *eLife* **9**, e61834, 10.7554/eLife.61834 (2020). Publisher: eLife Sciences Publications, Ltd.

8. Denker, M., Yegenoglu, A. & Grün, S. Collaborative HPC-enabled workflows on the HBP Collaboratory using the Elephant framework, 10.12751/INCF.NI2018.0019 (2018). Neuroinformatics 2018, P19.

9. Viejo, G. *et al.* Pynapple, a toolbox for data analysis in neuroscience. *eLife* **12**, 10.7554/eLife.85786.2 (2023). Publisher: eLife Sciences Publications Limited.

10. Magland, J., Soules, J., Baker, C. & Dichter, B. Neurosift: DANDI exploration and NWB visualization in the browser. *J. Open Source Softw.* **9**, 6590, 10.21105/joss.06590 (2024).

11. Gorgolewski, K. J. *et al.* The brain imaging data structure, a format for organizing and describing outputs of neuroimaging experiments. *Sci. Data* **3**, 160044, 10.1038/sdata.2016.44 (2016). Publisher: Nature Publishing Group.

12. Niso, G. *et al.* MEG-BIDS, the brain imaging data structure extended to magnetoencephalography. *Sci. Data* **5**, 180110, 10.1038/sdata.2018.110 (2018). Publisher: Nature Publishing Group.

13. Pernet, C. R. *et al.* EEG-BIDS, an extension to the brain imaging data structure for electroencephalography. *Sci. Data* **6**, 103, 10.1038/s41597-019-0104-8 (2019). Publisher: Nature Publishing Group.

14. Holdgraf, C. *et al.* iEEG-BIDS, extending the Brain Imaging Data Structure specification to human intracranial electrophysiology. *Sci. Data* **6**, 102, 10.1038/s41597-019-0105-7 (2019). Publisher: Nature Publishing Group.

15. Garcia, S., Sprenger, J., Holtzman, T. & Buccino, A. P. ProbeInterface: A Unified Framework for Probe Handling in Extracellular Electrophysiology. *Front. Neuroinformatics* **16**, 10.3389/fninf.2022.823056 (2022). Publisher: Frontiers.

16. Martone, M. *et al.* Call for community review of Neurodata Without Borders: Neurophysiology (NWB:N) 2.0—a data standard for neurophysiology. *F1000Research* **8**, 1731, 10.7490/f1000research.1117538.1 (2019). Publisher: F1000 Research Limited.

17. NIX – Neuroscience information exchange format.

18. Petersen, P. C. BrainSTEM: Brain STructured Experimental Metadata. Coordinate system documentation: https://support.brainstem.org/datamodel/schemas/coordinates/.

19. International Brain Laboratory *et al.* Reproducibility of in vivo electrophysiological measurements in mice. *eLife* **13**, e100840, 10.7554/eLife.100840 (2025).

20. Wang, Q. *et al.* The Allen Mouse Brain Common Coordinate Framework: A 3D Reference Atlas. *Cell* **181**, 936–953.e20, 10.1016/j.cell.2020.04.007 (2020).

21. Brochier, T. *et al.* Massively parallel recordings in macaque motor cortex during an instructed delayed reach-to-grasp task. *Sci. Data* **5**, 180055, 10.1038/sdata.2018.55 (2018). Publisher: Nature Publishing Group.

22. Mayorquin, H. *et al.* NeuroConv: Streamlining Neurophysiology Data Conversion to the NWB Standard. In *Proceedings of the 24th Python in Science Conference*, vol. 24, 245–258, 10.25080/cehj4257 (2025).

Acknowledgements

Author Contributions

Competing Interests

The authors declare no competing interests.

Funding

Ethics statement

Figures & Tables



Figure 1. microephys-BIDS folder structure and metadata files, illustrated with the `microephys_toy` example dataset. **(A)** Extracellular electrophysiology (`ecephys`). The directory tree shows the three core metadata files (`probes.tsv`, `electrodes.tsv`, `channels.tsv`), session-level recording sidecars, and coordinate-system files. Representative rows from each file are shown alongside the tree. **(B)** Intracellular electrophysiology (`icephys`). The same three-file hierarchy accommodates patch-clamp recordings, with pipette-specific fields in `electrodes.tsv` and a `recording_mode` column in `channels.tsv`. All values are taken from the publicly available toy dataset.



Figure 2. ProbeInterface integration with microephys-BIDS. Three colours encode the mapping to the file hierarchy: probe outline (*green*) maps to `probes.tsv`, contact positions (*pink*) to `electrodes.tsv`, and channel wiring (*orange*) to `channels.tsv`. **(A)** Colour-coded microephys-BIDS sidecar tables. **(B)** NeuroNexus A4x8 probe geometry (4 shanks, 32 channels) from the ProbeInterface library[15]; interleaved electrode identifiers reflect the manufacturer's connector pin numbering. **(C)** ProbeInterface JSON fields highlighted by their microephys-BIDS level. **(D)** Diversity of supported probe geometries, from tetrodes (4 ch) to Neuropixels 2.0 (5120 ch, 4 shanks). **(E)** Two mechanisms for linking probe definitions via the `*_probes.json` sidecar: a custom file in the dataset's `probes/` directory, or a reference to the ProbeInterface library. Device channel indices assume an Intan RHD2132 headstage with A32-OM32 adapter (pin $N \rightarrow$ input $N-1$).



Figure 3. Spatial localization and animal metadata in microephys-BIDS. **(A)** Stereotaxic surgical coordinates. Bregma and Lambda skull landmarks define the origin; six parameters per probe (AP, ML, DV and three rotation angles) are recorded in `probes.tsv`. **(B)** Dual coordinate representation. Probe-relative coordinates in `electrodes.tsv` describe contact geometry on the device, while a `space-<label>_electrodes.tsv` and matching `coordsystem.json` locate each contact in an anatomical reference frame. **(C)** Animal subject metadata in `participants.tsv`: species, strain, and strain RRID; `age_category` with UBERON life-cycle stages is pending (PR #2340).

Table 1. Supported coordinate systems for microelectrode electrophysiology in BIDS, grouped by species. Each system has a corresponding restricted keyword for use in `MicroephysCoordinateSystem` and the `space-<label>` entity. Users may also specify `Other` with a free-text description.

Species	Coordinate System	Reference
Mouse	AllenCCFv3	Wang et al. (2020) Cell
	WaxholmSpace	Johnson et al. (2010) NeuroImage
	FranklinPaxinos	Franklin & Paxinos, Academic Press
Rat	PaxinosWatson	Paxinos & Watson, Academic Press
	WistarRatAtlas	Papp et al. (2014) NeuroImage
	SwansonRat	Swanson, Elsevier
Macaque	CHARM	Jung et al. (2021) NeuroImage
	D99	Reveley et al. (2017) Cereb. Cortex
	PaxinosMacaque	Paxinos et al., Academic Press
Marmoset	MarmosetBrainAtlas	Hashikawa et al. (2015) NeuroImage
Any	Stereotaxic	Generic stereotaxic (Bregma origin)
	individual	Subject-specific anatomy
	Pixels	2D photo/rendering coordinates
	Other	Free-text description required