

ENTREGA DE DOCUMENTACIÓN / DOCUMENTATION DELIVERY

Tipo de Requisito Documental: <i>Type of Document Requirement:</i>	MC
Proveedor: <i>Supplier:</i>	LORK INDUSTRIAS S.L.
Nº Pedido: <i>Order Number:</i>	C-PE24/03901
Fecha: <i>Date:</i>	05/07/2024
Nº Pieza: <i>Part Number:</i>	T000982574-33003P01
Cantidad: <i>Quantity:</i>	2

										SSAB EMEA AB, SE-781 84 BORLÄNGE, Sweden A01																																																	
Inspection certificate EN 10 204 - 3.1 A02			Issuing department Quality inspection A05			Purchaser order no PC-14568 A07			Our order no 303473-1 A08			Invoice no 3343767 A19			Certificate no and date 20650290 2022-07-22 A03																																												
Purchaser A11 11628 ACEROS URS, S.A CALLE LA FORJA 20 ES-08840 VILADECANS SPANIEN			Product Hot rolled sheets B01			Marking Manufacturer, MATERIAL ID B06						Customer marks B15																																															
			Quantity B08 208	Dimensions [mm] T 2 W 1000 L 2000 B09-B11			Weight [kg] 6610 B12			Deliv. Cond. B04	Internal code B16																																																
			Consignee ACEROS URS, S.A CALLE LA FORJA 20 ES-08840 VILADECANS A06 SPANIEN						Standard/rules SSAB B02 Steel grade STRENX 700 MC E																																																		
MATERIAL ID 53-4506-674962-02 , 53-4506-674962-03 , 53-4506-674962-04 B07																																																											
Chemical composition																																																											
<table border="1"> <tr> <td>Heat no</td> <td>C</td> <td>Si</td> <td>Mn</td> <td>P</td> <td>S</td> <td>Cr</td> <td>Ni</td> <td>Mo</td> <td>V</td> <td>Ti</td> <td>Cu</td> <td>Al</td> <td>Nb</td> <td>B</td> <td>N</td> <td>CEV</td> </tr> <tr> <td>53-4506</td> <td>.059</td> <td>.01</td> <td>1.66</td> <td>.011</td> <td>.004</td> <td>.03</td> <td>.04</td> <td>.00</td> <td>.01</td> <td>.12</td> <td>.01</td> <td>.045</td> <td>.030</td> <td>.0001</td> <td>.005</td> <td>.35</td> </tr> </table>															Heat no	C	Si	Mn	P	S	Cr	Ni	Mo	V	Ti	Cu	Al	Nb	B	N	CEV	53-4506	.059	.01	1.66	.011	.004	.03	.04	.00	.01	.12	.01	.045	.030	.0001	.005	.35											
Heat no	C	Si	Mn	P	S	Cr	Ni	Mo	V	Ti	Cu	Al	Nb	B	N	CEV																																											
53-4506	.059	.01	1.66	.011	.004	.03	.04	.00	.01	.12	.01	.045	.030	.0001	.005	.35																																											
<table border="1"> <tr> <td colspan="15">C71-C92 Carbon equivalent etc C93-C99</td> </tr> <tr> <td colspan="15">CEV = C + Mn/6 + (Ni + Cu)/15 + (Cr + Mo + V)/5</td> </tr> </table>															C71-C92 Carbon equivalent etc C93-C99															CEV = C + Mn/6 + (Ni + Cu)/15 + (Cr + Mo + V)/5																													
C71-C92 Carbon equivalent etc C93-C99																																																											
CEV = C + Mn/6 + (Ni + Cu)/15 + (Cr + Mo + V)/5																																																											
<table border="1"> <tr> <td>Testtype C04</td> <td>Millcode C00</td> <td>Specimen position C01</td> <td>Direction C02</td> <td>Treatment B05</td> <td>Specimen type C10</td> <td>Temp [degr C] C03</td> <td colspan="8">Test results</td> </tr> <tr> <td>Tensile test</td> <td>HOK392</td> <td>Top end</td> <td>Longitudinal</td> <td>Delivery condition</td> <td>ISO6892-1 type 2</td> <td></td> <td>C11 Reh [MPa] 780</td> <td>C12 Rm [MPa] 832</td> <td>C13 A80 [%] 14.0</td> <td colspan="5"></td> </tr> <tr> <td>Bend test</td> <td>HOK393</td> <td>Top end</td> <td>Transverse</td> <td>Delivery condition</td> <td></td> <td></td> <td colspan="8">C50 The test is satisfactory</td> </tr> </table>															Testtype C04	Millcode C00	Specimen position C01	Direction C02	Treatment B05	Specimen type C10	Temp [degr C] C03	Test results								Tensile test	HOK392	Top end	Longitudinal	Delivery condition	ISO6892-1 type 2		C11 Reh [MPa] 780	C12 Rm [MPa] 832	C13 A80 [%] 14.0						Bend test	HOK393	Top end	Transverse	Delivery condition			C50 The test is satisfactory							
Testtype C04	Millcode C00	Specimen position C01	Direction C02	Treatment B05	Specimen type C10	Temp [degr C] C03	Test results																																																				
Tensile test	HOK392	Top end	Longitudinal	Delivery condition	ISO6892-1 type 2		C11 Reh [MPa] 780	C12 Rm [MPa] 832	C13 A80 [%] 14.0																																																		
Bend test	HOK393	Top end	Transverse	Delivery condition			C50 The test is satisfactory																																																				
Production time: 2022-06-29																																																											

This certificate is produced with EDP and valid without signature Z02		It is hereby certified that the material described above complies with the requirements of the order. Z01		A04 STRENX PERFORMANCE STEEL www.strenx.com	
Material Testing/ H Leu / M Modig Eriksson / V Esbelani / M Stolpe					