

DWG No:	KC-01-1704											
Revision:	V2.0											
Drawn:	J. Rostoker	6/20/2026										
Approved:	J. Kerman	6/20/2026										
Issued:	6/20/2026											
Status:	RELEASED											
Doc Type:	CCA Placement File											
Designator	Device	Footprint	Mid X	Mid Y	Ref X	Ref Y	Pad X	Pad Y	Pins	Layer	Rotation	SMD
C1	CL21B475KAFNNNE	C0805	304.927mm	-21.209mm	304.927mm	-21.209mm	303.927mm	-21.209mm	2 T		0	Yes
C10	CL10A105KB8NNNC	C0603	28.575mm	-27.051mm	28.575mm	-27.051mm	28.575mm	-27.751mm	2 T		90	Yes
C11	CL05B104KO5NNNC	C0402	52.705mm	-36.322mm	52.705mm	-36.322mm	52.705mm	-36.742mm	2 T		90	Yes
C12	CL10A106KP8NNNC	C0603	296.418mm	-12.7mm	296.418mm	-12.7mm	296.418mm	-13.4mm	2 T		90	Yes
C13	CC0603KRX7R9BB104	C0603	294.64mm	-12.7mm	294.64mm	-12.7mm	294.64mm	-13.4mm	2 T		90	Yes
C14	CL10A106KP8NNNC	C0603	281.305mm	-79.629mm	281.305mm	-79.629mm	281.305mm	-78.929mm	2 T		270	Yes
C15	CL05B104KO5NNNC	C0402	282.829mm	-79.629mm	282.829mm	-79.629mm	282.829mm	-79.209mm	2 T		270	Yes
C16	CL05B103KB5NNNC	C0402	312.801mm	-30.988mm	312.801mm	-30.988mm	312.801mm	-30.568mm	2 T		270	Yes
C17	CL05B103KB5NNNC	C0402	301.498mm	-46.037mm	301.498mm	-46.037mm	301.498mm	-45.617mm	2 T		270	Yes
C18	CL05A105KA5NQNC	C0402	130.429mm	-15.748mm	130.429mm	-15.748mm	130.009mm	-15.748mm	2 T		0	Yes
C19	CL10A106KP8NNNC	C0603	132.588mm	-17.145mm	132.588mm	-17.145mm	133.288mm	-17.145mm	2 T		180	Yes
C2	CL21B106KAYQNNNE	C0805	301.879mm	-17.399mm	301.879mm	-17.399mm	301.879mm	-18.399mm	2 T		90	Yes
C20	CL05B104KO5NNNC	C0402	132.334mm	-15.748mm	132.334mm	-15.748mm	132.754mm	-15.748mm	2 T		180	Yes
C21	CL05A105KA5NQNC	C0402	191.389mm	-15.748mm	191.389mm	-15.748mm	190.969mm	-15.748mm	2 T		0	Yes
C22	CL10A106KP8NNNC	C0603	193.548mm	-17.145mm	193.548mm	-17.145mm	194.248mm	-17.145mm	2 T		180	Yes
C23	CL05B104KO5NNNC	C0402	193.294mm	-15.748mm	193.294mm	-15.748mm	193.714mm	-15.748mm	2 T		180	Yes
C3	CL05A105KA5NQNC	C0402	305.266mm	-11.998mm	305.266mm	-11.998mm	305.266mm	-11.577mm	2 T		270	Yes
C4	CL05B104KO5NNNC	C0402	299.623mm	-12.042mm	299.623mm	-12.042mm	299.623mm	-12.462mm	2 T		90	Yes
C5	CL05A105KA5NQNC	C0402	300.893mm	-12.042mm	300.893mm	-12.042mm	300.893mm	-12.462mm	2 T		90	Yes
C6	RVT1E101M0607	CAP-SMD_BD6.3-L6.6-W6.6-LS7.2-R-RD	30.48mm	-18.415mm	30.48mm	-18.415mm	33.035mm	-18.415mm	2 T		0	Yes
C7	CC0603KRX7R9BB104	C0603	30.988mm	-22.86mm	30.988mm	-22.86mm	30.288mm	-22.86mm	2 T		0	Yes
C8	CC0603KRX7R9BB104	C0603	30.988mm	-24.638mm	30.988mm	-24.638mm	31.688mm	-24.638mm	2 T		180	Yes
C9	CL21A106KAYNNNE_C15850	C0805	48.514mm	-25.019mm	48.514mm	-25.019mm	49.514mm	-25.019mm	2 T		180	Yes
CN1	HF1004E	CONN-TH_4P-P2.54_HF1004E	16mm	-5mm	16mm	-5mm	12.19mm	-5mm	4 T		0	No
CN2	XDFH-0254-2*25P	CONN-TH_50P-P2.54_LX_XDFH-0254-2X25P	325mm	-45mm	325mm	-45mm	326.27mm	-75.48mm	50 T		90	No
CN3	2.54-2*17P直筒牛	IDC-TH_34P-P2.54_BOOMELE-2X17P	101.6mm	-50mm	101.6mm	-50mm	121.92mm	-48.73mm	34 T		180	No
CN4	2.54-2*17P直筒牛	IDC-TH_34P-P2.54_BOOMELE-2X17P	203.2mm	-50mm	203.2mm	-50mm	223.52mm	-48.73mm	34 T		180	No
D1	1N4148WS_C2128	SOD-323_L1.8-W1.3-LS2.5-RD	29.718mm	-29.591mm	29.718mm	-29.591mm	28.546mm	-29.591mm	2 T		0	Yes
DC1	DC-042Z-10A-2.5	DC-IN-TH_DC-042C-Z-2.5-A	35mm	-10mm	35mm	-10mm	39.85mm	-10.6mm	6 T		270	No
H1	PZ254V-12-4P	HDR-TH_4P-P2.54-V-M-R2-C2-S2.54	25.4mm	-35.56mm	25.4mm	-35.56mm	24.13mm	-36.83mm	4 T		0	No
H2	X6511FV-24-C85D32	HDR-TH_24P-P2.54-V-F	276.86mm	-40.64mm	276.86mm	-40.64mm	276.86mm	-11.43mm	24 T		270	No
H3	X6511FV-24-C85D32	HDR-TH_24P-P2.54-V-F	292.1mm	-40.64mm	292.1mm	-40.64mm	292.1mm	-11.43mm	24 T		270	No
H4	HDR-M_2.54_1x2P	HDR-TH_2P-P2.54-V-M-1	285.115mm	-86.487mm	285.115mm	-86.487mm	283.845mm	-86.487mm	2 T		0	No
LED1	KT-0805G	LED0805-R-RD	67.818mm	-11.43mm	67.818mm	-11.43mm	66.768mm	-11.43mm	2 T		180	Yes
LED2	KT-0603R	LED-SMD_L1.6-W0.8-R-RD	67.31mm	-13.97mm	67.31mm	-13.97mm	66.56mm	-13.97mm	2 T		180	Yes
LED3	KT-0805Y	LED0805-R-RD	46.482mm	-14.097mm	46.482mm	-14.097mm	45.432mm	-14.097mm	2 T		180	Yes
Q1	IRF9540NSTRLPBF_C33903	TO-263-2_L10.0-W9.1-P5.08-LS15.2-TL	39.497mm	-23.495mm	39.497mm	-23.495mm	42.037mm	-18.409mm	3 T		270	Yes
Q2	AO3400A_C20917	SOT-23-3_L2.9-W1.3-P1.90-LS2.4-BR	47.117mm	-22.225mm	47.117mm	-22.225mm	48.117mm	-23.175mm	3 T		0	Yes
R1	0402WGF1003TCE	R0402	308.229mm	-19.812mm	308.229mm	-19.812mm	308.229mm	-19.379mm	2 T		270	Yes

DWG No:	KC-01-1704											
Revision:	V2.0											
Drawn:	J. Rostoker	6/20/2026										
Approved:	J. Kerman	6/20/2026										
Issued:	6/20/2026											
Status:	RELEASED											
Doc Type:	CCA Placement File											
Designator	Device	Footprint	Mid X	Mid Y	Ref X	Ref Y	Pad X	Pad Y	Pins	Layer	Rotation	SMD
R10	0603WAF3003T5E	R0603	50.292mm	-23.241mm	50.292mm	-23.241mm	49.539mm	-23.241mm	2	T	0	Yes
R11	0402WGF1002TCE	R0402	48.133mm	-40.005mm	48.133mm	-40.005mm	48.566mm	-40.005mm	2	T	180	Yes
R12	0402WGF1002TCE	R0402	48.133mm	-41.148mm	48.133mm	-41.148mm	48.566mm	-41.148mm	2	T	180	Yes
R13	0603WAF470JT5E	R0603	273.558mm	-19.05mm	273.558mm	-19.05mm	274.311mm	-19.05mm	2	T	180	Yes
R14	0402WGF4701TCE	R0402	295.91mm	-71.247mm	295.91mm	-71.247mm	296.343mm	-71.247mm	2	T	180	Yes
R15	0603WAF470JT5E	R0603	295.91mm	-69.85mm	295.91mm	-69.85mm	296.663mm	-69.85mm	2	T	180	Yes
R16	0402WGF4701TCE	R0402	308.729mm	-31.756mm	308.729mm	-31.756mm	308.729mm	-31.323mm	2	T	270	Yes
R17	0402WGF4701TCE	R0402	308.729mm	-29.597mm	308.729mm	-29.597mm	308.729mm	-30.03mm	2	T	90	Yes
R18	0402WGF4701TCE	R0402	297.307mm	-46.863mm	297.307mm	-46.863mm	297.307mm	-46.43mm	2	T	270	Yes
R19	0402WGF4701TCE	R0402	297.307mm	-44.577mm	297.307mm	-44.577mm	297.307mm	-45.01mm	2	T	90	Yes
R2	FRC0402F1912TS	R0402	308.229mm	-17.653mm	308.229mm	-17.653mm	308.229mm	-17.22mm	2	T	270	Yes
R20	0402WGF1002TCE	R0402	310.934mm	-28.637mm	310.934mm	-28.637mm	311.366mm	-28.637mm	2	T	180	Yes
R21	0402WGF1002TCE	R0402	299.339mm	-43.688mm	299.339mm	-43.688mm	299.772mm	-43.688mm	2	T	180	Yes
R22	0402WGF1002TCE	R0402	287.782mm	-78.994mm	287.782mm	-78.994mm	288.215mm	-78.994mm	2	T	180	Yes
R23	0402WGF1002TCE	R0402	287.782mm	-80.264mm	287.782mm	-80.264mm	288.215mm	-80.264mm	2	T	180	Yes
R24	0402WGF5101TCE	R0402	88.773mm	-8.509mm	88.773mm	-8.509mm	88.34mm	-8.509mm	2	T	0	Yes
R25	0402WGF5101TCE	R0402	94.107mm	-8.509mm	94.107mm	-8.509mm	94.54mm	-8.509mm	2	T	180	Yes
R3	HoYLR2512-3W-15mR-1%	R2512	49.403mm	-30.734mm	49.403mm	-30.734mm	46.337mm	-30.734mm	2	T	0	Yes
R4	0603WAF1002T5E	R0603	30.988mm	-27.813mm	30.988mm	-27.813mm	31.741mm	-27.813mm	2	T	180	Yes
R5	0603WAF1003T5E	R0603	30.988mm	-26.289mm	30.988mm	-26.289mm	30.235mm	-26.289mm	2	T	0	Yes
R6	0603WAF2001T5E	R0603	64.008mm	-11.43mm	64.008mm	-11.43mm	64.761mm	-11.43mm	2	T	180	Yes
R7	0603WAF2700T5E	R0603	64.008mm	-13.97mm	64.008mm	-13.97mm	64.761mm	-13.97mm	2	T	180	Yes
R8	0603WAF1003T5E	R0603	48.514mm	-26.924mm	48.514mm	-26.924mm	49.267mm	-26.924mm	2	T	180	Yes
R9	0603WAF2001T5E	R0603	42.672mm	-14.097mm	42.672mm	-14.097mm	43.425mm	-14.097mm	2	T	180	Yes
TP1	HDR-M_2.54_1x3P	HDR-TH_3P-P2.54-V-M	60.96mm	-13.97mm	60.96mm	-13.97mm	60.96mm	-11.43mm	3	T	270	No
U1	MPM3610GQV-Z	QFN-20_L5.0-W3.0-TL-MPM3610GQV-Z	304.927mm	-18.034mm	304.927mm	-18.034mm	306.352mm	-18.984mm	14	T	180	Yes
U2	AP2112K-3.3TRG1	SOT-25-5_L2.9-W1.6-P0.95-LS2.8-BL	303.149mm	-12.065mm	303.149mm	-12.065mm	302.199mm	-13.365mm	5	T	0	Yes
U3	INA228AIDGSR	VSSOP-10_L3.0-W3.0-P0.50-LS4.9-BL	50.419mm	-36.322mm	50.419mm	-36.322mm	49.419mm	-38.672mm	10	T	0	Yes
U5	EMC2101-R-ACZL-TR	MSOP-8_L3.0-W3.0-P0.65-LS4.9-BL	285.115mm	-79.629mm	285.115mm	-79.629mm	284.14mm	-81.929mm	8	T	0	Yes
U6	LTC4311CSC6#TRPBF	SC-70-6_L2.1-W1.3-P0.65-LS2.1-BR	310.934mm	-30.676mm	310.934mm	-30.676mm	311.884mm	-31.326mm	6	T	0	Yes
U7	LTC4311CSC6#TRPBF	SC-70-6_L2.1-W1.3-P0.65-LS2.1-BR	299.339mm	-45.72mm	299.339mm	-45.72mm	300.289mm	-46.37mm	6	T	0	Yes
U8	CH334F_C5187527	QFN-24_L4.0-W4.0-P0.50-BL-EP2.8	132.398mm	-12.7mm	132.398mm	-12.7mm	134.397mm	-13.95mm	25	T	90	Yes
U9	CH334F_C5187527	QFN-24_L4.0-W4.0-P0.50-BL-EP2.8	193.358mm	-12.7mm	193.358mm	-12.7mm	195.357mm	-13.95mm	25	T	90	Yes
USB1	MicroXNJ	MICRO-USB-SMD_MICROXNJ_1	111.76mm	-3.048mm	111.76mm	-3.048mm	113.06mm	-4.38mm	9	T	180	No
USB2	MicroXNJ	MICRO-USB-SMD_MICROXNJ_1	172.72mm	-3.048mm	172.72mm	-3.048mm	174.02mm	-4.38mm	9	T	180	No
USB3	MicroXNJ	MICRO-USB-SMD_MICROXNJ_1	132.08mm	-3.048mm	132.08mm	-3.048mm	133.38mm	-4.38mm	9	T	180	No
USB4	MicroXNJ	MICRO-USB-SMD_MICROXNJ_1	193.04mm	-3.048mm	193.04mm	-3.048mm	194.34mm	-4.38mm	9	T	180	No
USB5	MicroXNJ	MICRO-USB-SMD_MICROXNJ_1	152.4mm	-3.048mm	152.4mm	-3.048mm	153.7mm	-4.38mm	9	T	180	No
USB6	MicroXNJ	MICRO-USB-SMD_MICROXNJ_1	213.36mm	-3.048mm	213.36mm	-3.048mm	214.66mm	-4.38mm	9	T	180	No
USBC1	TYPE-C-31-M-12	USB-C_SMD-TYPE-C-31-M-12_1	91.44mm	-4.064mm	91.44mm	-4.064mm	87.115mm	-5.77mm	16	T	180	No
USBC2	TYPE-C-31-M-12	USB-C_SMD-TYPE-C-31-M-12_1	233.68mm	-4.064mm	233.68mm	-4.064mm	229.355mm	-5.77mm	16	T	180	No

DWG No:	KC-01-1704												
Revision:	V2.0												
Drawn:	J. Rostoker	6/20/2026											
Approved:	J. Kerman	6/20/2026											
Issued:	6/20/2026												
Status:	RELEASED												
Doc Type:	CCA Placement File												
Designator	Device	Footprint	Mid X	Mid Y	Ref X	Ref Y	Pad X	Pad Y	Pins	Layer	Rotation	SMD	
X1	X322512MSB4SI	CRYSTAL-SMD_4P-L3.2-W2.5-BL	137.668mm	-15.24mm	137.668mm	-15.24mm	138.768mm	-14.39mm	4	T	180	Yes	
X2	X322512MSB4SI	CRYSTAL-SMD_4P-L3.2-W2.5-BL	198.628mm	-15.24mm	198.628mm	-15.24mm	199.728mm	-14.39mm	4	T	180	Yes	