

DWG No:	KC-01-1734											
Revision:	V2.0											
Drawn:	J. Rostoker	6/13/2026										
Approved:	J. Kerman	6/13/2026										
Issued:	6/13/2026											
Status:	RELEASED											
Doc Type:	CCA Placement File											
Designator	Device	Footprint	Mid X	Mid Y	Ref X	Ref Y	Pad X	Pad Y	Pins	Layer	Rotation	SMD
C1	CL21B475KAFNNNE	C0805	22.479mm	-70.993mm	22.479mm	-70.993mm	21.479mm	-70.993mm	2 B		0	Yes
C2	CL21B106KAYQNNE	C0805	19.558mm	-74.93mm	19.558mm	-74.93mm	19.558mm	-73.93mm	2 B		270	Yes
C3	CL05A105KA5NQNC	C0402	19.812mm	-80.264mm	19.812mm	-80.264mm	19.812mm	-80.684mm	2 B		90	Yes
C4	CL05B104KO5NNNC	C0402	15.24mm	-80.264mm	15.24mm	-80.264mm	15.24mm	-79.844mm	2 B		270	Yes
C5	CL05A105KA5NQNC	C0402	13.97mm	-80.264mm	13.97mm	-80.264mm	13.97mm	-79.844mm	2 B		270	Yes
CN1	2.54-2*17P直筒牛	IDC-TH_34P-P2.54_BOOMELE-2X17P	40mm	-64mm	40mm	-64mm	19.68mm	-62.73mm	34 B		0	No
P1	2.54-2*8P筒牛	IDC-TH_16P-P2.54_C3406	22mm	-88mm	22mm	-88mm	30.89mm	-89.27mm	16 B		180	No
P2	2.54-2*8P筒牛	IDC-TH_16P-P2.54_C3406	22mm	-106mm	22mm	-106mm	30.89mm	-107.27mm	16 B		180	No
P3	2.54-2*8P筒牛	IDC-TH_16P-P2.54_C3406	22mm	-124mm	22mm	-124mm	30.89mm	-125.27mm	16 B		180	No
P4	2.54-2*8P筒牛	IDC-TH_16P-P2.54_C3406	22mm	-142mm	22mm	-142mm	30.89mm	-143.27mm	16 B		180	No
P5	2.54-2*8P筒牛	IDC-TH_16P-P2.54_C3406	58mm	-88mm	58mm	-88mm	66.89mm	-89.27mm	16 B		180	No
P6	2.54-2*8P筒牛	IDC-TH_16P-P2.54_C3406	58mm	-106mm	58mm	-106mm	66.89mm	-107.27mm	16 B		180	No
P7	2.54-2*8P筒牛	IDC-TH_16P-P2.54_C3406	58mm	-124mm	58mm	-124mm	66.89mm	-125.27mm	16 B		180	No
P8	2.54-2*8P筒牛	IDC-TH_16P-P2.54_C3406	58mm	-142mm	58mm	-142mm	66.89mm	-143.27mm	16 B		180	No
R1	0402WGF1003TCE	R0402	25.527mm	-72.771mm	25.527mm	-72.771mm	25.527mm	-73.204mm	2 B		90	Yes
R2	FRC0402F1912TS	R0402	25.527mm	-74.93mm	25.527mm	-74.93mm	25.527mm	-75.363mm	2 B		90	Yes
R3	0402WGF1002TCE	R0402	53.975mm	-57.912mm	53.975mm	-57.912mm	53.975mm	-58.345mm	2 B		90	Yes
R4	0402WGF2002TCE	R0402	55.245mm	-57.912mm	55.245mm	-57.912mm	55.245mm	-57.479mm	2 B		270	Yes
U1	MPM3610GQV-Z	QFN-20_L5.0-W3.0-TL-MPM3610GQV-Z	22.733mm	-74.295mm	22.733mm	-74.295mm	24.158mm	-73.345mm	14 B		180	Yes
U2	AP2112K-3.3TRG1	SOT-25-5_L2.9-W1.6-P0.95-LS2.8-BL	17.526mm	-80.391mm	17.526mm	-80.391mm	16.576mm	-79.091mm	5 B		0	Yes
U4	DB1275-5.08-6P-GN-S	CONN-TH_6P-P5.08_DIBO_DB1275-5.08-	40mm	-44mm	40mm	-44mm	52.7mm	-44mm	6 B		0	No